



## NetKey® Bulk Copper Cable

NUC5C04IG-ME

Category 5e cable shall meet ANSI/TIA-568.2-E Category 5e and ISO 11801 Class D channel standards. The conductors shall be 24 AWG copper insulated with HDPE. The copper conductors shall be twisted in pairs and all four pairs shall be covered by flame retardant PVC (CM) jacket.

### Specifications

Environment	Indoor
Performance Level	Category 5e
Cable Construction	U/UTP
Flammability Rating	CM
Jacket Material	PVC
Nominal Cable Outside Diameter (In.)	0.204
Nominal Cable Outside Diameter (mm)	5.2
Sub Brand	NetKey®
Maximum Installation Tension (N)	110
Number of Pairs	4
Conductor Material	Copper
Conductor Type	Solid
Overall Length (ft.)	1000
Overall Length (m)	305
Conductor Gauge	24 AWG
Conductor Gauge (mm)	0.51
Insulation Material	Polyethylene
Maximum Voltage (V)	80
Color	International Gray
Packaging Type	Carton
Product Type	Bulk Copper Cable
Part Features	Copper Cable

**Packaging Detail**

UPC	61305689886
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	1.2693
Std. Ctn. Qty.	24
Std. Ctn. Volume (cf)	30.4630