



NetKey® Bulk Copper Cable

NUC6CR04BU-ME

Category 6 U/UTP copper cable shall meet ANSI/TIA-568.2-E Category 6 and ISO 11801 Class E channel standards. The conductors shall be 24 AWG copper insulated with HDPE. The copper conductors shall be twisted in pairs and covered by a flame-retardant PVC (CM) jacket.

Specifications

Environment	Indoor
Performance Level	Category 6
Cable Construction	U/UTP
Flammability Rating	CM
Copper Cable Flame Rating	CM
Jacket Material	PVC
Nominal Cable Outside Diameter (In.)	0.204
Nominal Cable Outside Diameter (mm)	5.2
Sub Brand	NetKey®
Maximum Installation Tension (N)	110
Number of Pairs	4
Conductor Material	Copper
Conductor Type	Solid
Overall Length (ft.)	1000
Overall Length (m)	305
Conductor Gauge	24 AWG
Conductor Gauge (mm)	0.51
Insulation Material	Polyethylene
Maximum Voltage (V)	80
Color	Blue
Packaging Type	Carton
Product Type	Bulk Copper Cable
Part Features	Copper Cable

Packaging Detail

UPC	61305689887
Std. Pkg. Qty.	1
Std. Pkg. Volume (cf)	2.1759
Std. Ctn. Qty.	14
Std. Ctn. Volume (cf)	30.4630