

HEYCO

Heyco® Original Series-35 Liquid Tight Cordgrips

Straight-Thru, PG Hubs




CABLE DIA. RANGE				PART NO.		DESCRIPTION	UL or IEC	PART DIMENSIONS									
Minimum		Maximum		Black	Gray			A		B		C		D		E	
in.	mm.	in.	mm.					Clearance Hole Dia.		Max. O.A. Length		Thread Length		Wrenching Nut Thk.		Wrenching Flat Size	
.064	1,6	.210	5,3	3444	3445	RLTF 7											
.114	2,9	.250	6,4	3207	3208	LTF 7	UL	.492	12,5	1.17	29,7	.33	8,4	.20	5,1	.59	15,0
.069	1,8	.187	4,7	3446	3447	RLTF 9											
.181	4,6	.312	7,9	3210	3211	LTF 9	UL	.599	15,2	1.30	33,0	.34	8,6	.20	5,1	.75	19,1
.069	1,8	.250	6,6	3448	3449	RLTF 11											
.230	5,8	.395	10,0	3213	3214	LTF 11	UL	.733	18,6	1.46	37,1	.39	9,9	.20	5,1	.86	21,8
.170	4,3	.450	11,4	3216	3217	LTF 13.5	UL	.804	20,4	1.53	38,9	.41	10,4	.20	5,1	.95	24,1
.230	5,8	.530	13,9	3219	3220	LTF 16	UL	.886	22,5	1.66	42,2	.45	11,4	.23	5,8	1.05	26,7
.250	6,4	.490	12,4	3454	3455	RLTF 21											
.450	11,4	.705	17,9	3222	3223	LTF 21	UL	1.115	28,3	1.87	47,5	.52	13,2	.23	5,8	1.30	33,0
.590	15,0	.990	25,1	3225	3226	LTF 29	UL	1.470	37,3	2.23	56,6	.59	15,0	.28	7,1	1.66	42,2

Standard colors black and gray.

For larger sizes, see *Heyco-Tite* Liquid Tight Cordgrips on page 3-2.

- IP 68 rated.
- Widest range of approved cable diameters.
- Acme threads on body prevent skipping and speed installation.
- For use in clearance or threaded holes.
- All nylon construction with TPE sealing gland resists salt water, weak acids, gasoline, alcohol, oil, grease, and common solvents. (This feature is not assessed by UL.)
- PG hub threads are steel conduit threads per DIN 40430.
- Multiple sizes for flexible cord diameters ranging from .064" (1,6 mm) to .990" (25,1 mm). For larger sizes, see *Heyco-Tite* Liquid Tight Cordgrips on page 3-2.
- We recommend using the fitting with the smallest maximum diameter that will fit your application.
- **Locknuts INCLUDED.**
- For non-liquid tight Heyco PG Threaded Plugs, see page 3-29.
- Consult Heyco for cordgrips molded in other colors.



Material	6/6 Nylon with TPE Gland
Certifications	- UL Listed under Underwriters' Laboratories File E51579 - UL Recognized under the Component Program of Underwriters' Laboratories File E51579 - CSA Certified by Canadian Standards Association File 93876C
Flammability Rating	94V-2
Temperature Rating	Static -40°F (-40°C) to 239°F (115°C) Dynamic -4°F (-20°C) to 212°F (100°C)
IP Rating	IP 68 (70 PSI, 5 BAR)

*Quick
Specs*