



1. PRODUCT AND COMPANY IDENTIFICATION					
Pe		Black RTV High IDH number: 274809 ilicone Gasket Maker			
		2. HAZARDS IDENTIFICATION			
	EMERGENCY OVERVIEW				
		HMIS:			
Physical state: Color: Odor:	paste black Mild	HEALTH: *2 FLAMMABILITY: 1 PHYSICAL HAZARD: 0 Personal Protection: See MSDS Section 8			
WARNING:	CA RE	OLONGED OR REPEATED CONTACT WITH UNCURED SEALANT MAY USE EYE, SKIN AND RESPIRATORY TRACT IRRITATION. PEATED OR PROLONGED CONTACT MAY CAUSE ALLERGIC SKIN ACTION.			
Relevant routes of exposure: Potential Health Effects		Skin, Inhalation, Eyes			
		Inhalation of vapors or mists of the product may be irritating to the respiratory system. When			
innalation:		heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit. The silane is a skin and eye irritant and prolonged contact may cause eye and skin burns. The low concentration makes such overexposure unlikely and minimizes its affect on health and safety.			
Skin contact:	:	Prolonged or repeated contact with uncured sealant may cause skin irritation. May cause allergic skin reaction.			
Eye contact: Ingestion:		Vapors may irritate eyes. Contact with eyes will cause irritation. May be harmful if swallowed. Not expected under normal conditions of use.			
Existing conditions aggravated by exposure:		Skin disorders.			
		This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).			

See Section 11 for additional toxicological information.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Silicone Resin	Proprietary	30 - 60
Reinforcing Filler	Proprietary	30 - 60
Silicone Resin	Proprietary	10 - 30
Filler	Proprietary	5 - 10
Oximino silane	Proprietary	1 - 5
Carbon black	1333-86-4	0.1 - 1

Exposure to moisture during cure will release 0.1 - 0.9% methanol. Methyl ethyl ketoxime (MEKO) is formed during cure. This product will release up to 5% MEKO.

4. FIRST AID MEASURES		
Inhalation:	Move to fresh air. If symptoms persist, seek medical advice.	
Skin contact:	Wipe off paste with paper towel or cloth. Wash with soap and water. If symptoms develop and persist, get medical attention.	
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, consult a specialist.	
Ingestion:	Do not induce vomiting. If symptoms develop and persist, get medical attention.	
5. F	IRE FIGHTING MEASURES	
Flash point:	> 93 °C (> 199.4 °F) Tagliabue closed cup	
Autoignition temperature:	Not available	
Flammable/Explosive limits - lower:	Not applicable	
Flammable/Explosive limits - upper:	Not applicable	
Extinguishing media:	Carbon dioxide. foam Dry chemical.	

Wear self	f contained breathing apparatus.
-----------	----------------------------------

Unusual fire or explosion hazards:	None
Hazardous combustion products:	Oxides of silicon. Oxides of carbon. Formal

Oxides of silicon. Oxides of carbon. Formaldehyde.

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Do not allow product to enter sewer or waterways.
Clean-up methods:	Scrape up as much material as possible. Maintain good ventilation for large spills. Store in a partly filled, closed container until disposal.

# 7. HANDLING AND STORAGE

Handling:

Special firefighting procedures:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Do not wear contact lenses.

Storage:

For safe storage, store between 8 °C (46.4 °F) and 28 °C (82.4 °F) Store in a dry area below 90° F. Keep container closed.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Silicone Resin	None	None	None	None
Reinforcing Filler	10 mg/m3 TWA Total dust.	5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
Silicone Resin	None	None	None	None
Filler	None	None	None	None
Oximino silane	None	None	None	None
Carbon black	3.5 mg/m3 TWA 3 mg/m3 TWA Inhalable fraction.	3.5 mg/m3 TWA	None	None

Engineering controls:

**Respiratory protection:** 

Eye/face protection:

Skin protection:

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

Use a NIOSH approved air-purifying respirator with an organic vapor cartridge. Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.

Safety goggles or safety glasses with side shields.

Butyl rubber gloves. Natural rubber gloves. Nitrile gloves. Impervious clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure: Boiling point/range: Melting point/ range: Specific gravity: Vapor density: Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: **Evaporation rate:** Solubility in water: Partition coefficient (n-octanol/water): VOC content:

paste black Mild Not available Not applicable < 5 mm hg (20 °C (68°F)) Not applicable Not available 1.3 at 20 °C (68°F) Heavier than air. > 93 °C (> 199.4 °F) Tagliabue closed cup Not applicable Not applicable Not available Not available Polymerises in presence of water. Not available 3.31 %; 40.69 g/l

#### **10. STABILITY AND REACTIVITY**

Stability:
------------

Stable

Hazardous reactions:

Will not occur.

formed during cure.

Hazardous decomposition products:

Incompatible materials:

Conditions to avoid:

Polymerizes on contact with water.

Moisture.

## **11. TOXICOLOGICAL INFORMATION**

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)	
Silicone Resin	No	No	No	
Reinforcing Filler	No	No	No	
Silicone Resin	No	No	No	
Filler	No	No	No	
Oximino silane	No	No	No	
Carbon black	No	Group 2B	No	
Hazardous components		Health Effects/Targe	et Organs	
Silicone Resin		No Target Organs		
Reinforcing Filler		Nuisance dust		
Silicone Resin		Irritant		

## **12. ECOLOGICAL INFORMATION**

**Ecological information:** 

Filler

Oximino silane

Carbon black

No specific studies have been conducted by Henkel on the ecotoxicity or environmental fate of this material; however, commonly available data on the material indicate that uncontrolled releases to soil, ground water, or surface waters could entail acute and/or chronic ecological effects, depending on the quantity and concentration of such releases. Releases of volatile components to the atmosphere are not believed to entail significant ecological consequences provided such releases are within the exposure levels set forth in this document. Accordingly, all appropriate measures should be taken to avoid uncontrolled releases to the environment, and any spills or other uncontrolled releases which may occur should be contained and cleaned up immediately in accordance with Section 6.

No Target Organs

Irritant, Allergen Respiratory, Some evidence of carcinogenicity

Oxides of carbon. Oxides of silicon. Formaldehyde. Methyl ethyl ketoxime

#### **13. DISPOSAL CONSIDERATIONS**

Information provided is for unused product only.

Recommended method of disposal:Cured rubber can be incinerated or landfilled following EPA and local<br/>regulations.Hazardous waste number:Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Hazard class or division: Identification number: Packing group: <u>9 CFR)</u> Not regulated None None None

International Air Transportation (ICAO/IATA)	
Proper shipping name:	Not regulated
Hazard class or division:	None
Identification number:	None
Packing group:	None
<u>Water Transportation (IMO/IMDG)</u> Proper shipping name: Hazard class or division: Identification number: Packing group: Exceptions:	Not regulated None None None None

# **15. REGULATORY INFORMATION**

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status:	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12(b) Export Notification:	None above reporting de minimus
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA 313:	None above reporting de minimus Immediate Health, Delayed Health None above reporting de minimus
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer.
Canada Regulatory Information	
CEPA DSL/NDSL Status:	One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.
WHMIS hazard class: D.2.A, D.2.B	