

1		2		3		4		5																																																																																					
								RoHS COMPLIANT																																																																																					
MARKING: E315658 AWM 2651 VW-1 105°C 300V 28 AWG NELTRON CSA AWM I A FT1 FT2 105°C 300V 28 AWG 244239																																																																																													
			<table><thead><tr><th>Code NO.</th><th>A(mm)</th><th>B(mm)</th><th>Code NO.</th><th>A(mm)</th><th>B(mm)</th><th>CONDUCTOR SIZE: 28AWG 7/0.12MM^{+0.003}₀</th></tr></thead><tbody><tr><td>830-127-04C-XXX</td><td>3.81±0.10</td><td>5.08±0.10</td><td>830-127-22C-XXX</td><td>26.67±0.15</td><td>27.94±0.15</td><td>PH: 1.27±0.08mm</td></tr><tr><td>830-127-06C-XXX</td><td>6.35±0.15</td><td>7.62±0.15</td><td>830-127-24C-XXX</td><td>29.21±0.15</td><td>30.48±0.15</td><td>T: 0.90±0.10mm</td></tr><tr><td>830-127-08C-XXX</td><td>8.89±0.15</td><td>10.16±0.15</td><td>830-127-25C-XXX</td><td>30.48±0.15</td><td>31.75±0.15</td><td>Marking Length: 260±20mm</td></tr><tr><td>830-127-09C-XXX</td><td>10.16±0.15</td><td>11.43±0.15</td><td>830-127-26C-XXX</td><td>31.75±0.15</td><td>33.02±0.15</td><td>Space Between: 70±20mm</td></tr><tr><td>830-127-10C-XXX</td><td>11.43±0.15</td><td>12.70±0.15</td><td>830-127-30C-XXX</td><td>36.83±0.15</td><td>38.10±0.15</td><td>[I2-I1]=I<0.15mm</td></tr><tr><td>830-127-12C-XXX</td><td>13.97±0.15</td><td>15.24±0.15</td><td>830-127-34C-XXX</td><td>41.91±0.20</td><td>43.18±0.20</td><td>[S2-S1]=S<0.15mm</td></tr><tr><td>830-127-14C-XXX</td><td>16.51±0.15</td><td>17.78±0.15</td><td>830-127-36C-XXX</td><td>44.45±0.20</td><td>45.72±0.20</td><td></td></tr><tr><td>830-127-15C-XXX</td><td>17.78±0.15</td><td>19.05±0.15</td><td>830-127-40C-XXX</td><td>49.53±0.20</td><td>50.80±0.20</td><td></td></tr><tr><td>830-127-16C-XXX</td><td>19.05±0.15</td><td>20.32±0.15</td><td>830-127-50C-XXX</td><td>62.23±0.20</td><td>63.50±0.20</td><td></td></tr><tr><td>830-127-18C-XXX</td><td>21.59±0.15</td><td>22.86±0.15</td><td>830-127-60C-XXX</td><td>74.93±0.20</td><td>76.20±0.20</td><td></td></tr><tr><td>830-127-20C-XXX</td><td>24.13±0.15</td><td>25.40±0.15</td><td>830-127-64C-XXX</td><td>80.01±0.20</td><td>81.28±0.20</td><td></td></tr></tbody></table>							Code NO.	A(mm)	B(mm)	Code NO.	A(mm)	B(mm)	CONDUCTOR SIZE: 28AWG 7/0.12MM ^{+0.003} ₀	830-127-04C-XXX	3.81±0.10	5.08±0.10	830-127-22C-XXX	26.67±0.15	27.94±0.15	PH: 1.27±0.08mm	830-127-06C-XXX	6.35±0.15	7.62±0.15	830-127-24C-XXX	29.21±0.15	30.48±0.15	T: 0.90±0.10mm	830-127-08C-XXX	8.89±0.15	10.16±0.15	830-127-25C-XXX	30.48±0.15	31.75±0.15	Marking Length: 260±20mm	830-127-09C-XXX	10.16±0.15	11.43±0.15	830-127-26C-XXX	31.75±0.15	33.02±0.15	Space Between: 70±20mm	830-127-10C-XXX	11.43±0.15	12.70±0.15	830-127-30C-XXX	36.83±0.15	38.10±0.15	[I2-I1]=I<0.15mm	830-127-12C-XXX	13.97±0.15	15.24±0.15	830-127-34C-XXX	41.91±0.20	43.18±0.20	[S2-S1]=S<0.15mm	830-127-14C-XXX	16.51±0.15	17.78±0.15	830-127-36C-XXX	44.45±0.20	45.72±0.20		830-127-15C-XXX	17.78±0.15	19.05±0.15	830-127-40C-XXX	49.53±0.20	50.80±0.20		830-127-16C-XXX	19.05±0.15	20.32±0.15	830-127-50C-XXX	62.23±0.20	63.50±0.20		830-127-18C-XXX	21.59±0.15	22.86±0.15	830-127-60C-XXX	74.93±0.20	76.20±0.20		830-127-20C-XXX	24.13±0.15	25.40±0.15	830-127-64C-XXX	80.01±0.20	81.28±0.20	
Code NO.	A(mm)	B(mm)	Code NO.	A(mm)	B(mm)	CONDUCTOR SIZE: 28AWG 7/0.12MM ^{+0.003} ₀																																																																																							
830-127-04C-XXX	3.81±0.10	5.08±0.10	830-127-22C-XXX	26.67±0.15	27.94±0.15	PH: 1.27±0.08mm																																																																																							
830-127-06C-XXX	6.35±0.15	7.62±0.15	830-127-24C-XXX	29.21±0.15	30.48±0.15	T: 0.90±0.10mm																																																																																							
830-127-08C-XXX	8.89±0.15	10.16±0.15	830-127-25C-XXX	30.48±0.15	31.75±0.15	Marking Length: 260±20mm																																																																																							
830-127-09C-XXX	10.16±0.15	11.43±0.15	830-127-26C-XXX	31.75±0.15	33.02±0.15	Space Between: 70±20mm																																																																																							
830-127-10C-XXX	11.43±0.15	12.70±0.15	830-127-30C-XXX	36.83±0.15	38.10±0.15	[I2-I1]=I<0.15mm																																																																																							
830-127-12C-XXX	13.97±0.15	15.24±0.15	830-127-34C-XXX	41.91±0.20	43.18±0.20	[S2-S1]=S<0.15mm																																																																																							
830-127-14C-XXX	16.51±0.15	17.78±0.15	830-127-36C-XXX	44.45±0.20	45.72±0.20																																																																																								
830-127-15C-XXX	17.78±0.15	19.05±0.15	830-127-40C-XXX	49.53±0.20	50.80±0.20																																																																																								
830-127-16C-XXX	19.05±0.15	20.32±0.15	830-127-50C-XXX	62.23±0.20	63.50±0.20																																																																																								
830-127-18C-XXX	21.59±0.15	22.86±0.15	830-127-60C-XXX	74.93±0.20	76.20±0.20																																																																																								
830-127-20C-XXX	24.13±0.15	25.40±0.15	830-127-64C-XXX	80.01±0.20	81.28±0.20																																																																																								
830-127-XXC-XXX Blank: 100Feet/Roll 250: 250Feet/Roll 500: 500Feet/Roll Number Pin 1.27mm Pitch Type			<table><tr><td>F</td><td></td><td></td><td></td><td rowspan="2">DRAWN: Jiang</td><td rowspan="2">GENERAL TOLERANCE: .X=±0.2 .XX=±0.15</td><td rowspan="2"> 繼德工業股份有限公司 Neltron Industrial Co., Ltd.</td></tr><tr><td>E</td><td></td><td></td><td></td></tr><tr><td>D</td><td></td><td></td><td></td><td rowspan="2">CHECKED: Ruby</td><td rowspan="2">UNIT: MM SCALE:</td><td rowspan="2">DESCRIPTION: FLAT CABLE ASSEMBLY</td></tr><tr><td>C</td><td></td><td></td><td></td></tr><tr><td>B</td><td></td><td></td><td></td><td rowspan="2">APPROVAL: Mike Wu</td><td rowspan="2">SHEET: 1 / 1</td><td rowspan="2">PART NO: 830-127-XXC-XXX</td></tr><tr><td>A</td><td>10-AUG-2010</td><td>(PC0001)</td><td>Jiang</td></tr><tr><td>REV</td><td>DATE</td><td>FILE</td><td>BY</td><td></td><td>PROJECTION: </td><td>SIZE A4</td></tr></table>							F				DRAWN: Jiang	GENERAL TOLERANCE: .X=±0.2 .XX=±0.15	繼德工業股份有限公司 Neltron Industrial Co., Ltd.	E				D				CHECKED: Ruby	UNIT: MM SCALE:	DESCRIPTION: FLAT CABLE ASSEMBLY	C				B				APPROVAL: Mike Wu	SHEET: 1 / 1	PART NO: 830-127-XXC-XXX	A	10-AUG-2010	(PC0001)	Jiang	REV	DATE	FILE	BY		PROJECTION:	SIZE A4																																												
F				DRAWN: Jiang	GENERAL TOLERANCE: .X=±0.2 .XX=±0.15	繼德工業股份有限公司 Neltron Industrial Co., Ltd.																																																																																							
E																																																																																													
D				CHECKED: Ruby	UNIT: MM SCALE:	DESCRIPTION: FLAT CABLE ASSEMBLY																																																																																							
C																																																																																													
B				APPROVAL: Mike Wu	SHEET: 1 / 1	PART NO: 830-127-XXC-XXX																																																																																							
A	10-AUG-2010	(PC0001)	Jiang																																																																																										
REV	DATE	FILE	BY		PROJECTION:	SIZE A4																																																																																							