



Our Milestones

Since its establishment in 1925 in Wisconsin, United States, the Blue-Point Tool Company has come a long way from when it first started out with a vision to create the best wrench in the world. Today, it is known simply as Blue-Point – and for hand tools that offer customers unparalleled Quality, Performance and Value. With a focus on the automotive industry, Blue-Point provides customers with a wide range of tools to suit their diverse needs. The company is also constantly on the lookout for ways to serve their customers better, and its innovative Blue-Point truck serves as a shining example of that.





2015 Significant expansion of new product range.

1945
Forged Steel Products
Company merged with
Snap-on Tools, Inc.





Contents

1	MASTER TOOL SETS	1	2 TOOLS STORAGE

89

155

201

- Modular Foam Kits
- Sets Building

TCHETS. SOCKETS 45

- 1/4"
- 3/8"
- 1/2"
- 3/4"
- 1"

WRENCHES

- Combination
- Adjustable
- Box
- Double Open End

- Special Wrenches
- Ratchet Combination
- T-Shape
- T & L Hex / L Torx

- Accessories
 - Roll Carts / Workstation

27

79

End Cabinets & Lockers . Tool Boxes / Tool Bags

TORQUE TOOLS

- **Torque Wrench**
- Adjustable

Roll Cabinets

Top Chests

- Preset Click-Type
- Electronic Type
- Torque Testers
- Checkers

PLIERS & CUTTERS 111

- Pliers Sets / Standard & Mini
- Cutters
- Miniature
- Locking
- Retaining Ring
- Circlip Standard
- Miniature & Special

SCREWDRIVERS 129 & BITS

- Screwdrivers
- Bits

STRIKING & CUTTING TOOLS 8

139

- Hammers
- Punches & Chisels
- Files
- Cutting Tools
- Scrapers

MEASURING & PECTION TOOLS

183

209

- Pneumatic Tools
- Impact Wrenches
- Drills / Ratchets
- Die Grinders Grinders
- Cut-off / Cutting Tools
- Sanders & Finishing Tools
- Impact Screwdrivers
- Accessories

- Measuring
- Lighting
- Battery & Testing

INSULATED TOOLS

POWER TOOLS

- Modular Foam Kits
- Set Buildings
- Wrenches
- **Cutting Tools**
- Cutters
- Pliers

AUTOMOTIVE WORKSHOP TOOLS

- Pick-up Tools
- Creepers
- Safety Equipment
- Hose Reels
- Floor Jacks
- Hydraulic Jacks
- Jack Stands
- Wheel Dolly
- Ballon Jacks
- Bottle Jacks
- Transmission

Jacks

- **Engine Cranes**
- Workbench
- Specialty Tools
- Riveters / Extractors
- Grease Guns / Spray Guns
- Bench Vise
- Pry Bars / C-Clamps
- Airconditioning Services
- Wheels & Tires
- Cooling & Oil Systems
- Steering & Brakes
- Engines
- Cleaning











Double Open End Wrench Set

BPS1A

CONTENTS

Set in modular foam kit

Double Open End Wrenches

6x7, 8x9, 10x11, 12x13, 14x15, 16x17, 18x19, 20x22, 21x23, 24x27, 30x32 mm



45° Double Ring Wrench Set

BPS2A

CONTENTS

Set in modular foam kit

45° Double Ring Wrenches

6x7, 8x9, 10x11, 12x13, 14x15, 16x17, 18x19, 20x22, 21x23, 24x27 mm



Packing: 1

Packing: 1

Packing: 1

75° Double Ring Wrench Set

BPS3A

CONTENTS Set in modular foam kit

75° Double Ring Wrenches 6x7, 8x9, 10x11, 12x13, 14x15, 16x17, 18x19, 20x22, 21x23, 24x27 mm



Combination Wrench Set

BPS4PA

 CONTENTS
 Set in modular foam kit

 Combination Wrenches
 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm



Ratcheting Combination Wrench Set

BPS5A

CONTENTS	Set in modular foam kit
Ratcheting Combination Wrenches	6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm



Adjustable Wrench Set

BPS6B

CONTENTS	Set in modular foam kit
Adjustable Wrenches	8", 10"
Curved Jaw Locking Plier	7"
Straight Jaw Locking Plier	7"



Standard Pliers Set

BPS7A

nodular foam kit	1
	ı

Packing: 1

Packing: 1

CONTENTS	Set in modular foam kit
Needle Nose Plier	6"
Diagonal Cutting Plier	6"
Combination Plier	8"
Slip Joint Plier	8"



Circlip Pliers Set

BPS8A



CONTENTS		Set in modular foam kit
External Circlip Plier, Straight	7"	
External Circlip Plier, 90°	7"	
Internal Circlip Plier, Straight	7"	
Internal Circlip Plier, 90°	7"	



Screwdrivers Set

BPS9A



CONTENTS	Set in modular foam kit
M Series Flat Tip	3.2x75, 5x100, 6x38, 6x150 mm
M Series Phillips® Tip	0x75, 1x75, 2x38, 2x100, 3x150 mm





^{**}BPS6A - for China & India only



1/4" Drive Socket Set

BPS10A Packing: 1

CONTENTS	Set in modular foam kit
Sockets	4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11,12,13 mm
Long Sockets	4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14 mm
Hex Socket Drivers	3, 4, 5, 6, 7, 8 mm
Flat Socket Drivers	4, 5.5, 6.5 mm
Phillips [®] Socket Drivers	#1, #2, #3
Pozidriv [®] Socket Drivers	#1, #2, #3
Torx [®] Socket Drivers	T8, T10, T15, T20, T25, T27, T30, T40
Quick Release Ratchet	1 pc.
Spinner Handle	1 pc.
Extension	2", 4"
Sliding T-handle	4.5"
Universal Joint	1 pc.
Flexible Extension	6"
Hex Bit Holder	1/4" Hex
Adaptor	1/4" * 3/8"



3/8" Drive Socket Set

BPS11A

Packing: 1

CONTENTS	Set in modular foam kit
Sockets	6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24 mm
Long Sockets	10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm
Quick Release Ratchet	1 pc.
Spark Plug Sockets	16, 21 mm
Sliding T-handle	6"
Adaptor	3/8" * 1/4"
Universal Joint	1 pc.
Locking Extension	3"



1/2" Drive Socket Set

BPS12A Packing: 1

CONTENTS	Set in modular foam kit
Sockets	10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 24, 27, 30, 32, 34 mm
Long Sockets	10, 13, 17, 19 , 22 mm
Quick Release Ratchet	1 pc.
Sliding T-handle	10"
Universal Joint	1 pc.
Locking Extension	6"



Impact Socket Set

BPS13A Packing: 1

CONTENTS	Set in modular foam kit
1/2" Impact Sockets	10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 24, 27, 30, 32 mm
3/8" Impact Sockets	7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm
Impact Extensions	3/8" Drive x 3", 1/2" Drive x 5"
Drive Adaptors	3/8"M * 1/4"F
Impact Adaptors	3/8"M * 1/2"F, 1/2"M * 3/8"F, 1/2"M * 3/4"F
Universal Joints	1/2" Drive



L-Shape Wrench Set

BPS14A

CONTENTS	Set in modular foam kit
Ball Hex Keys Set	1.5, 2, 2.5, 3, 4, 5, 6, 8, 10 mm
L-Shape Torx Wrench Set	T10, T15, T20, T25, T27, T30, T40, T45, T50
L-Shape Hex Keys	12, 14, 17, 19 mm



Packing: 1

Packing: 1

Packing: 1

Single Direction Combination Wrench Set

BPS15A

CONTENTS	Set in modular foam kit
Ratchet Combination Wrenches	6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm



L-Shape Long Torx Wrench Set

BPS16A

CONTENTS	Set in modular foam kit
Folding Hex Key Set	1.5, 2, 2.5, 3, 4, 5, 6, 8 mm
Extra Long Arm Torx Key Set	T10, T15, T20, T25, T27, T30, T40, T45, T50
Extra Long Ball End Hex Key Set	1.5, 2, 2.5, 3, 4, 5, 6, 8, 10 mm



File Set

BPS17A

CONTENTS	Set in modular foam kit
Half Round Second Files	6", 8"
Round Second Files	6", 8"
Flat Second Files	6", 8"









Pliers Set

BPS18A

Packing: 1	

CONTENTS		Set in modular foam kit
Plastic Cutter	6"	
Combination Plier	6"	
Diagonal Plier	6"	
Long Nose Plier	6"	



Large Combination Wrench Set

BPS19A

Packing:	1

CONTENTS	Set in modular foam kit
Combination Wrenches	20, 21, 22, 23, 24 mm



Adjustable Wrench & Pliers Set

BPS20A

Packing:	: '
----------	-----

CONTENTS	Set in modular foam kit
Long Nose Plier	6"
Combination Plier	8"
Adjustable Wrenches	8", 12"



Hammers & Striking Tools Set

BPS21A



CONTENTS	Set in modular foam kit
Punch & Chisel Set	5 pcs
Ball Peen Hammer	8 oz
Soft Face Hammer	300 mm



Torx® M Series Screwdriver Set

BPS22A




	Set in modular foam kit
TX6, TX7, TX8, TX9	
TX10, TX15, TX20, TX25	



VDE Screwdriver Set

BPS23A

CONTENTS	Set in modular foam kit
VDE Phillips® Screwdrivers	0×60, 1×80, 2×100, 3×150
VDE Slotted Screwdrivers	2.5×75, 4×100, 5.5×125, 6.5×150



Packing: 1

VDE Pliers Set

BPS24A

CONTENTS	Set in modular foam kit
VDE Nose Plier	6"
VDE Diagonal Plier	6"
VDE Stripping Plier	6"
VDE Combination Plier	7"
VDE Adjustable Joint Plier	10"



Double Ring, Single Direction, Ratcheting Wrench

BPS25B

CONTENTS	Set in modular foam kit
Ratcheting Wrenches, Double Ring	6×7, 8x9, 10x11, 12x13, 14x15, 17x19 18x20, 21x22, 23x24 mm



Pass-Through Screwdriver Set

BPS26A

CONTENTS	Set in modular foam kit
Pass-Through Screwdrivers, Phillips®	PH2x100, PH2x150, PH3x150, PH3x200
Pass-Through Screwdrivers, Slotted	SL6x100, SL6x150, SL8x150



Precision Screwdriver Set

BPS27A

CONTENTS	Set in modular foam kit
Precision Screwdrivers, Phillips®	PH0, PH00, PH000
Precision Screwdrivers, Torx®	T6, T8
Precision Screwdrivers, Slotted	SL1.4, SL2, SL2.4, SL3







Flare Nut Wrench Set

BPS28A Packing: 1

CONTENTS	Set in modular foam kit
Flare Nut Wrenches	8x10, 9x11, 13x14, 15x17, 17x19 mm



Combination Flex Socket Wrench Set

BPS29A Packing: 1

CONTENTS	Set in modular foam kit
Combination Flex Socket Wrenches	10, 13, 14, 17, 19 mm



Double Flex Socket Wrench Set

BPS30A

Packing: 1

CONTENTS	Set in modular foam kit
Double Flex Socket Wrenches	6x7, 8x9, 10x11, 16x17, 18x19 mm



Flex Flare Nut Wrench Set

BPS31A Packing: 1

CONTENTS	Set in modular foam kit
Flex Flare Nut Wrenches	10x11, 12x13, 14x17, 19x22 mm



1/4", 3/8" & 1/2" Drive Automotive Tool Set, 150pcs

BLPATSCM150 Packing: 1

CONTENTS		Set in storage ca
1/4" DRIVE:		
Standard Sockets	11 pcs.	4, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13 mm
Long Sockets	9 pcs.	4, 5, 6, 7, 8, 9, 10, 11, 12 mm
Quick Release Ratchet	1 pc.	
Extension Bar	1 pc.	4"
Spinner Handle	1 pc.	
Universal Joint	1 pc.	
Bit Holder	1 pc.	
Tamper Resistant Torx® Socket Drivers	6 pcs.	T10, T15, T20, T25, T27, T30
Torx® Socket Drivers	7 pcs.	T10, T15, T20, T25, T27, T30, T40
3/8" DRIVE:		
Standard Sockets	12 pcs.	8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm
Long Sockets	10 pcs.	8, 9, 10, 11, 12, 13, 14, 15, 17, 19 mm
External Torx® Sockets	8 pcs.	E8, E10, E11, E12, E14, E16, E18, E20
Spark Plug Sockets	2 pcs.	16, 21 mm
Quick Release Ratchet	1 pc.	
Universal Joint	1 pc.	
Adaptor	1 pc.	3/8"F * 1/2"M
Extension Bars	2 pcs.	3", 6"
Flat Socket Drivers	3 pcs.	5.5, 6.5, 8 mm
Phillips® Socket Drivers	2 pcs.	#1, #2
Hex Socket Drivers	4 pcs.	3, 4, 5, 6 mm
Torx® Socket Drivers	7 pcs.	T10, T15, T20, T25, T27, T30, T40
1/2" DRIVE:		
Standard Sockets	11 pcs.	14, 17, 18, 19, 20, 21, 22, 24, 27, 30, 32 mm
Long Sockets	9 pcs.	12, 13, 14, 15, 17, 18, 19, 21, 22 mm
Impact Sockets	4 pcs.	17, 19, 21, 23 mm
Extension Bars	2 pcs.	5", 10"
Quick Release Ratchet	1 pc.	
Universal Joint	1 pc.	
3-Way Adaptor	1 pc.	3/8"F * 1/2"M
TOOLS:		
M Series Screwdrivers	2 pcs.	Phillips® #2×38mm, Slotted #6×38mm
Pass-Through Screwdrivers	2 pcs.	Phillips® #2×100mm, Slotted #6×100mm
Double Ring Ratcheting Wrenches	3 pcs.	8×10, 12×14, 17×19 mm
Combination Wrenches	12 pcs.	8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm
L-Shape Hex Keys Wrench Set	1 set	
Long Nose Plier	1 pc.	6"

1 pc.





Slip Joint Plier



1/4", 3/8" & 1/2" Drive Socket & Tool Set, 128pcs

BLPATSCM128 Packing: 1

CONTENTS	Set in storage case
1/4" DRIVE:	
Standard Sockets 6-Point	10 pcs. 4 to 13 mm
Deep Sockets 6-Point	10 pcs. 4 to 13 mm
Flat Socket Drivers	3 pcs. 4, 5.5, 6.5 mm
Hex Socket Drivers	6 pcs. 3, 4, 5, 6, 7, 8 mm
Phillips® Socket Drivers	4 pcs. #0, #1, #2, #3
Tamper Resistant Torx® Socket Drivers	7 pcs. T10, T15, T20, T25, T27, T30, T40
Pozidriv® Socket Drivers	4 pcs. #0, #1, #2, #3
Quick Release Ratchet Handle	1 pc.
Spinner Handle	1 pc. 6"
Extension Bars	2 pcs. 38, 75 mm
Universal Joint	1 pc.
Flexible Handle	1 pc. 6"
Bit Adaptor	1 pc. 1/4"F * 1/4"H
Hex Bit Sockets	5 pcs. 1/8", 5/32", 3/16", 7/32", 1/4"
Flat Bit Sockets	4 pcs. 7/32", 3/16", 1/4", 9/32"
Torx® Bit Sockets	8 pcs. T8, T10, T15, T20, T25, T27, T30, T40
Bit Adaptor	1 pc.
3/8" DRIVE:	
Standard Sockets 6-Point	10 pcs. 10 to 19 mm
Deep Sockets 12-Point	10 pcs. 10 to 19 mm
Quick Release Ratchet Handle	1 pc.
Extension Bars	3 pcs. 75, 150, 250 mm
Flexible Handle	1 pc. 10"
Universal Joint	1 pc.
Spark Plug Sockets 6-Point	2 pcs. 16, 21 mm
Adaptor	1 pc. 3/8"F * 1/4"M
Sliding Bar	1 pc. 8"
1/2" DRIVE:	
Standard Sockets 6-Point	6 pcs. 20, 21, 22, 24, 27, 32 mm
Impact Sockets 6-Point	8 pcs. 14, 15, 16, 17, 18, 19, 21, 22 mm
Quick Release Ratchet Handle	1 pc.
Extension Bar	1 pc. 125 mm
Coupler	1 pc. 1/4"F * 1/4"H
TOOLS:	
Ratcheting Wrenches	4 pcs. 13, 14, 15, 17 mm
	9 pcs. 1.5, 2, 2.5, 3, 4, 5, 6, 8, 10 mm



1/4", 3/8" & 1/2" Drive Automotive Tool Set, 120pcs

BLPATSCM120 Packing: 1

CONTENTS	Set in storage case
1/4" DRIVE:	
Standard Sockets	10 pcs. 4, 5, 6, 7, 8, 9, 10, 11, 12, 13 mm
Deep Sockets	4 pcs. 8, 9, 10, 12 mm
Ratchet	1 pc.
Spinner Handle	1 pc.
Extension Bar	1 pc. 3"
Coupler	1 pc. 1/4" F * 1/4" H
Universal Joint	1 pc.
Hex Bit Sockets	6 pcs. 3, 4, 5, 6, 7, 8 mm
Flat Bit Sockets	3 pcs. 4, 5.5, 6.5 mm
Phillips [®] Bit Sockets	3 pcs. #1, #2, #3
Pozidriv® Bit Sockets	2 pcs. #1, #2
Torx® Bit Sockets	7 pcs. TT10, TT15, TT20, TT25, TT27, TT30, TT40
3/8" DRIVE:	
Standard Sockets	10 pcs. 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm
Deep Sockets 12-Point	4 pcs. 13, 14, 15, 17 mm
External Torx® Sockets	8 pcs. E8, E10, E11, E12, E14, E16, E18, E20
Ratchet	1 pc.
Extension Bars	2 pcs. 3", 6"
Spark Plug Sockets	2 pcs. 16, 21 mm
Universal Joint	1 pc.
Adaptor	1 pc. 3/8"F * 1/4"M
Sliding Handle	1 pc. 8"
1/2" DRIVE:	
Standard Sockets 6-Point	6 pcs. 20, 21, 22, 24, 27, 32 mm
Impact Sockets	4 pcs. 17, 19, 21, 23 mm
Ratchet	1 pc.
Extension Bars	2 pcs. 5", 10"
Universal Joint	1 pc.
Adaptor	1 pc. 1/2"F * 3/8"M
TOOLS:	
Adjustable 3-Claw Oil Wrench	1 pc.
Test Pen	1 pc.
Hex Key 9pcs Set	1 set
Bit Set	20 pcs.
Combination Wrenches	11 pcs. 8, 9, 10, 11, 12, 13, 14, 16, 17, 18, 19 mm
Socket for Air Cylinder	1 pc. T52







1/4", 3/8" & 1/2" Drive Socket & Wrench Set, 100pcs

BLPATSCM100 Packing: 1

CONTENTS	Set in storage case
1/4" DRIVE:	
Standard Sockets	10 pcs. 4, 5, 6, 7, 8, 9, 10, 11, 12, 13 mm
Deep Sockets	10 pcs. 4, 5, 6, 7, 8, 9, 10, 11, 12, 13 mm
Quick Release Ratchet Handle	1 pc.
Spinner Handle	1 pc.
Extension Bars	2 pcs. 1-1/2", 3"
Universal Joint	1 pc.
Flexible Handle	1 pc. 6"
Hex Bit Sockets	6 pcs. 3, 4, 5, 6, 7, 8 mm
Flat Bit Sockets	3 pcs. 4, 5.5, 6.5 mm
Phillips® Bit Sockets	4 pcs. #0, #1, #2, #3
Pozidriv® Bit Sockets	4 pcs. #0, #1, #2, #3
Tamper Torx® Bit Sockets	7 pcs. TT10, TT15, TT20, TT25, TT27, TT30, TT40
3/8" DRIVE:	
Standard Sockets 6-Point	10 pcs. 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm
Deep Sockets 12-Point	10 pcs. 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm
Quick Release Ratchet	1 pc.
Spark Plug Sockets	2 pcs. 16, 21 mm
Extension Bars	3 pcs. 3", 6", 10"
Universal Joint	1 pc.
Flexible Handle	1 pc. 10"
Adaptor	1 pc. 3/8"F * 1/4"M
Sliding T-Handle	1 pc. 8"
1/2" DRIVE:	
Standard Sockets 12-Point	6 pcs. 20, 21, 22, 24, 27, 32 mm
Impact Sockets 6-Point	8 pcs. 14, 15, 16, 17, 18, 19, 21, 22 mm
Ratchet Handle	1 pc.
Extension Bar	1 pc. 5"
WRENCH:	
Ratcheting Wrenches	4 pcs. 13, 14, 15, 17 mm



1/4", 3/8" & 1/2" Drive Torx® Bit Socket Set, 43pcs

BLPTSSC43 Packing: 1

CONTENTS	Set in storage case
1/4" DRIVE:	
External Torx® Sockets	5 pcs. E4, E5, E6, E7, E8
Tamper Resistant Torx® Socket Drivers	10 pcs. T6 to T10, T15, T20, T25, T27, T30
Tamper Resistant Long Torx® Socket Drivers	10 pcs. T6 to T10, T15, T20, T25, T27, T30
3/8" DRIVE:	
External Torx® Sockets	4 pcs. E10, E12, E14, E16
Tamper Resistant Torx® Socket Drivers	3 pcs. T40, T45, T50
Tamper Resistant Long Torx® Socket Drivers	3 pcs. T40, T45, T50
1/2" DRIVE:	
External Torx® Sockets	4 pcs. E18, E20, E22, E34
Tamper Resistant Torx® Socket Drivers	2 pcs. T55, T60
Tamper Resistant Long Torx® Socket Drivers	2 pcs. T55, T60



1/4" & 3/8" Drive Socket Set, 155pcs

BLPGSSC155 Packing: 1

CONTENTS	Set in storage case
1/4" DRIVE:	
Standard Sockets	10 pcs. Fractional, 3/16" to 9/16" 13 pcs. Metric, 4 to 14 mm
Deep Sockets	10 pcs. Fractional, 3/16" to 9/16" 11 pcs. Metric, 4 to 14 mm
1/4" Hex Bits With Bit Holders	20 pcs. Assorted
Ratchet / Socket Accessories	5 pcs.
Quick Release Ratchet	1 pc.
3/8" DRIVE:	
Standard Sockets	13 pcs. Fractional, 1/4" to 1" 19 pcs. Metric, 6 to 24 mm
Deep Sockets	11 pcs. Fractional, 3/8" to 1" 15 pcs. Metric, 10 to 24 mm
External Torx® Sockets	11 pcs. E4 to E20
Spark Plug Sockets	2 pcs. 5/8", 13/16"
Hex Socket Drivers	3 pcs. Metric, 7, 8, 10 mm
Tamper Resistant Torx® Socket Drivers	4 pcs. T40, T45, T50, T55
Ratchet / Socket Accessories	6 pcs.
Quick Release Ratchet	1 pc.
Spinner Handle	1 pc.









1/4" & 1/2" Drive Socket & Tool Set, 78pcs

BLPGSSCM78 Packing: 1

CONTENTS	Set in storage case
1/4" DRIVE:	
Standard Sockets	12 pcs. 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13 mm
Quick Release Ratchet	1 pc.
Spinner Handle	1 pc.
Extension Bar	1 pc. 4"
Coupler	1 pc. 1/4"F * 1/4"H
1/2" DRIVE:	
Standard Sockets	21 pcs. 8 to 24, 27, 30, 32, 34 mm
Quick Release Ratchet	1 pc.
Spark Plug Sockets	2 pcs. 16, 21 mm
Extension Bars	3 pcs. 3", 6", 10"
3-way Adaptor	1 pc. 3/8"F * 1/2"M
TOOLS:	
Hex Bit Sockets	4 pcs. 3, 4, 5, 6 mm
Phillips® Bit Sockets	4 pcs. #0, #1, #2, #3
Square Bit Sockets	2 pcs. S1, S2
Flat Bit Sockets	3 pcs. 4, 5, 5.5 mm
Torx [®] Bit Sockets	7 pcs. T8, T10, T15, T20, T25, T27, T30
Combination Wrenches	10 pcs. 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm
Side Cutter	1 pc. 7"
Long Nose Plier	1 pc. 6"
Slip Joint Plier	1 pc. 10"
Adjustable Wrench	1 pc. 8"



1/4" & 1/2" Drive Socket & Tool Set







1/4" Drive Automotive Tool Set, 38pcs

BLPATSCM38 Packing: 1

CONTENTS	Set in storage case
1/4" DRIVE:	
Standard Sockets	14 pcs. 3.5, 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13, 14 mm
Extension Bars	2 pcs. 2", 4"
Quick Release Ratchet	1 pc.
Spinner Handle	1 pc.
Universal Joint	1 pc.
Sliding T-Handle	1 pc.
Torx® Socket Drivers	6 pcs. T10, T15, T20, T25, T30, T40
Hex Socket Drivers	5 pcs. 3, 4, 5, 6, 8 mm
Phillips® Socket Drivers	2 pcs. #1, #2
Pozidrive® Socket Drivers	2 pcs. PZ1, PZ2
Flat Tip Socket Drivers	3 pcs. 4, 5.5, 6.5 mm



1/4" Drive Socket Set, 29pcs

BLPATSM1429 Packing: 1

CONTENTS	Set in storage case
1/4" DRIVE:	
Standard Sockets 6-Point.	13 pcs. 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13, 14 mm
Deep Sockets 6-Point.	11 pcs. 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14 mm
Quick Release Ratchet	1 pc.
Spinner Handle	1 pc.
Extension Bars	2 pcs. 3", 6"
Universal Joint	1 pc.



1/4" Drive Socket Set, 62pcs

BLPGSS1462

CONTENTS	Set in storage case
1/4" DRIVE:	
Standard Sockets	11 pcs. Fractional, 3/16" to 5/8" 11 pcs. Metric, 4 to 14 mm
Deep Sockets	11 pcs. Fractional, 3/16" to 5/8" 11 pcs. Metric, 4 to 14 mm
Bit Holder	1 pc.
Hex Bits	4 pcs. 9/64", 3/16", 7/32", 1/4"
Flat Tip Bits	3 pcs. 5/32", 3/16", 1/4"
Phillips® Bits	2 pcs. #1, #2
Ratchet / Socket Accessories	7 pcs.
Ratchet	1 pc.





1/4" Drive Socket Set, 51pcs

BLPGSS1451A

CONTENTS	Set in storage case
1/4" DRIVE:	
Standard Sockets	10 pcs. Fractional, 3/16" to 9/16" 13 pcs. Metric, 4 to 14 mm
Sockets 8-Point	3 pcs. Fractional, 1/4", 5/16", 3/8"
Torx® Socket Drivers	6 pcs. T8 to T27
Hex Socket Drivers	6 pcs. Fractional, 1/8" to 5/16"
Flat Tip Socket Drivers	3 pcs. 5/32", 7/32", 9/32"
Phillips [®] Socket Drivers	3 pcs. #0, #1, #2
Ratchet / Socket Accessories	6 pcs.
Ratchet	1 pc.





1/4" Drive Socket Set, 46pcs

BLP1446SI

CONTENTS	Set in storage case
1/4" DRIVE:	
Sockets 6-Point	13 pcs. 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13, 14 mm
Bit Sockets	3 pcs. 4, 5.5, 7 mm
Hex Bit Sockets	6 pcs. 3, 4, 5, 6, 7, 8 mm
Hex Torx® Bit Sockets	7 pcs. T8, T10, T15, T20, T25, T30, T40
Phillips® Bits	3 pcs. #1, #2, #3
Pozidriv® Sockets	3 pcs. PZ1, PZ2, PZ3
Ratchet Handle	1 pc.
Extenion Bars	2 pcs. 2", 4"
Flexible Extension	1 pc. 150 mm
Sliding T-Handle	1 pc.
Universal Joint	1 pc.
Spinner	1 pc.
Hex Keys	4 pcs. 1.27, 1.5, 2, 2.5 mm











1/4" Drive Socket Set, 27pcs

BLPGSS1427

Packing: 1

- Good for automotive and home use
- Range of deep and shallow sockets for common fastener applications
- Ratchet and Handle Driver both available for a variety of jobs

CONTENTS	Set in storage case
1/4" DRIVE:	
Shallow Sockets 6-Point	11 pcs. Fractional, 3/16" to 5/8"
Deep Sockets 6-Point	11 pcs. Fractional, 3/16" to 9/16"
Socket Adaptors / Extensions	3 pcs.
Quick Release Ratchet	1 pc.
Spinner Handle	1 pc.



1/4" Drive SAE Socket Set, 22pcs

BLPGSS1422

CONTENTS		Set in storage case
1/4" DRIVE:		
Standard Sockets 6-Point	11 pcs.	3/16", 7/32", 1/4", 9/32", 5/16", 11/32", 3/8" 7/16", 1/2", 9/16", 5/8"0
Deep Sockets 6-Point	11 pcs.	3/16", 7/32", 1/4", 9/32", 5/16", 11/32", 3/8", 7/16", 1/2", 9/16", 5/8"



1/4" Drive Stubby Bit Socket Set, 40pcs

BLPBSS40



CONTENTS	Set in storage case
1/4" DRIVE:	
Hex Drivers	10 pcs. Fractional 5/64", 3/32", 7/64", 1/8", 5/32", 3/16", 7/32", 1/4', 5/16", 3/8" 10 pcs. Metric 2, 2.5, 3, 4, 5, 6, 7, 8, 9, 10 mm
Torx® Tamper Proof Drivers	10 pcs. TP8, TP10, TP15, TP20, TP25, TP27, TP30, TP40, TP45, TP50
XZN Triple Square Drivers	6 pcs. XZN4, XZN5, XZN6, XZN8, XZN10, XZN12
Phillips® Drivers	2 pcs. #1, #2
Flat Tip Drivers	2 pcs. 1/4", 3/8"



3/8" Drive Socket Set, 77pcs

BLPATSM3877 Packing: 1

CONTENTS	Set in storage case
3/8" DRIVE:	
Standard Sockets 6-Point	19 pcs. 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24 mm
Deep Sockets 12-Point	19 pcs. 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24 mm
External Torx® Sockets	11 pcs. E4, E5, E6, E7, E8, E10, E12, E14, E16, E18, E20
Hex Bit Sockets	4 pcs. 6, 7, 8, 10 mm
Phillips® Bit Sockets	2 pcs. #3, #4
Pozidrive® Bit Sockets	2 pcs. #3, #4
Tamper Torx® Bit Sockets	8 pcs. TT10, TT15, TT20, TT25, TT27, TT30, TT40, TT45
Quick Release Ratchet	1pc.
Extension Bars	3 pcs. 3", 6", 10"
Spark Plug Sockets	2 pcs. 16, 21 mm
Universal Joint	1 pc.
Flexible Handle	1 pc. 10"
Adaptors	2 pcs. 3/8"F * 1/2"M, 3/8"F * 1/4"M
Spinner Handle	1 pc.
Sliding T-handle	1 pc. 8"



3/8" Drive Automotive Tool Set, 58pcs

BLPATSCM58 Packing: 1

CONTENTS	Set in storage case
3/8" DRIVE:	
Sockets	14 pcs. 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm
Quick Release Ratchet	1 pc.
Universal Joint	1 pc.
TOOLS:	
Long Arm Hex Key Wrench Set	1 set
Combination Wrenches	10 pcs. 8, 10, 11, 12, 13, 14, 15, 16, 18, 19 mm
Ratcheting Combination Wrench	1 pc. 17 mm
Adjustable Wrench	1 pc. 8"
M Series Screwdrivers	3 pcs. Slotted, #6x38 mm, #3.2x75 mm, #5x10 mm 4 pcs. Phillips®, #2x38 mm, #0x75 mm, #1x100 mm, #2x150 mm
Long Nose Plier	1 pc. 6"
Linesman Plier	1 pc. 8"
Snap Ring Plier Set	1 set
Measuring Tape	1 pc. 3 m
Blades Feeler Gauges, 20 pcs	1 pc. 0.02-1 mm
Stainless Steel Straight Ruler	1 pc. 150 mm
Fiberglass Ball Pein Hammer	1 pc. 16 oz
Pick Up Tool	1 pc. 380 mm
Utility Knife	1 pc. 18 mm
Compact Flashlight	1 pc.









3/8" Drive Socket Set, 24pcs

BLPATSM3824 Packing: 1

CONTENTS		Set in storage case
3/8" DRIVE:		
Standard Sockets 12-Point	10 pcs.	10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm
Deep Sockets 12-Point	10 pcs.	10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm
Quick Release Ratchet	1 pc.	
Extension Bar	1 pc.	3"
Spark Plug Sockets	2 pcs.	16, 21 mm



3/8" Drive Socket Set, 85pcs

BLPGSS3885 Packing: 1

CONTENTS	Set in storage case
3/8" DRIVE:	
Standard Sockets	13 pcs. Fractional, 1/4" to 1" 14 pcs. Metric, 6 to 19 mm
Deep Sockets	13 pcs. Fractional, 1/4" to 1" 14 pcs. Metric, 6 to 19 mm
External Torx® Sockets	11 pcs. E4 to E20
Phillips [®] Socket Driver	1 pcs. #3
Pozidriv® Socket Drivers	2 pcs. #3, #4
Tamper Resistant Torx® Socket Drivers	8 pcs. T10 to T45
Spark Plug Sockets	2 pcs. 5/8", 13/16"
Ratchet / Socket Accessories	4 pcs.
Ratchet	1 pc.
Breaker Bar	1 pc.
Spinner Handle	1 pc.



3/8" Drive Socket Set, 49pcs

BLPGSS3849

Packing: 1

CONTENTS	Set in storage case
3/8" DRIVE:	
Standard Sockets 6-Point	8 pcs. Fractional, 5/16" to 3/4" 14 pcs. Metric, 6 to 19 mm
Deep Sockets 12-Point	8 pcs. Fractional, 5/16" to 3/4" 13 pcs. Metric, 7 to 19 mm
Extension Bars	2 pcs. 3", 6"
Universal Joint	1 pc.
Adaptor	1 pc. 3/8"F * 1/4"M
Ratchet	1 pc.



3/8" Drive Socket & Wrench Set, 37pcs

BLPGSS3837

Packing: 1

CONTENTS	Set in storage case
3/8" DRIVE:	
Standard Sockets 6-Point	8 pcs. Fractional, 5/16" to 3/4" 14 pcs. Metric, 6 to 19 mm
Double Open End Wrenches	4 pcs. Fractional, 5/16"-3/8", 7/16"-1/2", 9/16"-5/8", 11/16"-3/4" 5 pcs. Metric, 10-11, 12-13, 14-15, 16-17, 18-19 mm
Extension Bars	2 pcs. 3", 6"
Ratchet	1 pc.
Universal Joint	1 pc.
Adaptors	2 pcs. 1/4"F * 3/8"M, 3/8"F * 1/4"M



3/8"Pass Thru Socket Set, 22pcs

BLPPTSS3822

CONTENTS	Set in storage case
TOOLS:	
Sockets	BLPPTS38 thru BLPPTS34 (3/8" to 3/4")
Metric Sockets	BLPPTSM8 thru BLPPTSM19 (8 to 19 mm)
Pass Thru Adaptor	BLPPTA3438
Extension Bars	BLPPTEXT3
Ratchet	BPRFPT10









Packing: 1

Packing: 1

3/8" Drive Impact Socket Set, 13pcs

BLPATSIMM3813

- Catered to Complement 3/8" Impact Wrenches
- Automotive and Two-Wheelers Workshops
- Compact Set with Only Commonly Used Sizes
- Complements existing BLPATSIMM1215 (1/2")

CONTENTS	Set in storage case
3/8" DRIVE:	
Shallow Impact Sockets	13 pcs. 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm



1/2" Drive Socket Set, 32pcs

BLPATSM1232

- For Automotive and General Fastener Tightening Jobs
- Improves on existing BLPATSM1225
- Includes smaller sizes 8, 9 & 23 mm sockets
- Additional range of 12-points sockets
- Universal Joint Added for more Applications

CONTENTS	Set in storage case
1/2" DRIVE:	
Sockets 6-Point	20 pcs. 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 27, 30, 32 mm
Sockets 12-Point	7 pcs. 8, 10, 12, 13, 14, 17, 19 mm
Ratchet	1 pc.
Extension Bars	2 pcs. 5", 10"
Universal Joint	1 pc.
Sliding Adaptor	1 pc. 1/2"F*3/8"M



1/2" Drive Socket Set, 25pcs

BLP1225SI

CONTENTS	Set in storage case
1/2" DRIVE:	
Sockets 6-Point	18 pcs. 8 to 22, 24, 27, 30, 32 mm
Spark Plug Sockets	2 pcs. 16, 21 mm
Ratchet Handle	1 pc.
Extension Bars	2 pcs. 5", 10"
Sliding T-Handle	1 pc.
Universal Joint	1 pc.



1/2" Drive Socket Set, 25pcs

BLPATSM1225

Packing: 1

CONTENTS	Set in storage case
1/2" DRIVE:	
Sockets 6-Point	19 pcs. 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 24, 27, 30, 32, 34, 36 mm
Quick Release Ratchet	1 pc.
Extension Bars	2 pcs. 5", 10"
3-way Adaptor	1 pc. 3/8"F * 1/2"M
Spark Plug Sockets	2 pcs. 16, 21 mm



1/2" Drive Socket Set, 33pcs

BLPGSS1233

Packing: 1

CONTENTS		Set in storage case
1/2" DRIVE:		
Standard Sockets	15 pcs. Fractional, 3/8" to 1 1/4" 12 pcs. Metric, 12 to 24 mm	
Breaker Bar	1 pc.	
Universal Joint	1 pc.	
Quick Release Ratchet	1 pc.	
Extension Bars	3 pcs. 3", 6", 10"	



1/2" Drive Impact Socket Set, 15pcs

BLPATSIMM1215

CONTENTS		Set in storage case
1/2" DRIVE:		
Impact Sockets 6-Point	14 pcs.	10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23, 24 mm
Impact Extension Bar	1 pc.	5"





Car Body Hammer Set, 7pcs

BPBHS7 Packing: 1

CONTENTS	Set in storage case
TOOLS:	
Bumping Hammer	1 pc.
Pick and Finish Hammer	1 pc.
Reverse Curve Hammer	1 pc.
Curve Dolly	1 pc.
Double End Dolly	1 pc.
Shrinking Dolly	1 pc.
Utility Dolly	1 pc.









TOOLS STORAGE

Roll Cabinets

Roll Cab 8 Drawers





Double-Walled Construction For rigidity.



High Performance Roller Bearing Railings
Railings withstanding
22.5kg per rail with roller
bearings for smoother
sliding of drawers.



Self-Lock Tabs Lock & Roll mechanism to prevent drawers from sliding open.



Seamless Design Cabinet doors edges are folded to form a seamless fit without gaps when closed; Cabinets walls reinforced with stiffeners to provide extra strength.



Double Hemmed Edges Drawer edges are hemmed to double thickness for extra stiffness.



Heavy-Duty Construction Reinforced base design to withstand higher overall load and reduce sagging.



Mobility Large 5" castor wheels are bolt fastened for better rolling and durability.













6 Drawers, Classic Roll Cab, 26"

- 26" full double walled construction making for a stronger box which resists the constant pounding of weight and vibration
- Stiffeners are added between the walls to reduce stress on the box and keep the drawers from sagging
- Welded lock tabs on the back of each drawer
- Casters fastened to roll cab using weld nuts to prevent loosening
- Drawer edges are hemmed to double thickness for extra stiffness



PART NO.	COLORS	FINISH	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
KRB2006KPQP	Blue	Matt		660	503	965
KRB2006BLU	Blue	Gloss				
KRB2006KPQR	Red	Matt	6			
KRB2006RED	Red	Gloss	6			
KRB2006BLK	Black	Gloss				
KRB2006YEL	Yellow	Gloss				

CUBIC (cm³)		NET WEIGHT (kg)		SHIPPING WEIGHT (kg)		
156,791		75		95		
SPECIFICAT	IONS	WIDTH I (mm)		DEPTH HEIGH (mm) (mm)		
Drawara	5	544		445	91	
Drawers	1	544		445	193	



TOOLS STORAGE

Roll Cabinets

7 Drawers, Classic Roll Cab, 40"

- 40" full length drawers for larger tools storage
- 45kg max load capacity per drawer, providing a total load of 600kg
- 5" ball bearing casters for durability and easy maneuvering
- Self locking latch keeps drawers in place for safety and security
- Drawer edges are hemmed to double thickness for extra stiffness
- Available in matt colors upon request



PART NO.	COLORS	FINISH	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
KRB4007KPCM	Blue	Gloss				
KRB4007KPC	Black	Gloss	7	1016	501	961
KRB4007KPES	Yellow	Gloss	/	1016		
KRB4007K	Red	Gloss				

CUBIC (cm³)	1	NET WEIGHT (kg)		IG WEIGHT (kg)
250,771		125		133
SPECIFICAT	IONS	WIDTH (mm)		
	3	905	496	48
Drawers	3	905	496	99

8 Drawers, Classic Roll Cab, 40"

- Packing: 1
- 40" double bank roll cab, greater capacity
- Welded lock tabs on the back of each drawer
- Popular choice with side cabinet for your work center
- Full double walled construction making for a stronger box which resists the constant pounding of weight and vibration
- Stiffeners are added between the walls to reduce stress on the box and prevent the drawers from sagging



PART NO.	COLORS	FINISH	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
KRB13008KPRB	Blue	Matt				961
KRB13008BLU	Blue	Gloss		1016	501	
KRB13008KPRR	Red	Matt	8			
KRB13008RED	Red	Gloss	0			
KRB13008BLK	Black	Gloss				
KRB13008YEL	Yellow	Gloss				

CUBIC (cm³)	NE	T WEIGHT (kg)	SHIPPING WEIGHT (kg)		
168,059		110	129		
SPECIFICATIONS		WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)	
Drawers	5	543	445	119	
Diaweis	1	543	445	250	
Cabinet Drawers	2	284	445	40	













5 Drawers, L-Series Roll Cab, 26"

Packing: 1

- High grade steel plate with PE Powder painting
- Fully-openable drawers can withstand up to 45 kg weight
- Bigger sized with greater capacity at 508 kg
- Tubular lock-stronger over molded key lock
- Ribs added for enhanced strength to prevent cabinet deformation



PART NO.	COLORS	FINISH	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
KRB13005KPRB	Blue	Matt			501	822
KRB13005BLU	Blue	Gloss				
KRB13005KPRR	Red	Matt	5	677		
KRB13005RED	Red	Gloss	5	077		
KRB13005BLK	Black	Gloss				
KRB13005YEL	Yellow	Gloss				

CUBIC (cm³)				SHIPP	ING WEIGHT (kg)
159,387		61 68			68
SPECIFICAT	IONS			HEIGHT (mm)	
	1	543		445	54
Drawers	2	543		445	119
-	2	543	445		184

6 Drawers, L-Series Roll Cab, 26"

- High grade steel plate with PE Powder painting
- Fully-openable drawers can withstand up to 45 kg weight
- Bigger sized with greater capacity at 508 kg
- Tubular lock-stronger over molded key lock
- Ribs added for enhanced strength to prevent cabinet deformation



PART NO.	COLORS	FINISH	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
KRB13006KPRB	Blue	Matt			501	
KRB13006BLU	Blue	Gloss				822
KRB13006KPRR	Red	Matt	6	677		
KRB13006RED	Red	Gloss	0	0//		
KRB13006BLK	Black	Gloss				
KRB13006YEL	Yellow	Gloss				

CUBIC (cm³)		NET WEIGHT (kg)		SHIPPING WEIGHT (kg)		
156,536		65		72		
SPECIFICAT	IONS	WIDTH (mm)		EPTH (mm)	HEIGHT (mm)	
	3	543		445	54	
Drawers	2	543		445	119	
	1	543		445	250	

TOOLS STORAGE

Roll Cabinets

7 Drawers, L-Series Roll Cab, 26"

Packing: 1

- High grade steel plate with PE Powder painting to avoid peel
- Fully-openable drawers can withstand up to 45 kg weight
- Bigger sized with greater capacity at 508 kg
- Tubular lock-stronger over molded key lock
- Ribs added for enhanced strength to prevent cabinet deformation



PART NO.	COLORS	FINISH	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
KRB13007KPRB	Blue	Matt				
KRB13007BLU	Blue	Gloss		677	501	822
KRB13007KPRR	Red	Matt	7			
KRB13007RED	Red	Gloss	7			
KRB13007BLK	Black	Gloss				
KRB13007YEL	Yellow	Gloss				

CUBIC (cm³)	1	NET WEIGHT (kg)		SHIPPING WEIGHT (kg)	
153,695		68		75	
SPECIFICAT	IONS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)	
	5	543	445	54	
Drawers	1	543	445	119	
	1	543	445	250	

6 Drawers, Roll Cab with Bumper, 26"

- Loading capacity up to 1000kg
- Composite drawer bumpers ensures protection against unexpected impact when drawer opens
- Safety sliders system that allows one drawer to be opened at a time
- User friendly cart PU handles for better grip
- Comes with 2 fixed and 2 swivel wheels
- High quality powder coating



PART NO.	COLORS	FINISH	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
KRB3006BLU	Blue	Gloss	6	692	510	950
KRB3006RED	Red	Gloss				
KRB3006BLK	Black	Gloss				
KRB3006YEL	Yellow	Gloss				

	CUBIC (cm³) 154,880		NET WEIGHT (kg)	SHIPPI	SHIPPING WEIGHT (kg)	
			75		85	
	SPECIFICATIONS		WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)	
		3	543	445	53	
Dr	Drawers	2	543	445	118	
		1	543	445	246	













7 Drawers, Roll Cab with Bumper, 26"

Packing: 1

- Loading capacity up to 1000kg
- Composite drawer bumpers ensures protection against unexpected impact when drawer opens
- Safety sliders system that allows one drawer to be opened at a time
- User friendly cart PU handles for better grip
- Comes with 2 fixed and 2 swivel wheels
- High quality powder coating



PART NO.	COLORS	FINISH	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
KRB3007BLU	Blue	Gloss		692	510	950
KRB3007RED	Red	Gloss	7			
KRB3007BLK	Black	Gloss	,			
KRB3007YEL	Yellow	Gloss				

CUBIC (cm³)		NET WEIGHT (kg)	SHIPPING WEIGHT (kg)		
151,988		80	90		
SPECIFICAT	IONS	WIDTH (mm)	DEPTH HEIGHT (mm) (mm)		
	5	543	445	53	
Drawers	1	543	445 118		
	1	543	445	246	

8 Drawers, Heavy Duty Cabinet, 30"



- High grade steel plate with PE Powder painting to avoid peel
- Fully-openable drawers with loading capacity of 1000kg
- Adjustable slot separation systems
- Tubular lock-stronger over molded key lock
- Ribs added for enhanced strength to prevent cabinet deformation



PART NO.	COLORS	FINISH	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
BLP30HDC8DKPCM	Blue	Gloss				
BLP30HDC8DKPC	Black	Gloss	8	762	699	1118
BLP30HDC8DKPES	Yellow	Gloss	0	702	099	1110
BLP30HDC8DKK	Red	Gloss				

CUBIC (cm³)		NET WEIGHT (kg)				
357,057		120		132		
SPECIFICAT	IONS	WIDTH (mm)	_	EPTH HEIGHT (mm) (mm)		
	1	625		625	197	
Drawers	3	625		625	66	
	4	625		625	131	



TOOLS STORAGE

Top Chest / End Cabinets & Lockers

4 Drawers, Classic Top Chest, 26"

Packing: 1

- 45kg max Load capacity per drawer, provides a total load 180kg
- Fits perfectly on the top of any Blue-Point 26" Roll Cabinets, providing users with additional tools storage solutions
- Drawer edges are hemmed to double thickness for extra stiffness



PART NO.	COLORS	FINISH	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
KRB2041PCM	Blue	Gloss				
KRB2041PC	Black	Gloss	4	678	501	399
KRB2041PES	Yellow	Gloss	4			
KRB2041K	Red	Gloss				

CUBIC (cm³)					SHIPPING WEIGHT (kg)		
63,204			30		180		
SPECIFICAT	IONS		WIDTH (mm)	_	DEPTH HEIGHT (mm) (mm)		
Drawers	2		566		496	48	
Diawers	2		566		496	99	

4 Drawers, Classic Top Chest, 40"

Packing: 1

- 45kg max Load capacity per drawer, provides a total load 225kg
- Self locking latch keeps drawers in place for safety and security
- Perfect add-ons top for Blue-Point 40"

Roll Cabinets

Drawer edges are hemmed to double thickness for extra stiffness



PART NO.	COLORS	FINISH	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
KRB4041PCM	Blue	Gloss		1016	501	399
KRB4041PC	Black	Gloss	4			
KRB4041PES	Yellow	Gloss	4			
KRB4041K	Red	Gloss				

CUBIC (cm³)		NET WEIGHT (kg)		SHIPPING WEIGHT (kg)		
100,993		58		62		
SPECIFICATION	ONS			EPTH (mm)	HEIGHT (mm)	
Drawers	2	904		496	48	
Diawers	2	904		496	99	

4 Drawers, Classic Top Chest, 40"

Packing: 1

- 45kg max Load capacity per drawer, provides a total load 225kg
- Self locking latch keeps drawers in place for safety and security
- Perfect add-ons top for Blue-Point 40" Roll Cabinets



PART NO.	COLORS	FINISH	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
KRB4042PCM	Blue	Gloss		1016	501	497
KRB4042PC	Black	Gloss	4			
KRB4042PES	Yellow	Gloss	4			
KRB4042K	Red	Gloss				

CUBIC (cm³)	NET WEIGHT (kg)		SHIPPING WEIGHT (kg)		
158,731		71	86		
SPECIFICATIONS	SPECIFICATIONS		DEPTH (mm)	HEIGHT (mm)	
Drawers	2	904	496	48	
Diaweis	2	904	496	99	
Top Compartment	-	1014	475	120	

5 Drawers, Classic Top Chest, 26"

Packing: 1

- Can be placed on all Blue-Point roll cabinets as a top chest
- Lockable top lid
- Side grooves for easy lifting



PART NO.	COLORS	FINISH	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
KRB2055KPQP	Blue	Gloss				
KRB2055KPQR	Red	Gloss	5	660	374	437
KRB2055KPC	Black	Gloss	5	000	374	437
KRB2055KPES	Yellow	Gloss	1			

CUBIC (cm³)	NE	ET WEIGHT (kg)	SHIPPING WEIGHT (kg)		
72,824		38		4	
SPECIFICAT	TIONS	ONS WIDTH DEPTH (mm) (mm)		HEIGHT (mm)	
Drawers	4	566	334	47	
Drawers	1	566	334 79		













WARNING WARNING Do not open multiple drawers
• Read safety precautions on page 251



4 Drawers, L-Series Top Chest, 26"

Packing: 1

- 45kg max Load capacity per drawer, provides a total load 180kg
- · Fits perfectly on the top of any Blue-Point 26" Roll Cabinets
- Drawer edges are hemmed to double thickness for extra stiffness

CUBIC



NET WEIGHT SHIPPING WEIGHT

PART NO.	COLORS	FINISH	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
KRB13004PCM	Blue	Gloss		678	501	419
KRB13004PC	Black	Gloss	4			
KRB13004PES	Yellow	Gloss	4			
KRB13004K	Red	Gloss				

(cm³)		(kg)		(kg)			
67,480		32		32			180
SPECIFICAT	IONS	NS WIDTH (mm)		EPTH (mm)	HEIGHT (mm)		
Drawers	3	566		496	62		
Diaweis	1	566		496	127		

Side Cabinet

KRB13003PCM

Packing: 1

Packing: 1

- Easy fit to any Blue-Point roll cabinets
- Max load of 15 kg per drawer
- Corner gussets and double wall construction for stiffness and strength



PART NO.	COLORS	FINISH	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
KRB13003PCM	Blue	Gloss	-	419	503	821
CUBIC	NET WEIGHT			SHIPF	ING WE	IGHT

	(cm³)			(kg)		(kg)		
	138,080	138,080		30		44		
ı	SPECIFICATIONS					DEPTH (mm)	HEIGHT (mm)	
	Shelves	2		383		496	-	

Breakdown Locker, 40"

🃦 Packing: 1

- Loading Capacity: 300kg
- High quality powder coating



PART NO.	COLORS	FINISH	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
BPKCABT40PCM	Blue	Gloss				
BPKCABT40K	Red	Gloss	-	1016	500	961
BPKCABT40PC	Black	Gloss				
BPKCABT40PES	Yellow	Gloss				

CUBIC (cm³)		NET WEIGHT (kg)		SHIPPING WEIGHT (kg)		
393,676	3,676 73		73			
SPECIFICATIONS		WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)		
Shelves	3	963	435	300		

Breakdown Locker, 46"

Loading Capacity: 400kg

Door will full length locking bar

Adjustable shelving systems



PART NO.	COLORS	FINISH	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
BLP46BDL4PCM	Blue	Gloss				
BLP46BDL4PC	Black	Gloss	-	1168	609	1827
BLP46BDL4PES	Yellow	Gloss				
BLP46BDL4K	Red	Gloss				

CUBIC NE		ET WEIGHT	SHIPPIN	G WEIGHT	
		(kg)	(I	kg)	
1,160,225		135	1	53	
SPECIFICATIONS		WIDTH	DEPTH	HEIGHT	
		(mm)	(mm)	(mm)	
Shelves	3	1168	609	1827	



TOOLS STORAGE



Magnetic Trays

Packing: 1

- Securely holds small parts and tools
- Magnetically attaches to any flat iron or steel surface
- Material: 430 Stainless Iron



PART NO.	DESCRIPTION	SIZES (mm)
MRB5B	Magnetic tray, Round	Round 152 diameter
MRB10B	Magnetic tray	250 x 140
MRB12B	Magnetic tray	355 x 140
MRB15B	Magnetic tray	290 x 265

Magnetic Rail

- Provides easy access and organization of sockets and wrenches
- Extruded aluminum, high strength and corrosion resistant rail body
- High impact plastic socket holders which resists oil and
- 8 magnets with protective foam covering hold rail in place



PART NO.	CLIP SIZE (inches)	RAIL LENGTH (inches)
BLPSWR14	1/4	13
BLPSWR38	3/8	15
BLPSWR12	1/2	18 ⁷ / ₁₆















Roll Cab Tops

Packing: 1

- For use with all Blue-Point roll cabinets of respective sizes
- Available in two thickness, 660mm and 1016mm
- For KRB13008 models, only 1016mm can be used



PART NO.	DESCRIPTION	THICKNESS
SKRWT4008	Wooden Top	660
SKRWT4008B	Wooden Top	1016
SKRSST4107	Stainless Steel Top	1016

Slots and Dots Side Panel

1470K-ACSIDE

- Panel size 822 x 419 x 20mm
- Can be hung or screwed on the roll cab side wall
- Mix and match storage accessories
- 18 Steel Gauge thickness
- PE paint, PE texture



Packing: 1

LED Light Top

Packing: 1

- Up to 15 hours continuous working or 3 months normal usage
- Available in 26" or 40"
- Each LED light set supply 72 lumens.
- 26" with 1 LED light on the middle front of the top
- 40" with 2 LED light on both side front of the top
- Run on 8 AAA batteries
- LED light will illuminate when movement is detected
- Lights cover every drawer
- Easy for locating small tools



PART NO.	WEIGHT (kg)	LENGTH (M)	WIDTH (M)	HEIGHT (M)	
KLTOP26	12.2	0.68	0.51	0.042	
KLTOP40	18.1	1.01	0.51	0.042	

Foldable Tray

1470K-AC1

- Folding tray
- 35 kg loading capacity
- 18 Steel Gauge thickness
- PE paint, PE texture



Packing: 1

Pry Bar Box

1470K-AC2

- Holds up to 23 pry bars or screwdrivers
- 18 Steel Gauge thickness
- PE paint, PE texture



Packing: 1

Can Holder

1470K-AC3

- Storage tray, holds up to 6 cans
- 18 Steel Gauge thickness
- PE paint, PE texture



Document Holder

1470K-AC4

- 18 Steel Gauge thickness
- PE paint, PE texture



TOOLS STORAGE

Heavy Duty Mini Cart

KRC1KPCM

- Packing: 1
- Max capacity load of 50kg per tray, 150kg load capacity
- Compact size suitable for workshop usage
- Pre-drilled holes convenient to place tools on it



PART NO.	COLORS	FINISH	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
KRC1KPCM	Blue	Gloss	400	501	960

CUBIC		NET WEIGHT SH		PPING WEIGHT	
(cm³)		(kg)		(kg)	
48,096		16		150	
SPECIFICATIONS		WIDTH	DEPTH	HEIGHT	
		(mm)	(mm)	(mm)	
Trays	3	400	501	80	

1 Drawer Roll Cart

KRBC3TDPCM

- Packing: 1
- 4" deep locking drawer with tubular lock for added tool security
- Two sturdy, 3" deep trays are positioned for convenience
- Friction drawer slides
- Made of heavy-gauge steel



PART NO.	COLORS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)	NET WEIGHT (kg)	LOAD CAPACITY (kg)
KRBC3TDPCM	Blue	813	452	920	29.5	136
KRBC3TD	Red		432	920	29.5	130

SPECIFICATIONS		WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)	
Drawers	1	368	686	102	
Trays	-	765	686	102	

2 Shelves Roll Cart

KRBC2TCPCM



- Trays feature rolled edges for improved strength and rigidity
- Maximum load capacity 68kg per tray
- Welded post holders
- Two locking casters



PART NO.	COLORS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)	NET WEIGHT (kg)	LOAD CAPACITY (kg)
KRBC2TCPCM	Blue	756	428	920	17.2	159
KRBC2TC	Red	756	428	920	17.2	159

SPECIFICATIONS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)	
Trays	765	428	75	

1 Drawer, Heavy Duty Roll Cart

- Two sturdy, 3" deep trays are positioned for convenience
- Heay duty ball bearing drawer slide
- Lock 'n Roll Drawers prevents drawer opens during movements
- High quality powder coating



PART NO.	COLORS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)	NET WEIGHT (kg)	LOAD CAPACITY (kg)
KRC3TKPCM	Blue					240
KRC3TKK	Red	805	500	060	960 40	
KRC3TKPC	Black		500	900		
KRC3TKPES	Yellow					

SPECIFICATIONS		WIDTH	DEPTH	HEIGHT
		(mm)	(mm)	(mm)
Drawers	1	680	384	117















4 Drawers Flip-Top Roll Cart

KRBC10TBPCM

- Auto locking mechanism locks drawers when lid is closed
- Plated fasteners resist corrosion and self locking nuts
- Non-toxic mats in shelf, drawers and top compartment




PART NO.	COLORS	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
KRBC10TBPCM	Blue	4	775	520	1,048
KRBC10TB	Red	4			

SPECIFICATIONS		WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
	2	292	445	64
Drawers	1	622	445	64
	1	622	445	64
Top Compartment	-	762	483	64
Bottom Shelf	2	762	483	89

4 Drawers Sliding Top Roll Cart

KRBCSSTPCM



 Roller bearing slide drawers, locking slide top, internal prybar holder



Packing: 1

PART NO.	COLORS	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
KRBCSSTPCM	Blue	2	747	524	982
KRBCSST	Red	2	141	524	902

CUBIC (cm³)	1	NET WEIGHT (kg)		CAPACITY (kg)
261,062		56		136
SPECIFICATION	PECIFICATIONS		DEPTH (mm)	HEIGHT (mm)
Drawers	2	745	445	69
Top Compartment	-	747	524	172
Bottom Shelf	-	745	445	76

4 Drawers Flip-Top Roll Cart

KRBC7TDPCM

Packing: 1

- Latch System to unlock all 4 drawers once the top lid is lifted
- Folding side work shelf provides extra work space
- Locking prybar compartment securely holds all length prybars and screwdrivers



PART NO.	COLORS	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)	NET WEIGHT (kg)
KRBC7TDPCM	Blue	4	869	431	1.041	56.2
KRBC7TD	Red	4	609	431	1,041	30.2

SPECIFICATIONS		WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
	2	350	399	51
Drawers	1	700	391	51
	1	700	391	102
Bottom Shelf	1	700	391	76

4 Drawers, Sliding Door Roll Cart

- Loading Capacity: 300kg
- Sturdy and heavy duty frame structure for long lasting use
- Spacious base compartment for storage of larger tools
- Latch lock system allows all 4 drawers to lock/unlock at once



PART NO.	COLORS	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
KRBC100BET	Blue				
KRBC100BN	Red				
KRBC100BFI	Black	4	825	501	918
KRBC100PWZ	Grey				
KRBC100BEG	Purple				

CUBIC (cm³)		NET WEIGHT (kg)	SHIPPI	NG WEIGHT (kg)	
371,154		58		75	
SPECIFICA	TIONS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)	
	2	321	451	51	
Drawers	1	679	451	51	
	1	679	451	116	

TOOLS STORAGE

Roll Carts / Workstation

5 Drawers, Sliding Top Roll Cart

Packing: 1

- Loading Capacity: 600kg
- Sturdy and heavy duty frame structure for long lasting use
- Spacious top compartment for storage of larger tools
- Latch lock system allows all 4 drawers to lock/unlock at once



PART NO.	COLORS	DRAWERS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
KRBC200BET	Blue				
KRBC200BN	Red				
KRBC200BFI	Black	5	807	501	912
KRBC200PWZ	Yellow				
KRBC200BEG	Purple				

CUBIC (cm³)				NG WEIGHT (kg)	
368,728		95		105	
SPECIFICA	TIONS		DEPTH (mm)	HEIGHT (mm)	
Drawers 3		679		451	51
Diaweis	2	679		451	116

Hand Trolley

BLPHTB

- Packing: 1
- Holds up to 45 kg of tools
- High quality carbon steel and plastic material
- Boxes are detachable for more variety of work



PART NO.	WIDTH	DEPTH	HEIGHT	
	(mm)	(mm)	(mm)	
BLPHTB	520	320	720	

SPECIFICATIONS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)	WEIGHT (kg)
Top Drawer	430	200	150	3.5
Center Drawer	390	210	65	5.2
Bottom Drawer	400	215	275	5.8

Workstation

BLPSUZTRWS

Packing: 1

6000 x 4000 mm room size 40" Top Cabinet x 1 40" Locker x 1 26" Top Cabinet x 1 40" Locker x 1 26" Locker x 1 26" Roll Cabinet x 1 Roll Cart x 1



TYPE 1	BLPCCTB1
BLPBL1DT	Single door breakdown locker - texture
BLP26TCT	Top chest 26" - texture
BLP26PP	Pore plate 26"
BLP52BB	Back beam 52"
BLP52SST	Stainless steel top 52"
BLPTSFL	Support leg for top



TYPE 2	BLPCCTB2
BLPBL1DT	Single door breakdown locker - texture
BLP40TCT	Top chest 40" - texture
BLP40PP	Pore plate 40"
BLP78BB	Back beam 78"
BLP78SST	Stainless steel top 78"
BLPTSFL	Support leg for top



TYPE 3	BLPCCTB3
BLPBL2DT	2 doors breakdown locker - texture
BLPBL1DT	Single doors breakdown locker - texture
BLP26TCT	Top chest 26" - texture
BLP40TCT	Top chest 40" - texture
BLP26PP	Pore plate 26"
BLP40PP	Pore plate 40"
BLP92BB	Back beam 92"
BLP92SST	Stainless steel top 92"
BLP13006FCT	6 drawer roll cabinet foot - texture
BLP13008CT	8 drawer roll cabinet caster - texture




















COMBINATION CABINETS

- Combination cabinets can be regarded as a Workstation, provide a well organized storage solution suitable for shop equipment, auto repair and technical academy.
- Including breakdown lockers, top chests, roll cabinets, pore plates, tops, legs, beams etc. It is customizable to various combinations making it suitable for different application scenaros.







677 mm • 1016 mm

Top Chests - 2 types of top chest:

3 pcs adjustable plate, 4 pcs supporting feet with adjustable height

5 combinations for top chests, maximum total length <2370 mm $\,$ Tops - 4 types of length for tops. Capacity of tops with legs 150 kg.

Pore Plates - The choice of pore plates are based on top chests i.e. 677 or 1016 mm. Pore plate height 460 mm. Pore plates should be fixed on the beams 3

The choice of tops are based on top chests

6

Roll Cabinets - 5,6,7,8 drawer roll cabinets can be used
Support type: Universal wheels or feet, Handle should be fixed in the front of the cabinet when using universal wheels as support type.


• 5,6,7 drawer roll cabinets: 677 x 501 x 946 mm

• 8 drawer roll cabinets: 1016 x 501 x 961 mm

TYPE 4	BLPCCTB4
BLP40TCT	Top chest 40" - texture
BLP26PP	Pore plate 26"
BLP40PP	Pore plate 40"
BLP92BB	Back beam 92"
BLP92SST	Stainless steel top 92"
BLP13006FCT	6 drawer roll cabinet foot - texture
	The state of the s



TYPE 5	BLPCCTB5
BLPBL2DT	2 doors breakdown locker - texture
BLP26TCT	Top chest 26" - texture
BLP40TCT	Top chest 40" - texture
BLP26PP	Pore plate 26"
BLP40PP	Pore plate 40"
BLPSCFC	Support column for roll cabinet foot
BLP92SST	Stainless steel top 92"



TYPE 6	BLPCCTB6		
BLPBL1DT	Single doors breakdown locker - texture		
BLP26TCT	Top chest 26" - texture		
BLP40TCT	Top chest 40" - texture		
BLP26PP	Pore plate 26"		
BLP40PP	Pore plate 40"		
BLP92BB	Back beam 92"		
BLP92SST	Stainless steel top 92"		
BLP13006FCT	6 drawer roll cabinet foot - texture		



TYPE 7	BLPCCTB7		
BLP26TCT	Top chest 26" - texture		
BLP40TCT	Top chest 40" - texture		
BLP26PP	Pore plate 26"		
BLP40PP	Pore plate 40"		
BLP92BB	Back beam 92"		
BLP92SST	Stainless steel top 92"		
BLP13006FCT	6 drawer roll cabinet foot - texture		





TOOLS STORAGE

Tool Boxes / Tool Bags

Metal Tool Box, 19" Cantilever Style

Packing: 1

- 19" steel constructed cantilever tool box
- Durable and portable
- 5 trays design to accommodate more tools
- Full length steel handle



PART NO.	COLORS	WIDTH (mm)	DEPTH (mm)	HEIGHT (mm)
CTK19KPCM	Blue	460	200	200
CTK19KPC	Black			
CTK19KPES	Yellow		200	200
CTK19K	Red			

CUBIC (cm³)	NET WEIGHT (kg)		SHIPPING WEIGHT (kg)	
17,131	4.6		35	
SPECIFICATIO	SPECIFICATIONS		DEPTH (mm)	HEIGHT (mm)
Small Tray	4	460	99	48
Large Tray	1 460		200	07

Metal Tool Boxes

KRBK17 / KRBK24

Packing: 1

- Portable steel tool box for users who prefer metal material over plastic
- High grade steel for greater strength & toughness
- PE powder painting for better protection against peel
- Triple latch to prevent box from opening when dropped
- Additional internal metal tray for separating small tools





PART NO.	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)
KRBK17	425	153	114
KRBK24	511	199	195

Metal Tool Box, 18" Cantilever Style

KRW48C

Packing: 1

Split top opening for tool access

Cantilever travs on either side of cover, carrying handle



PART NO.	CUBIC	LENGTH	WIDTH	HEIGHT
	(cm³)	(mm)	(mm)	(mm)
KRW48C	25,070	457	254	337

Plastic Tool Boxes

Packing: 1

- Ideal for a wide range of storage needs
- Made of tough, injection molded plastic to ensure a precise fitting lid and durability
- Top carrying handle, tension latches, tote tray and padlock provision are also featured



PART NO.	SIZE (inches)	LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)
YA482	16	419	210	165
YA484	23	587	260	267

Plastic Tool Box 18"

BPBOX18

- Steel pins connecting the lid and box for extra durable usage
- Separate top tray to hold small tools
- Strong handle and lock material
- Large capacity 18" box, light weight and portable
- Made from shock resistant ABS and PP for durability and toughness
- Steel pins connecting the lid and box for extra durable usage
- Strong handle and lock material

PART NO.	SIZE	LENGTH	WIDTH	HEIGHT
	(inches)	(mm)	(mm)	(mm)
BPBOX18	18	445	240	206















Tool Bag with Metal Handle

BLPMOTB2

- Packing: 1
- Dimension: L46 x W21 x H34 cm
- Recommended load capacity: 15 kg
- Wide open space below handle for easy access to tool carrier's main compartment
- Plastic reinforced internal pocket for utility knife or other tools
- Sturdy metal handle with molded foam grip for easy carrying

 Multi-use pockets to organize a wide range of tools and accessories



PART NO.	LENGTH	WIDTH	HEIGHT
	(cm)	(cm)	(cm)
BLPMOTB2	46	21	34

Tote Bag, 17"

BPTOTE

Packing: 1

- Made of heavy duty 600x300D polyester, with Blue-Point embroidered logo
- Rugged, versatile, water resistant
 Wide top opening for
- Wide top opening for easy access
- Multiple interior and external pockets for tool organization



PART NO.	SIZE	LENGTH	WIDTH	HEIGHT
	(inches)	(mm)	(mm)	(mm)
ВРТОТЕ	17	419	267	311

Mini Tool Box

BPKMTBB

- Packing: 1
- PE powder painting for better protection against peel
- Made of heavy gauge steel, tray thickness 0.9mm
- Perfect tools storage solution for ratchets and sockets



PART NO.	LENGTH	WIDTH	HEIGHT	WEIGHT
	(mm)	(mm)	(mm)	(kg)
ВРКМТВВ	208	79.5	41	0.45

Tool Bag, 17" Heavy Duty

BLPTBAG17

Packing: 1

- Dimension: L44.5 x W22 x H30.5 cm
- Recommended load capacity: 15 kg
- Constructed of heavy duty, water resistant material
- Ideal for carrying hand tools and other small to medium items
- Comfortable, cotton padded handles
- Rubber foam bottom keeps bag

sturdy, protect contents from hard falls

Designed to keep 3 modular sets in each bag




PART NO.	LENGTH	WIDTH	HEIGHT
	(cm)	(cm)	(cm)
BLPTBAG17	44.5	22	30.5

Backpack with Tools Holder

BLPBPACK2

Packing: 1



repellent finish

Color: Tough black with blue/grey stripes

 Comes with tools holder inside for more usage



PART NO.	LENGTH (cm)	WIDTH (cm)	HEIGHT (cm)
BLPBPACK2	31	18.5	48





RATCHETS, SOCKETS & ACCESSORIES 1/4" Ratchets / Sockets

1/4" Quick Release Ratchet

BPRTR936

- Packing: 1
- Features quick release button for rapid socket/accessory changes, even with greasy or oily hands
- Contoured handle for comfort and control
- Chrome finish for easy clean-up
- All ratchets in series meet or exceed ANSI B107-10M-1996 specifications



PART NO.	SQ. DRIVE (inches)	DESCRIPTION
BPRTR936	1/4	Standard Handle
GEAR TEETH	SWING ARC	A (mm)
36	10°	12
B (mm)	C (mm)	REPAIR KIT
25	143	RKRBPRTR936

1/4" Quick Release Ratchet, Soft Grip

BPRTR936SG



- Features quick release button for rapid socket/accessory changes, even with greasy or oily hands
- Corrosive resistant bi-mold cushion grip for improved comfort and performance
- Chrome finish for easy clean-up
- All ratchets in series meet or exceed ANSI B107-10M-1996 specifications



PART NO.	SQ. DRIVE (inches)	DESCRIPTION
BPRTR936SG	1/4	Soft Grip Handle
GEAR TEETH	SWING ARC	A (mm)
36	10°	12
B (mm)	C (mm)	REPAIR KIT
25	143	RKRBPRTR936

1/4" Finger Ratchet

FSDR

- Reversible, finger ratchet
- Small size works great for extremely tight areas
- Aluminum knurled outer ring for sure grip



PART NO.	SQ. DRIVE (inches)	
FSDR	1/4 male - 1/4 female	





1/4" Socket, mm, 6-Point

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	SIZE (mm)	LENGTH (mm)
BLPSM143.5	3.5	
BLPSM144	4	
BLPSM144.5	4.5	
BLPSM145	5	
BLPSM145.5	5.5	
BLPSM146	6	
BLPSM147	7	25
BLPSM148	8	25
BLPSM149	9	
BLPSM1410	10	
BLPSM1411	11	
BLPSM1412	12	
BLPSM1413	13	
BLPSM1414	14	

1/4" Socket, mm, 12-Point

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	SIZE (mm)	LENGTH (mm)
BLPDM144	4	
BLPDM144.5	4.5	
BLPDM145	5	
BLPDM145.5	5.5	
BLPDM146	6	
BLPDM147	7	
BLPDM148	8	24.8
BLPDM149	9	
BLPDM1410	10	
BLPDM1411	11	
BLPDM1412	12	
BLPDM1413	13	
BLPDM1414	14	

1/4" Socket, Inches, 6-Point

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	SIZE (inches)	LENGTH (mm)
BLPS14532	5/32	
BLPS14316	3/16	
BLPS14732	7/32	
BLPS1414	1/4	
BLPS14932	9/32	
BLPS14516	5/16	25
BLPS141132	11/32	23
BLPS1438	3/8	
BLPS14716	7/16	
BLPS1412	1/2	
BLPS14916	9/16	
BLPS1458	5/8	

1/4" Long Socket, mm, 6-Point

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	SIZE (mm)	LENGTH (mm)
BLPLSM144	4	
BLPLSM145	5	
BLPLSM146	6	
BLPLSM147	7	
BLPLSM148	8	
BLPLSM149	9	50
BLPLSM1410	10	
BLPLSM1411	11	
BLPLSM1412	12	
BLPLSM1413	13	
BLPLSM1414	14	



RATCHETS, SOCKETS & ACCESSORIES 1/4" Sockets / Bit Sockets

1/4" Long Socket, Inches, 6-Point

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds **ANSI Standards**





PART NO.	SIZE (inches)	LENGTH (mm)
BLPLS14316	3/16	
BLPLS14732	7/32	
BLPLS1414	1/4	
BLPLS14932	9/32	
BLPLS14516	5/16	
BLPLS141132	11/32	50
BLPLS1438	3/8	
BLPLS14716	7/16	
BLPLS1412	1/2	
BLPLS14916	9/16	
BLPLS1458	5/8	

1/4" Long Socket, mm, 12-Point

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds **ANSI Standards**





PART NO.	SIZE (mm)	LENGTH (mm)
BLPLDM144	4	
BLPLDM145	5	
BLPLDM146	6	
BLPLDM147	7	
BLPLDM148	8	
BLPLDM149	9	50
BLPLDM1410	10	
BLPLDM1411	11	
BLPLDM1412	12	
BLPLDM1413	13	
BLPLDM1414	14	

1/4" Double Square Socket, 8-Point

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds **ANSI Standards**





	_	
PART NO.	SIZE (inches)	LENGTH (mm)
BLPS81414	1/4	
BLPS814516	5/16	25
BLPS81438	3/8	

1/4" External Torx® Socket

Manufactured from high grade steel alloy

Features a Lifetime Warranty and exceeds **ANSI Standards**





PART NO.	# 1	LENGTH (mm)
BLPTE144	E4	
BLPTE145	E5	
BLPTE146	E6	25
BLPTE147	E7	
BLPTE148	E8	







1/4" Torx® Bit Socket, Tamper Resistant

- Packing: 6
- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	#]	A (inches)
BLPT146TP	T6	
BLPT147TP	T7	
BLPT148TP	Т8	
BLPT149TP	Т9	
BLPT1410TP	T10	1 7/16
BLPT1415TP	T15	1 7/10
BLPT1420TP	T20	
BLPT1425TP	T25	
BLPT1427TP	T27	
BLPT1430TP	T30	

1/4" Torx® Socket Driver

- The BLPTS Series of Stubby Torx® socket drivers feature a reduced fastener depth penetration to increase strength and improve fastener engagement
- Manufactured from S2 Steel for longer tool life



PART NO.	#]	LENGTH (mm)
BLPTS0148	Т8	
BLPTS01410	T10	
BLPTS01415	T15	
BLPTS01420	T20	
BLPTS01425	T25	
BLPTS01427	T27	19
BLPTS01430	T30	
BLPTS01440	T40	
BLPTS01445	T45	
BLPTS01447	T47	
BLPTS01450	T50	

1/4" Torx® Bit Socket, Long, Tamper Resistant

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



Packing: 6

PART NO.	# [LENGTH (mm)
BLPTL146TP	Т6	
BLPTL147TP	Т7	
BLPTL148TP	Т8	
BLPTL149TP	Т9	
BLPTL1410TP	T10	100
BLPTL1415TP	T15	100
BLPTL1420TP	T20	
BLPTL1425TP	T25	
BLPTL1427TP	T27	
BLPTL1430TP	T30	

1/4" Hex Socket Driver

- The BLPHSM Series of Stubby Hex socket drivers feature a reduced fastener depth penetration to increase strength and improve fastener engagement
- Manufactured from S2 Steel for longer tool life



PART NO.	SIZE (mm)	LENGTH (mm)
BLPHSM0142	2	
BLPHSM01425	2.5	
BLPHSM0143	3	
BLPHSM0144	4	
BLPHSM0145	5	19
BLPHSM0146	6	19
BLPHSM0147	7	
BLPHSM0148	8	
BLPHSM0149	9	
BLPHSM01410	10	



RATCHETS, SOCKETS & ACCESSORIES 1/4" Bit Sockets / Chrome Accessories

1/4" Hex Socket Driver, Tamper Resistant

Packing: 6

- The BLPTHSM Series of Stubby Hex Tamper Resistant socket drivers feature a reduced fastener depth penetration to increase strength and improve fastener engagement
- Manufactured from S2 Steel for longer tool life





PART NO.	SIZE (mm)	LENGTH (mm)
BLPTHSM0142	2	
BLPTHSM01425	2.5	
BLPTHSM0143	3	
BLPTHSM0144	4	
BLPTHSM0145	5	19
BLPTHSM0146	6	19
BLPTHSM0147	7	
BLPTHSM0148	8	
BLPTHSM0149	9	
BLPTHSM01410	10	

1/4" Phillips® Socket Driver

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds **ANSI Standards**





PART NO.	SIZE	LENGTH (mm)
BLPP140	#0	
BLPP141	#1	
BLPP142	#2	37
BLPP143	#3	
BLPP144	#4	

1/4" Phillips® Socket Driver, Stubby

Packing: 6

- Stubby Phillips® socket drivers feature a reduced fastener depth penetration to increase strength and improve fastener engagement
- Manufactured from S2 Steel for longer tool life





PART NO.	SIZE	LENGTH (mm)
BLPPS141	#1	19
BLPPS142	#2	19

1/4" Pozidriv® Socket Driver

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds **ANSI Standards**





PART NO.	SIZE	LENGTH (mm)
BLPPD141	#1	
BLPPD142	#2	37
BLPPD143	#3	







1/4" Flat Tip Socket Driver, Short

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards





PART NO.	SIZE (inches)	LENGTH (mm)
BLPFS01414	1/4	19
BLPFS01438	3/8	19

1/4" Triple Square Socket Driver

- Manufactured from high grade steel alloy
- Features a Lifetime
 Warranty and exceeds ANSI
 Standards





PART NO.	SIZE (mm)	LENGTH (mm)	
BLPXZN144	4		
BLPXZN145	5		6
BLPXZN146	6	27	6
BLPXZN148	8		
BLPXZN1410	10		1

1/4" Sliding T-Handle, 4"

BLPSTHD144

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	LENGTH (mm)
BLPSTHD144	114

1/4" Flat Tip Socket Driver, Standard

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards





PART NO.	SIZE (inches)	SIZE (mm)	LENGTH (mm)
BLPFT144	5/32	4	
BLPFT145.5	7/32	5.5	37
BLPFT146.5	9/32	6.5	

1/4" Breaker Bar

BLPBB146

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



ı	PART NO.	LENGTH (mm)
	BLPBB146	152

1/4" Spinner Handle

BLPCGHD146

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	LENGTH (mm)	
BLPCGHD146	152	

RATCHETS, SOCKETS & ACCESSORIES 1/4" Chrome Accessories / Impact Sockets & Accessories

1/4" Extension, Knurled

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds **ANSI Standards**



PART NO.	LENGTH (mm)
BLPTXK1.5	40
BLPTXK2	51
BLPTXK3	76
BLPTXK4	102
BLPTXK6	152

1/4" Extension, Extra Long Locking

Packing: 6

- Smooth, durable chrome finish
- Made from tough 6130 steel
- Secure socket retention
- Lifetime warranty on individual extensions
- Do not use with power or impact tools



PART NO.	LENGTH (mm)
BLPEXTL1412	305
BLPEXTL1418	457
BLPEXTL1424	610

1/4" Flexible Extension

BLPEXTF146

- Packing: 6
- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	LENGTH (mm)	
BLPEXTF146	152	

1/4" Universal Joint

BLPUJ14

Manufactured from high grade steel alloy

Features a Lifetime Warranty and exceeds ANSI Standards





Packing: 6

PART NO.	LENGTH (mm)
BLPUJ14	38

1/4" Adaptor

BLPAFM1438

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards





Packing: 6

PART NO.	INTERNAL SQ. DRIVE (inches)	EXTERNAL SQ. DRIVE (inches)
BLPAFM1438	1/4	3/8

Spinner Adaptors

- Ideal for getting into tight places while generating substantial torque
- Knurled nut body for positive grip
- Anodized knurled body design



PART NO.	SQ. DRIVE (inches)
FSD14	3/s male - 1/4 female
FSD38	1/4 male - 3/8 female









1/4" Bit Holder

BLPTMBS1414

- Packing: 6
- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards





PART NO.	LENGTH (mm)	DESCRIPTION
BLPTMBS1414	27	for 1/4" Hex Bits

1/4" Impact Adaptor

BLPAIM3814



- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove
- Suitable for use with pneumatic and electric impact wrenches



PART NO.	SIZE (inches)
BLPAIM3814	3/8 male x 1/4 female

1/4" Drive Fractional & Metric Impact Twist Socket Set

122TSTY

- Constructed from heat treated alloy steel
- Industrial black finish
- One quarter millimeter increments between sizes which ensure coverage regardless of fastener head condition or manufacturer's tolerance
- Can be used with impact wrench



	OD			
PART NO.	SIZE	WRENCH END	DRIVE END	LENGTH inches (mm)
TSTY45	4.50mm	0.29 (7.4)		
TSTY47	4.75mm & 3/ ₁₆ "	0.31 (7.9)		
TSTY50	5.00mm	0.32 (8.1)		
TSTY52	5.25mm	0.33 (8.4)		
TSTY55	5.50mm	0.34 (8.6)		
TSTY57	5.75mm	0.35 (8.9)	5.00 (127)	1.00 (25.4)
TSTY60	6.00mm	0.37 (9.4)		
TSTY62	6.25mm & 1/4"	0.38 (9.7)		
TSTY65	6.50mm	0.39 (9.9)		
TSTY67	6.75mm	0.40 (10.2)		
TSTY70	7.00mm	0.41 (10.4)		

	OD			
PART NO.	SIZE	WRENCH END	DRIVE END	LENGTH inches (mm)
TSTY72	7.25mm & 9/ ₃₂ "	0.42 (10.7)		
TSTY75	7.50mm	0.44 (11.2)		
TSTY77	7.75mm	0.45 (11.5)		
TSTY80	8.00mm & 5/ ₁₆ "	0.47 (11.8)		
TSTY82	8.25mm	0.48 (12.2)		
TSTY85	8.50mm	0.49 (12.6)	5.00 (127)	1.00 (25.4)
TSTY87	8.75mm & 11/ ₃₂ "	0.51 (12.9)		
TSTY90	9.00mm	0.52 (13.2)		
TSTY92	9.25mm	0.54 (13.6)		
TSTY95	9.50mm & 3/8"	0.55 (14.0)		
TSTY100	10.00mm	0.57 (14.5)		



RATCHETS, SOCKETS & ACCESSORIES 3/8" Ratchets

3/8" Quick Release Ratchet












3/8" Quick Release Ratchet

BPRFR938

- Packing: 1
- Features quick release button for rapid socket/accessory changes, even with greasy or oily hands
- Contoured handle for comfort and control
- Chrome finish for easy clean-up
- All ratchets in series meet or exceed ANSI R107-10M-1996 specifications




PART NO.	SQ. DRIVE (inches)	DESCRIPTION
BPRFR938	3/8	Standard Handle
GEAR TEETH	SWING ARC	A (mm)
38	9.5°	14
B (mm)	C (mm)	REPAIR KIT
33	197	RKRBPRFR938

3/8" Quick Release Ratchet, Soft Grip

BPRFR938SG

- Packing: 1
- Features quick release button for rapid socket/accessory changes, even with greasy or oily hands
- Corrosive resistant bi-mold cushion grip for improved comfort and performance Chrome finish for easy clean-up
- All ratchets in series meet or exceed ANSI B107-10M-1996 specifications



PART NO.	SQ. DRIVE (inches)	DESCRIPTION
BPRFR938SG	3/8	Soft Grip Handle
GEAR TEETH	SWING ARC	A (mm)
38	9.5°	14
B (mm)	C (mm)	REPAIR KIT
33	197	RKRBPRFR938

3/8" Pass Thru Ratchet

BPRFPT10

Packing: 1

• Ratchet features a flex head design that allows for seven different locking positions



PART NO.	LENGTH (mm)	
BPRFPT10	254	

3/8" Finger Ratchet

FSDR1

- Reversible, finger ratchet
- Small size works great for extremely tight areas
- Aluminum knurled outer ring for sure grip



PART NO.	SQ. DRIVE (inches)
FSDR1	3/8 male - 1/4 female

RATCHETS, SOCKETS & ACCESSORIES

3/8" Sockets

3/8" Socket, mm, 6-Point

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards





PART NO.	SIZE (mm)	
BLPSM386	6	
BLPSM387	7	
BLPSM388	8	
BLPSM389	9	25.5
BLPSM3810	10	25.5
BLPSM3811	11	
BLPSM3812	12	
BLPSM3813	13	
BLPSM3814	14	0.7
BLPSM3815	15	27

PART NO.	SIZE (mm)	
BLPSM3816	16	
BLPSM3817	17	27
BLPSM3818	18	
BLPSM3819	19	
BLPSM3820	20	29
BLPSM3821	21	
BLPSM3822	22	
BLPSM3823	23	31
BLPSM3824	24	

3/8" Socket, Inches, 6-Point

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	SIZE (inches)	LENGTH (mm)
BLPS3814	1/4	
BLPS38516	5/16	
BLPS3838	3/8	25
BLPS38716	7/16	
BLPS3812	1/2	
BLPS38916	9/16	
BLPS3858	5/8	27
BLPS381116	11/16	
BLPS3834	3/4	
BLPS381316	13/16	
BLPS3878	7/8	29
BLPS381516	15/16	
BLPS381	1	

3/8" Socket, mm, 12-Point

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



	_	Ni.	
U		F	
	13		
	-	1	
	Į		

Packing: 6

3/8" Long Socket, mm, 12-Point

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	SIZE (mm)		
BLPDM386	6		
BLPDM387	7		
BLPDM388	8		
BLPDM389	9	25.5	
BLPDM3810	10	20.0	
BLPDM3811	11		
BLPDM3812	12		
BLPDM3813	13		
BLPDM3814	14	27	
BLPDM3815	15	21	

PART NO.	SIZE (mm)	LENGTH (mm)
BLPDM3816	16	
BLPDM3817	17	27
BLPDM3818	18	
BLPDM3819	19	
BLPDM3820	20	29
BLPDM3821	21	
BLPDM3822	22	
BLPDM3823	23	31
BLPDM3824	24	

PART NO.	SIZE (mm)	
BLPLM386	6	
BLPLM387	7	
BLPLM388	8	
BLPLM389	9	
BLPLM3810	10	64
BLPLM3811	11	
BLPLM3812	12	
BLPLM3813	13	1
BL PL M3814	14	


PART NO.	SIZE (mm)	LENGTH (mm)
BLPLM3815	15	
BLPLM3816	16	
BLPLM3817	17	
BLPLM3818	18	64
BLPLM3819	19	04
BLPLM3820	20	
BLPLM3821	21	
BLPLM3822	22	

















3/8" Long Socket, Inches, 12-Point

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	SIZE (inches)	LENGTH (mm)
BLPL3814	1/4	
BLPL38516	5/16	
BLPL3838	3/8	
BLPL38716	7/16	
BLPL3812	1/2	
BLPL38916	9/16	
BLPL3858	5/8	64
BLPL381116	11/16	
BLPL3834	3/4	
BLPL381316	13/16	
BLPL3878	7/8	
BLPL381516	15/16	
BLPL381	1	

3/8" External Torx® Socket

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	# Ţ	LENGTH (mm)
BLPTE384	E4	
BLPTE385	E5	
BLPTE386	E6	
BLPTE387	E7	
BLPTE388	E8	31
BLPTE3810	E10	
BLPTE3811	E11	
BLPTE3812	E12	
BLPTE3814	E14	
BLPTE3816	E16	
BLPTE3818	E18	
BLPTE3820	E20	



RATCHETS, SOCKETS & ACCESSORIES 3/8" Bit Sockets / Chrome Accessories

3/8" Torx® Bit Socket, Tamper Resistant

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	#]	A
BLPT3810TP	T10	
BLPT3815TP	T15	
BLPT3820TP	T20	1 27/32
BLPT3825TP	T25	
BLPT3827TP	T27	
BLPT3830TP	T30	
BLPT3840TP	T40	
BLPT3845TP	T45	2
BLPT3850TP	T50	
BLPT3855TP	T55	

3/8" Torx® Bit Socket, Long, Tamper Resistant

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards





PART NO.	Α	LENGTH (mm)
BLPTL3840TP	T40	
BLPTL3845TP	T45	110
BLPTL3850TP	T50	

3/8" Torx® Socket Driver

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds **ANSI Standards**





PART NO.	#]	LENGTH (mm)
BLPTS3810	T10	
BLPTS3815	T15	
BLPTS3820	T20	48
BLPTS3825	T25	48
BLPTS3827	T27	
BLPTS3830	T30	
BLPTS3840	T40	
BLPTS3845	T45	
BLPTS3850	T50	51
BLPTS3855	T55	
BLPTS3860	T60	

3/8" Hex Socket Driver

Manufactured from high grade steel alloy

Features a Lifetime Warranty and exceeds ANSI Standards




PART NO.	SIZE (mm)	LENGTH (mm)
BLPH383	3	
BLPH384	4	
BLPH385	5	47
BLPH386	6	
BLPH387	7	
BLPH388	8	50.5
BLPH3810	10	30.3







3/8" Phillips® Socket Driver



Features a Lifetime Warranty and exceeds **ANSI Standards**



PART NO.	SIZE	LENGTH (mm)
BLPP381	#1	
BLPP382	#2	47
BLPP383	#3	
BLPP384	#4	

3/8" Triple Square Socket Driver

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	SIZE	LENGTH (mm)
BLPXZNM0384	M4	
BLPXZNM0385	M5	
BLPXZNM0386	M6	27
BLPXZNM0388	M8	
BLPXZNM03810	M10	
BLPXZNM03812	M12	

3/8" Breaker Bar

BLPBB3810

- Packing: 6
- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	LENGTH (mm)	
BLPBB3810	253	

3/8" Pozidriv® Socket Driver

Manufactured from high grade steel alloy

Features a Lifetime Warranty and exceeds **ANSI Standards**



PART NO.	SIZE	LENGTH (mm)
BLPPD381	#1	
BLPPD382	#2	47
BLPPD383	#3	
BLPPD384	#4	

3/8" Flat Tip Socket Driver

Manufactured from high grade steel alloy

Features a Lifetime Warranty and exceeds ANSI Standards





PART NO.	SIZE (mm)	LENGTH (mm)
BLPFT3855	5.5	
BLPFT3865	6.5	47
BLPFT388	8	

3/8" Sliding T-Handle

BLPSTHD388

- Packing: 6
- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	LENGTH (mm)	
BLPSTHD388	197	



RATCHETS, SOCKETS & ACCESSORIES

3/8" Chrome Accessories

3/8" Spinner Handle

BLPCGHD388



Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds



PART NO.	LENGTH (mm)
BLPCGHD388	219

3/8" Locking Extension

- Smooth, durable chrome finish
- Made from tough 6130 steel
- Secure socket retention
- Lifetime warranty on individual extensions



PART NO.	LENGTH (mm)	
FXLBP3	76	
FXLBP6	152	
FXLBP10	254	

3/8" Pass Thru Socket, mm

- Pass thru socket design avoids "bottoming out" on long fasteners and threaded rods
- Sockets can reach fasteners in tight spaces with relative ease





PART NO.	SIZE (mm)	LENGTH (mm)
BLPPTSM8	8	
BLPPTSM9	9	
BLPPTSM10	10	
BLPPTSM11	11	
BLPPTSM12	12	
BLPPTSM13	13	37
BLPPTSM14	14	37
BLPPTSM15	15	
BLPPTSM16	16	
BLPPTSM17	17	
BLPPTSM18	18	
BLPPTSM19	19	

3/8" Extension, Knurled

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds



PART NO.	LENGTH (mm)	
BLPEXTK383	75	
BLPEXTK386	150	
BLPEXTK3810	252	

3/8" Locking Extension, Extra Long

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds



PART NO.	LENGTH (mm)	
BLPEXTL3812	305	
BLPEXTL3818	457	
BLPEXTK3824	610	

3/8" Pass Thru Socket, Inches

- Pass thru socket design avoids "bottoming out" on long fasteners and threaded rods
- Sockets can reach fasteners in tight spaces with relative ease




PART NO.	SIZE (inches)	LENGTH (mm)
BLPPTS38	3/8	
BLPPTS716	7/16	
BLPPTS12	1/2	
BLPPTS916	9/16	37
BLPPTS58	5/8	
BLPPTS1116	11/16	
BLPPTS34	3/4	









3/8" Pass Thru Extension



PART NO.	LENGTH (mm)	
BLPPTEXT3	76	

3/8" Universal Joint

BLPUJ38

Manufactured from high grade steel alloy Features a Lifetime

Warranty and exceeds ANSI Standards







PART NO.	LENGTH (mm)	
BLPUJ38	52	

3/8" Bit Holder



PART NO.	LENGTH (mm)	DESCRIPTION
BLPTMBS3814	19	For 1/4" Hex Bits

3/8" Adaptor

Manufactured from high grade steel alloy

Features a Lifetime Warranty and exceeds ANSI Standards





PART NO.	INTERNAL SQ. DRIVE (inches)	EXTERNAL SQ. DRIVE (inches)
BLPAFM3814	3/8	1/4
BLPAFM3812	3/8	1/2
BLPAFW3812	3/8	1/2



RATCHETS, SOCKETS & ACCESSORIES

3/8" Chrome Accessories / Impact Sockets & Accessories

3/8" Spinner Adaptor

FSD1

- Ideal for getting into tight places while generating substantial torque
- Knurled nut body for positive grip
- Anodized body design.



PART NO.	SQ. DRIVE (inches)
FSD1	3/8 male - 3/8 female

3/8" Pass Thru Adaptor

BLPPTA3438

 Manufactured from high grade steel alloy

Features a Lifetime Warranty and exceeds ANSI Standards



a T

PART NO.	LENGTH (mm)
BLPPTA3438	32

3/8" Impact Socket, Shallow, mm, 6-Point

- Designed for maximum engagement on 6-point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



PART NO.	SIZE (mm)
BLPSMIM387	7
BLPSMIM388	8
BLPSMIM389	9
BLPSMIM3810	10
BLPSMIM3811	11
BLPSMIM3812	12
BLPSMIM3813	13
BLPSMIM3814	14
BLPSMIM3815	15
BLPSMIM3816	16
BLPSMIM3817	17
BLPSMIM3818	18
BLPSMIM3819	19

3/8" Impact Socket, Shallow, Inches, 6-Point

- Designed for maximum engagement on 6-point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



PART NO.	SIZE (inches)
BLPSIM3814	1/4
BLPSIM38516	5/16
BLPSIM3838	3/8
BLPSIM38716	7/16
BLPSIM3812	1/2
BLPSIM38916	9/16
BLPSIM3858	5/8
BLPSIM381116	11/16
BLPSIM3834	3/4

3/8" Impact Socket, Deep, mm, 6-Point

- Designed for maximum engagement on 6-point
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



PART NO.	SIZE (mm)
BLPLSMIM387	7
BLPLSMIM388	8
BLPLSMIM389	9
BLPLSMIM3810	10
BLPLSMIM3811	11
BLPLSMIM3812	12
BLPLSMIM3813	13

	Packing: 6
PART NO.	SIZE (mm)
BLPLSMIM3814	14
BLPLSMIM3815	15
BLPLSMIM3816	16
BLPLSMIM3817	17
BLPLSMIM3818	18
BLPLSMIM3819	19









Packing: 6

3/8" Impact Socket, Deep, Inches, 6-Point

- Designed for maximum engagement on 6-point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



PART NO.	SIZE
	(inches)
BLPLSIM3814	1/4
BLPLSIM38516	5/16
BLPLSIM3838	3/8
BLPLSIM38716	7/16
BLPLSIM3812	1/2
BLPLSIM38916	9/16
BLPLSIM3858	5/8
BLPLSIM381116	11/16
BLPLSIM3834	3/4

3/8" Universal Joints

BLPJIM38

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove



PART NO.	SIZE (inches)
BLPJIM38	3/8 male x 3/8 female

3/8" Impact Socket, Extra Long, Inches, 6-Point

- Extra length at 100 mm to reach two-wheelers transmission box screws
- Single piece construction
- For use on impact wrench without the need for extra extension



PART NO.	SIZE (inches)
BLPSMS8	8
BLPSMS10	10
BLPSMS12	12

3/8" Impact Adaptor

BLPAIM1238

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove



Packing: 6

PART NO.	SIZE (inches)
BLPAIM1238	1/2 male x 3/8 female

3/8" Extension

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove



PART NO.	SIZE (inches)
BLPEXIM383	3
BLPEXIM386	6



RATCHETS, SOCKETS & ACCESSORIES

1/2" Ratchets / Sockets

1/2" Quick Release Ratchet

BPRSR940

- Packing: 1
- Features quick release button for rapid socket/ accessory changes, even with greasy or oily hands
- Contoured handle for comfort and control
- Chrome finish for easy clean-up
- All ratchets in series meet or exceed ANSI B107-10M-1996 specifications



PART NO.	SQ. DRIVE (inches)	DESCRIPTION
BPRSR940	1/2	Standard Handle
GEAR TEETH	SWING ARC	A (mm)
40	9°	18
B (mm)	C (mm)	REPAIR KIT
44	251	RKRBPRSR940

1/2" Quick Release Ratchet, Soft Grip

BPRSR940SG



- Features quick release button for rapid socket/accessory changes, even with greasy or oily hands
- Corrosive resistant bi-mold cushion grip for improved comfort and performance
- Chrome finish for easy clean-up
- All ratchets in series meet or exceed ANSI B107-10M-1996 specifications



PART NO.	SQ. DRIVE (inches)	DESCRIPTION
BPRSR940SG	1/2	Soft Grip Handle
GEAR TEETH	SWING ARC	A (mm)
40	9°	18
B (mm)	C (mm)	REPAIR KIT
44	103	RKRBPRSR940

1/2" Socket, mm, 6-Point



- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards





PART NO.	SIZE (mm)	LENGTH (mm)
BLPSM128	8	
BLPSM129	9	
BLPSM1210	10	
BLPSM1211	11	
BLPSM1212	12	
BLPSM1213	13	38
BLPSM1214	14	
BLPSM1215	15	
BLPSM1216	16	
BLPSM1217	17	
BLPSM1218	18	

PART NO.	SIZE (mm)	LENGTH (mm)
BLPSM1219	19	
BLPSM1220	20	
BLPSM1221	21	
BLPSM1222	22	
BLPSM1223	23	
BLPSM1224	24	38
BLPSM1227	27	
BLPSM1230	30	
BLPSM1232	32	
BLPSM1234	34	
BLPSM1236	36	

1/2" Socket, Inches, 6-Point

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards





PART NO.	SIZE (inches)	LENGTH (mm)
BLPS12516	5/16	
BLPS1238	3/8	
BLPS12716	7/16	
BLPS1212	1/2	38
BLPS12916	9/16	30
BLPS1258	5/8	
BLPS121116	11/16	
BLPS1234	3/4	

PART NO.	SIZE (inches)	LENGTH (mm)
BLPS121316	13/16	38
BLPS1278	7/8	30
BLPS121516	15/16	
BLPS121	1	40
BLPSB121116	1 1/16	
BLPSB12118	1 1/8	
BLPSB121316	1 3/16	44
BLPSB12114	1 1/4	







1/2" Socket, mm, 12-Point

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	SIZE (mm)	LENGTH (mm)
BLPDM128	8	
BLPDM129	9	
BLPDM1210	10	
BLPDM1211	11	
BLPDM1212	12	
BLPDM1213	13	
BLPDM1214	14	38
BLPDM1215	15	30
BLPDM1216	16	
BLPDM1217	17	
BLPDM1218	18	
BLPDM1219	19	
BLPDM1220	20	
BLPDM1221	21	
BLPDM1222	22	
BLPDM1223	23	41
BLPDM1224	24	41
BLPDM1225	25	
BLPDM1226	26	
BLPDM1227	27	
BLPDM1228	28	
BLPDM1229	29	44
BLPDM1230	30	44
BLPDM1231	31	
BLPDM1232	32	
BLPDM1234	34	
BLPDM1236	36	50

1/2" Socket, Inches, 12-Point

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	SIZE (inches)	LENGTH (mm)
BLPD12516	5/16	
BLPD1238	3/8	
BLPD12716	7/16	
BLPD1212	1/2	
BLPD12916	9/16	38
BLPD1258	5/8	
BLPD121116	11/16	
BLPD1234	3/4	
BLPD121316	13/16	
BLPD1278	7/8	
BLPD121516	15/16	41
BLPD121	1	
BLPDB121116	1 1/16	
BLPDB12118	1 1/8	44
BLPDB12114	1 1/4	



RATCHETS, SOCKETS & ACCESSORIES

1/2" Sockets / Bit Sockets

Packing: 6

1/2" Long Socket, mm, 6-Point

LENGTH

(mm)

76

SIZE

(mm)

10

11

12

13

14

15

16

PART NO.

BLPLM1210

BLPLM1211

BLPLM1212

BLPLM1213

BLPLM1214

BLPLM1215

BLPLM1216

BLPLM1217 BLPLM1218

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	S
200	
Selection .	

PART NO.	SIZE (mm)	
BLPLM1219	19	
BLPLM1220	20	
BLPLM1221	21	
BLPLM1222	22	76
BLPLM1224	24	76
BLPLM1227	27	
BLPLM1230	30	
BLPLM1232	32	

1/2" Long Socket, Inches, 6-Point

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds **ANSI Standards**



PART NO.	SIZE (inches)	LENGTH (mm)
BLPL1238	3/8	
BLPL12716	7/16	
BLPL1212	1/2	
BLPL12916	9/16	76
BLPL1258	5/8	
BLPL121116	11/16	
BLPL1234	3/4	

PART NO.	SIZE (inches)	LENGTH (mm)
BLPL121316	13/16	
BLPL1278	7/8	
BLPL121516	15/16	
BLPL121	1	76
BLPLB121116	1 ¹ /16	
BLPLB12118	1 1/8	
BLPLB125114	1 1/4	

1/2" Long Socket, mm, 12-Point

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards

BLPDLM1218

BLPDLM1219

BLPDLM1220



Packing: 6

LENGTH

77

PART NO.	SIZE (mm)	LENGTH (mm)	PART NO.	SIZE (mm
BLPDLM129	9		BLPDLM1221	21
BLPDLM1210	10		BLPDLM1222	22
BLPDLM1211	11		BLPDLM1223	23
BLPDLM1212	12		BLPDLM1224	24
BLPDLM1213	13		BLPDLM1225	25
BLPDLM1214	14	77	BLPDLM1226	26
BLPDLM1215	15		BLPDLM1227	27
BLPDLM1216	16		BLPDLM1230	30
BLPDLM1217	17		BLPDLM1232	32

BLPDLM1234

BLPDLM1236

1/2" External Torx® Socket

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards




PART NO.	# [LENGTH (mm)
BLPTE1210	E10	
BLPTE1212	E12	
BLPTE1214	E14	
BLPTE1216	E16	38
BLPTE1218	E18	30
BLPTE1220	E20	
BLPTE1222	E22	
BLPTE1224	E24	



19







34





1/2" Torx® Bit Socket, Tamper Resistant

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards





PART NO.	# 1	A
BLPT1255TP	T55	2 5/16
BLPT1260TP	T60	2 5/16

E-Paints

1/2" Torx® Bit Socket, Long, Tamper Resistant

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards





PART NO.	# <u>T</u>	LENGTH (mm)
BLPTL1255TP	T55	120
BLPTL1260TP	T60	120

1/2" Torx® Socket Driver

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards





PART NO.	# Ţ	LENGTH (mm)
BLPT1220	T20	
BLPT1225	T25	
BLPT1227	T27	
BLPT1230	T30	
BLPT1240	T40	37
BLPT1245	T45	
BLPT1250	T50	
BLPT1255	T55	
BLPT1260	T60	

1/2" Torx® Socket Driver, Long

- Manufactured from high grade steel alloy
 Features a Lifetime
- Features a Lifetime Warranty and exceeds ANSI Standards





PART NO.	# 1	LENGTH (mm)
BLPTL1220	T20	
BLPTL1225	T25	
BLPTL1227	T27	
BLPTL1230	T30	
BLPTL1240	T40	100
BLPTL1245	T45	
BLPTL1250	T50	
BLPTL1255	T55	
BLPTL1260	T60	



RATCHETS, SOCKETS & ACCESSORIES 1/2" Bit Sockets / Chrome Accessories

1/2" Hex Socket Driver


Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	SIZE (mm)	LENGTH (mm)
BLPH123	3	
BLPH124	4	
BLPH125	5	
BLPH126	6	
BLPH127	7	
BLPH128	8	36.5
BLPH1210	10	
BLPHM1212	12	
BLPH1214	14	
BLPH1217	17	
BLPH1219	19	
BLPH125L180	5	180
BLPH126L70	6	70
BLPH126L140	6	140
BLPH126L250	6	250
BLPH128L120	8	120
BLPH1210L140	10	140

1/2" Triple Square Socket Driver



Features a Lifetime Warranty and exceeds ANSI Standards





Packing: 6

PART NO.	SIZE	LENGTH (mm)
BLPXZNM125	M5	
BLPXZNM126	M6	
BLPXZNM128	M8	
BLPXZNM1210	M10	37
BLPXZNM1212	M12	
BLPXZNM1214	M14	
BLPXZNM1216	M16	

1/2" Hex Socket Driver, Long

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	SIZE (mm)	LENGTH (mm)
BLPHL124	4	
BLPHL125	5	
BLPHL126	6	
BLPHL127	7	
BLPHL128	8	100
BLPHL1210	10	
BLPHL1212	12	
BLPHL1214	14	
BLPHL1217	17	

1/2" Breaker Bar

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	LENGTH (mm)
BLPBB1210	254
BLPBB1215	381
BLPBB1224AP	605

1/2" Sliding T-Handle

BLPSTHD1215

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	LENGTH (mm)
BLPSTHD1215	381







1/2" Speeder

BLPS12

Packing: 6

- Manufactured from high grade steel alloyFeatures a Lifetime
- Features a Lifetime Warranty and exceeds ANSI Standards





Packing: 6

PART NO.	LENGTH (mm)
BLPS12	457

1/2" Extension, Knurled

Manufactured from high grade steel alloy

 Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	LENGTH (mm)
BLPEXTK123	76
BLPEXTK125	127
BLPEXTK126	152
BLPEXTK1210	254

1/2" Universal Joint

BLPUJ12

Packing: 6

- · Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards





PART NO.	LENGTH (mm)
BLPUJ12	70

1/2" Sliding Head

BLPSH1238

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards





Packing: 6

PART NO.	LENGTH (mm)	
BLPSH1238	37	

1/2" Locking Extension

Manufactured from high grade steel alloy



PART NO.	LENGTH (mm)
SXLBP3	76
SXLBP6	152
SXLBP10	254

1/2" Adaptor

BLPAFM1238

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards





PART NO.	INTERNAL SQ. DRIVE (inches)	EXTERNAL SQ. DRIVE (inches)
BLPAFM1238	1/2	3/8



RATCHETS, SOCKETS & ACCESSORIES

1/2" Impact Sockets & Accessories

1/2" Impact Socket, Shallow, mm, 6-Point

- · Designed for maximum engagement on 6-point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



PART NO.	SIZE (mm)
BLPSMIM1210	10
BLPSMIM1211	11
BLPSMIM1212	12
BLPSMIM1213	13
BLPSMIM1214	14
BLPSMIM1215	15
BLPSMIM1216	16
BLPSMIM1217	17
BLPSMIM1218	18

PART NO.	SIZE (mm)
BLPSMIM1219	19
BLPSMIM1221	21
BLPSMIM1222	22
BLPSMIM1223	23
BLPSMIM1224	24
BLPSMIM1227	27
BLPSMIM1229	29
BLPSMIM1230	30
BLPSMIM1232	32

1/2" Impact Socket, Shallow, Inches, 6-Point

- · Designed for maximum engagement on 6-point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



PART NO.	SIZE (inches)
BLPSIM1238	3/8
BLPSIM12716	7/16
BLPSIM1212	1/2
BLPSIM12916	9/16
BLPSIM1258	5/8
BLPSIM121116	11/16
BLPSIM1234	3/4
BLPSIM121316	13/16

PART NO.	SIZE (inches)
BLPSIM1278	7/8
BLPSIM121516	15/16
BLPSIM121	1
BLPSIMB121116	1 1/16
BLPSIMB12118	1 1/8
BLPSIMB12114	1 1/4
BLPSIMB121516	1 5/16
BLPSIMB121716	1 7/16

1/2" Impact Socket, Deep, mm, 6-Point



- · Designed for maximum engagement on 6-point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



1/2" Impact Socket, Deep, Inches, 6-Point

- · Designed for maximum engagement on 6-point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



PART NO.	SIZE (mm)
BLPLSMIM1210	10
BLPLSMIM1211	11
BLPLSMIM1212	12
BLPLSMIM1213	13
BLPLSMIM1214	14
BLPLSMIM1215	15
BLPLSMIM1216	16
BLPLSMIM1217	17
BLPLSMIM1218	18

PART NO.	SIZE (mm)
BLPLSMIM1219	19
BLPLSMIM1221	21
BLPLSMIM1222	22
BLPLSMIM1224	24
BLPLSMIM1226	26
BLPLSMIM1227	27
BLPLSMIM1229	29
BLPLSMIM1230	30
BLPLSMIM1232	32

PART NO.	SIZE (inches)
BLPLSIM1238	3/8
BLPLSIM12716	7/16
BLPLSIM1212	1/2
BLPLSIM12916	9/16
BLPLSIM1258	5/8
BLPLSIM121116	11/16
BLPLSIM1234	3/4
BLPLSIM121316	13/16

PART NO.	SIZE (inches)
BLPLSIM1278	7/8
BLPLSIM121516	15/16
BLPLSIM121	1
BLPLSIMB12116	1 1/16
BLPLSIMB12118	1 1/8
BLPLSIMB121316	1 3/16
BLPLSIMB12114	1 1/4





1/2" Universal Joints

BLPJIM12

- Packing: 6
- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove



PART NO.	SIZE (inches)
BLPJIM12	1/2 male x 1/2 female

1/2" Impact Adaptor

Packing: 6

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove





BLPAIM3412

BLPAIM3812

PART NO.	SIZE (inches)
BLPAIM3412	3/4 male x 1/2 female
BLPAIM3812	3/8 male x 1/2 female

4-Lug Extension Spindle Nut Socket

SNS3195



- For high-shear rotating nuts
- 1/2-ton Dana 80 axle
- Socket I.D.: 2-3/8"



Plastic Lug Impact Socket Set, 3pcs

BLPLIM12S3AP



- Plastic sleeve on socket walls to ensure protection on rim surface
- Plastic insert inside the socket to ensure protection of wheel nuts



- Wheel impact sockets for easy access
- 3 sizes 6-points sockets: 17, 19 and 21 mm
- Comes with heavy duty blow mold box

1/2" Extension



- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove

ı		
ı		
l		
	Ļ	L

PART NO.	SIZE (inches)
BLPEXIM123	3
BLPEXIM125	5
BLPEXIM126	6
BLPEXIM1210	10



RATCHETS, SOCKETS & ACCESSORIES 3/4" Ratchets / Sockets / Chrome Accessories

3/4" Quick Release Ratchet

BPRSR942

- Packing: 6
- Features quick release button for rapid socket/ accessory changes, even with greasy or oily hands
- Contoured handle for comfort and control
- Chrome finish for easy clean-up
- All ratchets in series meet or exceed ANSI B107-10M-1996 specifications



PART NO.	SQ. DRIVE (inches)	LENGTH (mm)
BPRSR942	3/4	508

3/4" L-Shape Wrench

BLPLW3415

- Packing: 6
- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds **ANSI Standards**



PART NO.	LENGTH (mm)
BLPLW3415	381

3/4" Breaker Bar

BLPBB3419



- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds



PART NO.	LENGTH (mm)
BLPBB3419	483

3/4" Extension

Manufactured from high grade steel alloy

Features a Lifetime Warranty and exceeds **ANSI Standards**



Packing: 6

PART NO.	LENGTH (mm)
BLPEXT344	102
BLPEXT348	203
BLPEXT3416	406

3/4" Sliding T-Handle

BLPSTHD3418

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds



PART NO.	LENGTH (mm)
BLPSTHD3418	457

3/4" Universal Joint

BLPUJ34

Manufactured from high grade steel alloy

Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	LENGTH (mm)
BLPUJ34	110





3/4" Socket, mm, 6-Point

Packing: 6

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards





3/4" Socket, mm, 12-Point

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards



PART NO.	SIZE (mm)	LENGTH (mm)
BLPM3419	19	
BLPM3420	20	
BLPM3421	21	50
BLPM3422	22	
BLPM3423	23	
BLPM3424	24	51
BLPM3425	25	
BLPM3426	26	
BLPM3427	27	52
BLPM3428	28	
BLPM3429	29	
BLPM3430	30	54
BLPM3432	32	
BLPM3433	33	56
BLPM3434	34	
BLPM3435	35	58
BLPM3436	36	
BLPM3438	38	60
BLPM3441	41	64
BLPM3446	46	66
BLPM3450	50	70
BLPM3455	55	76
BLPM3460	60	78

PART NO.	SIZE (mm)	LENGTH (mm)
BLPDM3419	19	
BLPDM3421	21	47
BLPDM3422	22	
BLPDM3423	23	50
BLPDM3424	24	30
BLPDM3425	25	
BLPDM3426	26	
BLPDM3427	27	53
BLPDM3428	28	
BLPDM3429	29	
BLPDM3430	30	58
BLPDM3432	32	36
BLPDM3433	33	
BLPDM3434	34	60
BLPDM3435	35	
BLPDM3436	36	63
BLPDM3438	38	00
BLPDM3441	41	66
BLPDM3446	46	68
BLPDM3450	50	00
BLPDM3455	55	69
BLPDM3460	60	72

RATCHETS, SOCKETS & ACCESSORIES 3/4" Impact Sockets & Accessories

3/4" Impact Socket, Shallow, mm, 6-Point

Packing: 6

- Designed for maximum engagement on 6-point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



PART NO.	SIZE (mm)	PART NO.	SIZE (mm)
BLPSMIM3417	17	BLPSMIM3439	39
BLPSMIM3418	18	BLPSMIM3440	40
BLPSMIM3419	19	BLPSMIM3441	41
BLPSMIM3420	20	BLPSMIM3442	42
BLPSMIM3421	21	BLPSMIM3443	43
BLPSMIM3422	22	BLPSMIM3444	44
BLPSMIM3423	23	BLPSMIM3445	45
BLPSMIM3424	24	BLPSMIM3446	46
BLPSMIM3425	25	BLPSMIM3447	47
BLPSMIM3426	26	BLPSMIM3448	48
BLPSMIM3427	27	BLPSMIM3449	49
BLPSMIM3428	28	BLPSMIM3450	50
BLPSMIM3429	29	BLPSMIM3452	52
BLPSMIM3430	30	BLPSMIM3454	54
BLPSMIM3431	31	BLPSMIM3455	55
BLPSMIM3432	32	BLPSMIM3456	56
BLPSMIM3433	33	BLPSMIM3457	57
BLPSMIM3434	34	BLPSMIM3458	58
BLPSMIM3435	35	BLPSMIM3459	59
BLPSMIM3436	36	BLPSMIM3460	60
BLPSMIM3437	37	BLPSMIM3463	63
BLPSMIM3438	38	BLPSMIM3465	65

3/4" Impact Socket, Shallow, Inches, 6-Point

- Designed for maximum engagement on 6-point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



PART NO.	SIZE (inches)
BLPSIM341116	11/16
BLPSIM3434	3/4
BLPSIM341316	13/16
BLPSIM3478	7/8
BLPSIM341516	15/16
BLPSIM341	1
BLPSIMB341116	1 1/16
BLPSIMB34118	1 1/8
BLPSIMB341316	1 3/16
BLPSIMB34114	1 1/4
BLPSIMB341516	1 5/16
BLPSIMB34138	1 3/8
BLPSIMB341716	1 7/16
BLPSIMB34112	1 1/2
BLPSIMB341916	1 9/16
BLPSIMB34158	1 5/8
BLPSIMB3411116	1 11/16
BLPSIMB34134	1 3/4
BLPSIMB3411316	1 ¹³ /16
BLPSIMB34178	1 7/8
BLPSIMB3411516	1 ¹⁵ /16
BLPSIMB342	2





3/4" Impact Socket, Deep, mm, 6-Point

Packing: 6

- Designed for maximum engagement on 6-point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



PART NO.	SIZE (mm)
BLPLSMIM3417	17
BLPLSMIM3418	18
BLPLSMIM3419	19
BLPLSMIM3420	20
BLPLSMIM3421	21
BLPLSMIM3422	22
BLPLSMIM3423	23
BLPLSMIM3424	24
BLPLSMIM3425	25
BLPLSMIM3426	26
BLPLSMIM3427	27
BLPLSMIM3428	28
BLPLSMIM3429	29
BLPLSMIM3430	30
BLPLSMIM3431	31
BLPLSMIM3432	32
BLPLSMIM3433	33

PART NO.	SIZE (mm)
BLPLSMIM3434	34
BLPLSMIM3435	35
BLPLSMIM3436	36
BLPLSMIM3437	37
BLPLSMIM3438	38
BLPLSMIM3440	40
BLPLSMIM3441	41
BLPLSMIM3442	42
BLPLSMIM3443	43
BLPLSMIM3444	44
BLPLSMIM3445	45
BLPLSMIM3446	46
BLPLSMIM3447	47
BLPLSMIM3448	48
BLPLSMIM3449	49
BLPLSMIM3450	50
BLPLSMIM3455	55

3/4" Impact Adaptor

BLPAIM1234



- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove



PART NO.	SIZE (inches)
BLPAIM1234	1/2 male x 3/4 female

3/4" Impact Adaptor

BLPAIM134



- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove



PART NO.	SIZE (inches)
BLPAIM134	1 male x ³ / ₄ female

3/4" Universal Joint

BLPJIM34



- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove



PART NO.	SIZE (inches)
BLPJIM34	3/4 male x 3/4 female

3/4" Extension

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove



PART NO.	SIZE (inches)
BLPEXIM343	3 1/2
BLPEXIM344	4
BLPEXIM346	6
BLPEXIM347	7
BLPEXIM348	8
BLPEXIM3410	10
BLPEXIM3413	13

RATCHETS, SOCKETS & ACCESSORIES 1" Impact Sockets & Accessories

1" Impact Socket, Shallow, mm, 6-Point

Packing: 6

- Designed for maximum engagement on 6-point fasteners
- Suitable for use with pneumatic and electric impact wrenches
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



PART NO.	SIZE (mm)	PART NO.	SIZE (mm)
BLPSMIM117	17	BLPSMIM142	42
BLPSMIM118	18	BLPSMIM143	43
BLPSMIM119	19	BLPSMIM144	44
BLPSMIM120	20	BLPSMIM145	45
BLPSMIM121	21	BLPSMIM146	46
BLPSMIM122	22	BLPSMIM147	47
BLPSMIM123	23	BLPSMIM148	48
BLPSMIM124	24	BLPSMIM149	49
BLPSMIM125	25	BLPSMIM150	50
BLPSMIM126	26	BLPSMIM151	51
BLPSMIM127	27	BLPSMIM152	52
BLPSMIM128	28	BLPSMIM153	53
BLPSMIM129	29	BLPSMIM154	54
BLPSMIM130	30	BLPSMIM155	55
BLPSMIM131	31	BLPSMIM156	56
BLPSMIM132	32	BLPSMIM157	57
BLPSMIM133	33	BLPSMIM158	58
BLPSMIM134	34	BLPSMIM159	59
BLPSMIM135	35	BLPSMIM160	60
BLPSMIM136	36	BLPSMIM163	63
BLPSMIM137	37	BLPSMIM165	65
BLPSMIM138	38	BLPSMIM167	67
BLPSMIM139	39	BLPSMIM168	68
BLPSMIM140	40	BLPSMIM169	69
BLPSMIM141	41		

1" Impact Socket, Deep, mm, 6-Point

- Designed for maximum engagement on 6-point fasteners
- Suitable for use with pneumatic and electric impact
- Specially heat treated for impact use to provide long life, safety, and durability
- Drive end features pin retention hole and groove



PART NO.	SIZE (mm)
BLPLSMIM117	17
BLPLSMIM118	18
BLPLSMIM119	19
BLPLSMIM120	20
BLPLSMIM121	21
BLPLSMIM122	22
BLPLSMIM123	23
BLPLSMIM124	24
BLPLSMIM125	25
BLPLSMIM126	26
BLPLSMIM127	27
BLPLSMIM128	28
BLPLSMIM129	29
BLPLSMIM130	30
BLPLSMIM131	31

PART NO.	SIZE (mm)
BLPLSMIM132	32
BLPLSMIM133	33
BLPLSMIM134	34
BLPLSMIM135	35
BLPLSMIM136	36
BLPLSMIM137	37
BLPLSMIM138	38
BLPLSMIM140	40
BLPLSMIM141	41
BLPLSMIM142	42
BLPLSMIM143	43
BLPLSMIM146	46
BLPLSMIM149	49
BLPLSMIM150	50
BLPLSMIM155	55







1" Extension

Packing: 6

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove



PART NO.	SIZE (inches)
BLPEXIM17	7
BLPEXIM113	13

1" Impact Adaptor

BLPAIM1121

Packing: 6

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove



PART NO.	SIZE (inches)			
BLPAIM1121	1 1/2 male x 1 female			

1" Universal Joint

BLPJIM1

- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove



Packing: 6

PART NO.	SIZE (inches)
BLPJIM1	7

Impact Socket Pin and Rubber Ring

Packing: 1

- Fits both standard and deep impact sockets
- Accident proof ring and pinSuitable for electric and
- Suitable for electric and pneumatic tools
- Secures impact socket to main shaft of impact wrench



PART NO.	INTERNAL SQ. DRIVE (inches)	EXTERNAL SQ. DRIVE (inches)
BLP34RPRR1750	3/4"	17-50
BLP34RPRR5270	3/4"	52-70
BLP1RPRR1770	1"	17-70

1" Impact Adaptor

BLPAIM341


- Specially heat treated for impact use to provide long life, safety, and durability
- Suitable for use with pneumatic and electric impact wrenches
- Drive end features pin retention hole and groove



PART NO.	SIZE (inches)			
BLPAIM341	3/4 male x 1 female			















Adjustable Click-Type Torque Wrench

- Dual scale, calibrated dual direction
- · Positive lock with spring loaded pull down lock ring
- Fast, accurate and easy to set
- Easy-to-read laser marked scales
- Most feature quick release buttons which provide good socket retention as well as easy socket removal
- Accuracy: ± 3% CW ± 4% CCW of indicated value, CW, from 20% to 100% of full scale
- Meets or exceeds ASME B107.14-2004, ISO 6789 standards
- Individually serialized with matching certificate of calibration traceable to N.I.S.T.





PART NO.	SQ. DRIVE (inches)	RANGE (Nm)	RANGE (ft.lb.)	INCREMENT (Nm)	A (mm)	B (mm)	WEIGHT (g)
BP501NMRMH	1/4	1.0 - 5.0	1 - 4	0.06	258	27	386
BP2502NMRMH	3/8	4.0 - 27.7	3 - 20	0.12	286	27	431
BP602NMRMH	3/8	10 - 60	8 - 45	0.5	406	36	1,134
BP1002NMRMH	3/8	20 - 100	15 - 75	0.5	406	36	1,134
BP2003NMRMH	1/2	40 - 200	30 - 147.5	2	483	43	1,474
BP3403NMRMH	1/2	60 - 340	45 - 250	2	620	43	1,542
BP8004NMRMH	3/4	150 - 800	110 - 600	5	1,067	64	5,375
BP15005NMRMH	1	300 - 1500	220 - 1100	10	1,778	76	11,385

Preset Click-Type Torque Wrench

Packing: 1

- All parts are made of alloy steel for maximum life and calibration retention
- Square drives meet industrial requirements and government specifications
- Torques in both left and right hand directions
- Accuracy: ± 3% CW ± 4% CCW of indicated value
- Automatic re-set when force on handle is released
- Torque limiting positive sensory "click" when pre-set
- Smooth knurled steel hand hold for comfortable, safe grip
- Handle length proportioned to torque range of wrench for minimum user fatigue
- Tamper proof torque setting for production line use
- Torque values can be calibrated in English and Metric settings




PART NO.	SQ. DRIVE (inches)	RANGE (Nm)	RANGE (ft.lb.)	RANGE (in.lb.)	RANGE (M Kg)	LENGTH (mm)	WEIGHT (g)
BP5T-1R	1/4	1.4 - 5.4	1 - 5	12 - 60	0.10 - 0.70	165	227
BP10T-2R	3/8	3.9 - 27.7	3 - 9	36 - 108	0.42 - 1.24	184	397
BP50T-2R	3/8	10.2 - 98.3	10 - 50	120 - 600	1.25 - 7.00	292	680
BP100T-3R	1/2	34 - 197	45 - 150	540 - 1800	6.00 - 20.00	502	1,247
BP200T-3R	1/2	47 - 272	45 - 200	540 - 2400	6.00 - 27.00	603	1,361
BP300T-4R	3/4	85 - 400	100 - 300	1200 - 3600	14.00 - 42.00	711	2,155
BP600T-4R	3/4	280 - 830	200 - 600	2400 - 7200	28.00 - 83.00	1,321	5,443

Preset Click-Type Torque Wrench, Interchangeable Head

- 8 models available with torque ranges from 10 in.lb. to 600 ft.lb.
- Featuring a durable, non-slip cushion grip
- Uses universal round shank heads
- Audible click and feel impulse torque control mechanism
- Tamper proof torque setting for production line use
- Torque values can be calibrated in English or metric setting
- Accuracy: ± 4% of indicated value, from 20% to 100% of full scale
- Meets or exceeds ASME B107.14-2004, ISO 6789
- Optional Calibration certificate available at additional cost






PART NO.	SHANK SIZE	ENGLISH RANGE	RANGE (Nm)	A (mm)	B (mm)	C (mm)	D (mm)	WEIGHT (g)
BP5T-I	J	10 - 50 in.lb.	1.1 - 5.6	165	16	15	25	159
BP10T-I	J	50 - 250 in.lb.	5.6 - 28	254	16	15	25	249
BP10ST-I	J	60 - 300 in.lb.	6.8 - 34	157	17	22	36	340
BP50T-I	J	15 - 75 ft.lb.	20 - 102	279	17	22	36	635
BP100T-I	Y	30 - 150 ft.lb.	41 - 203	495	24	22	36	1,043
BP200T-I	Υ	40 - 200 ft.lb.	54 - 271	597	24	22	36	1,179
BP300T-I	Х	100 - 300 ft.lb.	135 - 406	704	28	25	36	1,769
BP600T-I	Z	120 - 600 ft.lb.	162 - 814	1,397	38	32	32	4,740











Ratcheting Interchangeable Head

Allows use of torque wrench bodies with sockets, crowfoot wrenches, or other similar attachment

Center of fastener to retaining

- pin:
- * J Series 2.50"
- * Y Series 3.00"
- * X Series 4.50"
- * Z Series 5.75"



SQ. DRIVE (inches)	SHANK SIZE J	SHANK SIZE Y	SHANK SIZE X	SHANK SIZE Z	HEAD O.D. (mm)	DEPTH (mm)	RATCHET SERVICE KIT
1/4	QJD8A-72* (350)	_	_	_	3	3.5	RKRT936
3/8	QJD12A* (900)	QYD12A* (1,200)	_	_	17	4.4	RKRF936
1/2	QJD16A* (900)	QYD16A* (2,400)	QXD16A* (3,000)	_	17	4.4	RKRS936
3/4	-	_	QXD24A (3,600)	QZD24B (7,200)	20	4.4	RKRQC4
1	_	_	QXD32A (3,600)	QZD32B (7,200)	20	4.4	RKRQC5

Open End Head, mm



Value in parentheses in chart is the Maximum Recommended Working Torque, in.lb.

<u> </u>	SHANK SIZE J	SHANK SIZE Y	SHANK SIZE X	SHANK SIZE Z	HEAD O.D. (mm)	HEAD DEPTH (mm)		SHANK SIZE J	SHANK SIZE Y	SHANK SIZE X	SHANK SIZE Z	HEAD O.D. (mm)	HEAD DEPTH (mm)
6	QJOM6A (60)	-	-	_	13.5	3.6	20	_	QYOM20A (1,925)	QXOM20A (1,925)	-	43.7	9.2
7	QJOM7A (75)	-	_	_	13.5	3.6	21	QJOM21A (900)	QYOM21A (2,160)	QXOM21A (2,160)	_	43.7	9.2
8	QJOM8A (120)	-	_	_	16.5	3.3	22	QJOM22A (900)	QYOM22A (2,400)	QXOM22A (2,470)	_	43.7	9.2
9	QJOM9A (170)	_	_	_	19.8	4.8	23	QJOM23A (900)	QYOM23A (2,400)	QXOM23A (2,745)	_	47	10
10	QJOM10A (265)	_	_	_	19.8	4.8	24	QJOM24A (900)	QYOM24A (2,400)	QXOM24A (2,970)	QZOM24A (2,970)	49	11
11	QJOM11A (400)	-	_	_	22.9	5.6	25	QJOM25A (900)	QYOM25A (2,400)	-	QZOM25A (3,295)	52	11
12	QJOM12A (430)	-	_	_	26.9	6.1	26	QJOM26A (900)	_	QXOM26A (3,570)	QZOM26A (3,570)	53	11
13	QJOM13A (495)	-	_	_	26.9	6.1	27	QJOM27A (900)	QYOM27A (2,400)	-	QZOM27A (3,825)	55	12
14	QJOM14A (665)	QYOM14A (665)	_	_	29.5	6.6	29	_	QYOM29A (2,400)	QXOM29A (3,600)	QZOM29A (4,550)	58	12
15	QJOM15A (885)	QYOM15A (885)	_	_	33.3	6.9	30	-	QYOM30A (2,400)	QXOM30A (3,600)	QZOM30A (4,950)	61	13
16	QJOM16A (900)	QYOM16A (1,060)	_	_	33.3	6.9	32	-	QYOM32A (2,400)	QXOM32A (3,600)	QZOM32A (5,755)	65	14
17	QJOM17A (900)	QYOM17A (1,235)	-	_	37.1	7.3	34	-	QYOM34A (2,400)	QXOM34A (3,600)	QZOM34A (6,595)	68	14
18	QJOM18A (900)	QYOM18A (1,375)	QXOM18A (1,375)	_	37.1	7.3	36	_	QYOM36A (2,400)	QXOM36A (3,600)	QZOM36A (7,200)	74	15
19	QJOM19A (900)	QYOM19A (1,650)	QXOM19A (1,650)	_	40.4	7.6							



COMPUTORQ 3 Digital Torque Wrench

- Uses CR123 replaceable batteries
- Audible tone indication













Packing: 1

COMPUTORQ 3 Digital Torque Wrench

- Sleek new design
- 15° flex ratcheting head
- Push button socket release head
- · Large, easy to read digital display
- Long battery life, uses 2 each CR123 lithium batteries
- Ergonomically designed molded non-slip rubber grip
- Torques in both clockwise and counterclockwise directions
- Battery saving auto-shutoff after two minutes
- COMPUTORQ 3 remembers last unit and torque setting selected
- Audible tone sounds when set torque value is reached, if the set torque value is exceeded, an alarm tone will sound
- 3 color LED light bar:

YELLOW LED indicates approaching desired torque setting GREEN LED indicates desired torque value is reached RED LED indicates fastener was overtorqued, loosen and retighten

- When desired torque value is reached, display will hold value and flash for ten seconds
- COMPUTORQ 3 will operate in any of four torque units, foot pound (ft.lb.), inch pound (in.lb.), newton meter (Nm)
 or kilogram centimeter (kg.cm.)
- ACCURACY:
 - $\pm\,2\%$ CW of readings from 10% to 100% of full scale
 - $\pm\,3\%$ CCW of readings from 20% to 100% of full scale
- N.I.S.T. traceable certificate of calibration included
- Meets or exceeds ASME B107.28 2005





PART NO.	SQ. DRIVE (inches)	RANGE (ft.lb.)	RANGE (in.lb.)	RANGE (Nm)	RANGE (kg.cm.)	LENGTH (mm)	WEIGHT (g)
BP2401CI3	1/4	2.0 - 20.0	24 - 240	2.71 - 27.10	27.6 - 276	381	910
BP1002CF3	3/8	10.0 - 100.0	120 - 1200	13.6 - 135.6	138 - 1382	432	1,000
BP2503CF3	1/2	25 - 250	300 - 3000	33.8 - 338	345 - 3456	686	1,590



Digital Torque Tester

- Remember last 500 cycle counts
- Audible tone signals









Digital Torque Tester

- Integral Transducer and sturdy housing allow mounting in virtually any position
- Integral Transducer: Full bridge strain gage, 350 ohm, 1500uE, 3mV/V F.S, 3.75 excitation
- Units of Torque: Nm, kg.cm., ft.lb., in.lb., in.oz.
- Audible (tone)
- Torque Accuracy: ± 0.5% ± 1% count CW and CCW from 10% to 100% of full scale at 25° C
- LCD Touch Screen: 4.7 inch color graphics display
- Screen resolution: 480 X 272 pixels
- Display Accuracy: 4 digits, 500 cycle counts
- 6 "AA" Alkaline cells for battery power included
- Track, Peak and First Peak modes of operation
- Operating Temperature: 40° to 110° F (5° to 42° C)
- Storage Temperature: 0° to 122° F (-20° to 50° C)
- Humidity up to 85% non-condensing
- ISO-6789-2003 and ASME B107-28-2005 standards compliant
- Certificate of N.I.S.T. traceability from 10% to 100% of full scale
- Includes storage case, AC adapter and USB cable 110v 220v
- Dates & times, serial numbers, required accuracy vs actual readings, percentage error & users of torque wrenches tested are stored




PART NO.	SQ. DRIVE (inches)	ENGLISH RANGE	RANGE (Nm)
BP1001-O-DTT	1/4	10 - 100 in.oz.	0.07 - 0.706
BP501-I-DTT	1/4	5 - 50 in.lb.	0.56 - 5.65
BP2502-I-DTT	3/8	25 - 250 in.lb.	2.82 - 28.25
BP2503-F-DTT	1/2	25 - 250 ft.lb.	33.90 - 338.9
BP6004-F-DTT	3/4	60 - 600 ft.lb.	81.35 - 813.5
BP10002-I-DTT	3/8	100 - 1000 in.lb.	11.3 -113









Combination Wrench Set

BLPCWS23

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards
- Set in pouch packaging





PART NO.	CONTENTS
BLPCWS23	Combination Wrenches Sizes: 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 27, 30, 32 mm





Combination, Long

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards

Packir	ng: 6
--------	-------

PART NO.	™ <u>T</u>	L (mm)
BLPCWM36	36	432
BLPCWM38	38	432
BLPCWM41	41	445
BLPCWM46	46	483




Combination, Regular

- Manufactured from high grade steel alloy
- Features a Lifetime Warranty and exceeds ANSI Standards
- New high polish



PART NO.	™ <u>T</u>	L (mm)
BLPCWM6AP	6	104
BLPCWM7AP	7	110
BLPCWM8AP	8	120
BLPCWM9AP	9	125
BLPCWM10AP	10	135
BLPCWM11AP	11	144
BLPCWM12AP	12	155
BLPCWM13AP	13	165
BLPCWM14AP	14	175
BLPCWM15AP	15	184
BLPCWM16AP	16	195
BLPCWM17AP	17	204
BLPCWM18AP	18	215
BLPCWM19AP	19	229

PART NO.	™ <u>T</u>	L (mm)
BLPCWM20AP	20	239
BLPCWM21AP	21	249.8
BLPCWM22AP	22	249.8
BLPCWM23AP	23	269
BLPCWM24AP	24	269
BLPCWM25AP	25	290
BLPCWM26AP	26	290
BLPCWM27AP	27	310
BLPCWM28AP	28	330
BLPCWM29AP	29	330
BLPCWM30AP	30	330
BLPCWM32AP	32	350
BLPCWM34AP	34	350



Adjustable Wrench Set, 3pcs

BLPADJ703



Adjustable Wrench Set, 4pcs

BLPADJ404







PART NO.	CONTENTS	
BLPADJ703	Adjustable Wrenches 15" GAJ15A, 18" GAJ18A, 24" GAJ24A	

PART NO.	CONTENTS
BLPADJ404	Adjustable Wrenches 6" GAJ6A, 8" GAJ8A, 10" GAJ10A, 12" GAJ12A

Adjustable Wrenches

- Wrench features a durable black phosphate finish
- Wide-open jaw design with polished head
- Heat treated steel alloy construction
- Inch scale laser etched on head face

PART NO.**	A (mm)	L (mm)	•
GAJ4AP	13	108	6
GAJ6AP	25	160	6
GAJ8AP	29	210	6
GAJ10AP	33	260	6
GAJ12AP	38	310	6
GAJ15AP	43	385	4
GAJ18AP	52	450	2
GAJ24AP	62	610	1
GAJS30AP	85	778	1









Packing: 4

Packing: 6

Adjustable Wrench Set, Soft Grip, 4pcs

BLPADJ404SG

- Now the most popular Blue-Point[®] Adjustable Wrenches are available with soft grips
- Durable black phosphate finish
- Wide open jaw design with oversized capacity
- Laser-etched SAE/metric scale for easy determination of bolt size
- · Soft Grip design for added comfort




PART NO.	CONTENTS
BLPADJ404SG	Adjustable Wrenches, Soft Grip 6" GAJ6SG, 8" GAJ8SG, 10" GAJ10SG, 12" GAJ12SG

Adjustable Soft Grip

- Now the most popular Blue-Point[®] Adjustable Wrenches are available with soft grips
- Durable black phosphate finish
- Wide open jaw design with oversized capacity
- Laser-etched SAE/metric scale for easy determination of bolt size
- Soft Grip design for added comfort

PART NO.*	A (mm)	L (mm)
GAJ6SG	25	160
GAJ8SG	29	210
GAJ10SG	33	260
GAJ12SG	38	310







Ring End Wrench Set, 12pcs

BBWDSMSET12

- Features a Lifetime Warranty and exceeds ANSI Standards
- Manufactured from high grade steel alloy
- Set in pouch packaging
- New high polish



PART NO.	A (mm)	L (mm)
BBWDSM67	6 - 7	160
BBWDSM89	8 - 9	175
BBWDSM1011	10 - 11	190
BBWDSM1213	12 - 13	205
BBWDSM1415	14 - 15	228
BBWDSM1617	16 - 17	232
DDWD3M1017	10 - 17	232

PART NO.	A (mm)	L (mm)
BBWDSM1819	18 - 19	246
BBWDSM2022	20 - 22	268
BBWDSM2123	21 - 23	315
BBWDSM2427	24 - 27	360
BBWDSM2528	25 - 28	360
BBWDSM3032	30 - 32	405

Packing: 1 (Set)

45° / 75° Offset Double Ring



PART NO.		mm	不	ı	_
45	75	_	Ţ	(m	m)
BBWSM67	BBWDM67	6 - 7	6 - 7	165	168
BBWSM89	BBWDM89	8 - 9	8 - 9	175	183
BBWSM810	BBWDM810	8 - 10	8 - 10	185	183
BBWSM911	BBWDM1011	9 - 11	10 - 11	195	198
BBWSM1011	BBWDM1012	10 - 11	10 - 12	195	198
BBWSM1012	BBWDM1113	10 - 12	11 - 13	195	218
BBWSM1113	BBWDM1213	11 - 13	12 - 13	205	218
BBWSM1213	BBWDM1214	12 - 13	12 - 14	205	218
BBWSM1214	BBWDM1415	12 - 14	14 - 15	220	235
BBWSM1314	BBWDM1417	13 - 14	14 - 17	220	260
BBWSM1415	BBWDM1617	14 - 15	16 - 17	235	260
BBWSM1417	BBWDM1719	14 - 17	17 - 19	235	292
BBWSM1516	BBWDM1819	15 - 16	18 - 19	240	292
BBWSM1617	BBWDM1921	16 - 17	19 - 21	240	318
BBWSM1719	BBWDM1922	17 - 19	19 - 22	250	318



PART NO.		mm	Ī	ı	_
45	75		Ţ	(m	m)
BBWSM1819	BBWDM2022	18 - 19	20 - 22	250	318
BBWSM1921	BBWDM2123	19 - 21	21 - 23	270	330
BBWSM1922	BBWDM2224	19 - 22	22 - 24	270	330
BBWSM2022	BBWDM2326	20 - 22	23 - 26	270	346
BBWSM2122	BBWDM2426	21 - 22	24 - 26	290	346
BBWSM2123	BBWDM2427	21 - 23	24 - 27	290	346
BBWSM2224	BBWDM2528	22 - 24	25 - 28	320	355
BBWSM2326	BBWDM2430	23 - 26	24 - 30	360	355
BBWSM2426	BBWDM2730	24 - 26	27 - 30	360	355
BBWSM2427	BBWDM3032	24 - 27	30 - 32	360	372
BBWSM2528	BWDM3436A	25 - 28	34 - 36	370	440
BBWSM2730		27 - 30		380	
BBWSM2732		27 - 32		380	
BBWSM3032		30 - 32		380	
BBWSM3436		34 - 36		405	









Packing: 1 (Set)

Double Flex Socket Wrench Set, 8pcs

BLPBWRES8

- Higher Torque 15% to 20% more turning power with Flank Drive wrenching system
- Flexible sockets wrench provides speed and accessibility to work round corners
- 12 point socket end gives great grip at either end making sure there is no slipping when tightening and loosening
- Manufactured from chrome vanadium steel for strength and durability
- Full polished chrome finish easily wipes clean of oil and dirt
- 2 sizes in one wrench
- Supplied in a canvas tool pouch for neat and easy storage and transportation



PART NO.	™ <u></u>	L (mm)
BLPBWREF67	6 - 7	185
BLPBWREF89	8 - 9	185
BLPBWREF1011	10 - 11	200
BLPBWREF1213	12 -13	220

PART NO.	™ <u>1</u>	L (mm)
BLPBWREF1415	14 - 15	242
BLPBWREF1617	16 - 17	254
BLPBWREF1819	18 - 19	275
BLPBWREF2123	21 - 23	305

Double Flex Socket Wrench

- Higher Torque 15% to 20% more turning power with Flank Drive wrenching system
- Flexible sockets wrench provides speed and accessibility to work round corners
- 12 point socket end gives great grip at either end making sure there is no slipping when tightening and loosening
- Manufactured from chrome vanadium steel for strength and durability
- Full polished chrome finish easily wipes clean of oil and dirt
- 2 sizes in one wrench



PART NO.	mm <u>↑</u>	L (mm)
BLPBWREF67	6 - 7	185
BLPBWREF89	8 - 9	185
BLPBWREF810	8 - 10	185
BLPBWREF1011	10 - 11	200
BLPBWREF1012	10 - 12	205
BLPBWREF1013	10 - 13	205
BLPBWREF1113	11 - 13	205
BLPBWREF1213	12 -13	220
BLPBWREF1214	12 -14	225
BLPBWREF1317	13 - 17	242

PART NO.	mm <u> </u>	L (mm)
BLPBWREF1415	14 - 15	242
BLPBWREF1417	14 - 17	244
BLPBWREF1617	16 - 17	254
BLPBWREF1719	17 - 19	260
BLPBWREF1819	18 - 19	275
BLPBWREF1922	19 - 22	300
BLPBWREF2022	20 - 22	305
BLPBWREF2123	21 - 23	305
BLPBWREF2427	24 - 27	335
BLPBWREF3032	30 - 32	345



Double Open End Wrench Set, 12pcs

BDOEMTSET12

- New high polish
- Manufactured from high grade steel alloy
 Features a Lifetime Warranty and exceeds ANSI Standards
- Set in pouch packaging



PART NO.	™ <u></u>	L (mm)
BDOEMT67	6 - 7	126
BDOEMT89	8 - 9	145
BDOEMT1011	10 - 11	162
BDOEMT1213	12 - 13	181
BDOEMT1415	14 - 15	189
BDOEMT1617	16 - 17	198
	<u> </u>	<u> </u>

PART NO.	™ <u>T</u>	L (mm)
BDOEMT1819	18 - 19	198
BDOEMT2022	20 - 22	220
BDOEMT2123	21 - 23	242
BDOEMT2427	24 - 27	264
BDOEMT2528	25 - 28	287
BDOEMT3032	30 - 32	287

Double Open End Wrench

Manufactured from high grade steel alloy

Features a Lifetime Warranty and exceeds **ANSI Standards**



Packing: 6

PART NO.	─ <u>T</u>	L (mm)
BDOEM67	6 - 7	125
BDOEM68	6 - 8	125
BDOEM89	8 - 9	135
BDOEM810	8 - 10	135
BDOEM1011	10 - 11	145
BDOEM1012	10 - 12	145
BDOEM1113	11 - 13	165
BDOEM1213	12 - 13	165
BDOEM1214	12 - 14	165
BDOEM1314	13 - 14	165
BDOEM1415	14 - 15	185
BDOEM1417	14 - 17	185
BDOEM1617	16 - 17	185
BDOEM1719	17 - 19	225
BDOEM1819	18 - 19	225
BDOEM1921	19 - 21	237

BDOEM1922 19 - 22 237 BDOEM2022 20 - 22 255 BDOEM2123 21 - 23 255 BDOEM2224 22 - 24 255 BDOEM2326 23 - 26 295 BDOEM2426 24 - 26 295 BDOEM2427 24 - 27 295 BDOEM2528 25 - 28 334 BDOEM3032 30 - 32 368	PART NO.	mm <u>T</u>	L (mm)
BDOEM2123 21 - 23 255 BDOEM2224 22 - 24 255 BDOEM2326 23 - 26 295 BDOEM2426 24 - 26 295 BDOEM2427 24 - 27 295 BDOEM2528 25 - 28 334	BDOEM1922	19 - 22	237
BDOEM2224 22 - 24 255 BDOEM2326 23 - 26 295 BDOEM2426 24 - 26 295 BDOEM2427 24 - 27 295 BDOEM2528 25 - 28 334	BDOEM2022	20 - 22	255
BDOEM2326 23 - 26 295 BDOEM2426 24 - 26 295 BDOEM2427 24 - 27 295 BDOEM2528 25 - 28 334	BDOEM2123	21 - 23	255
BDOEM2426 24 - 26 295 BDOEM2427 24 - 27 295 BDOEM2528 25 - 28 334	BDOEM2224	22 - 24	255
BDOEM2427 24 - 27 295 BDOEM2528 25 - 28 334	BDOEM2326	23 - 26	295
BDOEM2528 25 - 28 334	BDOEM2426	24 - 26	295
	BDOEM2427	24 - 27	295
BDOFM3032 30 - 32 368	BDOEM2528	25 - 28	334
	BDOEM3032	30 - 32	368

PART NO.	• 1	L (mm)
BDOE1012	5/16 - 3/8	5 5/16
BDOE1416	7/16 - 1/2	6 1/2
BDOE1820	9/16 - 5/8	7 9/32
BDOE2224	11/16 - 3/4	8 15/16









Flare Nut Wrench Set, 9pcs

BLPFNWS9

- Packing: 1 (Set)
- Higher Torque 15% to 20% more turning power with Flank Drive wrenching system
- Open side allows for easy access over tubing and lines
- Manufactured from chrome vanadium steel for strength and durability
- Full polished chrome finish easily wipes clean of oil
- and dirt Large hard stamped size markings allow for easy identification
- Supplied in a canvas tool pouch for neat and easy storage and transportation



PART NO.	™ <u>T</u>	L (mm)
BLPFNM810	8 - 10	139
BLPFNM911	9 - 11	153
BLPFNM1012	10 - 12	153
BLPFNM1314	13 - 14	174
BLPFNM1517	15 - 17	195
BLPFNM1618	16 - 18	213
BLPFNM1719	17 - 19	213
BLPFNM1921	19 - 21	228
BLPFNM2123	21 - 23	243

Water Pump Pulley Wrench

YA1350

- Packing: 1
- Essential tool for preventing pulley damage when removing or installing bolts
- Fixed pin dimension for quick, easy installation
- Unique bend to clear engine compartment obstacles
- Wrench head shaped for generous clearance around the bolts



Fan Clutch Pulley Holder

YA6160



- Removes and replaces the fan clutch on vehicles using "bolt on" water pump pulleys
- Reverse pulley holder for assembly operations



Chain Wrench

Packing: 6



Strap Wrench

- · Adjusts to fit any circumference or irregular shape
- Grip, loosen or tighten almost anything
- Won't scratch or damage surfaces
- Cushioned grip for maximum comfort
- Heavy duty construction for longer life
- Also available in set, PN: BLPSTWRKT



PART NO.	CHAIN LENGTH (inches)	CAPACITY (inches)	HANDLE LENGTH (inches)
CW12A	16	4	12
CW15A	19	5	15
CW24A	23	6	24

PART NO.	DIAMETER
BLPSTWR4	4" max
BLPSTWR6	6" max



Ratchet Combination Wrench Sets

Packing: 1

- Dual pawl ratcheting box end yields smooth operation and maximum strength
- 15° offset box head provides extra knuckle clearance
- 4.5° (5° on smaller wrenches) gear engagement means less movement to engage the next gear
- Inch scale laser etched on head face
- · Ratcheting box is reversible
- Box end features the FLANK DRIVE® wrenching configuration for greater torque with less applied force
- Tough, durable nickel-chrome finish
- Meets or exceeds strength specifications in ASME B107.6

PART NO.	CONTENTS			
BOERM712	8 to 19mm Ratchet Combination Wrench Set, 12pcs BOERM8 BOERM9 BOERM10 BOERM11 BOERM12 BOERM13 BOERM14 BOERM15 BOERM16 BOERM17 BOERM18 BOERM19			
BOERM704	21 to 25mm Ratchet Combination Wrench Set, 4pcs BOERM21 BOERM22 BOERM24 BOERM25			
BOER704	13/16" to 1" Ratchet Combination Wrench Set, 4 pcs BOER26 BOER28 BOER30 BOER32			
BOER708	5/16" to 3/4" Ratchet Combination Wrench Set, 8 pcs BOER10 BOER12 BOER14 BOER16 BOER18 BOER20 BOER22 BOER24			



Ratcheting Wrench Set, Flex Head, 12pcs

BOERMF712A

Packing:	1

PART NO.	CONTENTS			
BOERMF712A	8 to 19mm Flexible Head Rachet Combination Wrenches BOERMF8A BOERMF9A BOERMF10A BOERMF11A BOERMF12A BOERMF13A BOERMF14A BOERMF15A BOERMF16A BOERMF17A BOERMF18A BOERMF19A			





Ratcheting Wrench Set, Flex Head, 8pcs

BOERF708A

PART NO.	CONTENTS			
BOERF708A	BOERF10A	BOERF12A	Rachet Combin BOERF14A BOERF22A	




Ratchet Combination

- Dual pawl ratcheting box end yields smooth operation and maximum strength
- 15° offset box head provides extra knuckle clearance
- $\bullet~4.5^{\circ}$ (5° on smaller wrenches) gear engagement means less movement to engage the next gear
- Box end features the FLANK DRIVE® wrenching configuration for greater torque with less applied force
- Inch scale laser etched on head face
- Ratcheting box is reversible
- Tough, durable nickel-chrome finish
- Meets or exceeds strength specifications in ASME B107.6



PART NO.		A (mm)	B (mm)	L (mm)
BOERM6	6	6.6	3.6	114
BOERM7	7	6.6	3.9	125
BOERM8	8	6.5	4.0	135
BOERM9	9	7.4	4.0	150
BOERM10	10	8.0	5.0	160
BOERM11	11	8.5	5.5	170
BOERM12	12	9.0	5.5	175
BOERM13	13	10.0	6.3	180
BOERM14	14	10.0	6.5	190
BOERM15	15	11.0	7.0	200
BOERM16	16	11.0	7.0	210
BOERM17	17	12.0	7.0	230
BOERM18	18	12.0	8.0	240
BOERM19	19	12.9	8.7	250
BOERM21	21	13.7	9.4	266
BOERM22	22	14.5	9.4	286
BOERM24	24	15.5	11.2	305
BOERM25	25	15.5	11.2	327

PART NO.		A (inches)	B (inches)	L (inches)
BOER8	1/4	1/4	5/32	4 1/2
BOER10	5/16	1/4	5/32	5 5/16
BOER12	3/8	5/16	3/16	6 5/16
BOER14	7/16	11/32	7/32	6 11/16
BOER16	1/2	13/32	1/4	7 1/16
BOER18	9/16	13/32	1/4	7 1/2
BOER20	5/8	7/16	9/32	8 1/4
BOER22	11/16	15/32	9/32	9 1/16
BOER24	3/4	1/2	11/32	9 13/16
BOER26	13/16	17/32	3/8	10 1/2
BOER28	7/8	9/16	3/8	11 1/4
BOER30	15/16	5/8	7/16	12
BOER32	1	5/8	7/16	12 7/8









Packing: 6


Ratchet Combination, Flex Head

- Flex head pivots 90° in either direction
- Dual pawl reversible ratcheting box end
- Low profile easy action reverse lever won't get in your way
- Tough, durable nickel chrome finish
- Up to 80 gear teeth for ratcheting in tight areas




PART NO.	™ <u>T</u>	A (mm)	B (mm)	L (mm)
BOERMF8A	8	6.5	4.0	142
BOERMF9A	9	7.4	4.0	152
BOERMF10A	10	8.0	5.0	162
BOERMF11A	11	8.5	5.5	172
BOERMF12A	12	9.0	5.5	180
BOERMF13A	13	10.0	6.3	188
BOERMF14A	14	10.0	6.5	196
BOERMF15A	15	11.0	7.0	204
BOERMF16A	16	11.0	7.0	214
BOERMF17A	17	12.0	7.0	228
BOERMF18A	18	12.0	8.0	242
BOERMF19A	19	12.9	8.7	256

PART NO.		A (inches)	B (inches)	L (inches)
BOERF10A	5/16	1/4	5/32	5 19/32
BOERF12A	3/8	5/16	3/16	6 3/8
BOERF14A	7/16	11/32	7/32	6 3/4
BOERF16A	1/2	13/32	1/4	7 13/32
BOERF18A	9/16	13/32	1/4	7 23/32
BOERF20A	5/8	7/16	9/32	8 7/16
BOERF22A	11/16	15/32	9/32	8 31/32
BOERF24A	3/4	1/2	11/32	10 1/16







Ratcheting Wrench Sets, Short



PART NO.	CONTENTS			
BOERMS712	BOERMS8 BOERMS12	hort Ratchet C BOERMS9 BOERMS13 BOERMS17	BOERMS10 BOERMS14	ench Set, 12pcs BOERMS11 BOERMS15 BOERMS19
BOERS708	5/16" to 3/4" 3 BOERS10 BOERS18	Short Ratchet (BOERS12 BOERS20	Combination W BOERS14 BOERS22	rench Set, 8pcs BOERS16 BOERS24

Ratcheting Wrench Set, Short Flex Head, 8pcs



PART NO.	CONTENTS			
BOERSF708	BOERSF10	Short Flexible BOERSF12 BOERSF20	BOERSF14	20200

Short Ratchet Combination

Packing: 6

- Dual pawl reversible ratcheting box end
- Low profile easy action reverse lever won't get in your way
- Up to 80 gear teeth for ratcheting in tight areas
- Tough, durable nickel chrome finish



PART NO.	™ <u>T</u>	A (mm)	B (mm)	L (mm)
BOERMS8	8	6.5	4.0	90
BOERMS9	9	7.4	4.0	95
BOERMS10	10	8.0	5.0	100
BOERMS11	11	8.5	5.5	105
BOERMS12	12	9.0	5.5	110
BOERMS13	13	10.0	6.3	115
BOERMS14	14	10.0	6.5	120
BOERMS15	15	11.0	7.0	125
BOERMS16	16	11.0	7.0	128
BOERMS17	17	12.0	7.0	132
BOERMS18	18	12.0	8.0	138
BOERMS19	19	12.9	8.7	142

PART NO.	Ī	A (inches)	B (inches)	L (inches)
BOERS10	5/16	1/4	5/32	3 9/16
BOERS12	3/8	5/16	3/16	3 15/16
BOERS14	7/16	11/32	7/32	4 1/8
BOERS16	1/2	13/32	1/4	4 1/2
BOERS18	9/16	13/32	1/4	4 3/4
BOERS20	5/8	7/16	9/32	5 1/16
BOERS22	11/16	15/32	9/32	5 3/16
BOERS24	3/4	1/2	11/32	5 6/16

Short Flex Head Ratchet Combination

- Flex head pivots 90° in either direction
- Dual pawl reversible ratcheting box end
- Up to 80 gear teeth for ratcheting in tight areas



PART NO.	™ <u>T</u>	A (mm)	B (mm)	L (mm)
BOERMSF8	8	6.5	4.0	94
BOERMSF9	9	7.4	4.0	98
BOERMSF10	10	8.0	5.0	103
BOERMSF11	11	8.5	5.5	108
BOERMSF12	12	9.0	5.5	111
BOERMSF13	13	10.0	6.3	115
BOERMSF14	14	10.0	6.5	120
BOERMSF15	15	11.0	7.0	124
BOERMSF16	16	11.0	7.0	128
BOERMSF17	17	12.0	7.0	133
BOERMSF18	18	12.0	8.0	140
BOERMSF19	19	12.9	8.7	147

PART NO.	• 1	A (inches)	B (inches)	L (inches)
BOERSF10	5/16	1/4	5/32	3 11/16
BOERSF12	3/8	5/16	3/16	4 1/16
BOERSF14	7/16	11/32	7/32	4 1/4
BOERSF16	1/2	13/32	1/4	4 17/32
BOERSF18	9/16	13/32	1/4	4 23/32
BOERSF20	5/8	7/16	9/32	5 1/32
BOERSF22	11/16	15/32	9/32	5 1/4
BOERSF24	3/4	1/2	11/32	5 25/32









Single Direction Ratchet Combination



Packing: 10

PART NO.	₽ Ţ	A (mm)	B (mm)	L (mm)
BLPGWM5.5A	5.5	7	4.2	114
BLPGWM6A	6	7	4.2	114
BLPGWM7A	7	7	4.2	114
BLPGWM8A	8	7.7	4.7	132
BLPGWM9A	9	7.7	4.7	132
BLPGWM10A	10	8.2	5.3	149
BLPGWM11A	11	8.5	5.9	167
BLPGWM12A	12	9.4	6.5	185
BLPGWM13A	13	9.4	6.5	185
BLPGWM14A	14	9.7	7.1	202
BLPGWM15A	15	9.7	7.1	202
BLPGWM16A	16	10.8	7.7	220
BLPGWM17A	17	10.8	7.7	220
BLPGWM18A	18	11.3	8.3	238
BLPGWM19A	19	11.3	8.3	238
BLPGWM20A	20	11.3	8.3	238
BLPGWM21A	21	11.8	8.85	247
BLPGWM22A	22	11.8	8.85	247
BLPGWM23A	23	12.3	9.4	270
BLPGWM24A	24	12.3	9.4	270
BLPGWM26A	26	13.1	10.2	293

PART NO.	mm <u>Ţ</u>	A (mm)	B (mm)	L (mm)
BLPGWM27A	27	13.1	10.2	293
BLPGWM30A	30	14.1	11.2	322
BLPGWM32A	32	15.8	12.4	388
BLPGWM34A	34	15.8	12.4	388
BLPGWM36A	36	17.8	13.9	456
BLPGWM38A	38	17.8	13.9	456
BLPGWM40A	40	20.15	16.15	503
BLPGWM41A	41	20.15	16.15	503
BLPGWM42A	42	20.15	16.15	503
BLPGWM44A	44	22.6	18	540
BLPGWM45A	45	22.6	18	540
BLPGWM46A	46	22.6	18	540
BLPGWM48A	48	25.5	20	580
BLPGWM50A	50	25.5	20	580
BLPGWM55A	55	28.5	22.3	618
BLPGWM57A	57	28.5	22.3	618
BLPGWM58A	58	31.6	23.6	658
BLPGWM60A	60	31.6	23.6	658
BLPGWM65A	65	34.7	26.1	698
BLPGWM70A	70	37.9	28.6	738

Double Ring Ratcheting

Packing: 10



PART NO.	₽	A (mm)	L (mm)
BLPGWDM67P	6-7	14.3 - 16.8	115
BLPGWDM810P	8-10	18.5 - 21.7	130
BLPGWDM911P	9-11	21.7 - 23.6	150
BLPGWDM1214P	12-14	25 - 28	170
BLPGWDM1315P	13-15	28 - 30	190
BLPGWDM1719P	17-19	33.4 - 36.6	235
BLPGWDM1820P	18-20	33.4 - 36.6	235
BLPGWDM2122P	21-22	43 - 43	260
BLPGWDM2324P	23-24	43 - 49	290

Reversible Ratcheting Wrench Set, 2pcs


BLPMSWRH2S





••	Size (mm/inches)	(m	Size m/inches)	Size (mm/inches)	Size (mm/inches)
8	5/16	7	9/32	8	E10
10	3/8	-	11/32	10	E12
11	7/16	9	3/8	11	E14
12	1/2	11	7/16	13	E16
14	9/16	12	15/32	14	E18
16	5/8	13	17/32	16	E20
17	11/16	14	9/16	17	E22
19	3/4	16	5/8	19	E24

WRENCHES
Ratchet Combination



Ratcheting Wrench Set, **Locking Flex Head, 12pcs**



PART NO.	CONTENTS			
		8 to 19mm Locking Flexible Head Ratchet Combination Wrench		
BOERMFLCG712	BOERMFLCG8	BOERMFLCG9	BOERMFLCG10	
BOERWIFLOG/12	BOERMFLCG11	BOERMFLCG12	BOERMFLCG13	
	BOERMFLCG14	BOERMFLCG15	BOERMFLCG16	
	BOERMFLCG17	BOERMFLCG18	BOERMFLCG19	

Ratcheting Wrench Set, **Locking Flex Head, 8pcs**



PART NO.	CONTENTS				
	5/16" to 3/4" Locking Flexible Head Ratchet Combination Wrench				
BOERFLCG708	BOERFLCG10 BOERFLCG16 BOERFLCG22	BOERFLCG12 BOERFLCG18 BOERFLCG24	BOERFLCG14 BOERFLCG20		

Locking Flex Head Ratchet Combination

- Corrosive resistant bi-mold cushion grips for improved comfort and performance
- Wrenches have multiple locking head positions for easier access to tough to reach fasteners
- Long reach solid shank steel handle for improved reach and leverage
- Dual pawl reversible ratchet head
- Flex head pivots 90° in either direction



PART NO.	mm <u>T</u>	A (mm)	B (mm)	L (mm)
BOERMFLCG8	8	6.55	32	228
BOERMFLCG9	9	7.45	34	229
BOERMFLCG10	10	8.05	38	233
BOERMFLCG11	11	8.55	40	235
BOERMFLCG12	12	9.05	42	285
BOERMFLCG13	13	10.05	45	287
BOERMFLCG14	14	10.05	48	289
BOERMFLCG15	15	11.05	52	293
BOERMFLCG16	16	11.05	54	347
BOERMFLCG17	17	12.05	56	348
BOERMFLCG18	18	12.05	60	352
BOERMFLCG19	19	12.95	64	354

PART NO.	•	A (inches)	B (inches)	L (inches)
BOERFLCG10	5/16	1/4	1 1/4	9
BOERFLCG12	3/8	5/16	1 1/2	8 1/4
BOERFLCG14	7/16	11/32	1 9/16	9 19/32
BOERFLCG16	1/2	13/32	1 25/32	11 9/32
BOERFLCG18	9/16	13/32	1 29/32	11 3/8
BOERFLCG20	5/8	7/16	2 1/8	13 21/32
BOERFLCG22	11/16	15/32	2 7/32	13 23/32
BOERFLCG24	3/4	1/2	2 17/32	13 15/16









Ratcheting Box Wrench Sets, 5pcs



PART NO.	CONTENTS
RBZM605	7mm - 8mm to 15mm -17mm Ratcheting Box Wrench Set, 5pcs RBZM78 RBZM910 RBZM1112 RBZM1314 RBZM1517
RBZ605	1/4" - 5/16" to 3/4" - 7/8" Ratcheting Box Wrench Set, 5pcs RBZ810 RBZ1214 RBZ1618 RBZ2022 RBZ2428

Ratcheting Box

WRENCHES

Packing: 1

- Latch-on head keeps wrench on fastener
- Ring prevents nut/fastener head from sliding through wrench



PART NO.	m <u>Ţ</u>	A (mm)	L (mm)
RBZM78	7 - 8	15.1 - 17.1	114
RBZM910	9 - 10	20.4 - 22.6	140
RBZM1112	11 - 12	25.8 - 29.4	175
RBZM1314	13 - 14	25.8 - 29.4	175
RBZM1517	15 - 17	32.9 - 36.5	206
RBZM1618	16 - 18	32.9 - 36.5	206
RBZM1921	19 - 21	35.7 - 40.1	235

PART NO.	• 1	A (inches)	L (inches)
RBZ810	1/4 - 5/16	3/8	4 1/2
RBZ1214	3/8 - 7/16	3/8	5 7/2
RBZ1618	1/2 - 9/16	1/2	6 1/8
RBZ2022	5/8 - 11/16	1/2	9 1/4
RBZ2428	3/4 - 7/8	1/2	9 1/4

Ratchet Combination / T-Shape

T-Shape Speeder Wrench

Packing: 1

- Speedy socket wrench, convenience for use
- Magnetic inset for convenience





PART NO.	A (mm)	B (mm)	L (mm)
ВРТНМ08	8	200	250
ВРТНМ09	9	200	250
BPTHM10	10	200	250
BPTHM11	11	200	250
BPTHM12	12	250	250
BPTHM13	13	250	300
BPTHM14	14	250	300

T-Shape Speeder Wrench, Deep Socket, Slotted, Phillips®

- Durable Cr-V material, Matt finishing
- Deep Socket, socket length 50mm
- Suitable for motorcycle segment use





PART NO.	A (mm)	B (mm)	L (mm)
BLPTHDS250M8	8	200	250
BLPTHDS250M9	9	200	250
BLPTHDS250M10	10	200	250
BLPTHDS250M11	11	200	250
BLPTHDS250M12	12	200	250
BLPTHDS300M13	13	250	300
BLPTHDS300M14	14	250	300
BLPTHDS300M15	15	250	300
BLPTHDS300M16	16	250	300
BLPTHDS300M17	17	250	300
BLPTHD250PH0	PH0#	200	250
BLPTHD250PH1	PH1#	200	250
BLPTHD250PH2	PH2#	200	250
BLPTHD250PH3	PH3#	200	250
BLPTHD300PH4	PH4#	250	300
BLPTHD250S6	6	200	250
BLPTHD250S8	8	200	250
BLPTHD250S10	10	200	250
BLPTHD300S12	12	250	300



Folding Hex Key Set, 8pcs

BLFHKS8

Packing: 1

- Material: S2
- Finish: Satin



PART NO.	CONTENTS
BLFHKS8	Hex Key Sizes: 1.5, 2, 2.5, 3, 4, 5, 6, 8 mm

T-Hex Key

- Ergonomical handle for a better grip
- Made from high torque steel



Packing: 6

PART NO.	<u> </u>	A (mm)	L (mm)
BTWM1.5	1.5	83	122
BTWM2.5	2.5	83	122
втwм3	3	83	122
BTWM4	4	83	122
BTWM5	5	83	122
втwм6	6	134	186
втwм7	7	134	186
втwм8	8	134	186

T-Hex Ball End Key Set, 8pcs

BLWBS8

Packing: 1

- Set in metal stand
- Material: S2
- Finish: Satin



PART NO.	CONTENTS		
BLWBS8	T-Hex Ball End BLWTBM2 BLWTBM3 BLWTBM5 BLWTBM8	Key BLWTBM2.5 BLWTBM4 BLWTBM6 BLWTBM10	

T-Hex Ball End Key



PART NO.	<u> </u>	A (mm)	L (mm)
BLWTBM2	2	83	13
BLWTBM2.5	2.5	83	13
BLWTBM3	3	83	13
BLWTBM4	4	83	13
BLWTBM5	5	83	13
BLWTBM6	6	134	15
BLWTBM8	8	134	15
BLWTBM10	10	134	15





L-Hex Long Arm Key Set, 9pcs

BLPC9LHKSPI



- Material: S2
- Round bar for more comfortable use
- The head is machined by milling, more accurate dimensions, eliminates the risk of destroying the screw recess
- Set in plastic holder



PART NO.	CONTENTS		
BLPC9LHKSPI	L-Hex Long Arm BLPCLHK15P BLPCLHK25P BLPCLHK4P BLPCLHK6P BLPCLHK10P	Key BLPCLHK2P BLPCLHK3P BLPCLHK5P BLPCLHK8P	

L-Hex Long Ball End Key Set, 9pcs

BLPC9LBHKSPI



- Material: S2
- Round bar for more comfortable use
- The head is machined by milling, more accurate dimensions, eliminates the risk of destroying the screw recess, ball hex allows angle entry
- Set in plastic holder





PART NO.	CONTENTS		
BLPC9LBHKSPI	L-Hex Long Ball E BLPCLBHK15P BLPCLBHK25P BLPCLBHK4P BLPCLBHK6P BLPCLBHK10P	nd Key BLPCLBHK2P BLPCLBHK3P BLPCLBHK5P BLPCLBHK8P	

L-Hex Long Arm Key

- Material: S2
- Round bar for more comfortable use
- The head is machined by milling, more accurate dimensions, eliminates the risk of destroying the screw recess







L-Hex Long Ball End Key

- Material: S2
- Round bar for more comfortable use
- The head is machined by milling, more accurate dimensions, eliminates the risk of destroying the screw recess, ball hex allows angle entry





PART NO.	<u> </u>	A (mm)	L (mm)
BLPCLBHK15P	1.5	15	63
BLPCLBHK2P	2	17	76
BLPCLBHK25P	2.5	20	86
BLPCLBHK3P	3	22	91
BLPCLBHK4P	4	28	102
BLPCLBHK5P	5	32	118
BLPCLBHK6P	6	37	139
BLPCLBHK8P	8	43	155
BLPCLBHK10P	10	49	177




L-Hex Extra Long Arm Key Set, 9pcs

BLPC9XLHKSPI

- Material: S2
- The head is machined by milling, more accurate dimensions, eliminates the risk of destroying the screw recess
- Round bar for more comfortable use
- Set in plastic holder

BLPCC9XLHKSI (COLORED)

- High quality L-key set with color coded, convenient plastic sleeve
- Coloured sheath is made of PP material and coated with plastic technology
- Made of cylindrical material, more comfortable to grip and labor-saving to use, especially in small-scale applications
- Machined hexagonal head for more precise dimensions



n	Packing: 1	1
- Hill		
Ac.		
1000		



BLPCCXLHK2

BLPCCXLHK4

BLPCCXLHK8

BLPCCXLHK25

BLPCCXLHK5

BLPCCXLHK10

BLPCCXLHK15

BLPCCXLHK3

BLPCCXLHK6

BLPCC9XLHKSI


L-Hex Extra Long Ball End Key Set, 9pcs

BLPC9XLBHKSPI

- Material: S2
- The head is machined by milling, more accurate dimensions, eliminates the risk of destroying the screw recess
- Round bar for more comfortable use
- Set in plastic holder

BLPCC9XLBHKSI (COLORED)

- High quality L-key set with color coded, convenient plastic sleeve
- Coloured sheath is made of PP material and coated with plastic technology
- Made of cylindrical material, nore comfortable to grip and labor-saving to use, especially in small-scale applications
- Machined hexagonal head for more precise dimensions





PART NO.	CONTENTS		
BLPCC9XLBHKSI	BLPCCXLBHK3	BLPCCXLBHK2 BLPCCXLBHK4	BLPCCXLBHK25





L-Hex Extra Long Arm Key L-Hex Extra Long Arm Key, Colored



<u> </u>			
PART NO.	™ <u>T</u>	A (mm)	L (mm)
BLPCXLHK15P BLPCCXLHK15	1.5	15	91
BLPCXLHK2P BLPCCXLHK2	2	17	101
BLPCXLHK25P BLPCCXLHK25	2.5	20	113
BLPCXLHK3P BLPCCXLHK3	3	22	127
BLPCXLHK4P BLPCCXLHK4	4	28	142
BLPCXLHK5P BLPCCXLHK5	5	32	163
BLPCXLHK6P BLPCCXLHK6	6	37	184
BLPCXLHK8P BLPCCXLHK8	8	43	205
BLPCXLHK10P BLPCCXLHK10	10	49	231

L-Hex Extra Long Ball End Key L-Hex Extra Long Ball End Key, Colored



PART NO.	<u>mm</u> <u>T</u>	A (mm)	L (mm)
BLPCXLBHK15P BLPCCXLBHK15	1.5	15	91
BLPCXLBHK2P BLPCCXLBHK2	2	17	101
BLPCXLBHK25P BLPCCXLBHK25	2.5	20	113
BLPCXLBHK3P BLPCCXLBHK3	3	22	127
BLPCXLBHK4P BLPCCXLBHK4	4	28	142
BLPCXLBHK5P BLPCCXLBHK5	5	32	163
BLPCXLBHK6P BLPCCXLBHK16	6	37	184
BLPCXLBHK8P BLPCCXLBHK8	8	43	205
BLPCXLBHK10P BLPCCXLBHK10	10	49	231

L-Torx Long Arm Key Set, 9pcs

BLPC9LTSPI



- Material: S2
- Round bar for more comfortable use
- The head is machined by milling, more accurate dimensions, eliminates the risk of destroying the screw recess
- Set in plastic holder




PART NO.	CONTENTS	
BLPC9LTSPI	L-Torx Long Arm BLPCLT10P BLPCLT20P BLPCLT27P BLPCLT40P BLPCLT50P	BLPCLT15P BLPCLT25P BLPCLT30P BLPCLT45P

L-Torx Long Arm Key

- Material: S2
- Round bar for more comfortable use
- The head is machined by milling, more accurate dimensions, eliminates the risk of destroying the screw recess





PART NO.	# <u>T</u>	A (mm)	L (mm)
BLPCLT10P	T10	19	88
BLPCLT15P	T15	20	93
BLPCLT20P	T20	22	98
BLPCLT25P	T25	24	103
BLPCLT27P	T27	25	109
BLPCLT30P	T30	28	118
BLPCLT40P	T40	32	129
BLPCLT45P	T45	36	139
BLPCLT50P	T50	40	159








PLIERS & CUTTERS Pliers Sets / Standard & Mini

Combination Pliers









Pliers Set, Standard, 5pcs

BPL501

Packing: 6 (Set)

Storage tray packaging



PART NO.	CONTENTS	JAW CAPACITY (inches)	LENGTH (inches)
B48CPAP	Slip Joint Pliers	2 3/32	8 13/32
B58HLPAP	Lineman's Pliers	1 1/2	8 31/32
В96СРАР	Long Nose Pliers	2 1/32	6 5/16
BAWP100AP	Adjustable Joint Pliers	1 3/8	10 5/32
B87CPAP	Diagonal Cutters	31/32	6 19/32

Pliers Set, Dipped Grips, 8pcs

BDGPL800

Packing: 6 (Set)

Storage tray packaging



PART NO.	CONTENTS	JAW CAPACITY (inches)	LENGTH (inches)
BDGAWP100Z	Adjustable Joint Pliers	1 3/4	10
BDG48CPZ	Slip Joint Pliers	1 27/32	8
BDG98CPZ	Needle Nose Pliers	3	8
BDG9845CPZ	45° Bent Nose Pliers	2 13/16	7 3/4
BDG57CPZ	Lineman's Pliers	1 1/4	7 1/2
BDGEC7Z	End Cutter	7/16	7
BDG86CPZ	Diagonal Cutter	21/32	6 1/2
BDG88CPZ	Diagonal Cutter	15/16	8 1/8

Pliers Set, Standard, 7pcs

BDGCPL700

Packing: 6 (Set)

- Comes in a compact pouch, easy storage and portable
- Pouch design allows flexibility in storage of different
- Dipped grips deliver optimal comfort during high strength gripping
 Drop forged chrome vanadium steel and fine polished



PART NO.	CONTENTS	JAW CAPACITY (inches)	LENGTH (inches)
BDG98CPZ	Needle Nose Pliers	3	8
BDG88CPZ	Diagonal Cutter	15/16	8
BDG45CMP	Mini Combination Pliers	1	4.5
BDG95CLMP	Mini Needle Nose Pliers	2 1/16	6
BDG85CTMP	Mini Thin Diagonal Nose Pliers	23/32	4.5
BDG945CMP	Mini 45° Bent Nose Pliers	1	4.5
BDG48CPZ	Slip Joint Pliers	1 27/32	8

Pliers Set, Long Reach, 3pcs

BDGPL300LR

Packing: 6 (Set)

Storage tray packaging



PART NO.	CONTENTS	JAW CAPACITY (inches)	LENGTH (inches)
BDG311CPZ	Diagonal Cutters	1 9/16	11
BDG91145CPZ	45° Bent Nose Pliers	3 3/16	11
BDG911CPZ	Needle Nose Pliers	3 9/16	11



PLIERS & CUTTERS

Pliers Sets / Standard & Mini

Pliers Set, Extra Long Reach, 2pcs

BDGPL200XLR

- Packing: 6 (Set)
- Corrosion resistant finish
- Storage tray packaging
- Double dipped grips offer increased comfort and control during use
- Extra length provides additional access to difficult reach areas



PART NO.	CONTENTS	JAW CAPACITY (inches)	LENGTH (inches)
BDG91645CPZ	45° Bent Nose Pliers	3 3/16	16
BDG916CPZ	Needle Nose Pliers	3 9/16	16

Pliers Set, Extended Reach Hose Grip, 3pcs

BDGPL300HG

- Packing: 6 (Set)
- Leaf spring improve maneuverability
- Corrosion resistant finish
- Double dipped grips offer increased comfort and control during use
- Extra length provides additional access to difficult reach areas



PART NO.	CONTENTS	JAW CAPACITY (inches)	LENGTH (inches)
BDGPL410HGZ	Small Hose Grip Pliers	2 1/4	11
BDGPL411HGZ	Medium Hose Grip Pliers	2 1/4	11
BDGPL412HGZ	Large Hose Grip Pliers	2	11

Pliers Set, Miniature, 8pcs

BDGMPL845



- Comes in a compact pouch, easy storage and portable
- Pouch design allows flexibility in storage of different
- Drop forged chrome vanadium steel and fine polished
- Dipped grips deliver optimal comfort during high strength gripping



PART NO.	CONTENTS	JAW CAPACITY (inches)	LENGTH (inches)
BDG45CMP	Mini Combination Pliers	1	4.5
BDG85CMP	Mini Diagonal Nose Pliers	21/32	4.5
BDG85CTMP	Mini Thin Diagonal Nose Pliers	23/32	4.5
BDG945CMP	Mini 45° Bent Nose Pliers	1	4.5
BDG65CMP	Mini Flat Nose Pliers	1 5/32	4.5
BDG95CMP	Mini Long Nose Pliers	4 7/8	4.5
BDG95CLMP	Mini Needle Nose Pliers	2 1/16	6
BDGMPEC5	Mini End Cutters	4 1/32	4.5

Pliers Set, Miniature, 10pcs

BMPL1000

Packing: 6 (Set)

Storage tray packaging



PART NO.	CONTENTS	JAW CA- PACITY (inches)	LENGTH (inches)
B45CMPAP	Mini Combination Pliers	1	4 11/16
B65CMPAP	Mini Duck Bill Pliers	1 5/32	4 7/8
B75CMPAP	Mini Round Nose Pliers	1 5/32	5
B85CMPAP	Mini Diagonal Cutter	21/32	4 11/32
B85CTMPAP	Mini Thin Diagonal Cutter	23/32	4 5/8
B945CMPAP	Mini 45° Bent Nose Pliers	1	4 11/16
B95CMPAP	Mini Long Nose Pliers	1 1/8	4 7/8
B95CLMPAP	Mini Needle Nose Pliers	2 1/16	5 25/32
B960CMPAP	Mini 60° Bent Nose Pliers	15/16	4 11/16
BMPEC5AP	Mini End Cutter	5/16	4 1/32






Pliers Set, Miniature Long Reach, 4pcs

BDGPL400LMP

- Packing: 6 (Set)
- Chrome nickel finish prevents against rust and corrosion
- Cushioned grips offer comfort during extended use
- Vinyl grips provide easy clean-up and durability
- Pliers exceed ANSI standards



PART NO.	CONTENTS	JAW CA- PACITY (inches)	LENGTH (inches)
BDG96LMPZ	Mini Long Nose Pliers	1 5/16	6
BDG97LMPZ	Mini Needle Nose Pliers	2 13/32	7
BDG9645LMPZ	Mini 45° Bent Nose Pliers	1 7/32	6
BDG86LMPZ	Mini Diagonal Cutters	3/4	5 1/2

Combination Pliers

Packing: 6 (Set)

- Dipped grip handles for easy cleaning
- Laser hardened cutting edge
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	DESCRIPTION	JAW CA- PACITY (inches)	LENGTH (inches)
BDG57CPZ	Combination Pliers	1 1/4	7 1/2
BDGCB8K	Combination Pliers	7/8	8
врдсв9нк	Combination Pliers High Leveratge	7/8	9

Slip Joint Pliers

BDG48CPZ

- Packing: 6
- Dipped grip handles for easy cleaning
- Heat treated hardened cutting edge
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
BDG48CPZ	1 27/32	8

Adjustable Joint Pliers

BDGAWP100Z

- Packing: 6
- Dipped grip handles for easy cleaning
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
BDGAWP100Z	1 3/4	10



PLIERS & CUTTERS Pliers / Standard & Cutters





Screw Removal Pliers

BSP6

Packing: 6

· Jaws shaped specially for removing screws



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
BSP6	7/8	6

45° Bent Nose Pliers

BDG9845CPZ

Packing: 6

Blue-Point

- Dipped grip handles for easy cleaning
- Laser hardened cutting edge
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
BDG9845CPZ	2 13/16	8

Long Nose Pliers

BDGLN6K

Packing: 6

- Dipped grip handles for easy cleaning
- · Laser hardened cutting edge
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
BDGLN6K	1	6

Needle Nose Pliers

BDG98CPZ

Packing: 6

- Dipped grip handles for easy cleaning
- · Laser hardened cutting edge
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
BDG98CPZ	3	8

Diagonal Cutters

Packing: 6

- Dipped grip handles for easy cleaning
- Laser hardened cutting edge
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
BDG86CPZ	21/32	6 1/2
BDG88CPZ	15/16	8 1/8
BDGCT6K	7/16	6

End Cutters

BDGEC7Z

- Dipped grip handles for easy cleaning
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
BDGEC7Z	1/2	7

PLIERS & CUTTERS

Pliers / Standard & Cutters

Plastic Cutters

BPC6

- Packing: 6
- Flushed cutting edge for perfect cuts
- Thin cutting edge for precise trimming
- Laser hardened cutting edge



PART NO.	LENGTH (inches)
BPC6	6

Cable Diagonal Cutters

BDGCT6W



- Diagonal cutter with holes for stripping cable
- Laser hardened cutting edge



PART NO.	LENGTH (inches)
BDGCT6W	6

Cable Cutters



- Special flip over handle design allows tool to be used for slicing cable sleeve
- Drop forged chrome/nickel alloy is fine polish for corrosion resistant finish
- Precise machined joint for ease of use and longer life
- For cutting cables only



PART NO.	LENGTH (inches)	
BCC6HD	6	
BCC8HD	8	
BCC10HD	10	

High Leverage Diagonal Cutters

- High leverage design delivers superior crimping and cutting force
- Laser hardened cutting edge
- Dual compound soft grip handles provide good grip and comfort
- Precise machined joint for ease of use and longer life
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	LENGTH (inches)	
BCT6HD	6	
BCT7HD	7	
BCT8HD	8	







High Leverage Combination Pliers



Packing: 6

- High leverage design delivers superior crimping and cutting force
- Laser hardened cutting edge
- Dual compound soft grip handles provide good grip and comfort
- Precise machined joint for ease of use and longer life
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	LENGTH (inches)
BCB6HD	6
BCB7HD	7
BCB9HD	9

High Leverage Long Nose Pliers



- High leverage design delivers superior crimping and cutting force
- Laser hardened cutting edge
- Dual compound soft grip handles provide good grip and comfort
- Precise machined joint for ease of use and longer life
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	LENGTH (inches)	
BLN6HD	6	
BLN7HD	7	
BLN8HD	8	

PLIERS & CUTTERS

Pliers / Standard & Miniature

Combination Pliers

Packing: 6

- Dual compound soft grip handles provide good grip and comfort
- Laser hardened cutting edge
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
B58HLPAP	1 1/2	8 31/32
BDMCB6	5/8	6
BDMCB7	5/8	7
BDMCB8	7/8	8

Long Nose Pliers

Packing: 6

- Dual compound soft grip handles provide good grip and comfort
- Laser hardened cutting edge
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
B96CPAP	2 1/32	6 5/16
BDMLN6	1	6
BDMLN8	1 1/8	8

Adjustable Joint Pliers

BDMAJ10



- Dual compound soft grip handles provide good grip and comfort
- Drop forged chrome/nickel alloy is fine polished for



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
BDMAJ10	1 11/16	10

Slip Joint Pliers

B48CPAP

Packing: 6

- Dual compound soft grip handles provide good grip and comfort
- Drop forged chrome/nickel alloy is fine polished for



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
B48CPAP	2 3/32	8 13/32

BAWP100AP





PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
BAWP100AP	1 3/8	10 5/32







Diagonal Cutters



- Dual compound soft grip handles provide good grip and comfort
- Laser hardened cutting edge
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
B87CPAP	31/32	6 19/32
BDMCT5	5/16	5
BDMCT6	7/16	6
BDMCT7	1/2	7

Miniature Thin Diagonal Cutters

B85CTMPAP

Packing: 6

- Dual compound soft grip handles provide good grip and comfort
- Drop forged chrome/nickel alloy is fine polished for



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
B85CTMPAP	23/32	4 5/8

Miniature Cutters

B85CMPAP

Packing: 6

- Dual compound soft grip handles provide good grip and comfort
- Laser hardened cutting edge
- Drop forged chrome/nickel alloy is fine polished for



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
B85CMPAP	21/32	4 11/32

Miniature Combination Pliers

B45CMPAP

- Packing: 6
- Dual compound soft grip handles provide good grip and comfort
- Laser hardened cutting edge
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
 B45CMPAP	1	4 11/16

Miniature Round Nose Pliers

B75CMPAP

- Dual compound soft grip handles provide good grip and comfort
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
B75CMPAP	1 5/32	5

Miniature Long Nose Pliers

B95CMPAP

- Packing: 6
- Dual compound soft grip handles provide good grip and comfort
- Laser hardened cutting edge
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
B95CMPAP	1 1/8	4 7/8

Miniature Curved Long Nose Pliers

B945CMPAP

- Packing: 6
- Dual compound soft grip handles provide good grip and comfort
- Drop forged chrome/nickel alloy is fine polished for



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
B945CMPAP	1	4 11/16

Miniature 60° Bent Nose Pliers

B960CMPAP



- Dual compound soft grip handles provide good grip and comfort
- Drop forged chrome/nickel alloy is fine polished for



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
B960CMPAP	15/16	4 11/16

Miniature Needle Nose Pliers

B95CLMPAP

Packing: 6

- Dual compound soft grip handles provide good grip and comfort
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
B95CLMPAP	2 1/16	5 25/32

Miniature Duck Bill Pliers

B65CMPAP



- Dual compound soft grip handles provide good grip
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)	
B65CMPAP	1 5/32	4 7/8	

Miniature Pincers

BMPEC5AP



- Dual compound soft grip handles provide good grip
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
BMPEC5AP	5/16	4 1/32





Locking Pliers, Sheet Metal

VGP12808

- Wide jaws allow clamping, bending, forming and crimping of sheet metal without gripping effort
- E-coat provides extra resistance against corrosion and welding splatter
- Quality cold-rolled steel ensures years of service
- Drop forged jaws ensure a tough, durable tool
- Smooth rounded edges allow comfortable handling and reduce risk of injury
- Spring-loaded release lever permits quick "NO PINCH" release even when tool is firmly locked
- Piano wire spring provides smooth jaw opening
- Adjustment bolt features deep knurl to accommodate greasy hands
- Locking nut allows setting for repetitive jobs
- Drilled (not punched) holes in mobile jaw ensure maximum bearing with rivets for smooth action
- Large diameter rivets add strength and durability



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
VGP12808	1 3/4	8

Locking Pliers, U-Clamp

VGP12509

- · U-shaped jaws allow access and perfect visibility when welding
- E-coat provides extra resistance against corrosion and welding splatter
- Quality cold-rolled steel ensures years of service
- Drop forged jaws ensure a tough, durable tool
- Smooth rounded edges allow comfortable handling and reduce risk of injury
- Spring-loaded release lever permits quick "NO PINCH" release even when tool is firmly locked
- Piano wire spring provides smooth jaw opening
- Adjustment bolt features deep knurl to accommodate greasy hands
- Locking nut allows setting for repetitive jobs
- Drilled (not punched) holes in mobile jaw ensure maximum bearing with rivets for smooth action
- Large diameter rivets add strength and durability



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
VGP12509	2 5/16	9

Locking Pliers, C-Clamp

- Quick and easy handling clamps for autobody and metal fabrication applications
- Spring loaded release lever permits quick "NO PINCH" release even when tool is fimly locked
- Locking nut allows setting for repetitive jobs

PART NO.	DESCRIPTION	JAW CAPACITY (inches)	LENGTH (inches)
VGP12406		2 ⁵ /16	6
VGP12412	Otanada ad Tia	3 5/16	12
VGP12418	Standard Tip	10 1/4	18
VGP12424		15 ¹¹ /16	24



PART NO.	DESCRIPTION	JAW CAPACITY (inches)	LENGTH (inches)
VGP22406		1 5/16	6
VGP22412	Swival Tip	3 15/16	12
VGP22418	Swivel Tip	9 7/16	18
VGP22424		15 11/16	24

Locking Pliers, Chain Style

VGP18110

Packing: 1

• Wraps around and holds irregular shaped objects like oil filters and mufflers quickly and easily



	PART NO.	CHAIN CAPACITY (inches)	HANDLE LENGTH (inches)
•	VGP18110	up to 6 9/32	9 27/32

Locking Pliers, Straight Jaws

Packing: 6

- Exceeds ASME specification
- Straight jaws with maximum contact area
- Nickel plated to resist corrosion
- Convenient one hand release lever



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
BDGLP7SAP	1 5/16	7
BDGLP10SAP	1 3/4	10

Locking Pliers, Straight Jaws, Soft Grip

Packing: 6

- Exceeds ASME specification
- Straight jaws with maximum contact area
- Nickel plated to resist corrosion
- Convenient one hand release lever
- · Non-slip custhion grip



PART NO.	JAW CAPACITY (inches)	LENGTH (inches)
BDMLP7SAP	1 5/16	7
BDMLP10SAP	1 3/4	10

Pliers Set, Retaining Ring, 2pcs

PR36

Packing: 1 (Set)

• Optional Tip Kit PR5 and Tips sizes .047" 0°, .070" 0°, .047" 45°, .038" 90° are sold separately



PART NO.	CONTENTS	LENGTH (inches)
PR37	Internal Ring, size range 3/8 - 2" Tip Kit PR5, Tip sizes .047" 0°, .070" 0°, .047" 45°, .038" 90°, 2 pair each	6 1/4
PR38	External Ring, size range 1/4 - 2"	6 1/4

Pliers Set, Retaining Ring, 2pcs

PR50A

Packing: 1 (Set)

Plastic case packaging



PART NO.	CONTENTS	LENGTH (inches)
PR51	Internal Ring, size range 2 7/16 - 4" Tip Kit PR502, Tip size .108" 15° Optional: Tip Kit PR501. Tip size .108" 0°	9 1/2
PR52	External Ring, size range 1 1/2 - 3 11/32" Tip Kit PR 507, Tip size .120" 45° Optional: Tip Kit PR505, Tip size .120" 0°	9 1/2





Pliers Set, Retaining Ring, 3pcs

PRH503

- Packing: 1 (Set)
- Retaining rings size are convertible
- Available in 2pcs Set, PN: PRH502A consisting of PRH56A and PRH57A
- Storage case packaging



PART NO.	CONTENTS	LENGTH (inches)
PRH56A	Internal Ring, size range 1/4 - 1" External Ring, size range 1/8 - 1" Tip Kit PRH56A-1 Tip sizes .023" 0°, .036" 0°, .047" 0°, .036" 90°, .047" 90°, 1 pair each	6 3/8
PRH57A	Internal Ring, size range ³ / ₈ - 2" External Ring, size range ¹ / ₄ - 2" Tip Kit PRH57A-1 Tip sizes .036" 0°, .047" 0°, .070" 0°, .036" 90°, .047" 90°, 1 pair each	8
PRC65A	Internal Ring, size range 113/64 - 4" External Ring, size range 11/3 - 4" Tip Kit PRC65A-1 Tip sizes .090", .108", .120" (15° and 90°), 1 pair each	10

Retaining Ring 15" Pliers, External

PR8A



- Spring-loaded ratchet locking mechanism safely and securely holds large heavy rings
- Cushion grips for comfort and control
- Precision ground tips for maximum control and stability

Interchangeable tips



PART NO.	CONTENTS	LENGTH (inches)
	External Ring, size range 3 1/16 - 6 1/4" Tip Kit PR8A-1, Tip size .120" 0°	
PR8A	Optional Kits and Tip sizes: Tip Kit PR8A-2, Tip size .120" 45° Tip Kit PR8A-3, Tip size .120" 90°	15 11/16

Retaining Ring 19" Pliers, External

PR53



• Interchangeable tips



PART NO.	CONTENTS	LENGTH (inches)
PR53	External Ring, size range 6 1/2 - 10" Tip Kit PR53-1, Tip size .170" 0° Optional Kits and Tip sizes: Tip Kit PR53-2, Tip size .170" 45° Tip Kit PR53-3, Tip size .170" 90°	19

Retaining Ring 29" Pliers, Internal

PR54





PART NO.	CONTENTS	LENGTH (inches)
	Internal Ring, size range 6 ½ - 10" Tip Kit PR54-1, Tip size .150" 0°	
PR54	Optional Kits and Tip sizes: Tip Kit PR54-2, Tip size .150" 45° Tip Kit PR54-3, Tip size .150" 90°	29



PLIERS & CUTTERS

Pliers / Circlip Standard / Miniature & Special

Circlip Pliers, Straight



PART NO.	DESCRIPTION	SIZE RANGE (mm)	LENGTH (inches)
BCES7	External	19 - 60	7
BCES9	External	40 - 100	9
BCIS7	Internal	19 - 60	7
BCIS9	Internal	40 - 100	9

Circlip Pliers, 90°



PART NO.	DESCRIPTION	SIZE RANGE (mm)	LENGTH (inches)	
BCER7	External	19 - 60	7	
BCER9	External	40 - 100	9	
BCIR7	Internal	19 - 60	7	
BCIR9	Internal	40 - 100	9	

Miniature Circlip Pliers, Straight



- Dual compound soft grip handles provide good grip and comfort
- Precise machined joint for ease of use and longer life
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	DESCRIPTION	LENGTH (inches)
BCES5	External	5
BCES6	External	6



PART NO.	DESCRIPTION	LENGTH (inches)	
BCIS5	Internal	5	
BCIS6	Internal	6	

Miniature Circlip Pliers, 45°

- Dual compound soft grip handles provide good grip and comfort
- Precise machined joint for ease of use and longer life
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	DESCRIPTION	LENGTH (inches)
BCEH5	External	5
ВСЕН6	External	6



PART NO.	DESCRIPTION	LENGTH (inches)
BCIH5	Internal	5
BCIH6	Internal	6





Miniature Circlip Pliers, 90°



- Dual compound soft grip handles provide good grip and comfort
- Precise machined joint for ease of use and longer life
- Drop forged chrome/nickel alloy is fine polished for corrosion resistant finish



PART NO.	DESCRIPTION	LENGTH (inches)	
BCER5	External	5	
BCER6	External	6	



PART NO.	DESCRIPTION	LENGTH (inches)
BCIR5	Internal	5
BCIR6	Internal	6

Bolt Cutters, Heavy Duty

- Ideal for cutting rod, bolts, concrete form ties and fencing wire
- Hardened alloy steel jaws
- Center cut jaw configuration provides balance while cutting
- Cuts soft or hard materials
- Rubber gripped steel handles ensure firm grip during use



PART NO.	CAPACITY Soft Materials (inches)	CAPACITY Hard Materials (inches)	LENGTH (inches)	WEIGHT (kg)	*
BLPBC18	3/8	1/4	18	1.55	2
BLPBC24	7/16	5/16	24	2.55	2
BLPBC30	1/2	3/8	30	3.90	1
BLPBC36	9/16	7/16	36	6.45	1

Replacement Jaws



Packing: 1



PART NO.	LENGTH (inches)
BLPBC18-1	18
BLPBC24-1	24
BLPBC30-1	30
BLPBC36-1	36


Straight Hose Clamp, 13" Pliers

HCP13



- Newly designed superior ratchet mechanism for ease of operation
- Enables technician to access, release, remove and install constant tension hose clamps
- 360° rotating deep slotted tips firmly grip clamps at any angle
- Ergonomically designed with solid rivet construction for long life and durability
- Extended reach for easy access to engine compartment
- Soft touch grips are double dipped for increased comfort and control
- Heat treated steel for strength and corrosion resistance
- Electroplated arms and tips for durability





M Series, Phillips®

Packing: 6

- Tri-lobe handle shape for reducing user strain while operating and offering optimum torquee
- Soft cushion grip for the best performance without fatigue
- Concave hollow of the handle neck for firm pinch pressure and precision control



PART NO.	TIP SIZE (#)	A (mm)	L (mm)
BSGDM65PH00	00	65	136
BSGDM75PH0	0	75	148
BSGDM100PH0	0	100	173
BSGDM150PH0	0	150	223
BSGDM75PH1	1	75	181
BSGDM100PH1	1	100	206
BSGDM150PH1	1	150	256
BSGDM38PH2	2	38	100

PART NO.	TIP SIZE (#)	A (mm)	L (mm)
BSGDM100PH2	2	100	218
BSGDM150PH2	2	150	268
BSGDM200PH2	2	200	318
BSGDM250PH2	2	250	368
BSGDM150PH3	3	150	278
BSGDM200PH3	3	200	328
BSGDM200PH4	4	200	328
BSGDM200PH4	4	200	328

M Series, Slotted

- Tri-lobe handle shape for reducing user strain while operating and offering optimum torquee
- Soft cushion grip for the best performance without fatigue
- Concave hollow of the handle neck for firm pinch pressure and precision control



PART NO.	TIP SIZE (mm)	A (mm)	L (mm)
BSGDM65F2	2.4	65	136
BSGDM75F3	3.2	75	149
BSGDM100F3	3.2	100	175
BSGDM150F3	3.2	150	225
BSGDM75F5	5	75	182
BSGDM100F5	5	100	208
BSGDM150F5	5	150	258
BSGDM200F5	5	200	309

PART NO.	TIP SIZE (mm)	A (mm)	L (mm)
BSGDM38F6	6	38	100
BSGDM100F6	6	100	220
BSGDM150F6	6	150	270
BSGDM200F6	6	200	321
BSGDM250F6	6	250	372
BSGDM150F8	8	150	280
BSGDM200F8	8	200	331
BSGDM200F9	9.5	200	331











M Series, Pozidriv®

Packing: 6

- Tri-lobe handle shape for reducing user strain while operating and offering optimum torquee
- Soft cushion grip for the best performance without fatigue
- Concave hollow of the handle neck for firm pinch pressure and precision control



PART NO.	TIP SIZE (#)	A (mm)	L (mm)
BSGDM75PZ0	0	75	148
BSGDM100PZ0	0	100	173
BSGDM150PZ0	0	150	223
BSGDM75PZ1	1	75	181
BSGDM100PZ1	1	100	206
BSGDM150PZ1	1	150	256
BSGDM38PZ2	2	38	100

PART NO.	TIP SIZE (#)	A (mm)	L (mm)
BSGDM100PZ2	2	100	218
BSGDM150PZ2	2	150	268
BSGDM200PZ2	2	200	318
BSGDM250PZ2	2	250	368
BSGDM150PZ3	3	150	278
BSGDM200PZ3	3	200	328
BSGDM200PZ4	4	200	328


M Series, Torx®

- Packing: 6
- Tri-lobe handle shape for reducing user strain while operating and offering optimum torquee
- Soft cushion grip for the best performance without fatigue
- Concave hollow of the handle neck for firm pinch pressure and precision control



PART NO.	TIP SIZE	A (mm)	L (mm)
BSGDM75TX6	T6	75	148
BSGDM75TX7	T7	75	148
BSGDM75TX8	Т8	75	148
BSGDM75TX9	Т9	75	148
BSGDM100TX10	T10	100	206
BSGDM100TX15	T15	100	206

PART NO.	TIP SIZE	A (mm)	L (mm)
BSGDM100TX20	T20	100	206
BSGDM100TX25	T25	100	218
BSGDM100TX27	T27	100	218
BSGDM100TX30	T30	100	218
BSGDM100TX40	T40	100	218



P Series, Phillips®

P Series, Slotted

- 2-Component handle gives the screwdriver an ideal ergonomic shape
- Perfectly adapted to the forces exerted by the hand and permits work efficiently
- The chrome molybdenum vanadium blade is hardened to HRC 59±1
- Nickel and chrome plated blade and the tip is especially vapor-blasted for greater screw-tip adherence and a full anti-rust guarantee
- With hanging hole moulded to the blade
- The size and part number are laser-etched on the blade to ensure their permanence






PART NO.	TIP SIZE (#)	A (mm)	L (mm)
BSGD75PH0B	PH0	75	148
BSGD100PH0B	PH0	100	187
BSGD150PH0B	PH0	150	237
BSGD100PH1B	PH1	100	208
BSGD150PH1B	PH1	150	258
BSGD200PH1B	PH1	200	308
BSGD250PH1B	PH1	250	358
BSGD300PH1B	PH1	300	408
BSGD100PH2B	PH2	100	208
BSGD150PH2B	PH2	150	258
BSGD200PH2B	PH2	200	308
BSGD250PH2B	PH2	250	358
BSGD300PH2B	PH2	300	408
BSGD150PH3B	PH3	150	270
BSGD200PH3B	PH3	200	320

PART NO.	TIP SIZE (mm)	A (mm)	L (mm)
BSGD75S3B	3	75	147
BSGD75F4B	4	100	168
BSGD100S4B	4	125	188
BSGD125S4B	4	150	233
BSGD150S4B	4	250	308
BSGD250S4B	5.5	125	358
BSGD125S5B	5.5	150	208
BSGD150S5B	6.5	250	258
BSGD125F5B	4	75	233
BSGD125F6B	5.5	125	208
BSGD150F6B	6.5	125	258
BSGD250F6B	6.5	150	358
BSGD150F8B	8	150	270
BSGD175F8B	8	175	320
















Precision Screwdriver, Phillips®

Packing: 6

- Spinning handle for ease of use
- Oil resistant, bi-material handle
- Soft cushion grip for the best performance



PART NO.	TIP SIZE (#)	A (mm)	L (mm)
BSGPDM50PH0	PH0	50	145
BSGPDM50PH00	PH00	50	145
BSGPDM50PH000	PH000	50	145
BSGPDM50PH1	PH1	50	145
BSGPDM50PH2	PH2	50	145

Precision Screwdriver, Slotted

Packing: 6

- Spinning handle for ease of use
- Oil resistant, bi-material handle
- Soft cushion grip for the best performance



PART NO.	TIP SIZE (mm)	A (mm)	L (mm)
BSGPDM50F1	1.4	50	145
BSGPDM50F2	2	50	145
BSGPDM50F24	2.4	50	145
BSGPDM50F3	3	50	145

Pass-Through Screwdriver, Phillips®

Packing: 6

- High tensile Chrome Vanadium Steel
- Oil resistant, bi-material handle
- Ergonomically designed handle for excellent grip and user comfort




PART NO.	TIP SIZE (#)	A (mm)	L (mm)
BSGDPT100PH2	PH2	100	207
BSGDPT150PH2	PH2	150	257
BSGDPT150PH3	PH3	150	265
BSGDPT200PH3	PH3	200	315
BSGDPT250PH3	PH3	250	365

Pass-Through Screwdriver, Slotted

- High tensile Chrome Vanadium Steel
- Oil resistant, bi-material handle
- Ergonomically designed handle for excellent grip and user comfort



PART NO.	TIP SIZE (mm)	A (mm)	L (mm)
BSGDPT100F6	6	100	207
BSGDPT150F6	6	150	257
BSGDPT150F8	8	150	265
BSGDPT200F8	8	200	315
BSGDPT250F8	8	250	365



1/4" Ratchet Screwdriver, Pistol Handle

BSGDMR6



- 5" magnetic bit holder blade for 1/4" hex bits
- 45 tooth ratcheting mechanism ensures precise positioning and movement
- Bits are stored in a bit magazine inside the handle
- Includes six 1/4" hex bits: Flat Tip (4.5 and 5.5), Phillips® (#1 and #2) plus Torx® (T15 and T20)
- Ergonomically designed two component handle is textured for excellent grip and user comfort
- Provides three functional options, left and right turning and locked position · Blade features a knurled-grip for fast spinning of the fastener
- Screwdriver carries a lifetime warranty

(Bits are consumable and carry no warranty)











Packing: 1

Power Bit Set, 52pcs

YA52PBSQC

Ideal for use with cordless drills and screwdrivers

Set includes:

- 2 hex adaptors
- Flat tip bits (long): 6-8, 8-10, 10-12
- Hex bits (short): 1/8", 9/64", 5/32", 3/16", 7/32", 1/4", 9/32"
- Hex bits (long): 5/32", 3/16", 7/32"
- PHILLIPS® tip bits (short): #1, #2 (2 each), #3
- PHILLIPS® tip bits (long): #1, #2, #3
- TORX[®] tamper resistant bits (short and long): T10, T15, T20, T25, T27, T30, T40
- Square bits (short and long): #1, #2, #3
- Clutch bits (short and long): 5/32", 3/16"
- Double end bits: 6-8 x #2 PHILLIPS®, 8-10 x #3 PHILLIPS®
- Adaptors: 1/4" hex female to 1/4" hex female,
 1/4" hex male to 1/4" square male, 1/4" hex quick change chuck
- Storage case packaging



Master Ball Hex Bit Set, 32pcs

SDM32KT

1/4" shank bits for use in difficult access applications where fastener cannot be approached straight-on

Set includes:

- Fractional Ball Hex Bits: 3/32", 7/64", 1/8", 9/64", 5/32", 3/16", 7/32", 1/4", 5/16", 3/8"
- Metric Ball Hex Bits: 2, 2.5, 3, 4, 5, 6, 7, 8, 9, 10mm
- TORX® Ball Hex Bits: T10, T15, T20, T25, T27, T30, T40, T45, T50, T55
- Magnetic Insert Bit Holder
- 1/4" Female Hex to 1/4" Female Sq. Dr. Adaptor
- · All components store in case with belt clip



Torx Ball Hex Bit Set, 11pcs

SDM11KT

1/4" shank bits for use in difficult access applications where fastener cannot be approached straight-on

Set includes:

- TORX® Ball Hex Bits: T10, T15, T20, T25, T27, T30, T40, T45, T50
- Magnetic Insert Bit Holder
- 1/4" Female Hex to 1/4" Female Sq. Dr. Adaptor
- All components store in case with belt clip





SCREWDRIVERS & BITS

Hex Bits

Packing: 6

Phillips® Tip Bits







PART NO.	SIZE (#)
BLPPB0	0
BLPPB1	1
BLPPB2	2
BLPPB3	3



PART NO. BLPHBM3 3 BLPHBM4 4 **BLPHBM5** 5 BLPHBM6 6

Flat Tip Bits

Packing: 6

Tamper Resistant Torx® Bits






PART NO.	SIZE
BLPTB10TP	T10
BLPTB15TP	T15
BLPTB20TP	T20
BLPTB25TP	T25
BLPTB30TP	T30



PART NO.	SIZE (inches)
BLPFB532	5/32
BLPFB316	3/16
BLPFB732	7/32
BLPFB14	1/4
BLPFB932	9/32



Square Tip Bits


















Bits Set, 31pcs

BITSET31AP

Packing: 1

- S2 material
- Magnetic bit holder and 30 bits
- 1/4" hex bits
- Plastic box with clip packaging in display box
- Philips: #1, #2*2, #3
- Pz: #1, #2*2, #3,



- TORX®: T10,T15,T20,T25,T27,T30,T40
- TORX®: T10,T15,T20,T25,T27,T30,T40 Tampered
- Slotted: 3, 4, 5, 6 mm
- Hex: H3, H4, H5, H6

Bits Set, 72pcs

BLP72BITS



 Set consists of different sizes of TORX®, Slotted, Philips, Pozidriv, Square and Hex bits, and also includes a 60mm magnetic bit holder allowing for quick change of driving bits




- Folding case design is compact and robust with pivoting dual bit holders that allow for easy and quick access to the accessories.
- S-2 grade
- All parts are engineered and produced according to ANSI Standard





Ball Peen - Wood Handle







Ball Peen, Wood Handle



WEIGHT (oz.)
4
8
12
16
24
32
40

Ball Peen, Fiberglass Handle



PART NO.	WEIGHT (oz.)	HANDLE LENGTH (inches)	REPLACEMENT HANDLE
BPN8B	8	11	BPNH8B
BPN12B	12	12	BPNH12B
BPN16B	16	13	BPNH12B
BPN24B	24	14	BPNH24B
BPN32B	32	16	BPNH24B

Ball Peen, Fiberglass Handle

Packing: 1

- Head matrial is medium carbon steel with black baked paint finish, normal polished on strking face
 Non-slip Blue 60% PP jacketed fibreglass with
- Non-slip Blue 60% PP jacketed fibreglass with comfort grip
- Used for mainly metalwork, and for use with punch and chisels
- Striking and shaping metal materials



PART NO.	WEIGHT (oz.)	HANDLE LENGTH (mm)
BLPBPFG8	8	278
BLPBPFG12	12	283
BLPBPFG16	16	327
BLPBPFG32	32	385

Soft Face

- Combination steel and soft face dead blow
- One-piece urethane construction



PART NO.	WEIGHT (g)	HEAD LENGTH (mm)	HEAD WIDTH (mm)	LENGTH (mm)
BHW35	380	100	35	300
BHW45	500	110	45	320

Soft Face







Soft Face

BH232A

- Packing: 1
- · Combination steel and soft face dead blow
- One-piece urethane construction
- 13" long fiberglass handle has a plastic, shock-absorbing grip
- Tip diameter is 1 5/8"
- Includes 2 replaceable tips: BH232-2, Soft tip BH232-3, Hard tip
- Optional: BH232-4, Nylon tip



PART NO.	WEIGHT (oz.)	LENGTH (inches)
BH232A	32	13

Soft Blow

BF623

Packing: 1

- Use on all types of surfaces and assemblies including metal, glass, plastic and wood
- Conforms to irregular surfaces
- Designed for maximum surface contact
- Low rebound
- Dissipates hand jarring shock
- Resists most chemicals
- Wood handle
- Reduces denting and marring



PART NO.	LENGTH (inches)	FACE DIMENSIONS (inches)	HEAD COLOR
BF623	12 1/2	1 7/8 x 2 1/8	Blue

Cross Peen, Hickory Handle

Packing: 1

- Forged high-quality steel that has been hardened and tempered
- Concentrated weight distribution behind the striking face for added power
- Durable, flat black finish on the head
- Polished face, hickory handle
- Wood wedged for easy handle replacement



PART NO.	WEIGHT (oz.)	HEAD LENGTH (mm)	OVERALL LENGTH (mm)
BLPCPH3	4	128	360

Cross Peen, Hickory Handle



PART NO.	WEIGHT (oz.)	HEAD LENGTH (inches)	OVERALL LENGTH (inches)	REPLACEMENT HANDLE
BH141A	32	4 1/2	15	BPH20C
BH142A	40	5	15	BPH40C

Dead Blow

Packing: 1

- · Non-conductive face with no exposed metal
- Oil and chemical resistant
- Steel shot used for dead-blow action
- Steel-reinforced handle adds strength and safety
- Perfect for shaping and cutting fine amount of materials
- Come in 2 head sizes 55 and 65 mm



PART NO.	HEAD SIZE (mm)	LENGTH (mm)
BLPDBH55	55	350
BLPDBH65	65	370

Dead Blow, Interchangeable Tip

Packing: 1

- Steel head with nylon tip
- Tubular handle with black soft grip
- Steel shot used for dead blow action
- Steel-reinforced handle adds strength and safety
- Oil and chemical resistant
- Soft face help prevent marring of surfaces and equipment
- Come in 2 interchangeable head sizes 30 and 40 mm



PART NO.	HEAD SIZE (mm)	LENGTH (mm)
BLPDBH30I	30	298
BLPDBH40I	40	300

Rubber Head Mallet

Packing: 1

- Use wherever you want to protect what you are striking from damage
- Mallet head is constructed of synthetic material
- Bounce resistant head for better control and precise hits
- Genuine hickory handle



PART NO.	WEIGHT (ozs)	LENGTH (mm)	FACE DIMENSIONS (mm)
BLPRM12	12	266	59
BLPRM16	16	310	62
BLPRM24	24	310	70

Rubber Head Mallet

BF620C

- Solid rubber head
- 11" Hardwood handle
- Ideal for replacing hubcaps, bodywork, etc



PART NO.	LENGTH (inches)	FACE DIMENSIONS (inches)
BF620C	13 ¹ /4	3 ³ /4 x 2 ¹ /4





Curve Claw, Hickory Handle

Packing: 1

- Head material: Medium carbon steel
- Head finish: Sand-blasted finish, fully polish
- Handle: Hickory handle in natural color
- Used for general woodworking, curved claw provided better leverage for removing nails
- Great to use in heavy or professional carpentry for ripping and framing work



PART NO.	WEIGHT (ozs)	LENGTH (mm)	STRIKING FACE DIMENSIONS (mm)
BLPCCH7	7	292	22.5
BLPCCH10	10	295	24.5
BLPCCH13	13	318	27
BLPCCH16	16	329	28
BLPCCH20	20	330	30
BLPCCH24	24	356	33

Curve Claw, Fiberglass Handle

Packing: 1

- Head material: Medium carbon steel
- Head finish: Sand-blasted finish, fully polish
- Handle: Non-slip Blue 60% PP jacketed fiberglass with comfort grip
- Used for general woodworking, curved claw provided better leverage for removing nails
- better leverage for removing nails

 Great to use in heavy or professional carpentry for ripping and framing work



PART NO.	WEIGHT (ozs)	LENGTH (mm)	STRIKING FACE DIMENSIONS (mm)
BLPCCFG7	7	280	22.5
BLPCCFG10	10	292	24.5
BLPCCFG16	16	327	28
BLPCCFG20	20	329	30
BLPCCFG24	24	385	33

Curve Claw Hammer

BLPCL8

Packing: 1

8oz steel tube



PART NO.	WEIGHT	STRIKING FACE	LENGTH
	(oz.)	DIAMETER (mm)	(mm)
BLPC8	360	23	260

Brass Hammer

- Non-sparking/non-marring surface for many applications
- Brass head absorbs blow and reduces rebound
- Flat surface for even distribution of blow
- Fiberglass handle for strength
- · Comfortable, non-slip handle grip



PART NO. (lbs.) (inches)	LENGTH (inches)	
HBR15 1 1/2 12		
HBR25 2 1/2 12		

Wheel with Hammer SML Hook

WWH13SM

- Heavy-duty, Nuplaglas[®] handle is chemical-resistant and features non-slip cushioned grip
- 30 oz head weight for working on larger vehicles
- · Removes "perfect-style" wheel weights without touching rim of vehicle and larger v-clips found on medium duty truck rims



Fiberglass Hammer

- Fiberglass handle dampens vibration and provides extra strength and safety
- Handle is epoxy-welded to hammer head and will withstand 8,000 lbs. of separation force
- Handle is resistant to dry rot, warp and splintering
- Comfortable, non-slip handle grip
- · Materials will resist most shop chemicals

PART NO.	DESCRIPTION	WEIGHT (lbs)	STRIKING FACE DIAMETER (inches)	HANDLE LENGTH (inches)	OVERALL LENGTH (inches)	REPLACEMENT HANDLE
BC4SG	Cross Peen	4	1 1/2	12	14	BD4SG-1
BD4SG	Engineer	4	1 1/2	12	14	BD4SG-1
HD4SG	Hand Drilling	4	1 1/2	8 3/4	10 3/4	HD4SG-1
			•			







Pin Punch Set, 6pcs

BLPRP6

- High quality Cr-V
- Mix punch set



PART NO.	CONTENTS
BLPRP6	8 x 180mm L L Pin Punch
	6 x 180mm L Pin Punch
	5 x 165mm L Pin Punch
	4 x 150mm L Pin Punch
	3 x 125mm L Pin Punch
	2 x 115mm L Pin Punch

Punch Set

DPFT528B

- Packing: 1
- For transferring hole patterns
- Set includes punches from 3/32" to 1/2" in 1/64" increments plus 17/32"
- Each punch is marked with its size and manufactured from tempered steel to promote long tool life
- A metal index provides convenient storage
- Punches are 4 7/8" in length



Punch & Chisel Set, 5pcs

BLPPC5

Packing: 1

Packing: 1

- Chrome-plated for corrosion resistance
- Comes with a plastic holder



PART NO.	CONTENTS	
	#2 Central Punch	
	3mm Hole Punch	
BLPPC5	4mm Pin Type Punch	
	5mm Boring Bit	
	12mm Flat Chisel	

Automatic Center Punch

YA900

Packing: 1

- Strikes blow when pressure is applied
 no hammer needed
- · Cap adjusts force of blow
- 7/16" diameter
- 4 3/4" long



Automatic Center Punch

YA879A

- Single handed operation
- Design eliminates need for striking with hammer
- Hardened steel point is replaceable
- Adjustable spring tension cap
- 1/2" diameter
- 5" long



Transfer Punch Set, 31pcs

DPFT531


Packing: 1

- Set includes 31 punches from 3/32" 1" in roll bag provides convenient storage
- For transferring hole patterns
- Size marking on each punch and manufactured from tempered steel to promote long tool life Punches are 4 7/8" in length



Transfer Punch

- For transferring hole patterns
- Size marking on each punch and manufactured from tempered steel to promote long tool life
- Punches are 4 7/8" in length



PART NO.	CONTENTS
DPFT531-6	3/32" Transfer Punch
DPFT531-7	7/64" Transfer Punch
DPFT531-8	1/8" Transfer Punch
DPFT531-9	9/64" Transfer Punch
DPFT531-10	5/32" Transfer Punch
DPFT531-11	11/64" Transfer Punch
DPFT531-12	3/16" Transfer Punch
DPFT531-13	13/64" Transfer Punch
DPFT531-14	7/32" Transfer Punch
DPFT531-15	15/64" Transfer Punch
DPFT531-16	1/4" Transfer Punch
DPFT531-17	17/64" Transfer Punch
DPFT531-18	9/32" Transfer Punch
DPFT531-19	19/64" Transfer Punch
DPFT531-20	5/16" Transfer Punch
DPFT531-21	21/64" Transfer Punch

PART NO.	CONTENTS
DPFT531-22	11/32" Transfer Punch
DPFT531-23	23/64" Transfer Punch
DPFT531-24	3/8" Transfer Punch
DPFT531-25	25/64" Transfer Punch
DPFT531-26	13/32" Transfer Punch
DPFT531-27	27/64" Transfer Punch
DPFT531-28	7/16" Transfer Punch
DPFT531-29	29/64" Transfer Punch
DPFT531-30	15/32" Transfer Punch
DPFT531-31	31/64" Transfer Punch
DPFT531-32	1/2" Transfer Punch
DPFT531-34	17/32" Transfer Punch
DPFT531-48	3/4" Transfer Punch
DPFT531-56	7/8" Transfer Punch
DPFT531-64	1" Transfer Punch





Scraper Set, 3pcs

PKB500A



- Spring tempered, solid brass blades are non-marring, non-sparking, non-magnetic and non-corrosive
- Soft molded rubber handles maximize hand grip, easy to clean and resistant to most solvents
- Broad hilt design helps protect against hand slipping when scraping

•	Stiff blade style
	00
	The line in
	B. C. C.

PART NO.	HANDLE LENGTH (inches)	BLADE LENGTH (inches)	BLADE WIDTH (inches)	BLADE STYLE	EDGE
PKB50A	4 7/8	3 1/2	2	Stiff	Straight
PKB52A	4 7/8	3 19/32	1 1/4	Stiff	Straight
PKB53A	4 7/8	3 19/32	1 1/4	Stiff	Single Bevel

Scraper Set, 3pcs

USS103



- Remove gaskets, sealers and other caked on materials
- Blade edge designed to work effectively in both push and pull directions
- Stainless steel blades for durability
- Polished blades clean up easily
- Comfortable composite handles feature a contour thumb stop for maximum control and a wide hilt for control



PART NO.	BLADE STYLE	BLADE LENGTH (inches)	LENGTH (inches)
US710	Spoon	3 1/2	8
US711	Chisel Tip	2 1/2	7 1/8
US712	Oyster	2 1/8	6 3/4

Scraper Set, 3pcs

PK500A



- Features full length steel blades for strength and durability
- Soft molded rubber handles maximize hand grip, easy to clean and resistant to most solvents
- Broad hilt design helps protect against hand slipping when scraping



PART NO.	BLADE LENGTH (inches)	BLADE WIDTH (inches)	BLADE STYLE	EDGE
PK50A	3 1/2	2	Flexible	Straight
PK52A	5 19/32	1 1/4	Flexible	Straight
PK53A	2 19/32	1 1/4	Stiff Chisel	Single Bevel

Scraper, Walnut Handle

Packing: 1

- Remove gaskets, sealants and body weld breakaway
- Quality crafted for hard scraping applications
- Full length heavy duty blades for strength
- · Large steel cap for striking capability
- Walnut wood handle for comfort



PART NO.	BLADE LENGTH (inches)	BLADE WIDTH (inches)	BLADE STYLE	EDGE	LENGTH (inches)
PKWLR53A	5 1/2	1 1/4	Straight	Chisel	9 1/2
PKWSS53A	2 3/4	1 1/4	Straight	Chisel	6 3/4

Scraper, Wood Handle

PK23A



- Mirror finished hardened steel blade extends through hardwood handle, solidly riveted for durability
- Redwood handle has metal bolster where handle meets blade



PART NO.	HANDLE MATERIAL	HANDLE LENGTH (inches)	BLADE WIDTH (inches)	BLADE STYLE	EDGE
PK23A	Maple	3 7/8	1 1/4	Heavy Chisel	Single Bevel

File Sets

Packing: 1

- · Set in pouch for easy storage, portability or to hang in workshop Tough, durable HSS bi-material handle
- All sets are in 2nd-Cut



PART NO.	DESCRIPTION	SIZES (inches)
BLFF1S4	Coarse Flat File, 4pcs	6, 8, 10, 12
BLFF2S4	Flat 2nd Cut File Set, 4pcs	6, 8, 10, 12
BLFRS4	Round File Set, 4pcs	6, 8, 10, 12
BLFHRS4	Half Round File Set, 4pcs	6, 8, 10, 12
BLFT4	Triangle File Set, 4pcs	6, 8, 10, 12

Coarse Flat File

Packing: 3

- Tough, durable HSS bi-material handle
- Perfect for shaping and cutting fine amount of materials



PART NO.	LENGTH (inches)	
BLFFC6	6	
BLFFC8	8	
BLFFC10	10	
BLFFC12	12	

Flat 2nd-Cut File

Packing: 3

- Tough, durable HSS bi-material handle
- Perfect for shaping and cutting fine amount of materials



PART NO.	LENGTH (inches)
BLFFS6	6
BLFFS8	8
BLFFS10	10
BLFFS12	12

Half Round 2nd-Cut File

Packing: 3

- Tough, durable HSS bi-material handle
- Perfect for shaping and cutting fine amount of materials



PART NO.	LENGTH (inches)	
BLFHS6	6	
BLFHS8	8	
BLFHS10	10	
BLFHS12	12	

Round 2nd-Cut File

Packing: 3

- Tough, durable HSS bi-material handle
- Perfect for shaping and cutting fine amount of materials



PART NO.	LENGTH (inches)
BLFRS6	6
BLFRS8	8
BLFRS10	10
BLFRS12	12

Triangular 2nd-Cut File

- Tough, durable HSS bi-material handle
- Perfect for shaping and cutting fine amount of materials



PART NO.	LENGTH (inches)
BLFTS6	6
BLFTS8	8
BLFTS10	10
BLFTS12	12





Shears, Angled, Heavy Duty

SNP2A



- For leather, cloth, plastic, rubber sheet, rubber hose, cardboard, gasket material, rope and many other materials
- Stainless steel h'
- ¬ fasteners ensure durability ated for a long lasting
- Precision grou edge Ergonomic

* or left handed

wine

Jrage



- Top of blade is no.
 - Locking switch ensure
- Control switch allows blac
 - d in a tighter position for easier handling
- Angled shears allow easier cutting through flat materials
- Soft mold grip for comfort and control

Sheet Metal Snips, Offset

Packing: 1

- Special laborsaving, designed for easier cutting
- High tensional strength spring designed for longer life
- Solid, comfortable handle with non-design provide grip comfort
- Serrated edges prevent slipping
- Cr-Mo alloy steel hot forged blades for greater strength and longer durability



PART NO.	DESCRIPTION	BLADES LENGTH (mm)	OVERALL LENGTH (mm)
AVSNPOS1010	Offset, Left cutting Orange handle	30	245
AVSNPOS1020	Offset, Right cutting Blue handle	30	245

Sheet Metal Snips, Straight

- Special laborsaving, designed for easier cutting
- High tensional strength spring designed for longer life
- Solid, comfortable handle with non-design provide grip comfort Serrated edges prevent slipping
- Cr-Mo alloy steel hot forged blades for greater strength and longer durability



PART NO.	DESCRIPTION	BLADES LENGTH (mm)	OVERALL LENGTH (mm)
AVSNP01030CN	Straight Yellow handle	38	254
AVSNP01010CN	Straight, Left cutting Red handle	35	248
AVSNP01020CN	Straight, Right cutting Green handle	35	248

Tin Snips

Packing: 1

- Drop forged of steel in one piece construction
- Black cushion handle with smooth, comfortable bows for ease in use and safety
- Designed for cutting straight and wide curves to the left or right
- Induction hardened cutting edges 58-61 HRC



PART NO.	BLADES LENGTH (mm)	OVERALL LENGTH (mm)
BLPSPSNIP8	40	206
BLPSPSNIP10	51	263
BLPSPSNIP12	70	310
BLPSPSNIP16	63	415

Tin Snips

Packing: 1

Cut straight, circular, or irregular patterns; right or left cuts



PART NO.	DESCRIPTION	BLADES LENGTH (inches)	LENGTH (inches)
CD7A	Duckbill Snips	1 1/2	7
CD10A	Duckbill Snips	2 1/4	10
CD12A	Combination Snips	3	12
CD16A	Bulldog Snips	2 1/2	16

Scissors, Shop, Heavy Duty

HDSCISSORS

Packing:1

· For leather, cloth, plastic, rubber sheet, rubber hose, cardboard, gasket material, rope and many other materials



- Stainless steel blade and fasteners
- Precision ground and heat treated for a long lasting edge
- Ergonomic handles can be used right or left handed

Vinyl Cutter

YA444B

- Cleanly cuts plastic, rubber, vinyl, upholstery, leather, hoses, and rope
- Ergo Grip handle with safety lock
- Blade storage in handle
- Includes YA444B1 replacement blades



PART NO.	DESCRIPTION
YA444B	Vinyl Cutter with YA444B1`replacement blades
YA444B1	3 Replacement blades and anvil





Utility Knife

LBUK1

- Packing: 1
- Utility knife with 10 replacement blades in leather pouch, both with Blue-Point® logo
- Convenience and good looks of a folding lock back knife with easily replaceable two notch razor



- Folding lock back blade, hardwood handle with belt clip and thumb stud for one-hand opening
- Uses UKBU10 (10 pack) or UKBU50PK (50 pack) replacement blades

Utility Knife Blades

UKBU10

- High performance blades are perfect for thick, dense materials
- Bi-metal construction allows blade to bend/ flex without breaking under normal work conditions
- Bi-metal lasts up to 3 times longer than normal utility knife blades
- Two-notch blade design fits most standard utility knives
- Pack of 10 blades

UKBU50PK

- High performance blades are perfect for thick, dense materials
- Bi-metal construction allows blade to bend/flex without breaking under normal work conditions
- Bi-metal lasts up to 3 times longer than normal utility knife blades
- Two-notch blade design fits most standard utility knives
- Convenient dispenser provides storage for used blades
- Dispenser of 50 blades



Packing: 1



UKBU50PK

Mini Hacksaw

BLPMHF6



- 25 mm in length
- 24TPI blade



Junior Hacksaw, 6"

BLPHSAW6



- Aluminum alloy frame for lightweight
- Handle with rubber grip for comfort handling and control
- Tri-direction adjustable
- Length: 6"



Cutters, Multi-Purpose

Packing: 1

YA580A

- Features auto locking, fully retractable blade
- All metal body is black with pocket clip
- Includes (1) premium steel 13-point. snap blade
- Overall length of 5 3/8 (136.5mm)



YA580A-1

Replacement Blades

Pack of 5

YA581A

- 3 blades with 8 snap off points.
- Minimum blade wobble
- Fully retractable



YA581A-1 Replacement Blades

Pack of 10









POWER TOOLS Pneumatic Tools / Impact Wrenches





1/4" Impact Wrench, Mini

AT235MCA

- Packing: 1
- Composite housing contributes to an extremely durable, lightweight unit with new molded comfort grip
- Composite housing is not cold to the touch
- Forward/Reverse mechanism easily operated with one-finger
- Large, variable speed trigger for control
- Exhaust is from the handle bottom, keeping exhaust away from work area and user



PART NO.	DRIVE SIZE	MAX. TORQUE	FREE SPEED
	(inches)	(N•m)	(rpm)
AT235MCA	1/4	34	13,000
BLOWS PER	AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET	RECOMMENDED
MINUTE		THREAD SIZE	HOSE SIZE (inches)
2,900	47	¹ /4" - 18 NPT	3/8
VIBRATION	SOUND LEVEL	LENGTH	WEIGHT
LEVEL (m/s²)	dBa PRESSURE	(mm)	(kg)
<2.5	95.1	158	0.64

3/8" Impact Wrench

AT380A

- 🃦 Packing: 1
- 10% more power than the AT380
- Built-in five position adjustable air regulator plus a variable speed trigger for maximum user control
- Aluminum housing provides a lightweight yet durable tool
- Tapered nose increases accessibility to confined areas
- Ball-bearing mounted motor creates a smooth running operation for less user fatigue
- Brass inlet filter screens out dirt and grit; easy-to-remove filter for cleaning
- Twin-hammer impact mechanism designed to hit hard yet offer tool longevity. One-year limited warranty



PART NO.		DRIVE SIZE (inches)		RQUE 1)	FREE SPEED (rpm)	BLOWS PER MINUTE
AT380A	3/8		230		8,700	1,680
AIR CONSU			INLET EAD SIZE	RECOMMENDED HOSE SIZE (inches)		VIBRATION LEVEL (m/s²)
111		1/4" -	- 18 NPT		3/8	3.5
SOUND L dBa PRES		LENGTH (mm)		,	WEIGHT (kg)	VINYL BOOT (optional)
94		165			1.36	AT380ABOOT

3/8" Impact Wrench, Composite

AT370

- Packing: 1
- Shot Peen Anvils for improved durability
- Reverse Bias motor provides additional breakaway torque
- 3 position regulator to control power
- One handed forward/reverse lever for user convenience
- Composite housing with aluminum nose combine to deliver a durable, lightweight and balanced unit.
- Twin hammer impact mechanism delivers hard hitting blows to quickly remove stubborn fasteners



PART NO.	DRIVE SIZI	E MAX. TORQUI	E FREE SPEED	BLOWS PER
	(inches)	(N•m)	(rpm)	MINUTE
AT370	3/8	434	10,000(F), 11,000(R)	1,050
	UMPTION,	AIR INLET	RECOMMENDED	VIBRATION
	EED (I/min)	THREAD SIZE	HOSE SIZE (inches)	LEVEL (m/s²)
4.4 cfm(F),	4.7 cfm (R)	1/4" - 18 NPT	3/8	3.25
	LEVEL	LENGTH	WEIGHT	VINYL BOOT
	ESSURE	(mm)	(kg)	(optional)
9)2	160	1.19	AT370BOOT

3/8" Impact Wrench, Composite

AT3600C

- Packing: 1
- Composite housing with Magnesium Nose
- Lightweight at 1.7kg
- Maximum torque of 510Nm / 375 ft. lb. of Torque
- Twin Hammer Mechanism
- Ergonomic cushion grip reduces vibration



PART NO.	DRIVE SI		TORQU RANGE (N		FREE SPEED (rpm))	BLOWS PER MINUTE
AT3600C	3/8		108 - 37	'5	6,500		1,300
AIR CONSU	,		IR INLET READ SIZE		COMMENDED E SIZE (inches)		VIBRATION .EVEL (m/s²)
7.06	cfm	1/2	1" - 18 NPT		3/8		4
SOUND dBa PRE			LENGTH (mm)		WEIGHT (kg)	١	/INYL BOOT (optional)
94	1		149		1.47	ΑT	3600СВООТ





3/8" Impact Wrench, Single Hammer

AT321

- Packing: 1
- Single hammer impact mechanism
- · Steel nose case with lightweight aluminum housing
- Convenient slide bar forward/reverse



PART NO.	DRIVE SIZE (inches)	MAX. TORO (N•m)	QUE	FREE SPEED (rpm)	BLOWS PER MINUTE
AT321	3/8	237		11,000	1,500
AIR CONSU FREE SPEE		AIR INLET HREAD SIZE		ECOMMENDED SE SIZE (inches)	VIBRATION LEVEL (m/s²)
108	1	l/4" - 18 NPT		3/8	9.8
SOUND L dBa PRES		LENGTH (mm)		WEIGHT (kg)	VINYL BOOT (optional)
109		155		1.3	AT321-44

3/8" Impact Wrench, Compact

AT351

- Packing: 1
- Built-in air inlet swivel
- 8 position power regulator
- Rotary action air motor is ball bearing mounted for balance, speed and power
- Ideal tool for small engine repair and bench work



PART NO.	DRIVE SIZE (inches)	MAX. TORQUE (N•m)	FREE SPEED (rpm)
AT351	3/8	237	9,700
BLOWS PER MINUTE	AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)
1,200	71	1/4" - 18 NPT	3/8
VIBRATION LEVEL (m/s²)	SOUND LEVEL dBa PRESSURE	LENGTH (mm)	WEIGHT (kg)
3.09	109.2	194	1.2

3/8" Impact Wrench, Tight Access

AT4510



- 345 N.m of torque, 7500 RPM and 1300 blows per minute
- Compact size allowing access to limited spaces
- Extreme lightweight design to reduce users' fatigue
- Ergonomic designed grip delivering comfort when handling
- Twin hammer impact mechanism hits harder and delivers
- Increased tool longevity
- One handed forward/reverse switch for easy operation
- Muffler pad designed to provide low noise levels



PART	DRIVE SIZE	MAX TORQUI	FREE SPEED	BLOWS PER
NO.	(inches)	(N•m)	(rpm)	MINUTE
AT4510	3/8	345	7,500	1,300
AIR CONSUMPTION,		RECOM	VIBRATION	
FREE SPEED		HOSE	LEVEL	
(I/min)		(inc	(m/s²)	
2	232	3	1/8	4
	D LEVEL	LENGTH	WEIGHT	VINYL BOOT
	RESSURE	(mm)	(kg)	(optional)
	83	112	1.3	-

3/8" Impact Wrench

AT5300C



- Composite housing with Magnesium Nose
- Lightweight at 1.3kg
- Maximum torque of 400Nm /295 ft. lb. of torque
- Twin Hammer Mechanism
- Soft grip handle increased comfort and reduced vibration



PART NO.	DRIVE SIZE (inches)	MAX TORQU (N•m)	JE FREE SPEE (rpm)	D BLOWS PER MINUTE	
AT53000	3/8	400	9,000	1,300	
FRE	AIR CONSUMPTION, FREE SPEED (I/min)		RECOMMENDED HOSE SIZE (inches)		
	119		3/8		
	ID LEVEL RESSURE	LENGTH (mm)	WEIGHT (kg)	VINYL BOOT (optional)	
	89	143	1.3	-	

1/2" Impact Wrench, Composite

AT570

- Packing: 1
- Shot Peen Anvils for improved durability
- Reverse Bias motor provides additional breakaway torque
- 3 position regulator to control power
- One handed forward/ reverse lever for user convenience
- Composite housing with aluminum nose combine to deliver a durable, lightweight and balanced unit
- Twin hammer impact mechanism delivers hard hitting blows to quickly remove stubbom fasteners



PART NO.	DRIVE SIZE (inches)	MAX. TORQU (N•m)	FREE SPEED (rpm)	BLOWS PER MINUTE
AT570	1/2	773	6,900(F), 7,000(F	1,050
AIR CONSU FREE S (I/m	PEED	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
5.0 cfm (F), 5	.3 cfm (rev.)	1/4" - 18 NPT	3/8	6.08
SOUND dBa PRE		LENGTH (mm)	WEIGHT (kg)	VINYL BOOT (optional)
95	5	184	1.87	AT570BOOT

1/2" Impact Wrench

AT5500

- Built-in five position adjustable air regulator plus a variable speed trigger for maximum user control
- Twin-hammer impact mechanism designed to hit hard yet offer tool longevity
- Inlet filter screens out dirt and grit; easyto-remove filter for cleaning



PART NO.	DRIVE SIZE (inches)		MAX. TORQUE (N•m)	FREE SPEED (rpm)
AT5500	1/2		745	7,400
BLOWS PER MINUTE	AIR CONSUMPTION, FREE SPEED (I/min)		RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
1,200	11	8.9	3/8	4
SOUND LEVEL dBa PRESSURE	LENGTH (mm)	WEIGHT (kg)	VINYL BO	
94	200	2.9	AT5500BOOT	

1/2" Impact Wrench, Tight Access

AT4550



- 488 N.m of torque, 7500 RPM and 1300 blows per minute
- Compact size allowing access to limited spaces
- Extreme lightweight design to reduce users' fatigue
- Ergonomic designed grip delivering comfort when handling
- Twin hammer impact mechanism hits harder and delivers
- Increased tool longevity
- One handed forward/reverse switch for easy operation
- Muffler pad designed to provide low noise levels



PART NO.	DRIVE SIZE (inches)	MAX TORQU (N•m)	JE FREE SPEEI (rpm)	D BLOWS PER MINUTE
AT4550	1/2	488	7,500	1,300
FREE	SUMPTION, SPEED min)	HOS	RECOMMENDED HOSE SIZE (inches)	
2	32		3/8	4
	D LEVEL ESSURE	LENGTH (mm)		
8	33	112	1.3	-

1/2" Impact Wrench, Composite

AT5500C

- Composite housing with Magnesium Nose
- Lightweight at 1.7kg
- Maximum torque of 910Nm / 671 ft. lb. of torque!
- Twin Hammer Mechanism
- Ergonomic cushion grip reduces vibration



PART NO.	DRIVE SIZE (inches)	TORQUE. RANGE (N•r	n)	FREE SPEED (rpm)	BLOWS PER MINUTE
AT5500C	1/2	285 - 910		8,000	1,200
FREE	SUMPTION, SPEED min)	AIR INLET THREAD SIZE		COMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
7.06	6 cfm	1/4" - 18 NPT		3/8	4
	D LEVEL ESSURE	LENGTH (mm)		WEIGHT (kg)	VINYL BOOT (optional)
	94	152		1.73	AT5500CBOOT









1/2" Impact Wrench, Stubby

AT5500T

- Packing: 1
- 550 ft-lb of torque, 9000 RPM and 1200 blows per minute
- Compact and lightweight for reduced user fatigue
- Twin-hammer impact mechanism hits harder and delivers increased tool longevity
- Polished aluminum housing is durable and easy to clean
- Ball-bearing mounted motor for smooth running operation
- Removable brass inlet filter protects tool from grit and debris
- Large forward/reverse lever for one-handed operation



PART NO.	DRIVE SIZE	MAX. TORQUE	FREE SPEED
	(inches)	(N•m)	(rpm)
AT5500T	1/2	745	9,000
BLOWS PER	RECOMMENDED	VIBRATION	SOUND LEVEL
MINUTE	HOSE SIZE (inches)	LEVEL (m/s²)	dBa PRESSURE
1,200	3/8	4	94
LENGTH	WEIGHT		L BOOT
(mm)	(kg)		tional)
183	2.29	AT550	отвоот

3/4" Impact Wrench

AT670



- Aluminium nose with composite body for lightweight & durability
- Twin-hammer mechanism easily removes stubborn nuts
- Three-position lever controls amount of torque
- Two-way push buttons controls Forward/Reverse rotation



PART NO.	DRIVE SIZE (inches)	MAX. TORQUE (N•m)	FREE SPEED (rpm)
AT670	3/4	1,423	6,700(F), 6,900(R)
	WS PER NUTE	AIR CONS FREE SPE	
1	,050	15	59
VIBRATION LEVEL (m/s²)	SOUND LEVEL dBa PRESSURE	LENGTH (mm)	WEIGHT (kg)
2.44	114.4	215	3.44

1/2" Impact Wrench, Stubby Ext. Anvil

AT5500TL

Packing: 1

- 550 ft-lb of torque, 9000 RPM and 1200 blows per minute
- Compact and lightweight for reduced user fatigue
- Twin-hammer impact mechanism hits harder and delivers increased tool longevity
- Polished aluminum housing is durable and easy to clean
- Ball-bearing mounted motor for smooth running operation
- Removable brass inlet filter protects tool from grit and debris
- Large forward/reverse lever for one-handed operation
- Deep recessed application
- 2" anvil

PART NO.	DRIVE SIZE (inches)		TORQUE I•m)
AT5500TL	1/2	7	745
FREE SPEED (rpm)	BLOWS PER MINUTE		IMENDED ZE (inches)
9,000	1,200	:	3/8
VIBRATION LEVEL (m/s²)	SOUND LEVEL dBa PRESSURE	LENGTH WEIGHT (mm) (kg)	
4	94	205	2.33

1" Impact Wrench, Composite

AT100IMC

- 2983 N.m of torque, 5500 RPM and 1400 blows per minute
- Durable and powerful twin hammer mechanism
- Ergonomic housing design with steel protector ring
- High performance motor maximizes output torque
- Side mounted handle for better operator control
- Optional internal/external trigger set
- (3) forward and (3) reverse speeds

PART NO.	DRIVE SIZ (inches)	E MAX TORG (N•m)	QUE FREE S (rpr	
AT100IMC	1	2,983	5,00	1,400
AIR CONSU FREE SI (I/mi	PEED	HOS	MENDED SE SIZE ches)	VIBRATION LEVEL (m/s²)
340)		3/4	11.4
SOUND I dBa PRES		LENGTH (mm)		
108	3	375	6.8	-

1" Impact Wrench, Composite, Long Anvil

AT100IMCL

- Packing: 1
- 2983 N.m of torque, 5500 RPM and 1400 blows per minute
- Durable and powerful twin hammer mechanism
- · Ergonomic housing design with steel protector ring
- High performance motor maximizes output torque
- Side mounted handle for better operator control
- Optional internal/external trigger set
- (3) forward and (3) reverse speeds

Long anvil version



PART NO.	DRIVE SIZE (inches)	MAX TORQUE (N•m)	FREE SPEED (rpm)	BLOWS PER MINUTE
AT100IMCL	1	2,983	5,500	1,400
AIR CONSUI FREE SP (I/mir	EED	RECOMME HOSE S (inche	IZE	VIBRATION LEVEL (m/s²)
340		3/4		11.4
SOUND L dBa PRES		LENGTH (mm)	WEIGHT (kg)	VINYL BOOT (optional)
108		527	7.7	-

1" Impact Wrench

AT1300B

Packing: 1

- 2700 N.m of torque, 5000 RPM and 900 blows per minute
- Durable and powerful pin-less clutch mechanism
- Ergonomic housing design with steel protector ring
- High performance motor maximizes output torque
- Side mounted handle for better operator control
- Optional internal/external trigger set
- (3) forward and (3) reverse speeds



PART NO.	DRIVE SIZE (inches)	MAX. TORQUI (N•m)	FREE SPEED (rpm)	BLOWS PER MINUTE
AT1300B	1	2,700	5,000	900
AIR CONSU FREE S (I/m	PEED	RECOMMENDED HOSE SIZE (inches)		VIBRATION LEVEL (m/s²)
30	6	1	/2	12.01
SOUND dBa PRE		LENGTH WEIGHT (mm) (kg)		VINYL BOOT (optional)
10	9	345	10.5	-

1" Impact Wrench, Long Anvil 6"

AT1300BL



- 2700 N.m of torque, 5000 RPM and 900 blows per minute
- Durable and powerful twin hammer mechanism
- Ergonomic housing design with steel protector ring
- High performance motor maximizes output torque
- Side mounted handle for better operator control
- Optional internal/external trigger set
- (3) forward and (3) reverse speeds
- Long anvil 6" version



PART NO.	DRIVE S		MAX TOR (N•m		FREE SPEED (rpm)	BLOWS PER MINUTE
AT1300BL	1		2,700)	5,000	900
AIR CONSUM FREE SPE (I/min)	ED			MENI E SIZI ches)		VIBRATION LEVEL (m/s²)
306			1/2		10.66	
			ENGTH (mm)	,	WEIGHT (kg)	VINYL BOOT (optional)
109			496		12.2	-

1/4" Drill, Micro

AT801MCA

- · Composite housing with new molded comfort grip is more comfortable for the user while providing less user fatigue
- Small size, light weight and a powerful motor make this tool ideal for working in confined areas
- Durable single piece polymer composite housing stands up to rugged use, resists most shop chemicals and helps insulate against the cold generated by an air tool Variable speed trigger

PART NO.	CHUCK SIZE (inches)	RATED POWER (kW)	TOR RANGE	
AT801MCA	1/4	0.19	0 -	- 2
FREE SPEED (rpm)	SPINDLE THREAD (inches)	AIR CONSUMPTION, FREE SPEED (I/min)	AIR II	
1,800	3/8 - 24 UNF	266	1/4" - 1	18 NPT
RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)	SOUND LEVEL dBa PRESSURE	LENGTH (mm)	WEIGHT (kg)
3/8	< 2.5	96.4	183	0.68









3/8" Drill

AT3000

Packing: 1

- One hand forward/reverse operation
- Three planet gear design for durability and balance
- Bottom handle diffused exhaust
- Comfort grip handle
- Keyless chuck saves time when changing bits



PART NO.	CHUCK SIZE (inches)	RATED POWER (kW)	TORQUE RANGE (N•m)
AT3000	3/8	0.15	0 - 4
FREE SPEED (rpm)	SPINDLE THREAD (inches)		SUMPTION, EED (I/min)
2,000	3/8 - 24 UNF	!	99
AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)	SOUND LEVEL dBa PRESSURE
1/4" - 18 NPT	3/8	< 2.5	105
LENGTH (mm)	WEIGHT (kg)	Vinyl Boo	t (optional)
194	1.4	AT300	овоот

1/2" Drill

AT5000



- One hand forward/reverse operation
- Three planet gear design for durability and balance
- Bottom handle diffused exhaust
- Comfort grip handle
- Keyed chuck easily handles 120 in.lbs. of torque
- Chuck key stores in handle



PART NO.	CHUCK SIZE (inches)	RATED POWER (kW)	TORQUE RANGE (N•m)
AT5000	1/2	0.33	0 - 14
FREE SPEED (rpm)	SPINDLE THREAD (inches)	AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE
490	1/2 - 20 UNF	108	1/4" - 18 NPT
RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)	SOUND LEVEL dBa PRESSURE	LENGTH (mm)
HOSE SIZE	LEVEL	LEVEL dBa	
HOSE SIZE (inches)	LEVEL (m/s²)	LEVEL dBa PRESSURE	(mm) 229

3/8" Drill, Angle

AT811

Packing: 1

- Rugged, reversible right angle drill gets in tight spots comfortably
- Convenient one hand push button forward/reverse
- Rear exhaust keeps air away from the work area
- Built in chuck key holder keeps the key at hand for quick bit changes
- Paddle style trigger for greater comfort
- Ball bearing construction for longer tool life
- Lightweight helps avoid fatigue during prolonged use
- Bottom handle diffuse exhaust

			_	
PART NO.	CHUCK SIZE (inches)	RATED POWER (kW)	TOR RANGE	QUE E (N•m)
AT811	3/8	0.19	0 -	- 6
FREE SPEED (rpm)	SPINDLE THREAD (inches)	AIR CONSUMPTION, FREE SPEED (I/min)		NLET .D SIZE
1,320	3/8 - 24 UNF	95	1/4" - 1	I8 NPT
RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)	SOUND LEVEL dBa PRESSURE	LENGTH (mm)	WEIGHT (kg)
3/8	< 0.8	110	208	1.1

Spotweld Drill

AT184

- Twist depth control collar allows precise setting of drilling depth up to 1/4"
- Two speed trigger for low or high speeds
- Pistol grip design
- Includes one 5/16" (8 mm) drill bit and removeable clamp arm



PART NO.	CHUCK SIZE (inches)	FREE SPEE (rpm)	ED AIR CONSUMPTION, FREE SPEED (I/min)	
AT184	5/16	1,800	238	
AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATIO		
1/4" - 18 NPT	3/8	< 1.0	84	
		SUPPORT ARM 5.5 (optional)		
LENGTH (mm)	WEIGHT (kg)	SU		
		SU		
(mm)	(kg)		(optional)	
(mm)	(kg) 1.4	DRILL BIT	(optional)	

Air Hammer

AT2050 Packing: 1



PART NO.	BORE DIAMETER (inches)	BLOWS PER MINUTE	PISTON STROKE (inches)	SHANK OPENING (mm)
AT2050	3/4	3,400	2.75	10.1
AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOM! HOSE SIZ		VIBRATION LEVEL (m/s²)
71	1/4" - 18 NPT	5/	16	3.0
SOUND LEVEL dBa PRESSURE	LENGTH (mm)	WEI		VINYL BOOT (optional)
99	187	2	.1	AT2050BOOT

1/4" Ratchet

AT200D

- Packing: 1
- · Lightweight aluminum housing Rugged ball bearing mounted air motor and precision planetary gear system



PART NO.	DRIVE SIZE (inches)	TORQUE RANGE (N•m)	FREE SPEED (rpm)
AT200D	1/4	6 - 27	150
AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
40	1/4" - 18 NPT	3/8	3.3
SOUND LEVEL dBa PRESSURE	LENGTH (mm)	WEIGHT (kg)	VINYL BOOT (included)
85	222	0.50	AT200D22A

1/4" Ratchet

AT203A

Packing: 1

- Lightweight aluminum housing
- Rugged ball bearing mounted air motor and precision planetary gear system

Easy to use variable speed throttle



PART NO.	DRIVE SIZE	TORQUE RANGE	FREE SPEED
	(inches)	(N•m)	(rpm)
AT203A	1/4	6 - 34	285
AIR CONS		AIR INLET	RECOMMENDED
FREE SPE		THREAD SIZE	HOSE SIZE (inches)
8	8	1/4" - 18 NPT	3/8
VIBRATION	SOUND LEVEL	LENGTH	WEIGHT
LEVEL (m/s²)	dBa PRESSURE	(mm)	(kg)
< 4.4	100	188	0.57

1/4" Ratchet, Mini

AT204A

- Packing: 1
- · Compact size allows for greater access to tight spaces
- Easy to use with a variable speed throttle
- Lightweight design reduces fatigue
- Comfort grip, head boot & 5' braided PU hose



PART NO.	DRIVE SIZE (inches)	MAX TORQUE (ft.lbs)	FREE SPEED (rpm)
AT204A	1/4	30	350
AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
99	1/4" - 18 NPT	5/16	3.6
SOUND LEVEL dBa	PRESSURE	LENGTH (mm)	WEIGHT (kg)
94		130	0.48









1/4" Ratchet, Mini

AT2140

- Packing: 1
- 33 N.m of torque, powerful air ratchet for its size, easily remove and install fasteners
- · Robust head design for maximum strength and durability
- Adjustable exhaust directs airflow away from work area
- Soft grip handle increased comfort and reduced vibration
- Suitable for motorcycle and small engine work
- At just 0.5kg, the small, light weight designed allows longer period of handling without hand fatigue



PART NO.	DRIVE SIZE (inches)	MAX TORQUE (ft.lbs)	FREE SPEED (rpm)
AT2140	1/4	33	240
AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
99	1/4" - 18	3/8	3
SOUND LEVEL dBa	PRESSURE	LENGTH (mm)	WEIGHT (kg)
89		112	0.5

3/8" Ratchet

AT704A

- Packing: 1
- Lightweight aluminum housing
- Rugged ball bearing mounted air motor and precision planetary gear system
- Easy to use variable speed throttle plus adjustable air regulator



PART NO.	DRIVE SIZE (inches)	TORQUE RANGE (N•m)	FREE SPEED (rpm)
AT704A	3/8	6 - 75	200
AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
111	1/4" - 18 NPT	3/8	< 3.9
SOUND LEVEL dB	a PRESSURE	LENGTH (mm)	WEIGHT (kg)
104		266	1.5

3/8" Ratchet, Mini

AT2610

- Packing: 1
- 54 N.m of torque, powerful air ratchet for its size, easily remove and install fasteners
- Robust head design for maximum strength and durability
- Adjustable exhaust directs airflow away from work area
- Soft grip handle increased comfort and reduced vibration
- Suitable for motorcycle and small engine work
- At just 0.6kg, the small, light weight designed allows longer period of handling without hand fatigue



PART NO.	DRIVE SIZE (inches)	MAX TORQUE (ft.lbs)	FREE SPEED (rpm)
AT2610	3/8	54	600
AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
68	1/4" - 18	3/8	3
SOUND LEVEL dBa	PRESSURE	LENGTH (mm)	WEIGHT (kg)
89		159	0.6

3/8" Ratchet

AT7300

- Packing: 1
- 70 ft.lbs of torque output to remove stubborn fasteners
- 260 RPM's for fast removal / Installation of fasteners
- Large accessible reversing knob for easy mechanism direction changes
- · Robust head design for maximum strength and durability
- · Adjustable exhaust directs airflow away from work area
- Soft grip handle increased comfort and reduced vibration. Insulates against cold
- Ball bearing construction and high strength alloy steel gear system prolong tool's life



PART NO.	DRIVE SIZE	TORQUE RANGE	FREE SPEED
	(inches)	(N•m)	(rpm)
AT7300	3/8	7 - 95	260
AIR CONSUMPTION,	AIR INLET	RECOMMENDED	VIBRATION
FREE SPEED (I/min)	THREAD SIZE	HOSE SIZE (inches)	LEVEL (m/s²)
4.5 cfm	1/4" - 18 NPT	3/8	5
SOUND LEVEL	LENGTH	WEIGHT	VINYL BOOT
dBa PRESSURE	(mm)	(kg)	(included)
103	275	1.2	AT7300BOOT

3/8" Ratchet

AT700F

Packing: 1

- · Lightweight aluminum housing
- Rugged ball bearing mounted air motor coupled with precision planetary gear system
- Easy to use variable speed throttle plus adjustable air regulator



PART NO.	DRIVE SIZE (inches)	TORQUE RANGE (N•m)	FREE SPEED (rpm)
AT700F	3/8	6 - 61	150
AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
85	1/4" - 18 NPT	3/8	8.7
SOUND LEVEL dBa PRESSURE	LENGTH (mm)	WEIGHT (kg)	VINYL BOOT (included)
89	257	1.6	AT700E49A

1/2" Ratchet

AT7350



- 70 ft.lbs of torque output to remove stubborn fasteners
- 260 RPM's for fast removal / Installation of fasteners
- Large accessible reversing knob for easy mechanism direction changes
- Robust head design for maximum strength and durability
- Adjustable exhaust directs airflow away from work area
- Soft grip handle increased comfort and reduced vibration. Insulates against cold
- Construction and high strength alloy steel gear system



PART NO.	DRIVE SIZE (inches)	TORQUE RANGE (N•m)	FREE SPEED (rpm)
AT7350	1/2	7 - 95	260
AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
4.5 cfm	1/4" - 18 NPT	3/8	5
SOUND LEVEL dBa PRESSURE	LENGTH (mm)	WEIGHT (kg)	VINYL BOOT (included)
103	275	1.2	AT7350BOOT

1/2" Ratchet

AT705B



- 1/2" drive ratchet in a 3/8" drive body
- Delivers 50 ft. lb. of maximum torque
- Ball bearing mounted motor for longer tool life



PART NO.	DRIVE SIZE (inches)	TORQUE RANGE (N•m)	FREE SPEED (rpm)
AT705B	1/2	6 - 68	150
AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
85	1/4" - 18 NPT	3/8	8.7
SOUND LEVEL dBa PRESSURE	LENGTH (mm)	WEIGHT (kg)	VINYL BOOT (included)
89	273	1.14	AT700E49A

1/4" Die Grinder, Straight

AT1610



- 22,000 RPM free speed
- Lightweight, 1.4 lbs
- 1/2 HP thermally balanced air motor
- Built-in position speed control
- Ergonomic Alcryn® comfort grip handle

Safety style variable speed paddle trigger



PART NO.	COLLET SIZE (inches)	RATED POWER (kW)	FREE SPEED (rpm)
AT1610	1/4	0.375	22,000
AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
3.2 cfm	1/4" - 18 NPT	3/8	1.42
SOUND LEVEL dBa PRESSURE	LENGTH (mm)	WEIGHT (kg)	VINYL BOOT (included)
99	171	0.64	AT1610BOOT









1/4" Die Grinder, Standard

AT115

- Packing: 1
- Intended for most standard deburring operations
- Ergonomic handle grip increases comfort and control
- Safety lever throttle
- Built-in speed regulator
- Brass bearing cap and hose adaptor
- Rear diffused exhaust



1/4" Die Grinder, Standard

AT105

- Packing: 1
- Aluminum housing for long lasting durability
- Intended for most standard deburring operations
- High quality bearings improve productivity with less repair
- Rear exhaust directs air away from work area



PART NO.	COLLET SIZE (inches)	RATED POWER (kW)	FREE SPEED (rpm)
AT115	1/4	0.15	22,000
AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
113	1/4" - 18 NPT	3/8	< 2.5
SOUND LEVEL dBa PRESSURE		LENGTH (mm)	WEIGHT (kg)
102		165	0.61


PART NO.	COLLET SIZE (inches)	RATED POWER (kW)	FREE SPEED (rpm)
AT105	1/4	0.33	22,000
AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
113	1/4" - 18 NPT	3/8	< 2.5
SOUND LEVEL dBa PRESSURE		LENGTH (mm)	WEIGHT (kg)
102		165	0.61

1/4" Die Grinder, Right Angle

AT1620

Packing: 1

- 20,000 RPM free speed
- Compact design with 90° angle head
- Lightweight, only 1.7 lbs
- 1/2 HP thermally balanced air motor
- Built-in position speed control
- Ergonomic Alcryn® comfort grip handle





PART NO.	COLLET SIZE (inches)	RATED POWER (kW)	FREE SPEED (rpm)
AT1620	1/4	0.375	20,000
AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
3.2 cfm	1/4" - 18 NPT	3/8	1.55
SOUND LEVEL dBa PRESSURE	LENGTH (mm)	WEIGHT (kg)	VINYL BOOT (included)
101.4	175	0.81	AT1620BOOT

1/4" Die Grinder, 115° Angle

AT1630

- Packing: 1
- 20,000 RPM free speed
- Compact design with 115° angle head
- Lightweight, only 1.7 lbs
- Ergonomic Alcryn® comfort grip handle
- 1/2 HP thermally balanced air motor
- Built-in position speed control





PART NO.	COLLET SIZE	RATED POWER	FREE SPEED
	(inches)	(kW)	(rpm)
AT1630	1/4	0.375	20,000
AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET	RECOMMENDED	VIBRATION
	THREAD SIZE	HOSE SIZE (inches)	LEVEL (m/s²)
3.2 cfm	1/4" - 18 NPT	3/8	3.57
SOUND LEVEL	LENGTH	WEIGHT	VINYL BOOT
dBa PRESSURE	(mm)	(kg)	(included)
100.7	196	0.81	AT1630BOOT

1/4" Die Grinder, Mini, Right Angle

AT109



- · Aluminum housing for long lasting durability
- Compact mini design with 90° head for easy access
- High quality bearings improve productivity with less repair
- Rear exhaust directs air away from work area



PART NO.	COLLET SIZE inches (mm)	RATED POWER (kW)	FREE SPEED (rpm)
AT109	1/4	0.15	20,000
AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
59	1/4" - 18 NPT	3/8	2.5
SOUND LEVEL dBa PRESSURE		LENGTH (mm)	WEIGHT (kg)
93		140	0.50

Die Grinder Kit

AT109DGK



- Aluminum housing
- Compact mini design
- Rear exhaust

Kit contents in storage case:

AT109 Mini Angle Die Grinder

- 2" ROLOC® pad, 1 pc
- 2" Coarse discs, 2 pcs
- 2" Medium discs, 2 pcs
- 2" 24 grit discs, 2 pcs
- 2" 36 grit discs, 2 pcs
- 2" Crud discs, 2 pcs
- 3" ROLOC® pad, 1 pc
- 3" 50 grit discs, 2 pcs
- 3" 120 grit discs, 2 pcs
- 3" Crud discs, 2 pcs
- 1/4" Shank adaptor, 1 pc Spanner wrenches, 2 pcs



PART NO.	COLLET SIZE inches (mm)	RATED POWER (kW)	FREE SPEED (rpm)
AT109DGK	1/4	0.15	20,000
AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
59	1/4" - 18 NPT	3/8	2.5
SOUND LEVEL dBa PRESSURE		LENGTH (mm)	WEIGHT (kg)
93		140	0.50

1/4" Die Grinder, Mini, Right Angle

AT118



- Clean dies, rotors, backing plates and brake pad mounts
- Compact mini-design with 90° angled head for easy
- Ergonomic handle grip increases comfort and control
- Remove gasket material
- Grind dies and valve seats
- Dress welds and enlarge holes
- Safety lever throttle
- Built-in speed regulator
- Brass bearing cap and hose adaptor



PART NO.	COLLET SIZE (inches)	RATED POWER (kW)	FREE SPEED (rpm)
AT118	1/4	0.15	20,000
AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
113	1/4" - 18 NPT	3/8	2.5
SOUND LEVEL dBa PRESSURE		LENGTH (mm)	WEIGHT (kg)
93		140	0.50

1/4" Die Grinder, Mini, 115° Angle

AT119



- 115° offset head provides a more ergonomic grinding position
- Thread-on style disc provides a more compact head
- One 2" quick-change disc included so tool is ready for your abrasive pad



PART NO.	COLLET SIZE (inches)	RATED POWER (kW)	FREE SPEED (rpm)
AT119	1/4	0.15	20,000
AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
59	1/4" - 18 NPT	3/8	< 6.92
SOUND LEVEL dBa PRESSURE		LENGTH (mm)	WEIGHT (kg)
100		173	0.50









Die Grinder, Pencil

AT1070A

Packing: 1

- Twist-action variable speed control
- 5' long protected air hose
- Used with 1/8" shank grinding accessories rated higher than 54,000 RPM
- Ideal for tight spaces and easy cleaning of dies, rotors and brake pads



PART NO.	COLLET SIZE (inches)	FREE SPEED (rpm)	AIR CONSUMPTION, FREE SPEED (I/min)	
AT1070A	1/8	75,000	28	
AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)	SOUND LEVEL dBa PRESSURE	
1/4" - 18 NPT	3/8	2.0	72	
LENGTH (mm)		WEIGHT (kg)		
135			0.25	

4" & 5" Die Grinder, Angle

Packing: 1

- Excellent for weld preparation, rust removal, deburring and blending of steel, cast iron and aluminum

Compact, lightweight and high performance

- Rotatable protective guard
- Aluminum alloy housing
- Ergonomic side handle
- Rotary type start switch
- Front exhaust



PART NO.	PAD SIZE (inches)	(rpm)	AIR CONSUMPTION, FREE SPEED (I/min)	LENGTH (mm)
ATGD4	4	11,000	45	235
ATGD5	5	9,500	45	235
	AIR INLE	T WEIGHT	RECOMMENDED	DATED

PART NO.	AIR INLET THREAD SIZE (inches)	WEIGHT (kg)	HOSE SIZE (inches)	RATED POWER	
ATGD4	1/4	2.0	3/8	470 (W), 0.63 (HP)	
ATGD5	1/4	2.0	3/8	470 (W), 0.63 (HP)	

Die Grinder, Pencil, Right Angle

AT1070RA

Packing: 1

- Right angle lightweight pencil die grinder is ideal for getting in tight spaces
- Use for easy cleaning of dies, rotors, backing plates, brake pads, mounts plus many other applications
- Must be used with 1/8" shank grinding accessories rated higher than 70,000 RPM



PART NO.	COLLET SIZE (inches)	FREE SPEED (rpm)	AIR CONSUMPTION, FREE SPEED (I/min)	
AT1070RA	1/8	75,000	28	
AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)	SOUND LEVEL dBa PRESSURE	
1/4" - 18 NPT	3/8	2.0	72	
LENGTH (mm)		WEIGHT (kg)		
150			0.21	

7" Die Grinder, Angle

ATGD7

- Compact, lightweight and high performance
- 1.2 hp (895W) high performance motor
- Rotary type start switch with safety lock
- Rotatable protective guard
- Aluminum alloy housing
- Ergonomic L/R side handle
- Side exhaust
- Excellent for weld preparation, rust removal, deburring and blending of steel, cast iron and aluminum



PART NO.			AIR CONSUMPTION, FREE SPEED (I/min)	LENGTH (mm)
ATGD7	7	7,000	79	290
AIR INLET SIZE (ii		WEIGHT (kg)	RECOMMENDED HOSE SIZE (inches)	RATED POWER
1/	4	3.31	3/8	895 (W), 1.2 (HP)

2" Grinder, Angle

AT215

- Ideal for body shops, automobile, truck repair and confined areas
- Grease fitting in head enables gears to be greased for longer tool life
- Includes 6 2" wheels tool is ready for use providing convenience
- Moveable guard, up to 50° in either direction-fitting various applications
- Built in speed regulator allows user to set desired speed
- Rear exhaust with rotating deflector
- Comfort grip housing insulate from cold and vibration for less user fatigue
- Safety lever throttle prevents accidental start ups for increased safety



PART NO.	WHEELSIZE (inches)	RATED POWER (kW)	FREE SPEED (rpm)	AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE
AT215	2	0.37	15,000	85	1/4" - 18 NPT
RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)	SOUND LEVEL dBa PRESSURE	LENGTH (mm)	WEIGHT (kg)	GRINDING DISC (OPTIONAL)
3/8	< 2.86	73	188	0.82	AT215GWSET

3" Cut-off Tool

AT153



- Compact size is excellent for accessing areas with limited working space
- Heavy-duty bevel gears for tool longevity
- Indexing adjustable guard controls the direction of sparks



- Spindle lock eliminates the need for special wrenches for fast change of cutoff wheels
- Adjustable built-in regulator easily adjusts up to 17,000 RPM free speed

PART	PART NO.		RATED POWER (kW)	FREE SPEED (rpm)	AIR CONSUMPTION, FREE SPEED (I/min)	
AT	153	3	0.37	17,000	99.1	
	AIR INLET THREAD SIZE		MENDED E (inches)	VIBRATION LEVEL (m/s²)	SOUND LEVEL dBa PRESSURE	
1/4" - 1	8 NPT	3,	/8	< 2.86	85	
LENGTH WEIGHT (mm) (kg)		3" CUTTER WI 1/16" thick, 36 grit 1/32" th		TER WHEELS (OP 1/32" thick, 54 grit	•	
185	1.5	AT150)-20A	AT150C28A	AT150C29A	

3" Cut-off Tool, Reversible

AT157R



- Ideal for use in body shops and other general automotive applications
- Recommended for cutting mufflers, hose clamps, bolts and sheet metal



- Uses wheels only rated above 18,000 RPM
- Spark direction control
- Safety throttle lever
- Rear diffused exhaust
- Comfort grip handle

PART NO.	WHEEL RATED SIZE POWER (inches) (kW)		FREE SPEED (rpm)	AIR CONSUMPTION, FREE SPEED (I/min)	
AT157R	3	0.33	20,000	99	
AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)		VIBRATION LEVEL (m/s²)	SOUND LEVEL dBa PRESSURE	
1/4" - 18 NPT	3,	/8	< 3.8	100	
LENGTH (mm)	WEIGHT (kg)		3" CUTTER WH	HEELS (OPTIONAL) 54 grit	
185	0.8	86	AT150-20A	AT150-29A	









Reciprocating Saw, Micro

AT194A

- Packing: 1
- Compact size for easy access in tight quarters
- Low vibration level and lightweight yields reduced hand fatigue
- Performs straight or scroll cuts on metal or plastic
- Adjustable blade guard to control cutting depth



- Flexible, guarded hose extension helps prevent damage to finished surface and aids in maneuverability
- Blade change wrenches and guard adjustment
- Safety trigger prevent accidental start

PART NO.	FREE SPEED (rpm)	AIR CONSUMF FREE SPEI (I/min)		AIR II THREA		
AT194A	8,250	20		1/4" - 1	8 NPT	
RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)	SOUND LEV		LENGTH (mm)	WEIGHT (kg)	
3/8	< 6.6	87		175	0.45	
BI-METAL BLADE, 5PK, 3 3/34" LONG 18TPI 24TPI 32TPI						
AT190-39A	ΙA	AT190-40A		AT190-41	A	

Reciprocating Saw

AT192A

- Packing: 1
- Adjustable blade guard to control cutting depth
- Comfort grip housing for greater control



- Performs straight or scroll cuts in metal and plastic
- Safety lever throttle
- Optional blades in 4" lengths are also available

PART NO.	FREE SPEED (rpm)	AIR CONSUME FREE SPE (I/min)		AIR II THREA	
AT192A	11,000	28		1/4" - 1	8 NPT
RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)	SOUND LEVEL dBa PRESSURE		LENGTH (mm)	WEIGHT (kg)
3/8	10.1	94		235	0.80
BI-METAL BLADE, 5PK, 3 3/34" LONG 18TPI 24TPI 32TPI					
AT190-39A AT		190-40A		AT190-41	A

Air Powered Shears

AT195



- Trims, outlines and shears
- Replaceable brass filter screen
- Built-in speed regulator



PART NO.	AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)
AT195	113	1/4" - 18 NPT	3/8
VIBRATION LEVEL (m/s²)	SOUND LEVEL dBa PRESSURE	LENGTH (mm)	WEIGHT (kg)
< 2.5	99.6	254	1.3

Nibbler

AT180C

- Packing: 1
- Cuts mild steel sheet up to 16 gauge, 0.62" thick
- Anvil is adjustable for forward, backward and left or right cutting, enabling the nibbler to make sheet metal cuts of any configuration
- Readily cuts most non-ferrous materials including aluminum, brass, formica, laminates, fiberglass and



PART NO.	FREE SPEED (rpm)		AIR CONSUMPTION, FREE SPEED (I/min)
AT180C	3,500		113
AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)		VIBRATION LEVEL (m/s²)
1/4" - 18 NPT	3/	8	4.3
SOUND LEVEL dBa PRESSURE	LENGTH WEIGHT (mm) (kg)		STANDARD PUNCH
97	193	0.88	AT180B-10

In Line Sander, Heavy Duty

AT475A

Packing: 1

Packing: 5


- 5/8" stroke
- Minimal vibration
- For fast material removal
- Pad has positive locking clamps



PART NO.	FREE SPEED (rpm)	AIR CONSUMPTION, FREE SPEED I/min)		AIR INLET THREAD SIZE
AT475A	1,800	65		1/4" - 18 NPT
RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)		SOUND LEVEL dBa PRESSURE	
3/8	14	1.9		87
LENGTH (mm)	WEIGHT (kg)	STANDAF PAD		RD
406	3.09	AT475A-2		29

Belt Sander

AT615



Simple belt tracking adjustment knob to adjust belt slack Powerful 0.5 hp for long lasting

performance Belt guard detaches for quick

abrasive changes

Ergonomic 7° off set handle and lightweight design minimizes operator fatigue



Packing: 1

PART NO.	RATED POWER (kW)	FREE (rp	
AT615	0.3	20,	000
AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE	RECOMMENDED HOSE SIZE (inches)	
119	1/4" - 18 NPT	3/8	
VIBRATION LEVEL (m/s²)	SOUND LEVEL dBa PRESSURE	LENGTH (mm)	WEIGHT (kg)
1.36	95	359	1.20

Belts



PART NO.	DESCRIPTION	SIZE (inches)	GRIT
ATBA381860		³ /8 x 18	60 Grit
ATBA381880		3/8 x 18	80 Grit
ATBA3818120		³ /8 x 18	120 Grit
ATBA121860		1/2 x 18	60 Grit
ATBA121880	Coated Abrasive	1/2 x 18	80 Grit
ATBA1218120		1/2 x 18	120 Grit
ATBA341860		3/4 x 18	60 Grit
ATBA341880		3/4 x 18	80 Grit
ATBA3418120		3/4 x 18	120 Grit
ATBB121850		1/2 x 18	50 Grit
ATBB1218100		1/2 x 18	100 Grit
ATBB1218240		1/2 x 18	240 Grit
ATBB341850		3/4 x 18	50 Grit
ATBB3418100	Nonwoven Abrasive	3/4 x 18	100 Grit
ATBB3418240		3/4 x 18	240 Grit
ATBB381850		³ /8 x 18	50 Grit
ATBB3818100		3/8 x 18	100 Grit
ATBB3818240	1	3/8 x 18	240 Grit









Packing: 1

6" Sander, Dual Action

AT411A

 For fine sanding operations and swirl free finishing

- Comfort handle helps reduce fatigue
- Converts from rotary to random orbit action by sliding drive plate
 Built-in thumb wheel
- speed regulator



Packing: 1

PART NO.	PAD SIZE	RATED POWER	FREE SPEED
	(inches)	(kW)	(rpm)
AT411A	6	0.37	10,000
SPINDLE	AIR CONSUMPTION,	AIR INLET	RECOMMENDED
THREAD	FREE SPEED	THREAD	HOSE SIZE
(inches)	(I/min)	SIZE	(inches)
5/16 - 18 UNC	142	1/4" - 18 NPT	3/8
VIBRATION	SOUND LEVEL	LENGTH WEIGHT	STANDARD
LEVEL (m/s²)	dBa PRESSURE	(mm) (kg)	PAD
3.7	79	203 2.14	AT411A-1

8" Sander, Dual Action

AT408

Comfort handle helps reduce fatigue

Rear diffused exhaust

Built-in adjustable speed regulator

Variable speed control

Removable brass filter screens out debris



PART NO.	PAD SIZE (inches)	RATED POWER (kW)				FREE SPEED (rpm)
AT408	8	0.3	37	850		
SPINDLE THREAD (inches)	AIR CONSUMPTION, FREE SPEED (I/min)	AIR INLET THREAD SIZE		RECOMMENDED HOSE SIZE (inches)		
5/16 - 24	142	1/4" - 18 NPT		3/8		
VIBRATION LEVEL (m/s²)	SOUND LEVEL dBa PRESSURE	LENGTH (mm)	WEIGHT (kg)	STANDARD PAD		
3.7	87	281	2.18	AT408-2		

5" Sander Reversible, High Speed

AT425R

 Use in body shops and other general automotive applications Includes 3", 4" and 5"

- backing discs
- One hand forward / reverse lever
- Comfort grip handle
- Built-in speed regulator
- 1 year limited warranty on tool
- No warranty on consumables
- CE-DE, ES, FR, IT, GB



Packing: 1

PART NO.	PAD (inc		RATED POV	WER	FREE SPEED (rpm))
AT425R	į	5	0.33		13,000	
SPINDLE THREAD (inches)	AIR CONS FREE (I/n	SPEED	AIR INLET THREAD SIZE		RECOMMENDI HOSE SIZE (inches)	ED
7/16 - 20 UNC	12	22	1/4" - 18 NPT		3/8	
VIBRATION LEVEL (m/s²)	SOUND LEVEL dBa PRESSURE		LENGTH (mm)		WEIGHT (kg)	
< 0.8	9	3	135		1.28	
STANDARI) PAD	REP	LACEMENT F	PADS	(OPTIONAL)	
5"		;	3"		4"	
AT425R-	AT425R-24		AT425R-22		AT425R-23	

Polisher, Heavy Duty, Vertical

AT460BP

Packing: 1


Removable side handle



PART NO.	PAD S			RATED POWER (kW)	FREE SPEED (rpm)	SPINDLE THREAD (inches)
AT460BP	7	0.49		0.49	4,500	5/8 -11
AIR CONSUM FREE SPE (I/min)	ED	AIR INLET THREAD SIZE			RECOMMENDED HOSE SIZE (inches)	VIBRATION LEVEL (m/s²)
136		1/4	ļ" - 1	18 NPT	3/8	< 2.5
SOUND LEVEL dBa PRESSURE				STANDARD PAD	SPANNER WRENCH (opt.)	
83	185 2.27		AT450-46H	AT450-50		

5" Orbital Air Sanders

ATSDA5



- Vacuum type to keep dust-free environment and improve operator ease of usage
- High speed dual-action motion
- Small orbiting diameter of 5mm produces swirl-free finishes
- Low vibration level and low noise level for comfort prolong use
- ATSDA5KIT is the kit part no.



PART NO.	PAD SIZE (inches)		RATED POWER (kw)	FREE SPEED (rpm)	AIR INLET THREAD SIZE
ATSDA5	5		0.33	1,200	1/4" - 18 NPT
HOSE SIZ	RECOMMEDNED HOSE SIZE (inches)		ND LEVEL PRESSURE	LENGTH (mm)	WEIGHT (kg)
3/8		87	193	1	

Packing: 1

Packing: 1

Packing: 1

6" Orbital Air Sanders

ATSDA6

• Palm sized for one hand operation

 Vacuum type to keep dust-free environment and improve operator ease of usage

- High speed dual-action motion
- Small orbiting diameter of 6mm produces swirl-free finishes
- Low vibration level and low noise level for comfort prolong use
- ATSDA6KIT is the kit part no.



PART NO.	PAD SIZE (inches)	RATED POWER (kw)	FREE SPEED (rpm)	AIR INLET THREAD SIZE
ATSDA6	6	0.33	1,200	1/4" - 18 NPT
RECOMMED HOSE SIZ (inches)	ZE dBa	IND LEVEL PRESSURE	LENGTH (mm)	WEIGHT (kg)
3/8		90	203	1

3" Surface Prep Tool, Micro

AT401MCA

- Ideal for removing paint, rust, gasket material, grinding welds or brake rotors in confined areas
- Accepts 2" and 3" ROLOC® pads
- Built-in speed regulator offers easy one hand operation



Surface Prep Kit, Micro, 13pcs

AT401MCKA

Storage case packaging, Kit includes:

AT401MCA micro surface prep tool

2" ROLOC® pad, 1 pc 3" ROLOC® pad, 1 pc

2" 40 grit pads, 5 pcs

3" 80 grit pads, 5 pcs






PART NO.	PAD SIZE (inches)	POWER		SPEED pm)	SPINDLE THREAD (inches)
AT401MCA	3	0.19	15	,000	1/4 - 20 UNF
AIR CONSUM FREE SPE (I/min)	ED T	AIR INLET THREAD SIZE	HOS	IMENDED E SIZE ches)	VIBRATION LEVEL (m/s²)
59		1/4" - 18 NPT	;	3/8	< 2.5
SOUND LEVEL dBa PRESSURE		LENGTH (mm)	WEIGHT (kg)		
84		119			0.44













Packing: 1

Packing: 1

Packing: 1

3" Sander, Dual Action, Micro

AT402MCA

Delivers fine swirl free results when sanding, feather edging etc.

Durable single piece polymer composite housing on sander stands up to rugged use, and resists most shop chemicals



3" Sander Kit, Micro, Dual Action, 72pcs

AT402MCKA

• Storage case packaging, Kit includes:

AT402MCA micro sander

3" Hook-It® pad, 1 pc 3" 180 grit pads, 25 pcs

3" 200 grit pads, 25 pcs

3" 320 grit pads, 10 pcs

3" 800 grit pads, 25 pcs



PART NO.	PAD Si (inche	POWER		FREE SPEED (rpm)		SPINDLE THREAD (inches)
AT402MCA	3		0.19	15	5,000	5/16 - 24 UNF
AIR CONSUM FREE SPE (I/min)	ED	N, AIR INLET THREAD SIZE		RECOMMENDED HOSE SIZE (inches)		VIBRATION LEVEL (m/s²)
59		1/2	1/4" - 18 NPT		3/8	< 2.5
SOUND LEVEL dBa PRESSURE			LENGTH (mm)		WEIGHT (kg)	
84			133			0.50

3" Polisher, Micro

AT403MCA

- Ideal for polishing motorcycles, bumpers, wheels and more
- Durable single piece polymer composite housing on sander stands up to rugged use, and resists most shop chemicals



3"	Polisher	Kit,	Micro,	5pcs
----	-----------------	------	--------	------

AT403MCKA

Storage case packaging, Kit includes:

AT403MCA micro polisher

- 3" Hook-It® pad, 1 pc
- 3" wool pad, 1 pc
- 3" foam pad, 2 pcs





PART NO.	PAD SIZE (inches)		RATED POWER (kW)		SPEED pm)	SPINDLE THREAD (inches)
AT403MCA	3	0.19		6	,000	5/16 - 20 UNF
	CONSUMPTION, FREE SPEED (I/min) AIR INLET THREAD SIZE				MMENDED SE SIZE ches)	VIBRATION LEVEL (m/s²)
62		1/4" -	18 NPT	NPT		< 2.5
	SOUND LEVEL dBa PRESSURE		LENGTH (mm)		W	/EIGHT (kg)
86		143				0.60


Pistol Air Screwdriver 2500rpm

ATSD25

- Pistol type screwdriver
- **Cushion Clutch**
- Reversible one-hand operation
- Composite molded housing, light weight
- Adjustable torque
- Comfortable Ergo-grip handle
- Trigger with feathering, variable speed
- Low roll back reaction



PART NO.	SCREW CAPAG (mr	CITY	MAX. TORQUE (Nm)	FREE SPEED (rpm)	AIR CONSUMPTION, FREE SPEED (I/min)
ATSD25	6		17	2,500	283
LENGTH (mm)			IR INLET HREAD SIZE	NET WEIGHT (kg)	SOUND LEVEL dBa PRESSURE
212			1/4	1.08	88



Straight Air Screwdriver 1450rpm

ATSD15

Packing: 1

- Straight type screwdriver
- Cushion Clutch
- Adjustable torque
- Reversible button with lock on feature and throttle lever start





PART NO.	SCREW SIZE CAPACITY (mm)	MAX.TORQUE (Nm)
ATSD15	5	5
FREE SPEED (rpm)	AIR CONSUMPTION, FREE SPEED (I/min)	LENGTH (mm)
1,450	170	279
AIR INLET THREAD SIZE	WEIGHT (kg)	SOUND LEVEL dBa PRESSURE
1/4	0.97	75

Straight Air Screwdriver 1900rpm

ATSD19

- Packing: 1
- Straight type screwdriver
- Cushion Clutch
- Adjustable torque
- Reversible & lever start



PART NO.	SCREW SIZE CAPACITY (mm)	MAX.TORQUE (Nm)
ATSD19	5	5
FREE SPEED (rpm)	AIR CONSUMPTION, FREE SPEED (I/min)	LENGTH (mm)
1,900	127	229
AIR INLET THREAD SIZE	WEIGHT (kg)	SOUND LEVEL dBa PRESSURE
1/4	1.01	85











Pocket Blow Gun

BLPPBG14

- Packing: 1
- Light weight and easy operation
- Portable pencil style design
- It could be the inflator with rubber tip
- Max input pressure: 150PSI
- Max output pressure: 90PSI
- Plug type: ARO, TRU-FLATE, Universal 1/4" pipe threading
- Air flow: 450 L/m



Blow Gun

YA1050B

Packing: 1

- Pistol grip style with front full size trigger
- Infinitely variable flow
- 10 1/4" long



Blow Gun

YA105020

Packing: 1

- 20" bent nozzle
- Trigger provides variable air flow control
- Lightweight body with ergonomically designed grip provides comfort and control
- Insulated handle prevents cold hands
- Venturi tip directs air sideways if tip end is obstructed
- Reinforced 1/4"-18NPT inlet
- Maximum air pressure: 232 PSI (16 BAR)



Blow Gun

JT13B

Packing: 1

- Tapered, rubber tip for a leak proof connection between gun and fluid line
- Vinyl coated control lever

Hanging hook for storage

4 1/2" long

Blow Gun

YA1055B

Packing: 1

- Each gun includes hanging hook and paddle-type air control lever
- Variable flow trigger offers precise air flow control
- Six-outlet "star tip" delivers an even distribution of air
- 4" Full Flow tube and ergonomic handle for increased comfort
- Triggers regulate airflow from partial to full line pressure
- Maximum Working Pressure: 175 PSI (12 bar)
- Complies with OSHA safety standards
- Valve has no cutoff and no restrictions
- Each tip is side vented



Regulator, Combination Air Line

AHRB200



PART NO.	INLET/OUTLET PORT SIZE	ADJUSTABLE PRESSURE RANGE
AHRB200	1/2 " NPT (F)	5 - 120 psig (0.5 - 8.5 kgf/cm²)
MAXIMUM SERVICE PRESSURE	OIL CAPACITY	OPERATING TEMPERATURE RANGE PRESSURE
140 psig (9.9 kgf/cm²)	80ml	41° - 140° F (5° - 60° C)

Carbide Burr Set, 8pcs

BLPCBS8

- Nylon pouch with logo printing packaging
- Made of tungsten carbide K25 material
- Most popular burr style for ferrous applications
- Flutes ground in both the left and right hand directions
- Better operator control and rapid stock removal in harder materials
- Designed for surface milling and contouring in brass, copper, cast iron, carbon steels, stainless steel, steel elements and titanium



CONTENTS	BURR DESCRIPTION	SHANK SIZE (inches)	FLUTE LENGTH (inches)	HEAD DIAMETER (inches)
CBC-1	Cylindrical		5/8	1/4
CBCR-2	Cylindrical with radius end	1/4	3/4	3/8
CBB-3	Ball shaped	1/4	1/4	5/16
CBO-4	Oval		7/8	1/2

CONTENTS	BURR DESCRIPTION	SHANK SIZE (inches)	FLUTE LENGTH (inches)	HEAD DIAMETER (inches)
CBTR-5	Tree with radius end		1	1/2
CBTP-6	Tree with pointed end	1/4	3/4	3/8
CBAT-7	14° included angle taper	'/4	11/8	1/2
CBC-8	Cone shaped		7/8	1/2

Grinding Wheel Set

ETA125A

Packing: 1

- Use with ET1350/ET1360
- Maximum rating of 12,000 RPM

Pack of 5 discs

Cut Off Wheel

AT415CWMP

- Packing: 1
- Use for metal notching and bolt cutting
- Use on 4 1/2" grinders with 5/8" x 11" thread arbor
- Maximum rating of 13,300 rpm

Pack of 5 discs

Grinding Wheel

AT415T27MP

- Packing: 1
- Use for rough grinding applications
- Use on 4 1/2" grinders with 5/8" x 11" thread arbor
- Maximum rating of 13,300 rpm

Pack of 5 discs



Flap Discs



PART NO.	DIAMETER (inches)	TYPE	GRIT	QUANTITY TO PACK
AC2Z40T27MP	2	27	40	10
AC2Z60T27MP	2	27	60	10
AC2Z80T27MP	2	27	80	10
AC4Z60T27MP	4	27	60	10









Flap Wheels

- Applications include cleaning, edge blending and smoothing metal, plastic or wood
- 3" aluminum oxide flap wheel is designed to provide fast cutting action
- 1/4" stem on solid hub permits a higher RPM rating and increased productivity
- Use on electric and pneumatic drills



PART NO.	DIAMETER (inches)	GRIT	QUANTITY TO PACK	
AC3160FWMP	3	60	10	
AC3180FWMP	3	80	10	
AC31120FWMP	3	120	10	

Wire Wheel, Crimped, 3"

AC616

- Packing: 1
- A great general purpose cleaner
- Features individual crimped filaments that support each other while being flexible
- General applications include deburring, weld cleaning, rust and paint removal
- Use on electric and pneumatic drills
- 0.0118 CWS-1/4



PART NO.	BRUSH	SHANK SIZE	WIRE	MAXIMUM
	DIAMETER	ARBOR SIZE	DIAMETER	RATED
	(inches)	(inches)	(inches)	(rpm)
AC616	3	1/4	0.118	20,000

Wire Wheel, Knotted

- Use for heavy duty cleaning
- Ideal for prewelding prep and weld cleaning



PART NO.	BRUSH DIAMETER (inches)	SHANK SIZE ARBOR SIZE (inches)	WIRE DIAMETER (inches)	MAXIMUM RATED (rpm)
AC420A	4	5/8 x 11	0.020	20,000
AC421A	4	M10 x 1.25	0.020	20,000

End Brush

Packing: 1

- Features individual crimped filaments that support each other while being flexible
- Ideal for cleaning right angles



PART NO.	BRUSH DIAMETER (inches)	SHANK SIZE ARBOR SIZE (inches)	WIRE DIAMETER (inches)	MAXIMUM RATED (rpm)
 AC10302	1/2	1/4	0.014	25,000
AC10306	3/4	1/4	0.014	22,000

Wire Brush

Packing: 1

- Features individual crimped filaments that support each other while being flexible
- Use for medium duty general purpose cleaning



PART NO.	BRUSH DIAMETER (inches)	SHANK SIZE ARBOR SIZE (inches)	WIRE DIAMETER (inches)	MAXIMUM RATED (rpm)
AC17D	1	1/4	0.006	20,000
AC243	3	5/8 - 11	0.014	14,000

Wool Velcro Pad

ABU10-050

- 8" x 25" Wool Velcro Pad
- Ideal for cutting, buffing, and removal of scratches and paint imperfections
- 1 1/2" wool pile last longer than standard wool pads
- Washable for easy clean up
- Use for base and clear coats, acrylic, enamel, lacquer, urethane, fiberglass, plastics and other applications



Air Hoses

AIRHOSE35

- Packing: 1
- Extremely lightweight for easy maneuverability
- Reinforced construction eliminates layer separation resulting from expansion and contraction during pulsating operations
- More abrasion resistant than PVC and rubber hoses
- · Easy to wrap and store even in subzero weather



- UV stabilized for longer outdoor life
- Strain relief features a tight bending radius to virtually eliminate hose kinking
- Reusable fittings and strain reliefs for longer life

Step Drill Set, 3pcs

YAS203A





PART NO.	CONTENT	HOLE SIZES PER BIT	INCREMENTS (inches)	LENGTH (inches)	SHANK SIZE (inches)	SIZE RANGE (inches)
	YA261A	13	1/32	3 1/4	1/4	1/8 - 1/2
YAS203A	YA262A	6	1/16	3 3/8	1/4	3/16 - 1/2
	YA263A	9	1/16	2 5/8	3/8	1/4 - 3/4

Cobalt Drill Bit Set, 21pcs

(1/16" to 3/8") in metal drill bit

DBBPC21

index



• DBBPC1/16 thru DBBPC3/8

• DBBP1/16 thru DBBP3/8 (1/16" to 3/8") in metal drill bit index

HSS Drill Bit Set, 21pcs

Packing: 1

DBBP21





Titanium Coated Drill Bit Set, 13pcs

DBBPT13



• DBBPT1/16 thru DBBPT1/4 (1/16" to 1/4") in metal drill bit index













Packing: 1

Air Line Couplers & Adaptors

• All adaptors are plated steel to improve durability

PART NO.	DESCRIPTION	BODY SIZE (inches)	STYLE	THREAD SIZE (inches)	
AHC21PD*	Quick Coupler Female	1/4	Rigid Mounting	1/4 - 18 NPT	
AHC21PMD	Quick Coupler Male				
AHC21D	Quick Coupler Female	1/4	Industrial	1/4 - 18 NPT	
AHC21MD	Adaptor Male	1/4	Interchange	1/4 - 10 NPT	
AHC21FD	Adaptor Female				
AHC23PMD	Quick Coupler Male				
AHC23D	Quick Coupler Female	1/4	ARO®	1/4 - 18 NPT	
AHC23MD	Adaptor Male	1/4	ANO	1/4 - 16 NPT	
AHC23FD	Adaptor Female				
AHC24D	Quick Coupler Female				
AHC24MD	Adaptor Male	1/4	Tru-Flate®	1/4 - 18 NPT	
AHC24FD	Adaptor Female	1			9
AHC26D	Quick Coupler Female				4
AHC26MD	Adaptor Male	1/4	Lincoln	1/4 - 18 NPT	
AHC26FD	Adaptor Female				
AHC22E	Quick Coupler Female				
AHC22MD	Adaptor Male	3/8	Industrial Interchange	1/4 - 18 NPT	1
AHC22FD	Adaptor Female				
AHC28D	Quick Coupler Female				
AHC28MD	Adaptor Male	3/8	Industrial Interchange	3/8 - 18 NPT	
AHC28FD	Adaptor Female				
AHC25D	Quick Coupler Female	0/-	T	2/2 42 197	
AHC25MD	Adaptor Male	3/8	Tru-Flate®	3/8 - 18 NPT	178
AHC27D	Quick Coupler Female				
AHC27MD	Adaptor Male	1/2	Industrial Interchange	1/2 - 18 NPT	
AHC27FD	Adaptor Female	1			Α
AHCC91C	Quick Coupler Male				
AHCC90C	Quick Coupler Female	1/4	Hi-Flow HVLP	1/4 - 18 NPT	
AHCCP90C	Adaptor Female	1			Bish
AHCCP97C	Adaptor Male	1/4	Hi-Flow	1/4 - 18 NPT	AHCCP9

^{*} Conforms to Mil Spec MIL-C-4109F





Advanced Lighting, Imaging & Measuring





Measuring

Feeler Gauges, 13pcs

FB310B Packing: 1

Feeler Gauges, 25pcs

FB325A Packing: 1

Feeler Gauges, 35pcs

FB335

Packing: 1







PART NO.	INCREMENTS	BLADE SIZE	STYLE	BLADE DIMENSIONS (inches)	NO. OF BLADES	DESCRIPTION
FB310B	-	.001", .0015", .002" thru .008", .010", .012", .013", .015"	General Use	1/2 x 3	13	Double stamped with U.S. and metric sizes
FB325A	.001"	.0015", .002" thru .025"	General Use	1/2 x 3	25	Double stamped with U.S. and metric sizes
FB335	.001"	.0015", .002" thru .035"	General Use	1/2 x 3	35	Swedish feeler blade steel

Feeler Gauges, 18pcs

Packing: 1 FB316B

Feeler Gauges, 20pcs

Packing: 1 FBM320

Feeler Gauges, 25pcs

Packing: 1 FBL325A







PART NO.	INCREMENTS	BLADE SIZE	STYLE	BLADE DIMENSIONS (inches)	NO. OF BLADES	DESCRIPTION
FB316B	.001"	.010", .012", .013", .015" thru .022", .024" thru .026", .028", .030", .032", .035"	Short Blade Ignition / Spark Plug Gauge	1/4 x 1 3/4	18	Short Blade, Ignition / Spark Plug Gauge Set
FBM320	.05mm	.05 thru 1mm	Metric General Use	1/2 x 3	20	Metric Feeler Gauge Set
FBL325A	.001"	.0015", .002" thru .021", .025", .027", .030", .040"	Long Blade General Use	1/2 x 12	25	Long blade, double stamped with U.S. and metric sizes



10



Feeler Gauges, 12pcs

Feeler Gauges, 25pcs

Feeler Gauges, 26pcs

FB308D



FB300A

Packing: 1

FB326B









PART NO.	INCREMENTS	BLADE SIZE	STYLE	BLADE DIMENSIONS (INCHES)	NO. OF BLADES	DESCRIPTION
FB308D	.001"	.008"010", .011"013", .013"015", .014"016", .015"017", .017"019", .018"020", .020"022", .023"025", .025"027", .026"028", .028"030"	Step Blade	1/2 x 3	12	Step Feeler Gauge Set, Bent handle to clear manifolds, double stamped with U.S. / Metric sizes. Blades are mounted on FBFT7 holder
FB300A	.001"	.006" thru .030"	Bent Blade	1/2 x 3	25	Feeler Gauge Set
FB326B	.001"	.008", .010", .012", .013", .015", .017", .018", .020", .022", .024" thru .026", .028", .030", .032", .035"	Combination Feeler / Ignition Gauge	1/2 x 3	26	Double stamped with U.S. and metric sizes

Feeler Gauges, 2pcs

FB328A Packing: 1

Feeler Gauges, 2pcs

FBM322 Packing: 1

Feeler Gauges, 22pcs

FB322 Packing: 1







PART NO.	INCREMENTS	BLADE DIMENSIONS (inches)	BLADE SIZE	NO. OF BLADES	DESCRIPTION
FB328A	-	1/2 x 3	.011"013", .013"015"	2	For valve adjustment on GM 8.2L engines, double stamped with U.S. and metric sizes
FBM322	-	1/2 x 3	.2030mm, .4050mm	2	i.e. 10 3/4" long bent handle
FB322	.001"	1/2 x 3 3/8	.004"006" thru .025"027"	22	"Go-No Go" blades with 2 sizes each



Measuring

Feeler Gauges, 14pcs

FB307D

Packing: 1

Packing: 1

- Bent blade cummins diesel, blade ends are bent at 90° angle
- Blades are secured on FB307C1 ring



PART NO.	INCREMENTS	BLADE DIMENSIONS (inches)	BLADE SIZE	NO. OF BLADES
FB307D	.001"	1/2 x 4 1/2	.008", .011" thru .014", .016" thru .018", .020", .023" thru .025", .027", .029"	14

Measuring Tapes

- Rubberized coating for better grip
- Tape auto-lock when extended
- Nylon coated tape



PART NO.	LENGTH (meter)
BMPLM3	3
BMPLM5	5
BMPLM8	8

Dividers, 6"



Spring type divider has virtually no torsion or side play

Feeler Gauges, 20pcs

BLPFG20A



- Material: C45 Shiny surface
- Blade size: 0.05mm-1mm



Long Tape, Steel, 100ft

TPM100

Packing: 1

Packing: 1

- Includes inch and metric scale
- Quick rewind design for ease of use



- Rewinding lever conveniently stored in housing
- Non-slip grip provides confidence and comfort

Angle Locator

YA328A

- Precise, accurate tool to determine angle measurements
- Ideal for checking drive shaft angle
- Red degree indicator located behind numbers for exact reading of graduations



- English and metric scales molded into base of tool in 1/8" and DM
- Large 1 7/8" x 7/8" magnet inserted in base for secure retention











Digital Caliper

MCAL6A

- Packing: 1
- Gauge is 0" to 6" (0 to 150mm) in 0.0005" (0.01mm) resolutions
- Large LCD display
- Hardened stainless steel frame



- Use for inside, outside, depth and step measurements
- Inch/metric conversion with one button
- Conform to standard : GB1214

Magnetic Holder

CM6416

Packing: 1

- Magnet has "on/off" switch
- Base is 2 3/8" x 1 7/8" x 2 1/2"



- Post is 7" x 15/16"
- Rod is 6" x 25/64"
- Will grip flat or curved metal surfaces

Combination Measuring Set

SQUARECOMB12

Packing: 1

Storage case packaging



PART NO.	CONTENTS
	SQUAREB180 Square Protractor Head
SQUARECOMB12	RULER12BSQ Steel Ruler, 12"
	SQUAREB90 Square Sliding Head
	SQUAREB45 Square Sliding Head 45°

Digital Caliper

MCAL12A

Packing: 1

- Essential tool for working on larger vehicles, trucks, tractors and earth moving equipment
- Range is 0" to 12" (0 to 305mm) in 0.0005" (0.01mm) resolutions
- Use for inside, outside, depth and step measurements



- Inch/metric conversion with one button
- Large LCD display with floating zero set
- Locking nut and thumb roll for smooth action
- Conform to standard : GB1214

Dial Type Caliper

PMF147A

Packing: 1

 Gauge is 0" to 6" in high (0.001" increments) and metric (0.1mm increments)



- Includes storage case
- Conform to standard : GB1214

Machinist's Measuring Set

SQUAREB12

Packing: 1

Storage case packaging



PART NO.	CONTENTS
SQUAREB12	SQUAREB90 Square Sliding Head
3QUANEB12	RULER12BSQ Steel Ruler, 12"



Measuring

Digital Micrometers



PART NO.	RANGE (mm)	INCREMENTS (mm)	
MIC1MB	0-25	0.01	
MIC2MB	25-50	0.01	
МІСЗМВ	50-75	0.01	
MIC4MB	75-100	0.01	
MIC5MB	100-125	0.01	
MIC103MB	Digital Metric Micrometer Set, 3pcs MIC1MB, MIC2MB, MIC3MB in fitted case with standards		

Digital Micrometers



PART NO.	RANGE (inches)	INCREMENTS (inches)
MIC1B	0-1	0.0001
MIC2B	1-2	0.0001
МІС3В	2-3	0.0001
MIC4B	3-4	0.0001
MIC5B	4-5	0.0001
MIC103B Digital Micrometer Fractional Set, 3pcs MIC1B, MIC2B, MIC3B in fitted case with st		

Outside Micrometers



PART NO.	RANGE (inches)	INCREMENTS (inches)
MICB1B	0-1	0.0001
MICB2B	1-2	0.0001
МІСВ3В	2-3	0.0001
MICB4B	3-4	0.0001
MICB5B	4-5	0.0001
MICB103B SAE Set, 3pcs MICB1B, MICB2B, MICB3B in fitted case with standards		

Electronic Digital Micrometers

MICED1B



- Display reads to 0.00005" (0.001mm)
- Zero set for absolute and incremental measuring modes
- Auto shut-off after 10 minutes
- Insulated frame, hardened body, carbide tipped anvil, positive locking clamp and ratchet stop thimble



Inside Micrometer Set, 7pcs

MICINSIDE12



- Tubular design
- Range is 2" to 12" in .001" increments
- Includes inside micrometer head and a series of coil spring pressure contact rods



Depth Micrometer Set

DM6



- Measure depths of slots, counterbores, holes and keyways up to 6" in depth
- 4" satin chrome base for greater stability
- Graduated in .001" increments
- Includes fitted storage case

PART NO.	DESCRIPTION
DM61	4" rod
DM62	5" rod
DM63	6" rod
DM64	7" rod
DM65	8" rod
DM66	9" rod
DM67	Micrometer Head







Steel Rule, 15cm

BLPSR15

Packing: 1

Material: C45



Thermometer

ACT73A

Packing: 1

- Range 0° F to 220° F (-18° C to 105° C) in 2° increments
- Checks temperature of condenser, outside air, and cooling power



Dial Type Thermometer

ACT83A

Packing: 1

- Range 0° F to 220° F in 2° increments
- Stem should be immersed about 2" in liquids, 4" in gases

Storage case



Pocket Digital Thermometer

TEMP10

Packing: 1

- Measures liquid, air and surface temperatures via sturdy stainless steel probe
- Digital display for easy viewing
- Angle viewing head can be lifted and rotated 180° for a different viewing angle
- Convertible from Fahrenheit (F) to Centigrade (C) temperature ranges
- The -58° F to 300° F (-50° C to 150° C) temperature range enables use on a wide range of applications
- Tactile on/off button for easy operator use (auto off function extends battery life)
- Tactile data hold button holds the reading when the display cannot be seen
- Temperature range noted on bevel
- Plastic carrying sheath protects the user when carried in shirt pocket



Infrared Thermometer

RTEMPB3A

Packing: 1

- Temperature range of -58° to 932°F (-20°C to 500°C)
- Use for most automotive and industrial applications requiring an infrared thermometer
- Compact size of 5.88" x 3.62" x 1.38" (149.2 x 92.1 x 34.9mm)
- Laser targeting accuracy
- Enhanced backlit 4 digit LCD for easy viewing
- Automatic power-off after 10 seconds
- Nylon holster for transport and safe storage
- Safely monitor hot, hazardous, or hard to reach materials without contamination or damage to the surface
- Simply point at target, pull the trigger, and read the temperature on the large, backlit LCD display

Antifreeze Hydrometer

AF102

Packing: 1

- Degree of protection is indicated by direct reading-no temperature compensating scales are required
- Range of +32°F to -60°F
- Includes Celsius scale

Tests hot and cold solutions

Digital Tire Inflator

BLPDTPG175

Packing: 1


- Easy change chuck system
- 1 button operation
- Auto shut-off for increased battery life
- Displays KgF, BAR, PSI, KPA measurements
- Large face LCD digital read-out
- Unit covered with rubber sleeve for extra comfort and durability
- ON power Button, auto shut off in 90 seconds if not in use
- LCD backlight
- 2-position lever 1st position deflates, 2nd position in deflates
- With 21" hose

2 AAA batteries




Measuring


Dial Tire Gauge



Dial Tire Inflator / Gauge




Pressure Gauge



- Swiveling hose for easy gauge positioning
- Zinc body with heavy duty brass valves
- Easy to read sight glass featuring PSI and kPa readings

Pressure Gauge

TPGP120





Packing: 1

Tread Depth Gauge



Air Adjusting Valve, with Gauge

Designed for use with HVLP spray guns

Includes 160 PSI pressure gauge

BF555

Air Inlet: 1/4" M.P.T Air Outlet: 1/4" F.P.T.

(swivel nut)



Packing: 1

Brake Gauge Set

BTG8

- Color coded gauges provide instant feedback on brake pad/shoe condition
- Constructed from 20 gauge sheet metal with durable powder coat finish
- Pad/shoe condition is indicated with color by the respective testing gauge
- · Set includes 8 different testing blades of various colors and thickness

RED Indicates service required	YELLOW Indicates caution	GREEN Indicates an OK situation		
	Blade Thickness			
2mm (0.0787") 3mm (0.1181")	4mm (0.1575") 5mm (0.1969") 6mm (0.2362")	8mm (0.3150") 10mm (0.3937") 12mm (0.4724")		











Gauge Set

FBS5



PART NO.	CONTENTS		
	FB300A	Bent Blade Feeler Gauge	
	FB305A	Non-magnetic Feeler Gauge	
FBS5	FB325A	General Use Feeler Gauge	
1 533	GA461B	Spark Plug Gap Gauge	
	FB360B	Spark Plug Gap Gauge	
	FBS5-1	Kit Bag	

Digital Drum Gauge

DG530



- Measures automotive and heavy duty brake drums
- Pointed anvils and 4.25" long arms allow increased measurement accuracy and coverage
- Easy to read digital display with inch/metric conversion
- Selectable depth stops for easier use
- Range 6"-20.65"/150mm-515mm
- Graduations .0005"/.01mm



Rotor Micrometer

RM130



- Range of .30" to 1.3" in .0001" graduations
- 3.5" deep frame
- Pointed anvil for checking grooves
- Includes 1" checking standard and storage case



Brake Spring Tool

BT9



- Quickly and easily removes or replaces springs
- Allows mechanics to press spring into place with one simple motion, taking the place of the slide mechanism
- Includes two mechanisms to allow easy removal and replacement of springs on brakes
- Patent pending
 8 3/4" long

Brake Caliper Kit, 7pcs

YA8610B



- Set includes one tool and seven adaptors in a storage case
- Assists in replacement of brake pads on most 4-wheel disc brake cars
- Tool and adaptors position brake piston back into caliper to allow clearance for newer, thicker brake pads
- Designed for most Audi, Chrysler Corporation, Ford, GM, Honda, Jaguar, Mazda, Mini Cooper, Mitsubishi, Nissan, Saturn, Subaru, Toyota, Volkswagen and Volvo



Brake Caliper Press

BTCP1



- Easy left and right side use
- Works on both fixed and floating calipers
- Generates more than 1600 ft. lbs. of force to retract the toughest caliper pistons
- Single lever mechanism used to apply and release force for ease of operation and faster service
 Prevents damage to
- pistons, hubs or calipers
 Ensures parallel piston retraction on dual and quad piston calipers





MEASURING & INSPECTION TOOLS Lighting

Penlight, Black

BLPFL1LAP

- Packing: 1
- Lightweight portable LED penlight with metal clip
- 1 LED providing 25 lumens
- Lighting distance up to 18m
- Runtime: 12 hours on two AAA batteries



SPECIFICATION					
Lamp	1 LED	Battery Type	2xAA alkaline batteries included		
Luminous Flux	25lm	Size	12.9x1.6cm		
Lighting Distance	18m	Material	Aluminum + Metal Clip		
Runtime	12h	Weight	25g (without batteries)		

Penlight, Blue

ECFB200BL



- High intensity 3 watt LED, 100 lumen penlight
- 6.25" in length and 1/2" in diameter
- Includes pocket clip and protective rubber tip
- Extremely bright light output
- Uses (3) AAA alkaline batteries



Rechargeable LED Penlight, Blue

ECFPEN7HOB

- Packing: 1
- Lightweight portable LED penlight with pocket clip
- 7 LED provides up to 470 lumens
- Lithium battery run time up to 4 hours
- Additional spot light at bottom
- Comes with magnet
- Charger included



Aluminum Police Style Flashlight

ECF201A





- The flashlight body is aerospace grade extruded aluminum with heavy anodization
- Average run time is 10-hours on 2D alkaline batteries
- Reflector is highly polished for maximum light output
- Requires 2 "D" cell batteries (not included)
- The switch is self cleaning
- · Water and shock resistant



Compact Flashlight

BLED1



- · Adjustable beam by sliding zoom
- Anodized aluminum casing
- LED type: CREE XP-E-R2
- Luminance flux:195mm
- Switch mode: High Light, Low Light, Strobe, SOS
- Uses (3) AAA alkaline batteries
- Waterproof grade: IPX6









Packing: 1

Flexible Magnetic SMD LED Work Light

ECFLEX3

- Brightness: 110 Lumens
- Strong magnetic base with hang hook
- Sturdy aluminium housing with (3) 0.5W SMD LED lights
- Heavy duty spring adjusts light beam to needed angle with limitless positions
- Comes with (3) AAA batteries



LED Compact Shop Light

ECFHKYAP



- Small pocket size housing $\, \bullet \,$ Close to 360° rotatable
- 6 LED supply 350 lumens Strong magnetic on bottom

Packing: 1

Packing: 1

Magbender 6 SMD LED Work Light

ECFBP6

- IP65-resistant to water and dust in filtration
- 180° hinge for mounting flexibility

- Two brightness settings 100% and 50% for longer time
- USB charger and cable included for easy charging anywhere



PART NO.	LIGHT OUTPUT	BATTERY	RUN TIME	CHARGING TIME
ECFBP6	450LUX (0.5 M)	3.7V Li-ion 2000mAh	3 hours	4-5 hours

Bendable Light



- Heavy duty barrel handle and switch
- Features 10 flexible shaft and 3/16" high intensity lamp
- Includes (2) AA batteries



10



Battery & Testing

Battery Charger, Shop

BLPBBC200

- Packing: 1
- Smart microprocessor controlled, prevent overcharged
- Usage 12V lead acid, AGM, deep cycle and gel cell.



- Different charging modes express, fast and trickle
- Damage prevention reverse polarity, short circuit and overheat

Battery Tester

BLPBBTP612



- Integrated thermal printer battery tester
- Designed for testing all types of 6V and 12V starter batteries, including lead-acid, gel and AGM, Bad cell detection capability
- Voltmeter mode for testing both the starter and the charging system, Anti-sparking clamps for safe operation
- Back-lit Display, 4 Lines 16 Characters LCD for easy viewina
- Designed with the technician in mind, the button layout and housing allows for one-handed operation



- Test Range: 100-1400 CCA
- Starter system testing: pressing the down arrow displays the captured voltage from cranking the engine
- Charging system testing: pressing the up arrow displays the captured high voltage from the alternator
- Detachable Test Lead: 50cm/2"
- Screen Size: 76mm x 39mm
- Voltmeter: 7.6V ~ 17V via Battery Clamp
- Multi Languages Display: English, German, Italian, Portuguese
- Weight: 0.52kg
- Clamp Size: 90mm







Automotive Amp Meter

EECT72

- Packing: 1
- Allows easy component testing and parasitic drain location
- Real time readings of current in fused circuit without removing fuse or a snapshot
- Special ruse adapters lock on to fuse to give user hands free control or use the standard probes



PART NO.	CASE	OPERATING VOLTAGE	AMPERAGE RANGE		
EECT72	Nylon Pouch	6V, 12V, 24V	5mA to 50A		
MINIMUM DETECTABLE CURRENT	SMALL SCALE RESOLUTION		LARGE SCALE RESOLUTION		
5ma for 5A fuse, 50ma for 50A fuse	.01A (10mA)		.1A (100mA)		
FU	SE TYPE	/ RANGE*			
MINI (atm) MICRO (atr)/LP	STANDARD (atc)		MAXI		
5A, 7.5A, 10A, 15A, 20A, 25A, 30A	5A, 7.5A, 10A, 15A, 20A, 25A, 30A		30A, 40A, 50A		
ACCURACY	BATTERY	POWERED	BATTERY LIFE		
+/- 5% of display	3 x AA Alkaline Battery (not Included)		Approx. 500 hrs of continuous use		
AUTO-OFF	BANAN	A JACKS	SIZE		
After Approx. 10 minutes of inactivity	Standard 4mm Safety shrouded Jacks				5.5"x3.5"x1.5"
WEIGHT	OPERATING TEMPERATURE		TEST LEADS		
0.5 lbs	20°F	- 120°F	36" 1000V CATIII 10A		

Fuse Buddy Pro Test Kit

EEFB310

- Packing: 1
- Great tool for reading circuit amperage draws and troubleshooting up to 30 amps
- Kit includes 1 meter with 3 interchangeable test functions: 30 amp MINI circuit current test, 30 amp ATC circuit current test and 30 amp all purpose current test
- Plugs directly into MINI and ATC fuse sockets



- Additional 30 amp test clips expand the testing capability
- Original fuse is replaced in-line, thereby maintaining circuit protection
- Easy connection into fuse socket, Fuse Body[™] end is shaped like a fuse
- LCD display features analog bar graph
- Unit also features Data Hold and Auto Power-Off
- Measuring Range: 0 30 Amps/48 VDC-10 seconds
- Accuracy: ± 2% of reading
- Resolution: 100 mA

Max Fuse Buddy®

EEFB315

- Packing: 1
- MAXI circuit testing capability up to 80 Amps
- Also works with ATC and mini circuits-includes adapters
- Large LCD display with analog bar graph
- Unit powered by 9 volt battery, features peak hold functi



- Accuracy: + 2.0% of reading + 4 digits
- One touch zero function
- Amps: 0 80 Amps DC
- Resolution: 0.1A

Battery & Testing

Automatic Meter

MT454C

- Packing: 1
- MT454C is a durable, easy to use compact size digital multimeter
- Compact size fits comfortably in the palm of your hand
- Easy-to-read 4000 count digital
- Automatically selects correct function of DC Volts, AC Volts or Ohms (Resistance)
- Use DC Voltage ranges to verify proper voltage level is arriving at a sensor or circuit
- Measure Ohms to determine resistance of a coil
- Also test resistance of fuses, fusible links, components and circuits
- Measure AC voltage signals on digital MAF sensors plus wheel and vehicle speed sensors
- Protective boot with tilt stand, test leads, battery and instruction manual included
- 5 year limited warranty

Meter Manual Ranging

MT501C



Packing: 1

- MT501C ergonomic, compact size fits comfortably in the palm of the
- Measure Ohms to determine resistance of a coil or spark plug
- Also test continuity of fuses, fusible links, components and circuits
- Use DC voltage ranges to verify proper voltage level is arriving at a sensor or circuit
- Easy-to-read, 2000 count LCD display
- Lock readings on display with data hold
- Measure AC voltage signals on digital MAF sensors plus wheel and vehicle speed sensors
- Added protection against drops and the elements with included rubber boot
- Safety cULus 3111 Listed. Meets CE and IEC 1010 safety standards
- 5 year limited warranty

Meter Autoranging

MT574C



- MT574C offers both automatic and manual ranging
- Measure Ohms to determine resistance of a coil or spark plug wire
- Use the diode function to test the diode pack on a typical alternator
- Use DC voltage ranges to verify proper voltage level is arriving at a sensor or circuit
- Easy-to-read, 4000 count LCD display with low battery indication
- Lock readings on display with data hold
- Measure AC voltage signals on digital MAF sensors plus wheel and vehicle speed sensors
- Measure DC current to determine presence of a parasitic load
- Added protection against drops and the elements with included rubber boot
- Safety cULus 3111 Listed. Meets CE and IEC 1010 safety standards
- 5 year limited warranty







PART NO.	DISPLAY COUNT	AC / DC VOLTS	BASIC DC ACCURACY	AC / DC AMPS (mA)	RESISTANCE (Ohm)	AUTO RANGE	DATA HOLD	MIN / MAX	AUTO POWER OFF	CE OR UL LISTED	CAT RATING
MT454C	4,000	600 / 600	0.50%	-/-	40M	YES	_	_	YES	CE, cULus 3111	CATIII 600 Volt
MT501C	2,000	600 / 600	0.75%	-/-	2K	_	YES	_	_	CE, cULus 3111	CATIII 600 Volt
MT574C	4,000	600 / 600	0.30%	400 / 400	40M	YES	YES	YES	YES	CE, cULus 3111	CATIII 600 Volt









Multimeter, General

BLPMM1AP

- Measures voltage up to 1000V AC/DC, DC current, resistance and diode test Shiny surface
- Large backlit LCD display with data hold and relative zero
- Protective rubber guards for drop protection
- Designed to safely and accurately troubleshoot a variety of industrial and household electrical problems
- CE certified





Battery & Testing

Circuit Tester


BPECT1

- Packing: 1
- · Circuit tester for 6 and 12 volt systems
- Quickly and safely tests high and low voltages on all vehicles including computerized engine
- Can be used to detect power, ground and find shorts and breaks



- High impedance to protect sensitive electronic sensors, microprocessors, electronic ignition components and air bags
- LED indicates red for power (high) and green for ground (low)
- Insulated alligator clip

Probe, Coil-On-Plug





Mini Engine Electronic Stethoscope

YA6910

- Packing: 1
- Sensor clamp helps to detect noises during test drives that can not be duplicated in the work bay
- Sensor tip mounted on 6" flexible shaft allows access to reach difficult areas



- 5" inductive metal probe allows user to pinpoint source of noise or vibration
- Ultra sensitive microphone provides a full range of sound
- Rotary volume controlallows easy adjustment
- Ear-bud style earphones provide excellent sound quality

Test Pen, 250VAC



Voltage Test Range: 110-250V

Universal EFI Quick Probe

YA76462



Packing: 1

- · Quickly detects electronic fuel injector functions on any gas or diesel engine
- Specifically designed to detect the vibrations emitted when the electronic injector fires
- No hunting for injector wires to test at the connector
- No need to remove the injector for testing
- Super bright LED strobe
- 7" removable probe tip
- Battery operation
- · Sensitivity thumb wheel

Inspection Mirrors



PART NO.	MIRROR DIAMETER (inches)	LENGTH (inches)
UIM125	1 1/4	6 1/2, extendable to 35
UIM225	2 1/4	6 1/2, extendable to 35
UIM325	3 1/4	6 1/2, extendable to 29 1/2





Gas / Diesel Combustion Leak Tester

GDCT16

- Packing: 1
- Provides an easy and quick way to diagnose engine overheating problems
- Checks for leaks between the combustion chamber and the cooling system



- Test head and gasket for combustion leaks before removing the radiator
- Double chamber in testing unit provides a high level of accuracy
- For use on water cooled gas and diesel engines
- Kit includes complete test chamber, 16 oz. bottle of testing fluid and instructions

Battery Carrier

BL1B

Packing: 1

For top post and side terminal batteries



- Rubber pads securely grip battery widths from 5" to 7"
- Plastic hand grip provides a firm hold

Terminal Tool Kit

TT12KT

Packing: 1

 Applications include most GM and other domestic computer connectors and terminals. Individual handles for easy assess in tight places. Designed for weather pack and pack-con terminals with flat blade to open connectors and fork for ALDL connectors to access trouble codes. Color coded: Red handle for GM and Green for wire terminal tools. Includes storage case



 Kit includes these GM C3 System Terminal Tools (red handle):
 Tube, Spring Loaded, 3.3mm x 28mm

Square Blade, 1.4 x 19.00mm
Flat Blade, 1.5 x 24.75mm
Flat Blade, 2.0 x 23.00mm
Fork Blade, 8.0 x 24.00mm
Flat Blade Screwdriver, 3/16" x 1.00"

 Kit includes these Wire Terminal Tools (green handle):

Tube, 3.30 x 28.0mm Tube, 4.30 x 13.0mm

Tube, 3.75 x 13.0mm

Tube, 3.00 x 13.0mm


Flat Twin Blade, 3.0mm

Flat Twin Blade, 1.6mm

10



INSULATED TOOLS Modular Foam Kits / Sets Building





Insulated Toolbox Set, 20pcs

BLPISD20SET Packing: 1

Set includes:

- Insulated Open Wrench 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 24, 27, 30, 32 mm
- Insulated Adjustable Wrench 250 mm
- · Suitable for automotive electric and hybrid cars servicing
- Tools are VDE certified with certificate
- Made from high impact resistance injection for increased connection for torque
- Insulation material are anti-burn with high low temperature resistance
- Test up-to 10000v with GS/VDE certification IEC 60900:2012




Insulated Wrench Set, 37pcs

BLPISD37SET Packing: 1

Set includes:

- Insulated Open Wrench 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 24, 27, 30, 32 mm
- Insulated Ratcheting Wrench 10, 11, 12, 13, 14, 15, 16, 17, 18, 19 mm
- Insulated Hex Key 3, 4, 5, 6, 8, 10 mm
- In foam cut kit
- Tools are VDE certified with certificate
- Made from high impact resistance injection for increased connection for torque
- Insulation material are anti-burn with high low temperature resistance
- Test up-to 10000v with GS/VDE certification IEC 60900:2012



Insulated Ring Wrench Set, 21pcs

BLPISDRW21SET Packing: 1

Set includes:

- 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 24, 27, 30, 32 mm
- Insulated Scissor 160 mm
- In foam cut kit
- Tools are VDE certified with certificate
- Made from high impact resistance injection for increased connection for torque
- Insulation material are anti-burn with high low temperature resistance
- Test up-to 10000v with GS/VDE certification IEC 60900:2012





INSULATED TOOLS

Modular Foam Kits / Sets Building

Insulated Tool Set with Plastic Box, 30pcs

BLPISDCOM30SET

**Tool Set: Customizable

Packing: 1

- Tools are VDE certified with certificate
- Made from high impact resistance injection for increased connection for torque
- Insulation material are anti-burn with high low temperature resistance
- Test up-to 10000v with GS/VDE certification IEC 60900:2012





Set includes:

- Insulated Phillips Screwdriver PH2x100, PH3x150 mm
- Insulated Slotted Screwdriver 4x100, 6.5x150 mm
- 3/8" Insulated Socket 8, 10, 11, 12, 13, 14, 16, 17, 18, 19 mm
- 3/8" Insulated Extension Bar 125, 250 mm
- 3/8" Insulated Socket Driver 4x75, 5x75, 6x75, 8x75 mm
- 3/8" Insulated Ratchet Wrench 200 mm
- Insulated Ring Wrench 8, 10, 12, 14, 17 mm
- Insulated Combination Plier 8"
- Insulated Diagonal Cutter Plier 6"
- Insulated Cable Knife (Straight)
- In Plastic Box





Insulated Tool Set, 115pcs

BLPISDPRO115SET

**Tool Set: Customizable

Packing: 1

- Tools are VDE certified with certificate
- Made from high impact resistance injection for increased connection for torque
- Insulation material are anti-burn with high low temperature resistance
- Test up-to 10000v with GS/VDE certification IEC 60900:2012



Set includes:

- 1/4" Insulated Hex Sockets 5x42, 6x42, 7x42, 8x42, 9x42, 10x42, 11x42, 12x42, 13x42, 14x42 mm
- 1/4" Insulated Bits Sockets 3x65, 4x65, 5x65, 6x65 mm
- 1/4" Insulated Ratchet Wrench 145 mm
- 1/4" Insulated Extension Bar 75 mm
- 3/8" Insulated Hex Sockets 8x44, 10x44, 11x44, 12x44, 13x44, 14x44, 16x44, 17x44, 19x44 mm
- 3/8" Insulated Double Hex Sockets, Long 8x80, 10x80, 12x80 mm
- 3/8" Insulated 2-Layer Hex Socket 15*45 mm
- 3/8" Insulated 2-Layer Double Hex Bit Sockets 6x75, 8x75, 10x75, 12x75 mm
- 3/8" Insulated 2-Layer Torx Bit Sockets T20*75, T25*75, T27*75, T30*75, T40*75, T45*75, T50*75 mm
- 3/8" Insulated Ratchet Wrench 200 mm
- 3/8" Insulated T-Handle Wrench 200 mm
- 3/8" Insulated Extension Bar 125 mm
- 1/2" Insulated Hex Sockets 10x54, 12x54, 13x54, 14x54, 16x54, 17x54, 18x54, 19x54, 21x54, 22x54, 24x54, 27x54, 32x54 mm
- 1/2" Insulated Bits Sockets 5x120, 6x120, 8x120, 10x120 mm
- 1/2" Insulated 2-Layer Hex Socket 15*45 mm
- 1/2" Insulated Ratchet Wrench 250 mm
- 1/2" Insulated T-Handle Wrench 200mm
- 1/2" Insulated Extension Bar 125mm
- Insulated Phillips Screwdrivers PH0x60, PH1x80, PH2x100, PH3x150 mm
- Insulated Slotted Screwdrivers 0.4x2.5x75, 0.8x4.0x100, 1.0x5.5x125, 1.2x6.5x150 mm
- Insulated Adjustable Spanner 10"
- Insulated Side Cutter 160 mm
- Insulated Long Nose Plier 200 mm
- Insulated Combination Plier 200 mm
- Insulated Wire Stripper
- Insulated Cable Knife (Straight) 50x80 mm
- Insulated Nut Screwdrivers 4x125, 5x125, 6x125, 7x125, 8x125, 9x125, 10x125, 12x125, 13x125, 14x125 mm
- Insulated Open-End Spanners 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 24 mm
- Insulated Ring Spanners 8, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21 mm



INSULATED TOOLS

Wrenches / Cutting Tools

1/2" Insulated Extension Bars

Packing: 1

- Tools are VDE certified with certificate
- Made from high impact resistance injection for increased connection for torque
- Insulation material are anti-burn with high low temperature resistance
- Test up-to 10000v with GS/VDE certification IEC 60900:2012



PART NO.	Size (mm)	
BLPISDEXT125	4 x 120	
BLPISDEXT250	5 x 120	

Insulated Hex Key

Packing: 1

- Tools are VDE certified with certificate
- Made from high impact resistance injection for increased connection for torque
- Insulation material are anti-burn with high low temperature resistance
- Test up-to 10000v with GS/VDE certification IEC 60900:2012



PART NO.	Size (mm)	Length (mm)
BLPISDH3	3	130
BLPISDH4	4	140
BLPISDH5	5	160
BLPISDH6	6	180
BLPISDH8	8	200
BLPISDH10	10	235
BLPISDH12	12	260

1/2" Insulated T-Wrench

BLPISDT200 Packing: 1 200mm length Tools are VDE certified with certificate Made from high impact resistance injection for increased connection for toraue Insulation material are anti-burn with high low temperature resistance Test up-to 10000v with GS/VDE certification

Insulated Adjustable Wrench

BLPISDADJ10

IEC 60900:2012

Packing: 1

- Tools are VDE certified with certificate
- Made from high impact resistance injection for increased connection for torque
- Insulation material are anti-burn with high low temperature resistance
- Test up-to 10000v with GS/VDE certification IEC 60900:2012



PART NO.	Length (inches)
BLPISDADJ10	10

Insulated Scissors

- Tools are VDE certified with certificate
- Made from high impact resistance injection for increased connection for torque
- Insulation material are anti-burn with high low temperature resistance



PART NO.	Length (mm)
BLPISDSC160	160









Insulated Ring wrench

Packing: 1

- Tools are VDE certified with certificate
- Made from high impact resistance injection for increased connection for torque
- Insulation material are anti-burn with high low temperature resistance
- Test up-to 10000v with GS/VDE certification IEC 60900:2012



PART NO.	Size (mm)	Length (mm)
BLPISDRW6	6	130
BLPISDRW7	7	140
BLPISDRW8	8	150
BLPISDRW9	9	160
BLPISDRW10	10	170
BLPISDRW11	11	180
BLPISDRW12	12	190
BLPISDRW13	13	200
BLPISDRW14	14	210
BLPISDRW15	15	215
BLPISDRW16	16	215
BLPISDRW17	17	220
BLPISDRW18	18	230
BLPISDRW19	19	240
BLPISDRW21	21	250
BLPISDRW22	22	260
BLPISDRW24	24	280
BLPISDRW27	27	290
BLPISDRW30	30	310
BLPISDRW32	32	320

Insulated Open End Wrench

- Tools are VDE certified with certificate
- Made from high impact resistance injection for increased connection for torque
- Insulation material are anti-burn with high low temperature resistance
- Test up-to 10000v with GS/VDE certification IEC 60900:2012



PART NO.	Size (mm)	Length (mm)
BLPISDOE6	6	89.5
BLPISDOE7	7	89.9
BLPISDOE8	8	99.5
BLPISDOE9	9	99.2
BLPISDOE10	10	110
BLPISDOE11	11	120
BLPISDOE12	12	130
BLPISDOE13	13	140
BLPISDOE14	14	150
BLPISDOE15	15	160
BLPISDOE16	16	165
BLPISDOE17	17	165
BLPISDOE18	18	175
BLPISDOE19	19	180
BLPISDOE21	21	195
BLPISDOE22	22	205
BLPISDOE24	24	230
BLPISDOE27	27	249
BLPISDOE30	30	284
BLPISDOE32	32	308

INSULATED TOOLS

Pliers & Cutters

Insulated Side Cutters

- Chrome vanadium steel
- Tested under 10,000 voltage testing machine

PART NO.	LENGTH (mm)	
WT1003-6	160	
WT5403-8	203	

Specially designed soft grips

Laser hardened cutting edge



Insulated Long Nose Pliers

- Chrome vanadium steel
- Tested under 10,000 voltage testing machine

PART NO.	LENGTH (mm)
WT1001-6	160
WT1001-8	200

- Specially designed soft grips
- Laser hardened cutting edge



Insulated Combination Pliers

- Chrome vanadium steel
- Tested under 10,000 voltage testing machine

PART NO.	LENGTH (mm)
WT1014-6	160
WT1014-7	180
WT1014-8	200
WT5414-9	225

- Specially designed soft grips
- Laser hardened cutting edge



Packing: 6

Packing: 6







Packing: 6

Packing: 6

Insulated Slip Joint Pliers

WT8627-10

- Chrome vanadium steel
- Tested under 10,000 voltage testing machine

PART NO.	LENGTH (mm)
WT8627-10	250

Specially designed soft grips

Laser hardened cutting edge



Insulated Wire Stripping Pliers

WT1017C-6

- Chrome vanadium steel
- Tested under 10,000 voltage testing machine

PART NO.	LENGTH (mm)
WT1017C-6	160

- Specially designed soft grips
- Laser hardened cutting edge









AUTOMOTIVE WORKSHOP TOOLS

Pick-up Tools / Creepers



Pick Up Tool



- Lifts 2.5 lbs.
- Chrome plated shaft extends from 5 1/2" to 25 1/2"
- Black cushion grip will not slip in oily or wet hands
- Hinged head magnetic pick up tools
- Powerful magnets are fitted into the brass sleeve Adjustable hinged heads
 - Includes pocket clip

Pick Up Tool



- This 5 7/8" tool extends to 25 9/16"
- Magnet lifts up to 2 lbs.
- Hinged head magnetic pick up tools
- Includes pocket clip
- Powerful magnets are fitted into the brass sleeve
- Adjustable hinged heads
- Chrome

Pick Up Tool



- This 5 7/8" tool extends to 25 9/16"
- Magnet lifts up to 2 lbs.
- Hinged head magnetic pick up tools
- Powerful magnets are fitted into the brass sleeve
- Adjustable hinged heads
- Includes pocket clip
- Blue

Pick Up Tool



- Lifts 2 lbs.
- 6 5/8" long, and extends to 33 1/4"
- Adjustable hinged heads
- Hinged head magnetic pick up tools
- Powerful magnets are fitted into the brass sleeve

Pick Up Tool



- 6 1/2" tool extends to 21 1/4"
- Hinged head magnetic pick up tools
- Powerful magnets are fitted into the brass sleeve
- Includes pocket clip
- Magnet lifts up to 0.66 lbs.

Pick Up Tool



- 29" aluminum shaft can be easily bent at any angle to retrieve dropped metal objects in hard to reach areas
- Power cap slides over the magnet and shield its
- sides from attaching to unwanted metal surfaces
- Will pick up 5 lbs. with the power cap
- Textured cushion pistol grip will not slip in wet or oilv hands









Pick Up Tool

UPT50A Packing: 1

- Lifts 10 lbs.
- 6 5/8" long, and extends to 33 1/4"
- Hinged head magnetic pick up tools
- Powerful magnets are fitted into the brass sleeve
- Adjustable hinged heads

Pick Up Tool

UPT65



- Perfect for retrieval of heavy ferrous objects in hard to reach areas
- Goblet shaped magnetic head pushes the flux to the front of the magnet enabling the user to lift 16 lbs
- Head shields the sides of the magnet from attaching to unwanted ferrous surfaces



- Telescopes from 9" to 34 1/4" (229 to 870mm)
- Stainless steel handle is strong, lightweight and inhibits corrosion
- Cushion textured pistol grip will not slip in wet or oily hands

Box Seat Creeper

BPSCKPCM



- Size: :L500 x W420 x H360 mm
- 2 drawers with depth of 3.6" provide more storage space for users
- PE Blue paint powder to protect against corrosion and provide durability



- Top and bottom panel thickness of 1.5mm for extra durability
- 3.6" drawer depth for more tools storage
- Each drawer designed to withstand 45kg of tools
- Plywood backing for extra strength
- High density foam for comfort and durability
- 2" ball bearing casters

Pick Up Tool



- Lifts 4 1/2 lbs.
- 6 5/8" long, and extends to 33 1/4"
- · Adjustable hinged heads
- Hinged head magnetic pick up toolsPowerful magnets are
- Powerful magnets are fitted into the brass sleeve

Adjustable Headrest Creeper

BLPCPER

Packing: 1

OVERALL SIZE

- 3 Positions adjustable head rest
- Powered coated steel frame for long lasting usage
- 6 oil resistant, full ball bearing 3" casters
- High density foam cushion headrest provides comfort to users
- Overall Dimensions: 1117 x 520 x 115mm



		COLOR	(kg)	(inches)
BLPC	CPER	Blue	13	L44 x W20.5 x H4.5
PAD WIDTH PAD LENGTH (inches)		NUMBI CAST		CASTER DIAMETER (inches)
11	39	6		3

WEIGHT

Pick Up Tools Set



- Quick release telescope for easy switch between usage
- Super bright white LED
- Magnet able to lift up to 8 lbs.
- Include 2 mirrors; rectangular 64x43mm, round 60mm diameter
- Batteries life of 10-12 hours of normal usage



AUTOMOTIVE WORKSHOP TOOLS

Safety Equipment

YA4282

Welders Gloves

YA427B



Tig Welding Gloves

Welding Sleeves 1 Pair

YA4280





- Helps protect hands from sparks when welding
- Leather construction with added insulation for heat protection
- Reinforced palm for durability



Packing: 1

- Ideal for TIG welding processes
- Pigskin material for precise control
- Thick leather cuff for wrist protection
- Helps protect hands from heat and sparks



- Helps protect arms from sparks when welding or cutting
- Elastic bands at each end of sleeve
- Constructed of flame retardant fabric
- 18" long
- 1 pair

Washable Work Gloves

Packing: 1

- Gloves feature stretch knit with padded back to provide extra feel and flexibility to grasp small objects
- Extra knuckle protection on back of fingers
- Heat resistant synthetic double layered leather palm for longer life
- Elastic cuff with hook and loop closure



PART NO.	SIZE	COLOR
GLOVE103MABAP	Medium	Blue
GLOVE103LABAP	Large	Blue
GLOVE103XLABAP	X-Large	Blue

Abrasion Resistant Nitrile Gloves

- Nitrile dipped coating for protection on dirty jobs
- Ergonomically pre-curved design gives you comfort at all times
- High abrasion resistance protects hand on sharp edges and rough castings Incredible grip and dexterity on wet and dry surfaces
- Lightweight nylon shell provides a nice snug fit
- CE rated for abrasion, blade cut, tear and puncture resistance



PART NO.	SIZE
GLOVE400S	Small
GLOVE400M	Medium
GLOVE400L	Large
GLOVE400XL	X-Large
GLOVE400XXL	XX-Large





Safety Glasses

Packing: 1

- Complies with ANST Z87.1-2003
- Lens provide 99.9% UV protection
- Angle and length adjustable temples provide various suitable fitting
- Soft nose pad and soft temple tips provide comfort for long-time wearing
- Anti-fog lens coating with anti-scratch protection
- GLASS30BK and GLASS30R have a ventilation channel between frame and lens



PART NO.	LENS	FRAME
GLASS30R	Clear	Red
GLASS30BK	Clear	Black
GLASS31R	Clear	Red
GLASS31BK	Clear	Black

Ear Protector

GA3200

- Packing: 1
- Noise reduction rating of 28 dB for protection
- Lightweight and comfortable with cushioned headband
- Cushioned ear piece pivots to provide for a comfortable and snug fit that keeps out noise
- Blue hard protective ear cups with Blue-Point® logo in white
- Each ear piece easily adjusts to fit a variety of



PART NO.	NOISE REDUCTION Rating, dB	HEADBAND
GA3200	28	Cushioned
EAR PIECE	ADJUSTABLE EAR PIECE	WEIGHT (lbs.)
Cushioned	Plastic	0.77

UV Leak Detection Flashlight Kit

ECFUVLITE



Packing: 1

- High intensity LED bulb with 100,000 hour service life
- Over four hours of peak performance per charge
- Power comparable to high intensity 75 watt lamps
- Compatible with all standard leak detection dyes
- Inspection range of up to 6'
- Includes (3) "AAA" batteries and fluorescence enhancing glasses

Face Shield

GA225




- Adjustable, cushioned head band is removable
- Face shield provides impact resistance
- Includes shield (GA225-1) with PETG (impact resistance perferred)
- Optional shield (GA225-2) with PC (high temperature resistance) is available

PART NO.	SHIELD STYLE	SHIELD SIZE (inches)	HEADBAND
GA225	Flat	7 3/4 x 15 1/4	Yes
ADJUSTABLE HEADBAND	IMPACT RESISTANCE	SHIELD INCLUDED	REPLACEMENT SHIELDS
Yes	Yes	Clear	GA225-1 (with PETG) GA225-2 (with PC)

Ear Protector, Ear Plug Style

YA160A



- Cushioned ear piece for comfort and snug fit to keep out noise
- Non-conductive
- Includes extra set of foam ear piece and reusable storage bag



PART NO		EDUCTION ing, dB	HEADRAND		
YA160A		25		Plastic	
EAR PIECE		USTABLE R PIECE	EAR PIE	_	WEIGHT (lbs.)
Foam		Foam	YA160A	1	0.06

Safety Equipment / Hose Reels / Floor Jacks

Fender Cover

BLPFEN1B

• Dimension: 1070 x 400 mm

· Upper layer material: PVC synethic leather

• Underlay material: Brushed fabrics

• 8 pcs magnet for secure hold onto vehicle

• Color: Blue with white Blue-Point logo printing

• Applications: Use in automotive maintenance and repair work



Packing: 1

Packing: 1

Packing: 1

Hose Reel, Electric

BLPSDCR10A

- 10m cable length with better coverage
- 180° free rotation between mounting bracket and rewinding feature
- Current overload protection feature

- Outer polypropylene casing increases impact resistance and durable
- Ergonomic designed grip delivering better handling

PART NO.	CABLE LENGTH (mm)	POWER PLUG LENGTH (mm)	CABLE TYPE (mm)	
BLPSDCR10A	10,000	900	H05VV-F, 1.5mm 2, 3 cores	
PLUG TYPE	RATED VOLTAGE	POWER - FULLY RETRACTED	POWER - FULLY EXTENDED	
UK Plug Type	AC230V	100 W	2000 W	
DIMENS L X W X H			VEIGHT (g)	
280 x 160	x 305	3.4		



Hose Reel, Air

BLPSDHR10A

- 9m cable length with better coverage
- 180° free rotation between mounting bracket and rewinding feature
- Excellent Capacity(Air): 9m of reinforced 1/4"
- Outer polypropylene casing increases impact resistance and durable
- Ergonomic designed grip delivering better handling

PART NO.	HOSE LENGTH (mm)	HOSE I.D. MAX WORKING PRESSU			
BLPSDHR10A	9,000	6 12 BAR			
HOSE MAX TEN	MPREATURE	INLET / OUTLET			
140°F / 0	60°C	1/4" thread/quick connector			
DIMENS L X W X H		NET WEIGHT (kg)			
280 x 160	x 305	3			













Floor Jack, 1.5 Ton Low Profile

YF1AP

Packing: 1

- Extra-large foot pedal for quick and safe usage
- Dual pistons decrease the number of necessary strokes
- Protective cover minimize dust enters through pistons and spring
- Polyurethane covered steel wheels ensure both durability and reducing sound
- Rubber saddle prevent scratches and slipping during usage
- Miniature tray at the bottom of the handle for storage of tools, screws and nuts
- Safety pressure valve prevents from overloading during usage
- Applicable for small size vehicles
- Low profile for easy access under vehicle

PART NO.	CAPACITY (tons)	MIN. HEIGHT (mm)	MAX. HEIGHT (inches)	SADDLE SIZE (mm)	FRAME LENGTH (mm)
YF1PH	1.5	70	610	120	960

Floor Jack, 2 Ton Low Profile

YF2AP

Packing: 1

- Extra-large foot pedal for quick and safe usage
- Dual pistons decrease the number of necessary strokes
- Protective cover minimize dust enters through pistons and spring
- Polyurethane covered steel wheels ensure both durability and reducing sound
- Rubber saddle prevent scratches and slipping during usage
- Miniature tray at the bottom of the handle for storage of tools, screws and nuts
- Safety pressure valve prevents from overloading during usage
- Applicable for small size vehicles
- Low profile for easy access under vehicle

PART NO.	CAPACITY (tons)	MIN. HEIGHT (mm)	MAX. HEIGHT (inches)	SADDLE SIZE (mm)	FRAME LENGTH (mm)
YF2AP	2	70	490	120	750

Floor Jack, 3 Ton

YF3APH

- Fast acting pump reaches lifting height in less than a pump to allow user to reach a variety of service height situations quickly
- One piece handle features a foam pad to limit damage to vehicles
- Universal joint release mechanism for smooth action
- Rolled side frames with generous flanges to resist flexing
- Meets ANSI-PALD standards





PART NO.	CAPACITY	MIN. HEIGHT	MAX. HEIGHT	SADDLE SIZE	FRAME LENGTH	HANDLE LENGTH
	(tons)	(mm)	(mm)	(mm)	(mm)	(mm)
YF3APH	3	130	462	119	617	1,243

Floor Jacks / Hydraulic Jacks

Floor Jack, 3 Ton

YF3AP



- Extra-large foot pedal for quick and safe usage
- Dual pistons decrease the number of necessary strokes
- Protective cover minimize dust enters through pistons and spring
- Polyurethane covered steel wheels ensure both durability and reducing sound
- Rubber saddle prevent scratches and slipping during usage
- Miniature tray at the bottom of the handle for storage of tools, screws and nuts
- Safety pressure valve prevents from overloading during usage
- Long chassis allows to reach further under the vehicle
- Applicable for small size vehicles

PART NO.	CAPACITY (tons)	MIN. HEIGHT (mm)	MAX. HEIGHT (inches)	SADDLE SIZE (mm)	FRAME LENGTH (mm)
YF3AP	3	90	552	120	825

Long Floor Jack, 3 Ton

YF3LAP



- Extra-large foot pedal for quick and safe usage
- Dual pistons decrease the number of necessary strokes
- Protective cover minimize dust enters through pistons and spring
- Polyurethane covered steel wheels ensure both durability and reducing sound
- Rubber saddle prevent scratches and slipping during usage
- Miniature tray at the bottom of the handle for storage of tools, screws and nuts
- Safety pressure valve prevents from overloading during usage
- Long chassis allows to reach further under the vehicle
- Applicable for small size vehicles

PART NO.	CAPACITY (tons)	MIN. HEIGHT (mm)	MAX. HEIGHT (inches)	SADDLE SIZE (mm)	FRAME LENGTH (mm)
YF3LAP	3	130	800	120	1370

Floor Jack, 2.5 Ton / 3 Ton / 3.5 Ton

- PVC handle for insulation and comfort
- Speed descend by controlled swivelling of lever
- Quick lift pump
- Foam bumper protection on the lever to prevent damage to the vehicles
- Inbuilt tray for storage of tools, screws, bolts, etc.
- Rubber pad prevent damage under part of the car
- Steel wheels
- Professional matt powder coating



PART NO.	CAPACITY (tons)	A (mm)	D (mm)	E (mm)	F (mm)	WEIGHT (kg)
BLPLPSJ25T	2.5	1175	740	75	505	33.5
BLPPSJ3T	3	1160	682	133	465	33.7
BLPPSJ35T	3.5	1175	730	132	533	47.8

4 Ton Portaset

YA1544A

- · 4-ton capacity kit includes hydraulic unit, five "Snap-Set" extensions, spreader plus a full selection of attachments for most push applications
- Automatic pump overload system protects against damage to rams and equipment
- 1/2-ton capacity hydraulic spreader has 2" jaw and spreads from 5/8" to 3 3/4"
- Flex head includes permanently molded rubber pad
- Heavy walled extensions tubes stand up to the toughest loads
- Long handle reduces required pumping effort
- 18 piece set is stored in durable storage case













10 / 20 / 30 Ton Pneumatic Hydraulic Jack

YF102040AP

Packing: 1

- Hydraulic jack for vehicles up to max. 40t
- Low chassis clearance height: 125mm
- Heavy duty design ensures durability
- Large wheel enables easy maneuverability
- PU protection on the steel lever minimize abrasion during usage
- Safety pressure valve prevents from overloading during usage
- Ideally suited for daily workshop use
- Two adaptors included to increase elevation to 45mm or 75mm



PART NO.	CAPACITY (tons)	MIN. HEIGHT (mm)	MAX. HEIGHT (inches)	SADDLE SIZE (mm)	FRAME LENGTH (mm)
YF102040AP	10/20/40	125	285/232/182	70	825

20 / 40 / 60 Ton Pneumatic Hydraulic Jack

YF204060AP

Packing: 1

- Hydraulic jack for vehicles up to max. 60t
- Heavy duty design ensures durability
- Large wheel enables easy maneuverability
- PU protection on the steel lever minimize abrasion during usage



- Safety pressure valve prevents from overloading during usage
- Ideally suited for daily workshop use
- Two adaptors included to increase elevation to 45mm or 75mm

PART NO.	CAPACITY (tons)	MIN. HEIGHT (mm)	MAX. HEIGHT (inches)	SADDLE SIZE (mm)	FRAME LENGTH (mm)
YF1530AP	20/40/60	150	311/254/206	84	875

15 / 30 Ton Pneumatic Hydraulic Jack

YF1530AP

Packing: 1

- Hydraulic jack for vehicles up to max. 30t
- Heavy duty design ensures durability
- Large wheel enables easy maneuverability
- PU protection on the steel lever minimize abrasion during usage
- Safety pressure valve prevents from overloading during usage
- Two adaptors included to increase elevation to 45mm or 75mm



PART NO.	CAPACITY (tons)	MIN. HEIGHT (mm)	MAX. HEIGHT (inches)	SADDLE SIZE (mm)	FRAME LENGTH (mm)
YF1530AP	15/30	150	288/223	70	810

15 / 30 Ton Compact Pneumatic Hydraulic Jack

YF1530CAP

- Hydraulic jack for vehicles up to max. 30t
- Heavy duty design ensures durability
- Large wheel enables easy maneuverability
- PU protection on the steel lever minimize abrasion during usage



- Safety pressure valve prevents from overloading during usage
- Ideally suited for daily workshop use
- Two adaptors included to increase elevation to 45mm or 75mm

PART NO.	CAPACITY (tons)	MIN. HEIGHT (mm)	MAX. HEIGHT (inches)	SADDLE SIZE (mm)	FRAME LENGTH (mm)
YF1530CAP	15/30	150	292/224	70	430



Jack Stands / Wheel Dolly / Balloon Jacks / Bottle Jacks

12 Ton Jack Stands

YA512A

- Packing: 1
- Counter-weighted pawl serves as a secure locking device to prevent the load from accidentally disengaging
- Sturdy, welded steel construction for superior strength
- One piece, multi-position ductile ratchet bar provides super strength, durability and quick adjustment mechanism that securely locks into desired location



PART NO.	CAPACITY (tons)	LOW HEIGHT (inches)	MAXIMUM HEIGHT (inches)
YA512A	12 (per pair)	17 1/2	27 1/2

3 Ton Jack Stands

BLPJS3TAP

- Packing: 1
- Counter-weighted pawl serves as a secure locking device to prevent the load from accidentally disengaging
- Sturdy, welded steel construction for superior strength
- One piece, multi-position ductile ratchet bar provides super strength, durability and quick adjustment mechanism that securely locks into desired location



PART NO.	CAPACITY (tons)	LOW HEIGHT (inches)	MAXIMUM HEIGHT (inches)
BLPJS3TAP	3 (per pair)	290	415

Wheel Dolly, Car

BLP15WD



- Extra-large foot pedal for quick and safe usage
- Ratcheting system lift the wheel of the vehicle in
- 4 multi-directional free-swivel casters with bearings allow effortless mobility
- 2 Locking mechanism ensure safety when operating
- BLP15WDST is the rack



PART NO.	CAPACITY	LOW HEIGHT	MAX HEIGHT
	(tons)	(mm)	(mm)
BLP15WD	0.8	450	810

Wheel Dolly, Truck

BLP600WDT



- Hydraulic system actuated provides smooth, positive power for the removal and installation
- Heavy-duty steel frame tilts to allow precise positioning of truck tyres Capable to lift wheels up to 600kg
- Adjustable mechanical system allows users to fit wide range of tyres
- Large caster enables easy maneuverability



TAITI NO.	(tons)	(mm) (mm)	
BLP600WDT	BLP600WDT 0.6		535
DIMENSION (mm)	NET WEIG (kg)	GHT GROSS WEIGH (kg)	
1030 x 1050 x 1020	85	93.5	

CAPACITY LOW HEIGHT MAX HEIGHT









2 Step Ballon Jacks


- 2T pneumatic balloon jack with 2-step operation
- Extremely low entry height: 115 mm
- Maximum lifting height: 345 mm (425 mm with the height extension assembled)
- Air pressure to be used should be minimum 7 bar, maximum 10 bar
- 2-step balloon jacks are available with a short or long handle
- Operated by the triggers at the end of the handle
- Supplied with a 80 mm height extension
- CE certified by Official Independent Technical Inspection Association


PART NO.	CAPACITY (tons)	HANDLE TYPE	AIR INLET	BAR	MINIMUM HEIGHT (mm)	MAXIMUM HEIGHT (mm)	WEIGHT (kg)	PACKAGE DIMENSION (mm)
BLPBJ22L	2	Long	1/4"	7 - 10	115	345	18	1000 x 265 x 265
BLPBJ22S	2	Short	1/4"	7 - 10	115	345	15	345 x 265 x 265



8 Ton Bottle Jack

YA1228





Fabricated from hard-cast steel



Packing: 1

PART NO.	CAPACITY (tons)	LOW HEIGHT (inches)	MAX HEIGHT (inches)	ADJUST HEIGHT (inches)	BASE (inches)	HANDLE (inches)	CAP DIAMETER (inches)	OPERATING FORCE (lbs)
YA1228	8	8 1/8	17 5/8	2 3/4	4 3/4 x 4 3/4	18 1/8 (assembled)	1 3/8	101

2/4/6 Ton Bottle Jack

 Hydraulic system is protected from internal damage by a patented by-pass mechanism

 Machined and polished cylinders with die-cut threading provide non-abrasive leak-free, durable performance

Fabricated from hard-cast steel



PART NO.	CAPACITY (tons)	LOW HEIGHT (inches)	MAX HEIGHT (inches)	ADJUST HEIGHT (inches)	BASE (inches)	HANDLE (inches)	CAP DIAMETER (inches)	OPERATING FORCE (lbs)
BLP2BJ	2	7 1/10	13 3/5	1 9/10	3 1/5 x 3 3/5	11	4/5	5.3
BLP4BJ	4	7 3/5	14 7/10	2 2/5	3 1/2 x 4 /10	11	1	7
BLP6BJ	6	8 3/10	16 2/5	2 4/5	3 9/10 x 4 1/2	11	1 1/5	8.8



Transmission Jacks / Engine Cranes

Transmission Jack, 1/2 Ton

BLPTJ05TSG

Packing: 1

- Dual pump for quick lifting
- Large foot pedal for ease of operation
- Large wheel enables easy maneuverability
- PU protection on the steel lever minimize abrasion during usage
- Safety pressure valve prevents from overloading during usage
- 2006/42/EC and BS EN1494 Certified



PART NO.	CAPACITY	LOW HEIGHT	MAX HEIGHT
	(tons)	(mm)	(mm)
BLPTJ05TSG	0.5	1175	1985
			GROSS
DIMENSION	CERTIFICATE	NET WEIGHT	WEIGHT
(mm)		(kg)	(kg)

Transmission Jack, 1 Ton

BLPTJ1TSG

Packing: 1

Packing: 1


- Dual pump for quick lifting
- Large foot pedal for ease of operation
- Large wheel enables easy maneuverability
- PU protection on the steel lever minimize abrasion during usage
- Safety pressure valve prevents from overloading during usage 2006/42/EC
- and BS EN1494 Certified



PART NO.	CAPACITY (tons)	LOW HEIGHT (mm)	MAX HEIGHT (mm)
BLPTJ1TSG	1	899	1899
DIMENSION		NET WEIGHT	GROSS
(mm)	CERTIFICATE	(kg)	WEIGHT (kg)

Universal Saddle, 1 Ton

BLP1TUS



- Large foot pedal for ease of operation
- · Large wheel enables easy maneuverability
- PU protection on the steel lever minimize abrasion during usage
- Safety pressure valve prevents from overloading during usage
- 2006/42/EC and BS EN1494 Certified



PART NO.	CAPACITY (tons)	DIMENSION (mm)	CERTIFICATE	NET WEIGHT (kg)	GROSS WEIGHT (kg)
BLP1TUS	1	420 x 340 x 250	CE	18.1	19.5







Foldable Engine Crane, 1 Ton

BLP1TFOLDEC

Packing: 1

- Foldable 1T crane with 4 fixed positions of the lifting arm
- Quick raising of the arm from the dual-effect cylinder
- Safety overload valve
- Rotating pump cylinder allows pumping from any direction
- Foldable legs; the crane takes up limited space when not in use
- Certified according to 2006/42/EC + BS EN149



PART NO.	CAPACITY (tons)	LOW HEIGHT (mm)	MAX HEIGHT (mm)	DIMENSION (mm)	CERTIFICATE	NET WEIGHT (kg)	GROSS WEIGHT (kg)
BLP1TFOLDEC	1	88	2175	2175 x 1480 x 1030	CE	85	95

Foldable Engine Crane, 2 Ton, Lightweight

BLPEC2TAP

- Foldable 2T crane with 4 fixed positions of the lifting arm
- Quick raising of the arm from the dual-effect cylinder
- Safety overload valve
- Rotating pump cylinder allows pumping from any direction
- Foldable legs; the crane takes up limited space when not in use
- Comes with Chain and hook
- Certified according to 2006/42/EC + BS EN149
- Lightweight version



PART NO.	CAPACITY (tons)	LOW HEIGHT (mm)	MAX HEIGHT (mm)	DIMENSION (mm)	CERTIFICATE	NET WEIGHT (kg)	GROSS WEIGHT (kg)
BLPEC2TAP	2	NA	2200	1745 x 50 x 1460	CE	86	92

Work Bench / Specialty Tools

2M Adjustable Workbench, 3 Drawers

BLP200ADWB3D

Packing: 1



- Features a full bottom shelf and superior powder coat finish
- Dimensions: 78.74" x 31.49" x 70.87"
- Net Weight: 363 lbs (165kg)
- Weight Capacity: 440 lbs (200kg)

- Top panel: 50mm thickness
- Bottom shelf: 50mm thickness
- Steel support: 50mm thickness
- Back panel (BLP200WBBP02) sold separately

Tweezer Kit, 5pcs

TZK5

Packing: 1

Packing: 1

- Vinyl zipper pouch packaging
- All stainless construction



PART NO.	CONTENTS	LENGTH (inches)
	Pointed tweezers with plain ends	4 3/8
	Self-closing tweezers with plain ends	4 1/2
TZK5	Self-closing, weighted solder tweezers with serrated blunt end	7
	Sharp point utility tweezers with bent plain ends	7
	Sharp point utility tweezers with plain ends	7

Tweezer Kit, 7pcs

TZK7

- Black vinyl zipper pouch packaging
- All stainless construction



PART NO.	CONTENTS	LENGTH (inches)
	Pointed tweezers	4 3/8
	Curved head utility tweezers	6 3/4
	Self-closing, heat-resistant tweezers	6
TZK7	Sharp pointed utility tweezers	7
	Side locking tweezers	6
	Spade point tweezers	4 3/8
	Weighted solder tweezers	6





Pick Sets

Packing: 1

Heavy duty shank diameter is 0.02" thicker than standard picks for added durability and extended tool life

PART NO.	DESCRIPTION	LENGTH (inches)		
PSLR4-1	Hook Pick	9 3/4		
PSLR4-2	90° Hook Pick	9 3/4		
PSLR4-3	Straight Pick	9 3/4		
PSLR4-4	Complex Pick	9 3/4		
PSLR4-5	Combo Pick	9 3/4		
PSLR4-6	Double Angle Pick	9 3/4		
PSLR6	Extra Long Pick Set, 6pcs PSLR4-1, PSLR4-2, PSLR4-3, PSLR4-4, PSLR4-5, PSLR4-6 in vinyl storage pouch			
PSLR4	Extra Long Pick Set, 4pcs PSLR4-1, PSLR4-2, PSLR4-3, PSLR4-4 in vinyl storage pouch			



Cable Cutter

PWC80A Packing: 1

- For cutting battery cables and other soft metal cables
- Has vinyl covered handles
- 7 1/2" long

Leverage Hose Cutter



- (8 1/2") Compound action multiplies normal hand pressure to easily slice through many types of rubber and plastic hose up to 1 1/8" in diameter
- Includes stainless steel cutter blades and internal components

Wire Cutter, Micro Shear



PART NO.	LENGTH (inches)	STRIPS AWG SIZES	STRIPS METRIC SIZES (mm)
PWC19	5 1/8	Up to 20	Up to .80

Wire Stripper, Automatic

PWC27

Packing: 1

- One-step stripping enhances productivity
- Cleanly strips wire up to full 7/8" (22mm)
- Spring-action motion increases leverage and reduces operator fatigue

 Precision ground, knife-type blades provide clean, accurate stripping



PART NO.	LENGTH (inches)	STRIPS AWG SIZES	APPLICATION	REPLACEMENT BLADES
PWC27	6 1/4	10, 12, 14, 16, 18, 20, 22	Strips PVC, THHN and THWN	PWC27-7

Specialty Tools

Wire Stripper

PWC6 Packing: 1



PART NO.	DESCRIPTION	LENGTH (inches)
PWC6	Wire Stripper /Cutter Pliers	6
STRIPS AWG SIZES	STRIPS METRIC SIZES (mm)	APPLICATION
10, 12, 14, 16, 18, 20	2.6, 2.0, 1.6, 1.3, 1.0, 0.80	Strips PVC, THHN, and THWN

Wire Stripper

PWC28A Packing: 1



PART NO.	DESCF	RIPTION	LENGTH (inches)
PWC28A	Wire Stripper /Cutter / Crimper /Bolt Cutter		8 1/4
STRIPS AWG SIZES		STRII	PS METRIC SIZES (mm)
	10, 12, 14, 16, 18, 20, 22 Stranded, 8, 10, 12, 14, 16,18 Solid		I-Insulated Terminals and Crimp Sleeves

Wire Stripper



PART NO.	DESCRIPTION		LENGTH (inches)
PWC14	Wire Stripper /Cutter / Crimper /Bolt Cutter		8 3/4
STRIPS AWG SIZES		STRI	PS METRIC SIZES (mm)
10 12 14 16 18 3	20. 22		2mm Insulated and

Wire Stripper



PART NO.	DESCRIPTION		LENGTH (inches)
PWC12A	Wire Stripper /Cutter / Crimper		9 1/2
STRIPS AWG SIZES		STRIPS METRIC SIZES (mm)	
10, 12, 14, 16, 18			3mm Insulated and ated 7 - 8mm Ignition Terminals

Boot Pliers



- Vinyl coated jaws and handles assure gripping ability
- Use only on automotive type ignition systems
- 9 1/2" long

Boot Pliers



- 9 3/4" long



Terminals



Oil Drainer

• High Capacity 90 litres

litres collecting bowl

and air tank pressure Includes Plastic tray for

consumables

holding tools, parts and

reservoir tank with a 18

Indicator to display oil level

YB900D





Oil Filter Pliers, Extra Large

YA4275



- Use on filters from 4 1/4" to 7" (108-178mm) diameters
- Applications include truck, tractor and high torque diesel engines
- Spring action size adjustment assures a solid grip on filter
- Offset handle offers increased accessibility
- Industrial black finish with blue grips
- Heavy duty forged levers
- Cushioned grips for comfort
- Overall length of 19"



Seal Pliers

YA8230



- Removes valve stem seals from overhead camshaft engines including 4 valve per cylinder engines that have restricted access to the valve stem seal due to the head design
- Gripping serrations in the pliers tip easily grab both OEM and aftermarket seals with ease

Easy grip handles



Windshield Removal Tool

YA109C



- Steel cable pull handle
- Replaceable steel cutting blades can be resharpened
- For GM, Chrysler, and other cars with windshields set in place with sealant



Crimp Tool

PWC34

Packing: 1

- Double compound action with ratchet control for almost effortless operation
- Use with insulated connectors on 10 to 22 gauge wire
- For easy, efficient, single squeeze crimping of modular connectors
- Both primary and secondary crimps are made simultaneously to factory specifications

Has a comfortable ergonomic design and full cycle ratchet action

Exhaust Hanger Removal Pliers

YA3202



- For removing hanger brackets from their rubber mounting straps
- Place removal jaw behind the rubber grommet ring and the forcing pin of the pliers on the end of the steel hanger
- When handles are squeezed, the forcing pin pushes the ring off the hanger
- Applications on most domestic and import cars as well as light trucks
- 14" long



Specialty Tools

Flexible Spring Claw Set, 2pcs

BLPFSCS

Packing: 1

- Polybag packaging
- Cold roll steel with nickel plating handle
- Spring steel claw
- 4 claws hold up to 2 lbs



PART NO.		CONTENTS	LENGTH (mm)
BLPFSCS	BLPFSC240	Flexible Spring Claw	340
BEF1 303	BLPFSC600	Flexible Spring Claw	600

Wire Brushes

- Stainless steel bristles
- General-purpose cleaning, rust removal, deburring, edge blending, and roughing for adhesion.
- Perfect for cleaning debris in tight spots



PART NO.	LENGTH (Inches)
AC5CAP	7 7/8
AC59CAP	13 3/4

Multi-Tool Set, 4pcs

BLP4GIFT

Packing: 1

- Small and Medium 12-in-1 multi tool
- Corrosion resistant steel blade
- Pliers fold for safety and compact storage
- Aluminum housing with durable anodized finish



- Folding pocket knife
 - 2.5" blade length
 - 85 grams
- LED mini multi tool keychain 5 different functions (Slotted & Philips screwdriver, knife, bottle opener, flashlight)

Magnetic Tool Holder

MAGWRENCH

Packing: 1

- Industrial strength magnets keep it secured to a metal surface
- Holds tools for quick and easy access



- Chrome plated steel bar with chrome plated nylon ends
- Overall size is 20" (with approximately 12" of magnetic holding space)





Door and trim panel tool set, 19pcs (Plastic)

BLPDTPS19AP





- Avoid scratches or permanent dent on car surfaces when using door trim tools
- Constructed from heavy-duty plastic nylon fibre
- Cloth pouch for easy tool storage and access while working on your project
- Body panel removal tool package includes -
 - (11) plastic crowbar interior trim tools,
 - (5) audio disassembly tools,
 - (1) clip removal pliers,
 - (2) door upholstery fastener removers,
 - (1) storage bag

Door Lockout Set

LOS145B





- No danger of airbag activation or disconnected door linkages
- Actuate the door handle, manual lock button or electric lock button on most cars and trucks
- Includes:
 - 4 pcs door-unlocking tool that screws together without couplers for easy assembly and storage, plastic slim jim, 2 glow-in-the-dark tips, 2 plastic wedges to create gap between door and frame without damaging door or weather stripping and BF272 inflatable wedge
- Use the BF272 to easily separate door from body without damage to the vehicle
- Unlocking tool features a middle extension piece to reach across the car in extended use applications
- For sale to registered locksmiths, police and bona fide repair professionals only

Riveters / Extractors / Grease Guns

Air Riveter

HP301C



- Sets structural rivets, KLIK-FAST® rivets from 5/32" to 1/4" diameter in all alloys plus KLIK-SPLIT® / Monobolt rivets from 3/16" to 1/4" Includes 5/32", 3/16" and 1/4" nosepieces plus
- mandrel collection bottle

		-
PART NO.	RECOMMENDED AIR PRESSURE (psi)	
HP301C	85-95	
AIR INLET THREAD SIZE	TRACTION POWER (lbs)	
1/2" NPT	3,300	1
STROKE	WEIGHT (kg)	
5/8" (15.8 mm)	3.0	



Pivot Riveter





• 360° swivel head for easy riveting in narrow and awkward places at any angle

Positive-Lock Rotation for turning and holding swivel head in positive lock position to avoid undesired rotation that may result in poor riveting job

- Superior materials, high strength aluminum head and body
- Heavy duty steel handle, hardened steel parts
- Durable powder coating with polished logos
- Ratchet sound for alerting desired or unexpected rotation of swivel head



Thread Setter Kits

HP650 / HP650M

Packing: 1

HP650

- Includes: rugged thread setter tool and an assortment of fractional
- Klik Poly-Nuts: 12 each 8-32, 10-24, 10-32; (8) 1/4"-20 and (6) 5/16"-18 threads
- Includes required nosepieces and mandrels for setting the above sizes
- Packaged in a storage case

HP650M

- Metric version of the HP650 with metric poly-nuts, including 25 each 4 and 5mm, (15) 6mm and (10) 8mm threads
- Includes thread setter tool, required nosepieces and mandrels packaged in a storage case



Extractor Set

E1020

Packing: 1


- Extracts broken screws from 1/4" to 1/2" diameter
- Storage case packaging



Industrial Hand Riveter

HR-26

Packing: 1



- Anti-wear design with high strength aluminum body and steel insert
- Special shock absorber on body
- Auto-ejection design allows quick replacement of inside worn parts such as jaws, by removing retaining screw
- Long leverage and power saving design; extra long handles 260mm for better leverage to save hand force



Extractor Set

E1025

- Extract broken screws from 1/4" to 1" diameter and standard pipe sizes 1/8" to 1"
- Storage case packaging











Grease Gun, Air

YA772B

- Packing: 1
- Automatic operation provides continuous grease flow with trigger depressed
 Pumps at a 40:1 ratio with a maximum
- Pumps at a 40:1 ratio with a maximum pressure of 6,000 PSI
- Use with standard 14 oz. cartridge, bulk fill or filler tube
- Heavy duty 18" flexible nylon hose improves accessibility and reach
- Air vent allows easy removal of trapped air after loading grease tube
- Light weight of 3.52 lbs
- Helps reduce operator fatigue




PART NO.	PSI	Air Operating (psi)	Pump Ratio
YA772B	4,000	60 - 150	40:1
Capacity	Flexible Hose (inches)	Rigid Extension (inches)	Loading

Grease Gun, Lever

YA728A

- Packing: 1
- Lever operated, large capacity gun accepts 16 oz. bulk or 14 1/4 oz. cartridge grease
- Develops 6,000 PSI
- Includes tough, 18" flexible whip hose with coupler and 6" rigid extension



PART NO.	PSI	CAPACITY
YA728A	6,000	16 oz. Bulk and 14 1/4 oz. Cartridge
FLEXIBLE HOSE (inches)	RIGID EXTENSION (inches)	LOADING

Grease Gun, Pistol Grip

GA472

Packing: 1

- Standard series grease guns
- All are steel with zinc plating
- Inner-spring chamber can be either cartridge or bulk loaded



PART NO.	PSI	NOZZLE (inches)
GA472	5,000	13 1/4
CAPACITY (oz.)	RIGID EXTENSION (inches)	LOADING

Grease Gun, Pistol Grip

YA734A

- Develops 6,000 PSI maximum pressure
- Pistol grip unit features suction, cartridge, or filler pump loading
- Includes flip over follower, 18" flexible hose,
 6" rigid extension and hydraulic coupler



PART NO.	PSI	CAPACITY
YA734A	6,000	16 oz. Bulk and 14 1/2 oz. Cartridge
FLEXIBLE HOSE (inches)	RIGID EXTENSION (inches)	LOADING



Grease Guns / Spray Guns / Bench Vise

Oil Suction Gun

YA745A

Packing: 1

- 16 oz. capacity
- Fast, clean method for removing or adding transmission and gear oil



- Special follower is impervious to oil, grease, and water

1.4 HVLP Spray Gun

BLPK14HVLP



- Lightweight and comfortable for all kinds of painting jobs
- Provides superior spray performance
- Stainless steel needle and tip



PART NO.	FLUID TIP (mm)	AIR CONSUMPTION (scfm)	AIR INLET THREAD SIZE
BLPK14HVLP	1.4	14.5	1/4" NPSM
FLUID (WATER (mL/n		AIR PRESSURE RANGE (psi)	CUP SIZE (cc)
190 to	250	30 to 43	600

HVLP Spray Gun



- Designed for the automotive refinishing painter, Blue-Point[®] spray guns are lightweight and feature great balance while delivering a quality, first class automotive finish
- A new generation of Blue-Point® spray guns for primer, base and clear coat
- · Lowest trigger pull among guns in their class
- Unmatched spray pattern size and quality repair kits
- Optional interchangeable 125cc, 250cc and 600cc aluminum cups are available
- Optional 3M PPS adaptor is also available



PART NO.	FLUID TIP (mm)	AIR CONSUMPTION (scf m)	MAX. INLET HVLP psi (bar, kpa)	DRY WEIGHT WITHOUT CUP oz (grams)	AIR INLET THREAD SIZE	CUP SIZE (cc)	APPLICATION
BLP13HVLP	1.3	9.5	29 (2.0, 200)	12.6 (359)	1/4" NPSM	600	High solids, colors and clears
BLP14HVLP	1.4	9.5	29 (2.0, 200)	12.6 (359)	1/4" NPSM	600	High solids, colors and clears
BLP15HVLP	1.5	9.5	29 (2.0, 200)	12.6 (359)	1/4" NPSM	600	Medium solids, colors and clears
BLP18HVLP	1.8	9.5	29 (2.0, 200)	12.6 (359)	1/4" NPSM	600	Primer, high viscosity materials





1.0 Mini HVLP Spray Gun

BLP10MHVLP





PART NO.	FLUID TIP (mm)	AIR CONSUMPTION (scfm)		AIR INLET THREAD SIZE
BLP10MHVLP	1.0	7.0		1/4" NPSM
MAX. INLET HVLP psi (bar, kPa)	DRY WEIGHT WITHOUT CUP oz (grams)	CUP SIZE (cc)	AF	PPLICATION
29 (20, 200)	11.4 (322)	125	Prime	er, base and clear

1.4 Conventional Spray Gun

BLP14CONV





PART NO.	FLUID TIP (mm)	AIR CONSUMPTION (scfm)	AIR INLET THREAD SIZE
BLP14CONV	1.4	9.5	1/4" NPSM
DRY WEIGHT W oz. (gra		CUP SIZE (cc)	APPLICATION

Bench Vise

Packing: 1

- Single piece steel blocks for higher load capacity
- Extended anvil
- Lubrication points for maintenance
- Optional swivel base
- Capacity range from 3.5 ton to 9 ton at maximum opening
- Reinforced cantilever support
- Interchangeable jaws
- Diamond ground for better grip
- Heavy duty cast iron construction
- Precise jaw alignment
- Rolled thread spindle for easy locating and tightening parts
- Protected spindle



PART NO.	JAW WIDTH (inches)	
BLPMV4	4	
BLPMV5	5	
BLPMV6	6	

Bench Vise

- Heavy duty, used for a variety of shop application
- Medium carbon steel serrated jaws, replaceable
- Built-in pipe handle with chrome finish
- Swivel base and large anvil to handle a variety of jobs
- Available in 4 sizes: 4", 5", 6" and 8"



PART NO.	JAW WIDTH (inches)
BLPM4A	4
BLPM5A	5
BLPM6A	6
BLPM8A	8

41.5" Curved Fiberglass Prybar

PBFG415





- Drop forged, hardened steel wedge end with rustresistant black finish, is chemically bonded to fiberglass handle
- 50,000 strands of fiberglass are sleeved by a polypropylene jacket for comfort and variable hand placement during use
- About one-half the weight of a steel prybar of the same length and less flexible than a steel prybar for greater
- Polypropylene sleeve is resistant to heat and cold for greater comfort in all temperatures

Prybar Set

BLPPB704

Packing: 1

All bars have a 100% black oxide finish



PART NO.	CONTENTS	LENGTH (inches)
BLPPB704	1412A Pinch Bar	14
	2420A Pinch Bar	20
	7031A Close Quarter Bar	16
	BPPC1878 Flat Chisel	18

Pinch Bars

- Pinch bars are used to align, adjust and move metal and wood
- Angled chisel end for extra leverage when prying



PART NO.	SQ. STOCK (inches)	EDGE (inches)	LENGTH (inches)
1412A	1/2	5/8	14
1658C	1/2	5/8	16
2420A	3/4	15/16	20
2430C	3/4	5/8	30
2438C	3/4	7/8	38
2842C	7/8	1	42





C-Clamp Compressor

CF19B

Packing: 1

 This compact model includes CF19-3A Jaws for 1/4" to 1 1/16" diameter springs on small,



air cooled engines and CF19A5 Jaws for both 17mm and 20.8mm diameter springs on Honda engines

C-Clamps

Packing: 1

- Similar to CL series c-clamps
- High visibility models conform to OSHA safety color standard for physical hazards regulation #19110.144
- 3/4" spindle diameter



PART NO.	CAPACITY (inches)	THROAT DEPTH (inches)
CL404VIS	0 - 4 1/2	3 1/4
CL406VIS	0 - 6 1/16	3 5/8
CL408VIS	0 - 8 1/4	5

C-Clamp Compressor

CF811B

Packing: 1

- 1" to 2" capacity
- For "L" head, valve-in-head, high compression engines and vehicles with overhead valves



 Activating mechanism prevents cocking of valve spring as it is compressed

Airconditioning Services

Bender, Tubing

TBS200A

Packing: 1

- Makes left, right, or offset bends up to a 90° angle
- Degrees shown for accurate bending angle
- Handles 3/16", 1/4", 5/16", and 3/8" (4, 6, and 8mm) OD aluminum, copper, and stainless steel tubing Aluminum unit is 8 1/4" long when opened



Deburring Tool

DEBUR300

- Easily deburr drilled and machined holes
- Push button locking collet enables quick, easy blade changes
- Includes three round head deburring blades
- Blades conveniently store in handle of tool
- Weighs 1 lb
- 6" long



Manifold Set

ACTR4131A



- Anti-flutter gauges smooth out needle movement
- Easy grip all metal side mounted knobs
- Piston type free floating valves reduce O-ring wear
- Manual R134a couplers



- Gauges can be recalibrated to maintain accuracy
- 60" inner nylon layer hoses meet EPA, SAE, and **UL** standards
- Yellow hose includes shut off valve

Manifold Repair Kit

ACT1234PKT



- Includes various replacement lens, knobs, O-rings, gaskets and more
- Kit components are used to service ACTR41511









Replacement Hose (R12)

ACTB72A / ACTY72A Packing: 1

ACTB72A

- Automatic shutoff valves
- Blue, 6' length

ACTY72A

- Automatic shutoff valves
- Yellow, 6' length

Replacement Hose (R12)



ACTB72

- 1/4 turn manual shutoff valves
- Blue, 6' length

ACTY72

- 1/4 turn manual shutoff valves
- Yellow, 6' length

Replacement Hose (R134a)

ACTRB72 / ACTRR72 / ACTRY72 Packing: 1



ACTRB72

• Blue, 6' length

ACTRR72

· Red, 6' length

ACTRY72

- Yellow, 6' length
- Low permeation hoses for internal equipment connections

Replacement Hose (R134a)

ACTRB96 / ACTRP96 / ACTRY96



ACTRB96

• Blue, 8' length

ACTRR96

· Red, 8' length

ACTRY96

Yellow, 8' length



• Low permeation hoses for internal equipment connections

Airconditioning Services

Double Flaring Tool Sets



Packing: 1



TF5A Imperial Double Flaring Tool Set

- · Makes double or single flares on soft steel, brass, or aluminum tubing from 3/16" to 1/2" OD
- Makes a smooth fitting, crack free 45° flare
- Set includes five adaptors, yoke assembly, bar assembly, and handle
- Storage case included

TFM5A Metric Double Flaring Tool Set

- Same design as TF5A except it is for tubing with an OD from 4.75 to 10mm
- Set includes yoke, bar assembly, handle, and five adaptors: 4.75, 5, 6, 8, and 10mm
- Storage case included

Flaring and Swaging Set

TF275A



- 45° flare or swage soft copper, brass, or aluminum
- Die blocks handle 1/8", 3/16", 1/4", 5/16", 3/8", 7/16", 1/2", 5/8", and 3/4" OD tubing
- Swages 3/16", 1/4", 5/16", 3/8", 1/2", 5/8", and 3/4"
- TF275PB storage case included







Tube Cutting and Double Flaring Set

TF528D





- Contains TC28C tubing cutter and a double flaring set with a flaring bar, rod handle, yoke, and 5 adaptors (3/16", 1/4", 5/16", 3/8", 1/2")
- Storage case included

Metric Bubble Flaring Set

TFM428





- For automotive brake systems
- Designed for crack free bubble flares on soft wall tubing up to a wall thickness of .028"
- Adaptors included for 4.75, 6, 8, and 10mm flares
- TFM428PB storage case included



Airconditioning Services / Wheels & Tires

Manual A/C Hose Crimper

ACTMAN2100

Packing: 1

• Unit is easily mounted to bench with holding fixture or held securely in a vise



- Includes a complete set of dies covering standard #6, #8, #10 and #12 hose sizes
- Includes storage case

Wheel Lock Kit

LSR1000A

Packing: 1

- Wheel Lock Removal Socket Set
- Easily removes most lug nuts and wheel locks on most domestic and import passenger vehicles and light trucks



- Use with hand driver or impact wrench
- Some sockets cover specific GM, Ford and Chrysler applications
- Set includes 11 sockets, extension and extractor punch in storage case

Core Service Tool

ACT81290

Packing: 1



Use on R12/R134a standard valve cores and JRA/ EATON large bore R134a valve cores

Fin Straightener & Cleaner

ACT407

Packing: 1



- Multi-head tool handles 8, 9, 10, 12, 14, 15 fins per inch
- 4 1/4" long

Spanner Wrench

ACT499A



- Adjustable three stud design for GM R-4 compressors
- Also has applications on some GM, Warner, Pitts, and Ogura clutches





Universal Valve Core Tool

VT14

- Packing: 1
- Double ended wrench removes and installs large and small valve cores
- Reverse the double ended wrench in the tool body to fit both large and small valve cores
- Use the cup end to remove valve caps



- Valve Stem Inserters
- Simplify installation of valve stem in tubeless tire rim
- Shank is notched to accommodate various rim styles
- Has a comfortable, screwdriver type handle
- 12" long

1/2" Torque Stick



- Take the guesswork out of tightening lug nuts
- Strobe marks stop turning at precisely the correct torque on each and every job



- Engineered for rugged professional environments
- Manufactured with heat-treated spring steel in a solid one-piece design
- Sticks are individually packaged
- This is an extension use your existing sockets for different sizes

PART NO.	COLOR	TORQUE LIMIT (ft.lbs)	
BLPTSK65	Yellow	65	
BLPTSK80	Dark Blue	80	
BLPTSK90	Beige	90	
BLPTSK100	Grey	100	
BLPTSK120	White	120	
BLPTSK140	Aqua Blue	140	
BLPTSK160	Green	160	
BLPTSK175	Red	175	
BLPTSK190	Purple	190	
BLPTSK200	Brow	200	

Flush Kit

ACT1046C

Packing: 1

Provides pressure flushing of condensers, evaporators, and refrigerant lines after the A/C system is completely discharged



- Designed to work with any lightweight flushing material that can be mixed with pressurized air
- Includes flush gun, hose, canister, and canister adaptor

1/2" Torque Stick Set, 5pcs

BTQS500



- Entry level set covers the most popular models
- Size ranges from 19 to 22mm
- Torque range from 80 to 147 ft. lbs
- 1/2" drive
- Includes BTQS12B, BTQS12BB, BTQS12C, BTQS12EE and BTQ12SI (5 pcs) in BTQSCASE storage case

Cooling & Oil Systems

Cooling System Pressure Tester

- Packing: 1
- Inflatable bladder sealing system enables use with most passenger and light commercial vehicles
- Tests header tanks and radiator systems as well as thread type and bayonet-style caps
- Locate leaks from head gaskets, radiator and heater cores, Welch plugs and housings, water pumps and hoses



- · Test cap relief pressure and seal condition
- Suitable for marine applications
- Fluid drain tube allows coolant to be returned to reservoir or safely collected for recycling
- Bladders are cycle tested to over 1,500 inflations

Gas Cap Adaptor

EELDGASCAP1





- · Quickly pops-on virtually any filler neck
- Costly replacement seals are no longer needed
- One size fits all (new model vehicles may be subject to change)

Cooling System Adaptor Set

SVTAB1400



- TAB Series Adaptors feature a composite metal/plastic construction for a lower cost option
- Set includes 14 radiator composite metal/plastic radiator adaptors



- Includes all TAB Series Adaptors plus TA4503 Adaptor
- PBSVTA1417 Storage Case has a removable cover for display purposes

Hose Nozzle

NOZZLE360A



- Turns any standard 5/8" hose into a multi-function cleaning tool
- Five different spray patterns for multiple applications
- Wash/rinse vehicles or water plants using a softer, cascading stream
- Clean pools, deck and driveways with heavy duty



- Clean service bays, shop floors and blast mud/dirt from vehicles with a powerful jet stream
- 360° jetted nozzle is engineered from rugged extruded aluminum, forged stainless steel, high grade fiberglass and comfort grip santoprene rubber
- Patented 2-way shut off







Oil Filter Wrenches

Packing: 1



PART NO.	SIZE (mm)	STEPS	FLATS	STYLE	SQ. DRIVE (inches)	APPLICATION
FW656714A	65, 67	2	14	Cup	3/8	Fram-PH4386, PH4967, PH6017, PH6018, PH6607
FW757715A	75, 77	2	15	Cup	3/8	NAPA, AC Delco, Castrol, STP, Penske
FW7630A	76	1	30	Cup	3/8	Fram, IAPCO, Motorcraft, Parts Plus, Pennzoil
FWA62121A	62, 121	-	-	Adjustable	3/8	Adjustable filter wrench for 62 to 121mm diameter oil filters, 3/4" external hex

Oil Filter Strap Wrench

BLPOFSW





- Use on spin-type oil filters up to 6" diameter
- Cold rolled steel bracket
- Strong nylon belt prevent slippage
- Use with 1/2" ratchet

Heavy Duty Toyota Oil Filter Tool

OFTOY468



 Suits all Toyota and Lexus models with catridge style engine oil filter



- 65mm across flat
- Manufactured from heavy duty chrome vanadium material to withstand loads required to remove frozen oil filter covers
- 1/2" square drive and 24mm (15/16") hex

Cooling & Oil Systems

Master Line Disconnect Set

LDT8

Packing: 1

- A complete set of disconnect tools for spring lock and quick disconnect couplings used on air conditioning and fuel lines on Ford, GM and Chrysler vehicles
- Includes a set of six standard disconnect tools (5/16", 3/8", 1/2", 5/8", 3/4" and 7/8") and six color coded, angled disconnect tools for use in tight spots



- SPECIALIZED GM APPLICATIONS: Includes tools for use on GM 3/8" flex fuel capable fuel filter removal plus 5/16" and 3/8" GM fuel modules
- SPECIALIZED FORD APPLICATIONS: Includes tools for use on 3/8" and 1/2" Ford transmission and cooler lines with stepped line plus 5/16" x 3/8" scissor disconnect and Ford coupler disconnect tools

Master Plus Disconnect Set

LDT14



Packing: 1

- LDT14 contains all tools from the popular LDT8, Master Disconnect Set; in addition the kit has:
- The two most popular Jiffy-tite Disconnect tools



- The new blue 5/16" fuel line adapter
- A set of 4 air line push-pull disconnect tools that work on heavy duty trucks and industrial applications
- Label inside cover of carrying case shows images and applications

Line Clamp Set

HCP3KT



• HCP6A, HCP7A and HCP10A (6", 7", 10") in storage pouch

HCP6A Hose Pinching Pliers

- For sealing hose sizes 1/8" to 5/16"
- Also use on brake lines, fuel lines and vacuum hoses
- 6" long

HCP7A Hose Pinching Pliers

- For sealing hose sizes 1/2" to 3/4"
- Also use on heater hoses and vacuum lines
- 7" long

HCP10A Hose Pinching Pliers

- For sealing hose sizes 3/4" to 2 1/4"
- Also use on radiator hoses
- 10" long







Disconnect Set

ACT1370 Packing: 1



- Set includes six tools for disconnecting spring couplings on fuel lines
- Convenient plastic holder included
- Also useful on A/C spring couplings as well as push lock connectors on radiator and transmission lines
- Includes six tools for disconnecting spring couplings on Ford, GM, and Chrysler A/C lines
- Works on fuel lines and can be used as push lock connectors on radiator and transmission lines
- Included sizes are 5/16", 3/8", 1/2", 5/8", 3/4" and 7/8"

Gasoline Engine Injector Set

BPENGKIT



- For test gasoline fuel injection pressure
- Ideal for most American, Asian and European cars



- Set includes pressure gauge, hose, hook for securing gauge to under vehicle's hood, 34 size types of fuel valves
- Blow mold
- **Not to be used on diesel engines

3/8" Drain Nuts

BLPODKIT

- 3/8" sq drive: 15 pcs oil drain kit
- 14 different socket sizes (8-17mm) and 1 pc sliding T-handle bar



- Suitable for transmission, differential and gear oil plugs
- Blow molded case



Cooling & Oil Systems

Manual Fluid Dispenser

VAC201

- Packing: 1
- Easily remove engine oil, gear and transmission oil, coolant and brake fluids
- Unit creates vacuum or pressure providing a clean, fast and simple way to evacuate or dispense a wide range of fluids
- Automatic shut off prevents the overflow of the reservoir tank with shut off at 8 liters



- 2.3 gallon (8.8 liter) total capacity
- Durable polyethylene construction is impervious to automotive and house hold chemicals
- No electrical or compressed air required
- Sturdy base with exterior pump helps prevent evacuator from tipping
- Complete system includes manual fluid evacuator, main hose assembly (5/16" ID x 54" long) plus two rigid dipstick tubes for engine oil removal (3/16" ID x 34" and 1/8" ID x 34")

Terminal Brush

BTC3A



- Stiff wire bristles thoroughly clean posts and clamps
- 3 3/8" long

Serpentine Belt Tool Kit

YA9350B

Packing: 1

Hex Applications

YA9350-6 (13mm or 1/2") - GM "Quad 4" 2.3L and Volkswagen 2.0L

(14mm) - Isuzu 3.1L, Lexus (2.5L, 3.0L, 4.0L), Mazda (2.3L, 3.0L, 4.0L), Saturn YA9350-2 1.9L with 4mm hex on idler pulley,

Toyota 3.0L, Volkswagen (1.8L, 2.5L, 2.8L) (15mm) - GM 2.2L, Isuzu 2.8L, Jeep 4.7L

YA9350-8 YA9350-7 (16mm or 5/8") - Ford / Lincoln / Mercury (2.3L, 3.8L, 4.0L, 4.9L, 5.0L, 5.8L),

GM (4.3L, 5.0L, 5.7L) YA9350-3 (18mm) - GM (2.0L, 3.1L, 3.3L, 3.4L, 3.8L) YA9350-9

(19mm or 3/4") - Mercedes (use with 15mm adapter for extra reach), Toyota (1.8L, 2.4L)

Wrench Only - Dodge / Chrysler / Plymouth (3.0L, 3.3L, 3.9L) (has 15mm drive), Ford/Lincoln/Mercury (2.3L, 3.0L, 3.8L)



Square Applications

YA9350-4 (3/8") - Ford/Lincoln/Mercury (1.9L, 2.3L,

2.5L, 4.0L), GM (2.0L, 2.2L, 2.8L, 3.1L,

3.4L), Isuzu (2.8L, 3.1L)

YA9350-5 (1/2") - Dodge/Chrysler/Plymouth (2.0L,

3.0L), Ford / Lincoln/Mercury (2.3L, 3.0L,

4.2L, 4.6L)

Serpentine Belt Tool

SBT26



- Works on all serpentine belts
- Clamping jaw allows user to position serpentine belt without the belt slipping out of the tool



- · Positive grip allows belt routing in tight access areas that would normally be difficult to reach
- Ergonomic handle provides comfort and ease in use, acting as an extension of the user's hand
- Lightweight steel body for durability and strength







12" Hose YA751 Packing: 1

- For powered and hands operated grease guns
- 1/8" NPT(m) both ends
- 4,500 maximum PSI
- 12" long



Adaptor, Needle Type

YA801 Packing: 1

- For universal joint fittings, water pumps, and metal covered springs
- 4 7/8" long

Accessory Pack, Grease-dispensing

YA7500

• Includes 10 pcs. as follows in a storage tray:

Universal swivel
Needle nozzle coupler
Flex whip hose 12"
Flex whip hose 18" (for manual grease guns)
Flex whip hose 18" (for powered grease guns)
Heavy duty coupler
Swivel coupler
Coupler
Coupler extension
Angle lube adaptor





Cooling & Oil Systems / Steering & Brakes

Bearing Race and Seal Driver Set

A1310A

Packing: 1



- Collars fit most standard wheel bearing sizes
- The three largest sizes fit most late model 4 wheel drive vehicles

Ring Compressors

Packing: 1

- Clutch control holds tension band in position as piston is inserted into cylinder
- 1/2" wide spring bands equalize tension over belt width so ring assembly may be compressed into groove until flush with piston



- "V" beads on lower edge of belt keep tool from entering cylinder
- RC40C can be used upside down for Chevrolet, Mercury, and Ford trucks with angled blocks

PART NO.	BAND	CAPACITY (inches)	DEEP (inches)	
RC40C	2	2 ½/8 to 5	3 1/2	
RC50C	2	3 1/2 to 7	3 1/2	

Pad Spreader

YA2440



- For use on most domestic and import cars and light duty trucks with single piston disc brakes without parking brakes
- Compresses the disc brake piston for easy pad installation

Spreader

GA395



- For standard four piston caliper disc brakes
- Frees hands to assemble caliper over rotor
- 6 3/4" long

Throttle Depressor

B240B



- · Holds throttle at a constant RPM
- Easily adjusts to desired length
- Adjustment screw fine tunes desired RPM



- Rubber tip keeps the tool firmly positioned on the accelerator pedal
- Can also be used as a pedal depressor
- Overall length of 40" (102cm)







Brake Service Tools

YA4000B

- Packing: 1
- Produces vacuum or pressure at the turn of a switch
- Comfortable ergonomic design
- One finger trigger vacuum/pressure release
- Durable, accurate diaphragm type pressure/ vacuum gauge
- Handheld vacuum/pressure pump with 2" compound gauge and rubber boot
- 12 oz. fluid reservoir bottle with fluid transfer and storage lids plus fluid pick up tube



- 6 tapered adaptors for connecting to tubing from .09" to .50" ID
- 2 tapered manifold plugs
- 2 universal bleed screw adaptors
- 12 vacuum cap plugs, vacuum line T-adaptor
- (2) 1/4" ID x 24" long connection tubes with quick-change connector
- 5/32" ID x 1/4" ID tubing adaptor
- 5/32" ID x 3" long vacuum test tube
- Rubber cupped adaptor
- Master cylinder refill kit Applications:
- Vacuum and pressure related engine performance diagnostics and tune-ups
- Brake bleeding
- Fluid transfer, evacuation and sampling

Brake Rotor Tool

YA9329A



- Use to rotate piston back into caliper cylinder when replacing pads
- Also rotates parking brake cylinder back into the caliper cylinder on vehicles with four wheel disc brakes
- For 1975 and later Ford and Mercury plus some imports

Master MacPherson Strut Tool

MSC1





- Designed to quickly and easily compress most MacPherson strut springs
- Compresses up to 5/8" (.625mm) coil diameter
- Broad spring contact for stable compression
- Acme threaded rod and built in detent latches to help lock coil in place
- Forged construction for strength and durability

Power Steering Adaptor Kit

YA4008





- Aids in the removal of trapped air from power steering systems.
- Adaptor designed to fit snuggly in the neck of the power steering reservoir to form an air-tight seal when vacuum applied



Steering & Brakes / Engines / Cleaning

Cam Lock Tool Set

ML6000COMBO

- Packing: 1
- Includes (4) CC100 Single Cam Clamps and (1) ML6000 Dual Cam Clamp in storage tray
- Single cam clamp can be used on engines where the dual clamp will not fit
- Compact design permits easy operation in confined engine areas
- Simple and easy to use



- Manufactured from high strength industrial polymers which will not corrode or damage engine pulleys
- Dual cam clamp prevent engine damage resulting from incorrect timing
- Maintain valve timing during belt replacement on twin and quad cam engines
- Compact design allows access in transverse engines
- Fits timing gear diameters from approximately 4" (101mm) to 6" (152mm)
- Fits gear spacing from approximately 0.06" (1.6mm) to 3" (76mm)

Ring Compressor Set

RC980





- Works both horizontally and vertically with pliers grip handle
- Has a fine tooth ratcheting mechanism
- Includes 6 hardened steel bands: 2 7/8" to 3 1/8", 3 1/8" to 3 3/8", 3 3/8" to 3 5/8", 3 5/8" to 3 7/8", 3 7/8" to 4 1/8", and 4 1/8" to 4 3/8"

Valve Spring Compressor

CF700B





- Operates on 90 PSI to 150 PSI, but develops up to 3 times output pressure
- 7/8" to 2 1/2" capacity
- Tool measures 1" x 8"

Coil Spring Compressor

MSC2





- Removes and installs coil springs quickly and safely
- Compresses coil springs on all passenger cars and pick up trucks
- Features Acme threaded rod







Vacuum Cleaner - Shop

YB30VU

- Packing: 1
- Powerful 1300 watts output motor
- Water lift of 100 inch
- 30L HD stainless steel tank
- Wet and dry function
- EVA hose 3m , Cord 9m

Available Accessories:

- PET Washable Cartridge Filter
- 1 Steel Elbow w/ Air Flow Adjuster
- Round Brush with Horse Hair









Crevice Tool





Deluxe Air Vacuum System

AV1000A

Packing: 1

- Ideal for vehicle media installation and body shops plus other applications in need of picking up dust, metal shavings or broken glass
- Large collection bag includes a debris baffle and sliding bag clamp for emptying debris
- Lightweight ergonomic handle design
- Includes 8.7" aluminum extension tube 8 1/2" plastic extension tube (AV1000A10), flexible extension tube (AV1000A9), pointed nozzle



. (AV1000A11) and crevice tool with brush (AV1000A8)

PART NO.	AIR CONSUMPTION, AVERAGE, DFM (scfm) [l/min]	SOUND LEVEL, FREE SPEED, (dBa)
AV1000A	3 (21) [84.95]	81.2
SOUND LEVEL, WORKING (dBa)	RECOMMENDED HOSE SIZE (inches)	LENGTH (WITHOUT BAG), INCHES (mm)
81.2	3/8	13 (330)
BRUSH SIZE, inches (mm)	BAG SIZE, inches (mm)	WEIGHT, lbs. (kg)
1 ¹ /8 x 2 ⁵ /8 (28.5 x 66.7)	6 ½ x 11½ (165 x 285)	0.88 (0.4)

Industrial Paper

BPAP1



- Excellent for cleaning off oil and residue from tools, hardware, equipment and mechanical components
- Tough for industrial use
- Lint free to prevent electrostatic charge as well as a clean surface
- Made from cellulous and polypropylene for better absorbability



PART NO.	SIZE (mm)	COLOR	PIECES / ROLL
BPAP1	310 * 340	White	1100

Industrial Paper

BPAP2



- Excellent for cleaning off oil and residue from tools, hardware, equipment and mechanical components
- Tough for industrial use
- Lint free to prevent electrostatic charge as well as a clean surface
- Made from cellulous and polyethylene for softness and finer surface





PART NO.	SIZE (mm)	COLOR	PIECES / ROLL
BPAP2	250 * 350	Green	300



Important Words About Safety for Users and Bystanders

Following these basic safety rules is a good start toward protecting yourself and others in the vicinity from injury while using tools

- Wear safety goggles
- Use the right tool
- Use the tool properly
- Maintain the tool regularly
- Keep tools away from children
- Do not use tools on live electrical circuits unless specifically designed for such use
- Read and follow instructions

Hazard Alerts Prohibited Actions Mandatory Actions THIS SYMBOL THIS SYMBOL INDICATES THIS SYMBOL PROHIBITED ACTION **INDICATES INDICATES MANDATORY ACTION** A HAZARD ALERT RED BACKGROUND - DANGER DO NOT OVER-TORQUE MANDATORY EAR ORANGE BACKGROUND - WARNING YELLOW BACKGROUND - CAUTION NO PIPES OR LEVER **PROTECTION EXTENSIONS** NO HAMMERING **MANDATORY** VIBRATION HAZARD FACE SHIELD **NO PRYING** MANDATORY MASK RISK OF EXPLOSION DO NOT STRIKE HARD OVERHEAD / **MANDATORY OBJECTS** OVERLOAD HAZARD **RESPIRATOR MANDATORY** NO IMPACT / RISK OF ELECTRIC PROTECTIVE CLOTHING **POWER DRIVE** SHOCK DO NOT STEP IN OR MANDATORY ON DRAWERS PROTECTIVE GLOVES RISK OF FIRE DO NOT OPEN MULTIPLE MANDATORY EYE **RISK OF** DRAWERS **PROTECTION ENTANGLEMENT** MUST READ DO NOT PULL TO MOVE **INSTRUCTIONS BEFORE USE** KEEP CHILDREN AWAY

Safety messages in this catalog use the guidelines of the American National Standard ANSI Z535. 4 for Product Safety Signs and Labels and ANSI Z535.3 Criteria for Safety Symbols. Messages associated with specific products use a triangular hazard alert symbol, signal word (CAUTION, WARNING, DANGER) and how to avoid the hazard.

PLEASE READ AND FOLLOW these messages to avoid injury to yourself and bystanders.



1/4"	Socket Drivers	
	Torx®	59
1/4" Square Drive Tools	Hex	59
Adaptors53 - 54	Phillips®	60
Automotive Tool Kit Set11,13,18	Pozidriv®	60
Bit Socket Sets	Flat Tip	60
Bit Sockets51 - 52	Triple Square	60
Breaker Bar52	Socket & Wrench Kit Set	23
Extensions53	Universal Joints	62, 64
Handles52		
Impact Wrench158		
Ratchets45, 47, 165 - 166	4 /011	
Sockets, Torx®50 - 51	1/2"	
Socket Drivers	1/2" Square Drive Tools	
Torx®50 - 51	Adaptors	70. 72
Hex50 - 51	•	
Phillips®51 - 52	Bit Sockets	
Pozidriv®51	Breaker Bar	
Flat Tip52	Bit Socket Sets	-, , -
Triple Square52	Extensions	- /
Universal Joints 53	Flip Impact Socket Set	
	Handles	
	Impact Socket Set	
	Impact Sockets	
1/4" & 1/2"	Impact Wrench	
1/4" & 1/2" Square Drive Tools	Plastic Lug Socket Set	
-	Ratchets	
Socket & Tool Kit Set16	Sockets, Torx®	
	Torque Stick Set Universal Joints	
1/4" & 3/8" 1/4" & 3/8" Square Drive Tools Socket Kit Set	3/4"	
	3/4" Square Drive Tools	
	Adaptors	76
4/4 0 0/0 0 4/0	Breaker Bar	73
1/4" & 3/8" & 1/2"	Extensions	73, 76
1/4" & 3/8" & 1/2" Square Drive Tools	Handles	73
Automotive Tool Kit Set11,13	Impact Sockets	75 - 76
Sockets, Torx®	Impact Wrench	
Socket & Tool Kit Set	L-Shape Wrench	
Socket & Wrench Kit Set	Ratchets	
	Universal Joints	
2/011		
3/8"	1"	
3/8" Square Drive Tools	-	
Adaptors62 - 64	1" Square Drive Tools	
Automotive Tool Kit Set21	Adaptors	78
Bit Socket Sets	Impact Sockets	
Bit Sockets	Impact wrench	
Breaker Bar60	Extensions	
	Universal Joints	
Extensions	0111701001 00111t0	70
Handles		
Impact Socket Set		
Impact Wrench		
Ratchets56, 166 - 167		

Sockets, Torx®......59



Abrasion Resistant Nitrile Gloves		213
Accessories		
Adaptor, Air Line		180
Couplers, Air		180
Adaptor		
1/4" Drive	53 -	- 54
3/8" Drive	62 -	- 64
1/2" Drive	70 -	- 72
3/4" Drive		. 76
1" Drive		. 78
Air Line		180
Gas Cap		242
Power Steering		248
Needle Type		246
Oil Injector		240
Spinner		. 53
Adaptor Sets		
Cooling System		247
Adjustable		
Joint Pliers	. 116,	121
Torque Wrenches		. 82
Wrenches5,	8, 93 -	- 94
Air		
Grease Gun		230
Hammer	·	163
Hoses	·	179
Line Couplers & Adaptors	·	180
Riveter		229
Shears	·	170
Screwdriver	174 - '	175
Vacuum		250
Valve		191
Amp		
Meter	·	196
Angle		
Drill	·	162
Grinder	166 - 1	168
Locator		187
Shears		152
Antifreeze Hydrometer		190
Automatic		
Center Punch		148
Meter		197
Wire Stripper		224
Automotive		
Amn Meter		196

Tool Sets......11,13,18,21

-1	_
-	_

Bags	
Tool	44
Tote	44
Backpack	44
Ball Hex	
Bit Set	. 136
Ball Peen Handle	. 142
Ballon Jacks	
Battery	
Carrier	200
Tester	
Charger, Shop	
Bearing Race & Seal Driver Set	
Belt Sander	
Belt Tools	247
Bench	
Vise	
Work	
Bendable Light	
Bender, Tubing	. 235
Bit Sockets	
Stubby, 1/4" Drive	
Torx®, Tamper Resistant50 - 51, 59, 68,	
Torx®, Set	15
Bits	
Drill	. 179
Screwdriver	. 137
Set, Power	. 136
Sets	,138
Blade	
Knife	. 154
Utility Knife	
Blow Gun	
BodyHammer	
Bolt Cutters	
Boot Pliers	
Bottle Jacks	
Box	. 220
Metal Tool	40
Plastic Tool	
Pry Bar	
Wrench, Ratcheting	. 106
Brake	
Caliper Kit	
Caliper Press	
Gauge Set	
Rotor Tool	
Service Tools	
Spring Tool	
Brass Hammer	. 147
Breaker Bar	
1/4" Drive	52
3/8" Drive	60
1/2" Drive	69
3/4" Drive	73
Brush	
End	. 178
Terminal	
Wire	
	1



4	,	۹	١
•	1		

Cabinet	
Roll30	- 34
Side	36
Top35	- 36
Cable, Cutters117,	
Caliper	
Dial	188
Digital	
Brake	
Cam Lock Tool Set	
Can Holder	
Car Body Hammer Set	
Carrier, Battery	
Carts	
C-Clamps	
Compressor	
Locking	
Pliers	124
Chain	
Wrench	
Pliers	
Chests, Top35	
Chisel, Punch Set148 -	
Circlip Pliers	128
Circuit	
Tester	199
Clamp, Line	243
Claw Hammer	146
Cleaner & Fin Straightener	239
Click-Type Torque Wrenches	
Adjustable	82
Preset	
Coarse Flat File	
Cobalt Drill Bit Set	
Coil Spring Compressor	
Combination	
Measuring Set	100
Pliers116, 120 - 122,	
Wrenches	
Ratchets	
Regulator, Air Line	1/6
Compact	
Flashlight	193
Composite	
Impact Wrench156, 158 -	161
Compressor	
Coil Spring	249
Ring247,	
niig247,	249
Valve Spring247,	
Valve Spring	249
Valve Spring COMPUTORQ 3 Digital Torque	249
Valve Spring COMPUTORQ 3 Digital Torque Wrench	249 86
Valve Spring	249 86 241
Valve Spring	249 86 241
Valve Spring	249 86 241 241

D

С	Deburring Tools		23
	Deluxe Air Vacuum System		250
С	Depth Micrometer Set		189
	Diagonal Cutters118 -	119,	122
С	Dial Gauges		189
С	Dial Indicators186, 1	188 -	189
	Die Grinders	.167-	170
	Diesel, Leak Tester		200
	Digital		
	Caliper		188
	Drum Gauge		192
	Micrometers		189
	Tire Inflator		
	Thermometer		
	Torque Tester		
	Torque Wrench		86
_	Disconnect Tools		
	Set2		
	Dispenser		
	Dividers		
	Document Holder		
	Door Lockout Set		
	Door Trim Panel Tool Set	•••••	228
D	Double End	_	
	Ratcheting Wrench	9,	104
L	Double Square		
_	Socket, 1/4" Drive		
	Oouble Flaring Tool Sets2		
C	Orain Nut	234,	244

	Drill		F		
	1/4"	161	=	ace Shield	214
	3/8"	162		an Clutch Pulley Holder	
	1/2"	162		eeler Gauges	
	Bit, Sets	179			
	Bit, Step	179	Г	iberglass Hammer	
	Step, Bit	179	_	Prybar	243
	Driver		F	File	
	Flat Tip	52, 60, 137		Flat	
	Hex, Bit			Round	15 ⁻
	Phillips®			Set	7, 15 ⁻
	Pozidriv®			Triangular	15
	Set, Bearing Race & Seal		F	Filter	
	-			Oil	245
	Socket			Pliers	226
	Square Drive			Toyota	242
	Stubby			Wrenches	
	Torx®		F	in Straightener & Cleaner	
	Triple Square	52, 60, 69		inger Ratchets	
	Dual			Flap Wheels and Disc	
	Action, Sander	174		Flare Nut Wrench	
					•
		_		Flaring Tools, Tubing	237 - 230
_			F	Flashlights	400
Ε				Aluminum	
	Ear Protector	214		Compact	
	End			UV Leak Detection	214
	Brush	178	F	Flex Head	
	Cutters	118		Ratchet	·
	Engine			Ratchet, Combination	100 - 103
	Crane	222	F	Ratchet, Locking	105
	Exhaust Hanger Removal Pliers			Wrench, Locking	105
	Extension	220	F	Flexible	
	1/2" Drive	70. 72		Extensions, 1/4" Drive	53
				Lights	194
	1/4" Drive		F	Flip Impact Socket	
	3/8" Drive	*		-i Flip-Top, Roll Cart	
	3/4" Drive			loor Jack	
	1" Drive			Fluid Dispenser, Manual	
	Flexible, 1/4" Drive	53		lush Kit	
	Insulated			olding	240
	Knurled, 3/8" Drive	61		Tray	20
	Knurled, 1/2" Drive				
	Locking, 1/4" Drive	53	_	Hex Keys	107
	Locking, 3/8" Drive	61	F	use	
	Locking, 1/2" Drive	70		Buddy®	196
	Extra Long				
	L-Hex	108 - 109			
	Pliers	115	G		
	Extractor Set	229			
	= 1.1.4010.		C	Gas	
				Adaptor, Cap	24
				Leak Tester	200
				auge	
				Air Adjusting	19 ⁻
				Brake	19 ⁻
				Drum	
				Feeler	
				Pressure, Tire	
				Set	
				Tire	
				Tread Depth	
				HEAD DEDILL	



Gloves	
Abrasion Resistant	213
Nitrile	213
Washable	213
Welding	213
Grease	
Dispenser	246
Guns	
Guns, Lever	230
Grinder	
Angle	168 - 170
Die	
Die, Kit	169

Н

Hammer	
Air	163
Ball Peen	142
Body	26
Brass	147
Claw	
Cross Peen	
Fiberglass	
Rubber Mallet	
Sets	8
Soft Blow	
Soft Face	
Wheel	
Hacksaw	
Junior	154
Mini	154
Heavy Duty	
Bolt Cutters	128
Cabinet	34
Mini Cart	39
Oil Filter	242
Polisher	
Sander	
Scissors	
Shears	
Tool Bag	
Workbench	
Hex	
Bit Sockets, 1/4" Drive	50 - 51
Blt Sockets, 3/8" Drive	
Bit Sockets, 1/2" Drive	
Bits	
Bits, Set	136
Keys	
Key Sets	
High Leverage, Pliers, Cutters	
High Speed, Sander	174
Holder	
Can	38
Document	38
Fan Clutch Pulley	
Tool, Magnetic	

Hose	
12"	246
18"	246
Air	181
Crimper	239
Cutter	224
Nozzles	243
Pliers	115, 128
Replacement	236
Reel, Air	215
Reel, Electric	215
HSS Drill Bit Set	181
HVLP Spray Gun	231 - 232
Hydraulic Jack	218
Hydrometer	

Impost 1/4" Drive	
Impact, 1/4" Drive	F 4
Adaptor	
Socket Set	54
Impact 3/8" Drive	
Adaptor	
Sockets	
Socket, Set	24
Impact 1/2" Drive	
Adaptor	
Sockets	
Socket, Set	25
Impact, 3/4" Drive	
Adaptor	
Sockets	75 - 76
Impact	
Wrench15	8, 160 - 163
In Line Sander	173
Industrial Paper	250
Inflator, Gauge	190 - 191
Infrared Thermometer	
Inside Micrometers	189
Inspection Mirrors	200
Insulated	
Cutters	207
Extension	205
Hex Key	205
Pliers	207 - 208
Wrench	205 - 206
Wrench Sets	202
Scissors	205
Tool Sets	203 - 204
Toolbox Sets	202
Interchangeable	
Heads, Ratcheting	84
Torque Wrench	
- 4	

J			Magnetic	
	Jack		Holder	188
	Balloon2	20	Trays	37
	Bottle 2		Work Light	194
	Transmission		Mallet, Rubber Head	145
	Floor216 - 2		Manifold	
	Hydraulic		Repair Kit	235
	Stands		Set	
	Statius2	.19	Manual	
			A/C Hose Crimper	220
			Fluid Dispenser	
_				245
N			Master	0.40
	Key		Line Disconnect Set	
	Ball End107 - 1	10	MacPherson Strut Tool	
	Folding1	07	Master Ball Hex Bit Set	136
	Insulated Hex2	05	Max Fuse Buddy®	196
	L-Hex108 -1		Measuring Tape	187
	L-Torx 1	10	Metal Tool Boxes	43
	Long, Extra Arm109 - 1	10	Meter	
	Long, Extra Ball End109 - 1		Automatic	197
	T-Hex		Manual	197
	Knife, Utility1		Ranging	197
			Metric	
			Flaring Tools	237 - 238
			Micro	
			Polisher	176
_			Sander	
	Large Combination Wrench	8	Shears	224
	Leak Detector/Tester		Surface Prep	175
	Gas2	00	Wire Cutter	
	Diesel		Micrometers	
			Depth	189
	Ultraviolet2		Digital	
	Leverage Hose Cutter2	24	Inside	
	Lights		Outside	
	Bendable1	94	Rotor	
	Flashlights1		Mini	192
	Leak Detection			20
			Cart, Heavy Duty	
	LED193 - 1		Hacksaw	
	Magnetic1	94	Grinder	
	Pen1	93	Impact Wrench	
	Rechargeable1	93	Ratchet	
	Shop 1		Spray Gun	
	·		Stethoscope	199
	Work1		Tool Box	44
	Line Clamp Set2	43	Miniature	
	Lock		Cutters	122
	Cam, Tool2	49	Pincers	123
	Wheel2	39	Pliers115 - 11	6. 122 - 123
	Locking	.00	Mirror, Inspection	
	9	0.5	Multimeter	
	Pliers124 - 1	25	Multi-purpose Cutter	
			• •	
			Multi-Tool Set	227
М				
_	M Series			
	Phillips®1	31 N		
	•		Needle	
		02		
	Pozidriv®1	31	Nose Pliers	188
	Slotted Screwdriver1		Nose Pliers	
	Slotted Screwdriver	32	Nozzle	246
	Slotted Screwdriver1	32 88		246 173



-	Offset Wrenches95
	Oil
	Drainer
	Filter, Wrenches
	Suction Gun
	Open End
	Head84
	Wrench Set, Double Open End4, 97
)	
	P Series
	Phillips® 133
	Pad
	Spreader247
	Wool Velcro180
	Pen
	Light193
	Pencil Die Grinders170
	Pick Sets224
	Pick Up Tools211 - 212
	Pinch Bar
	Pistol
	Air, Screwdriver176
	Ratchet Screwdriver135
	Pistol Grip, Grease Gun230
	Plastic
	Cutters119
	Tool Boxes43
	Pliers
	Adjustable Joint116, 121
	Bent Nose118, 123
	Chain
	Boot
	Circlip5, 127 - 128
	Clamping
	Combination
	Duck Bill
	Extended Reach
	Exhaust Hanger Removal225
	Grip
	High Leverage
	Hose
	Insulated
	Locking
	Long Nose118, 120 - 121, 123, 207
	Long Reach114 - 116
	Needle Nose
	Oil Filter
	Removal
	Retaining Ring125 - 126
	Round Nose
	Seal
	Sets5, 8 - 9, 114 - 116, 125 - 126

Slip Joint	116, 121, 208
Soft Grip	
Straight Jaw	
Standard	
	*
VDE	
Wire Stripping	208
Plug	
Coil-On, Probe	
Style, Ear Protector	214
Polisher	
Micro	176
Heavy Duty	174
Pocket Digital Thermometer	190
Portaset 4 Ton	
Power	
Steering Adaptor Kit	248
Air, Shears	
Bit Sets	130
Pozidriv®	
Bit Socket Driver	- ,
Precision Screwdriver	
Preset Torque Wrenches	83
Pressure	
Gauge	191
Probe	
Coil-On-Plug	199
Quick, Universal EFI	
Prybar	
Box	20
Fiberglass	
Set	223
Punch	
Centre	
Chisel Set	148
Set	148 - 149
Quick Release Ratchets	47. 56. 65. 73
Radiator Pressure Test Kit	244
Ratchet	
1/4" Drive	47. 135. 165 - 166
3/8" Drive	
1/2" Drive	
3/4" Drive	
Combination	
Finger	
Flex Head	
Flex Head, Locking	105
Handle	135
Head	103
Mini	166
Pass Thru	47, 56
Screwdriver	*
Quick Release	
Quick Helease	77, 00, 00, 70

R

Ratchet, Sockets & Accessories45 - 78	Screwdriver
Ratcheting	Air176 - 17
Box Wrenches106	Insulated Series
Combination4, 103 - 105	M Series8, 131 - 13
Cutter238	P Series13
Double Ring9, 104	Pass-Through9, 13
Flex Head100 - 103	Phillips®131, 133 - 134, 20
Locking, Flex Head105	Pistol Handle13
Interchangeable Head84	Pozidriv®13
Set 4, 100 - 101, 103, 105 - 106	Precision
Short103	Ratchet13
Wrench100 - 101, 103, 105	Set8 - 9
Wrench, Insulated204	Slotted 131, 133, 20
Rechargeable Pen Light193	Torx®
Reciprocating Saw172	VDE
Regulator, Air Line178	Seal
Repair Kit, Manifold236	Driver Set & Bearing Race24
Replacement	Pliers22
Hose	Serpentine Belt Tool24
Jaws	Shears
Retaining Ring Pliers125 - 126	Air Powered17
Reversible	Angled, Heavy Duty15
Cut-Off Tool	Shop
Ratcheting Wrench106	Light, Rechargeable19
Ring	Sliding
Compressors	Top Roll Cart40 - 4
Wrench	Sliding Head70
Riveter 229	Slip-Joint Pliers
Roll Cab	Slot and Dots Side Panel
Roll Cart	Soft Face Hammers
1 Drawer	Speeder Wrench
2 Shelves	Spotweld Drill
	•
4 Drawers Sliding Top	Spreader
4 Drawers Sliding Top	Spring Compressor
5 Drawers Sliding Top41	Valve Spring
Rotor	Stand, Jack21
Micrometer192	Strap, Wrench24
Round	Spray, Gun231 - 23
2nd-Cut File	Steel Rule
Half, 2nd-Cut File151	Step Drill Set
Rubber	Surface Prep Kit, Mirco17
Head Mallet145	
	T-Shape Wrenches
Safety Glasses214	T-Hex Wrenches
Sander	Tamper Resistant
Belt	Bit
Dual Action174	Bit Socket
Heavy Duty173	Tapes, Measuring18
High Speed174	Terminal
Micro176	Brush24
Scissors, Shop, Heavy Duty153	Tool Kit20
Scraper150	Test Pen19
Screw Removal Pliers 118	



Tester
Battery 195
Circuit
Cooling System Pressure241
Digital Torque88
Gas/Diesel Combustion Leak200
Thermometer
Dial Type190
Infrared 190
Pocket Digital190
Thread Setter Kits
Throttle Depressor247
Tig Welding Gloves213
Tin Snips
Titanium Coated Drill Bit Set
Tool Bag44
Tool Box
Cantilever Style
Metal
Mini
Plastic
Toolbox Set
Insulated
Tool Holder, Magnetic
Top Chest
Tops, Roll Cab
Torque Stick
Torx®
Torx® Bits15, 50, 59, 68, 137
Torx® Bits
Torx® Bits
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15 Driver 50, 59, 68
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15 Driver 50, 59, 68 Screwdriver 8, 132
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15 Driver 50, 59, 68 Screwdriver 8, 132 Socket, 1/4" Drive 49 - 50
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15 Driver 50, 59, 68 Screwdriver 8, 132 Socket, 1/4" Drive 49 - 50 Socket, 3/8" Drive 58 - 59
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15 Driver 50, 59, 68 Screwdriver 8, 132 Socket, 1/4" Drive 49 - 50 Socket, 3/8" Drive 58 - 59 Socket, 1/2" Drive 67 - 68
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15 Driver 50, 59, 68 Screwdriver 8, 132 Socket, 1/4" Drive 49 - 50 Socket, 3/8" Drive 58 - 59 Socket, 1/2" Drive 67 - 68 Tamper Resistant, Bit 137
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15 Driver 50, 59, 68 Screwdriver 8, 132 Socket, 1/4" Drive 49 - 50 Socket, 3/8" Drive 58 - 59 Socket, 1/2" Drive 67 - 68 Tamper Resistant, Bit 137 Tamper Resistant, Bit Socket 5 0 - 51, 59, 68
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15 Driver 50, 59, 68 Screwdriver 8, 132 Socket, 1/4" Drive 49 - 50 Socket, 3/8" Drive 58 - 59 Socket, 1/2" Drive 67 - 68 Tamper Resistant, Bit 137 Tamper Resistant, Bit Socket 5 0 - 51, 59, 68 Wrenches, L-Shape 7, 110
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15 Driver 50, 59, 68 Screwdriver 8, 132 Socket, 1/4" Drive 49 - 50 Socket, 3/8" Drive 58 - 59 Socket, 1/2" Drive 67 - 68 Tamper Resistant, Bit 137 Tamper Resistant, Bit Socket 5 0 - 51, 59, 68 Wrenches, L-Shape 7, 110 Tote Bag 44
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15 Driver 50, 59, 68 Screwdriver 8, 132 Socket, 1/4" Drive 49 - 50 Socket, 3/8" Drive 58 - 59 Socket, 1/2" Drive 67 - 68 Tamper Resistant, Bit 137 Tamper Resistant, Bit Socket 5 0 - 51, 59, 68 Wrenches, L-Shape 7, 110 Tote Bag 44 Trans Jacks 221
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15 Driver 50, 59, 68 Screwdriver 8, 132 Socket, 1/4" Drive 49 - 50 Socket, 3/8" Drive 58 - 59 Socket, 1/2" Drive 67 - 68 Tamper Resistant, Bit 137 Tamper Resistant, Bit Socket 5 0 - 51, 59, 68 Wrenches, L-Shape 7, 110 Tote Bag 44 Trans Jacks 221 Trays
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15 Driver 50, 59, 68 Screwdriver 8, 132 Socket, 1/4" Drive 49 - 50 Socket, 3/8" Drive 58 - 59 Socket, 1/2" Drive 67 - 68 Tamper Resistant, Bit 137 Tamper Resistant, Bit Socket 5 0 - 51, 59, 68 Wrenches, L-Shape 7, 110 Tote Bag 44 Trans Jacks 221 Trays Foldable 38
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15 Driver 50, 59, 68 Screwdriver 8, 132 Socket, 1/4" Drive 49 - 50 Socket, 3/8" Drive 58 - 59 Socket, 1/2" Drive 67 - 68 Tamper Resistant, Bit 137 Tamper Resistant, Bit Socket 5 0 - 51, 59, 68 Wrenches, L-Shape 7, 110 Tote Bag 44 Trans Jacks 221 Trays Foldable 38 Magnetic 37
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15 Driver 50, 59, 68 Screwdriver 8, 132 Socket, 1/4" Drive 49 - 50 Socket, 3/8" Drive 58 - 59 Socket, 1/2" Drive 67 - 68 Tamper Resistant, Bit 137 Tamper Resistant, Bit Socket 5 0 - 51, 59, 68 Wrenches, L-Shape 7, 110 Tote Bag 44 Trans Jacks 221 Trays Foldable 38 Magnetic 37 Tread Depth Gauge 191
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15 Driver 50, 59, 68 Screwdriver 8, 132 Socket, 1/4" Drive 49 - 50 Socket, 3/8" Drive 58 - 59 Socket, 1/2" Drive 67 - 68 Tamper Resistant, Bit 137 Tamper Resistant, Bit Socket 5 0 - 51, 59, 68 Wrenches, L-Shape 7, 110 Tote Bag 44 Trans Jacks 221 Trays Foldable 38 Magnetic 37
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15 Driver 50, 59, 68 Screwdriver 8, 132 Socket, 1/4" Drive 49 - 50 Socket, 3/8" Drive 58 - 59 Socket, 1/2" Drive 67 - 68 Tamper Resistant, Bit 137 Tamper Resistant, Bit Socket 5 0 - 51, 59, 68 Wrenches, L-Shape 7, 110 Tote Bag 44 Trans Jacks 221 Trays Foldable 38 Magnetic 37 Tread Depth Gauge 191 Triangular 2nd-Cut File 151 Tube
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15 Driver 50, 59, 68 Screwdriver 8, 132 Socket, 1/4" Drive 49 - 50 Socket, 3/8" Drive 58 - 59 Socket, 1/2" Drive 67 - 68 Tamper Resistant, Bit 137 Tamper Resistant, Bit Socket 5 0 - 51, 59, 68 Wrenches, L-Shape 7, 110 Tote Bag 44 Trans Jacks 221 Trays Foldable 38 Magnetic 37 Tread Depth Gauge 191 Triangular 2nd-Cut File 151 Tube Cutter 238
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15 Driver 50, 59, 68 Screwdriver 8, 132 Socket, 1/4" Drive 49 - 50 Socket, 3/8" Drive 58 - 59 Socket, 1/2" Drive 67 - 68 Tamper Resistant, Bit 137 Tamper Resistant, Bit Socket 5 0 - 51, 59, 68 Wrenches, L-Shape 7, 110 Tote Bag 44 Trans Jacks 221 Trays Foldable 38 Magnetic 37 Tread Depth Gauge 191 Triangular 2nd-Cut File 151 Tube
Torx® Bits 15, 50, 59, 68, 137 Bits, Set 136 Bit Socket, 1/4" Drive 15, 50 Bit Socket, 3/8" Drive 59 Bit Socket, 1/2" Drive 68 Bit Socket, Sets 15 Driver 50, 59, 68 Screwdriver 8, 132 Socket, 1/4" Drive 49 - 50 Socket, 3/8" Drive 58 - 59 Socket, 1/2" Drive 67 - 68 Tamper Resistant, Bit 137 Tamper Resistant, Bit Socket 5 0 - 51, 59, 68 Wrenches, L-Shape 7, 110 Tote Bag 44 Trans Jacks 221 Trays Foldable 38 Magnetic 37 Tread Depth Gauge 191 Triangular 2nd-Cut File 151 Tube Cutter 238

U	
	U-Clamp, Pliers
	Universal Joint. 1/4" Drive53
	Joint, 1/4 Drive
	Joint, 1/2" Drive
	oint, 3/4" Drive
	Joint, 1" Drive
	EFI Quick Probe
	Utlity
	Saddle221
	Knife
	UV Leak Detection Flashlight Kit214
	OV Loak Dotootion Flaoringht Ne
V	
	Vacuum System250
	Vacuum Cleaner
	Valve
	Adjusting Tools191
	Core
	Spring Compressor
	VDE
	Pliers9
	Screwdriver9
	Velcro, Wool Pad180
	Vinyl Cutter
	Vise, Bench232
W	
	Weld
	Gloves
	Sleeves 213
	Washable Work Gloves
	Water Pump Pulley Wrench
	Wheel
	Cut Off179
	Dolly219
	Flap180
	Grinding179
	Grinding Set179
	Hammer147
	Lock Kit239
	Wire, Crimped180
	Wire, Knotted
	Windshield Removal Tool
	Wire
	Brush
	Cutter
	Stripper224 - 225
	Wheel
	Wool Velcro Pad180

Workbench, Adjustable223	
Workstation41 - 42	2
Wrenches89 - 110)
Wrench	
Adjustable5, 8, 82, 93 - 94	ļ
Combination4, 7 - 8, 91, 100)
Composite158, 161	
Chain99	
Double Flex10, 96	3
Double Open End4, 97	7
Double Ring4, 9, 95, 97	7
Flare Nut10, 98	
Flex Head, Locking105	5
Flex Head, Ratcheting100 - 103	3
Flex Socket10, 96	3
Impact158, 160 - 161	ı
Insulated202	2
Interchangeable Head83	3
L-Shape7, 73	3
Oil Filter245	5
Open End4, 97, 206	3
Locking105	
Preset Click-Type83	
Ratchet Combination7, 100)
Ratcheting100 - 101	
Ratcheting Box106	3
Ratcheting, Flex Head100 - 101	
Ratcheting, Locking Flex Head105	
Ratcheting, Short103	
Ratcheting, Short Flex Head103	3
Ring End95	
Sets4, 5, 7 - 8, 93 - 98, 100 - 106, 202	2
Single Direction7	7
Spanner239)
Speeder106	3
Strap	5
Torx®, Long7, 110)
Torque82 - 83	
Torque, Digital86	3
Water Pump Pulley)



This page intentionally left blank



Showing Millimeter Sizes, Fractional and Decimal Inch Sizes, and Drill Number Sizes

Note: To convert from inches to millimeters, multiply by 25.4; to convert from millimeters to inches, multiply by 0.03937

М	DE	F	DN	М	DE	F	DN	М	DE	F	DN	М	DE	F	DN	М	DE	F	М	DE	F
0.10	0.0039	_	_	1.85	0.0728		DIV		0.1660	•	19	7.25	0.2854	_	_	13.49	0.5313	17/32	35.00	1.3780	
0.10	0.0059			1.03	0.0728		49	4.25	0.1663		—	7.30	0.2874			13.50	0.5315	17/32	36.00	1.4173	
0.13	0.0039			1.90	0.0730		45	4.30	0.1673			7.30	0.2900		L	13.89	0.5313	35/64	36.51	1.4375	17/16
0.25	0.0098	_	_	-	0.0760	_	48	-	0.1695	_	18	7.40	0.2913	_	_	14.00	0.5512	-	37.00	1.4567	
0.30	0.0118		_	1.95	0.0768		_	4.37	0.1719	11/64	_	_	0.2950	_	М	14.29	0.5625	9/16	38.00	1.4961	
_	0.0135	_	80	1.98	0.0781	5/64	_	_	0.1730	_	17	7.50	0.2953	_	_	14.50	0.5709	_	38.10	1.5000	1 1/2
0.35	0.0138	_	_	_	0.0785	_	47	4.40	0.1732	_	_	7.54	0.2969	19/64	_	14.68	0.5781	37/64	39.00	1.5354	_
_	0.0145	_	79	2.00	0.0787	_	_	_	0.1770	_	16	7.60	0.2992	_	_	15.00	0.5906	_	39.69	1.5625	1 9/16
0.40	0.0156	1/64	_	2.05	0.0807	_	_	4.50	0.1772	_	_	_	0.3020	_	N	15.08	0.5938	19/32	40.00	1.5748	
0.40	0.0157	_	_	_	0.0810	_	46	_	0.1800	_	15	7.70	0.3031	_	_	15.48	0.6094	39/64	41.00	1.6142	_
	0.0160	_	78	_	0.0820	_	45	4.60	0.1811	_	_	7.75	0.3051	_	_	15.50	0.6102	_	41.28	1.6250	1 5/8
0.45	0.0177	_	_	2.10	0.0827	_	_	_	0.1820	_	14	7.80	0.3071	_	_	15.88	0.6250	5/8	42.00	1.6535	_
	0.0180		77	2.15	0.0846			4.70	0.1850	_	13	7.90	0.3110			16.00	0.6299		42.86	1.6875	1 11/16
0.50	0.0197		_	_	0.0860	_	44	4.75	0.1870	_	_	7.94	0.3125	5/16	_	16.27	0.6406	41/64	43.00	1.6929	
	0.0200		76	2.20	0.0866	_		4.76	0.1875	3/16	_	7.80	0.3150		_	16.50	0.6496	_	44.00	1.7323	_
-	0.0210	_	75	2.25	0.0886		- 42	4.80	0.1890		12	-	0.3160	_	0	16.67	0.6563	21/32	44.45	1.7500	13/4
0.55	0.0217	_	74	- 220	0.0890	_	43	400	0.1910		11	8.10	0.3189	_	_	17.00	0.6693	42/64	45.00	1.7717	
0.60	0.0225		74	2.30	0.0906		_	4.90	0.1929		10	8.20	0.3228		— Р	17.07 17.46	0.6719	43/64 11/16	46.00 46.04	1.8110 1.8125	1 13/16
	0.0230		73		0.0923		42		0.1960		9	8.25	0.3230			17.50	0.6890	-	47.00	1.8504	1 13/10
	0.0250		72	2.38	0.0938	3/32		5.00	0.1969		_	8.30	0.3268			17.86	0.7031	45/64	47.63	1.8750	1 7/8
0.65	0.0256	_	-	2.40	0.0945	- J/JE	_		0.1990	_	8	8.33	0.3281	21/64	_	18.00	0.7087	-13/01	48.00	1.8898	-
	0.0260	_	71	_	0.0960		41	5.10	0.2008	_	_	8.40	0.3307	_		18.26	0.7188	23/32	49.00	1.9291	_
0.70	0.0276	_	_	2.45	0.0965	_	_	_	0.2010	_	7	_	0.3320	_	Q	18.50	0.7283	_	49.21	1.9375	1 15/16
	0.0280	_	70	_	0.0980	_	40	5.16	0.2031	13/64	_	8.50	0.3346	_	_	18.65	0.7344	47/64	50.00	1.9685	_
_	0.0292	_	69	2.50	0.0984	_	_	_	0.2040	_	6	8.60	0.3386	_	_	19.00	0.7480	_	50.80	2.0000	2
0.75	0.0295	_	_	_	0.0995	_	39	5.20	0.2047	_	_	_	0.3390	_	R	19.05	0.7500	3/4	51.00	2.0079	_
_	0.0310	_	68	_	0.1015	_	38	<u> </u>	0.2055	_	5	8.70	0.3425	_	_	19.45	0.7656	49/64	52.00	2.0472	_
0.79	0.0313	1/32	_	2.60	0.1024	_	_	5.25	0.2067	_	_	8.73	0.3438	11/32	_	19.50	0.7677	_	52.39	2.0625	2 1/16
0.80	0.0315	_	_	_	0.1040	_	37	5.30	0.2087	_	_	8.75	0.3445	_	_	19.84	0.7813	25/32	53.00	2.086	_
	0.0320	_	67	2.70	0.1063				0.2090	_	4	8.80	0.3465		_	20.00	0.7874		53.98	2.1250	2 1/8
_	0.0330		66	<u> </u>	0.1065	_	36	5.40	0.2126	_	_	_	0.3480	_	S	20.24	0.7969	51/64	54.00	2.1260	
0.85	0.0335		_	2.75	0.1083	_	_	_	0.2130		3	8.90	0.3504	_	_	20.50	0.8071	_	55.00	2.1654	
_	0.0350	_	65	2.78	0.1094	7/64	_	5.50	0.2165	_	_	9.00	0.3543	_	_	20.64	0.8125	13/16	55.56	2.1875	23/16
0.90	0.0354		_	_	0.1100		35	5.56	0.2188	7/32		_	0.3580		T	21.00	0.8268	_	56.00	2.2047	
	0.0360	_	64	2.80	0.1102		_	5.60	0.2205	_	_	9.10	0.3583	_	_	21.03	0.8281	53/64	57.00	2.2441	_
-	0.0370		63	_	0.1110	_	34 33		0.2210	_	2	9.13	0.3594	23/64	_	21.43	0.8438	27/32	57.15	2.2500	2 1/4
0.95	0.0374	_	62	2.90	0.1130	_	33	5.70 5.75	0.2244			9.20 9.25	0.3622		_	21.50	0.8465	55/64	58.00 58.74	2.2835	25/16
	0.0380		61	2.50	0.1142		32	3.73	0.2280		1	9.30	0.3661			22.00	0.8394	33/04	59.00	2.3123	23/10
1.00	0.0394	_	-	3.00	0.1181	_	31	5.80	0.2283	_	_		0.3680	_	U	22.23	0.8750	7/8	60.00	2.3622	_
_	0.0400	_	60	_	0.1200	_	_	5.90	0.2323	_	_	9.40	0.3701	_	_	22.50	0.8858		60.33	2.3750	23/8
	0.0410	_	59	3.10	0.1220		_	_	0.2340		A	9.50	0.3740	_		22.62	0.8906	57/64	61.00	2.4016	
1.05	0.0413	_	_	3.18	0.1250	1/8	_	5.95	0.2344	15/64	_	9.53	0.3750	3/8	_	23.00	0.9055	_	61.91	2.4375	27/16
	0.0420	_	58	3.20	0.1260	_	_	6.00	0.2362	_	_	_	0.3770	_	V	23.02	0.9063	29/32	62.00	2.4409	_
_	0.0430	_	57	3.25	0.1280	_	30	_	0.2380	_	В	9.60	0.3780	_	_	23.42	0.9219	59/64	63.00	2.4803	_
1.10	0.0433	_	_	_	0.1285	_	_	6.10	0.2402	_	_	9.70	0.3819	_	_	23.50	0.9252	_	63.50	2.5000	2 1/2
1.15	0.0453	_	_	3.30	0.1299	_	_	_	0.2420	_	С	9.75	0.3838	_	_	23.81	0.9375	15/16	64.00	2.5197	_
_	0.0465	_	56	3.40	0.1339	_	_	6.20	0.2441	_	_	9.80	0.3858	_	_	24.00	0.9449	_	65.00	2.5591	_
1.19	0.0469	3/64	_	_	0.1360	_	29	6.25	0.2460	_	D	_	0.3860	_	W	24.21	0.9531	61/64	65.09	2.5625	29/16
1.20	0.0472	_	_	3.50	0.1378	_	_	6.30	0.2480	_	_	9.90	0.3898	_	_	24.50	0.9646	_	66.00	2.5984	_
1.25	0.0492	_	_	_	0.1405	_	28	6.35	0.2500	1/4	E	9.92	0.3906	5/64	_	24.61	0.9688	31/32	66.68	2.6250	25/8
1.30	0.0512			3.57	0.1406	9/64	_	6.40	0.2520	_		10.00	0.3937	_	_	25.00	0.9843	_	67.00	2.6378	_
_	0.0520	_	55	3.60	0.1417	_	_	6.50	0.2559	_	_	_	0.3970	_	Х	25.00	0.9844	63/64	68.00	2.6772	_
1.35	0.0531	_	_	_	0.1440	_	27	_	0.2570	_	F	_	0.4040	_	Υ	25.40	1.0000	1	68.26	2.6875	211/16
_	0.0550	_	54	3.70	0.1457	_	_	6.60	0.2598	_	_	10.32	0.4063	3/32	_	26.00	1.0236	_	69.00	2.7165	_
1.40	0.0551	_	_	_	0.1470	_	26	_	0.2610	_	G	_	0.4130	_	Z	26.99	1.0625	1 1/16	69.85	2.7500	23/4
1.45	0.0571	_	_	3.75	0.1476	_	-	6.70	0.2638	-	_	10.50	0.4134	-	_	27.00	1.0630	_	70.00	2.7559	_
1.50	0.0591	_	-	200	0.1495	_	25	6.75	0.2656	17/64	_	10.72	0.4219	27/64	_	28.00	1.1024	11/0	71.00	2.7953	212/45
1.55	0.0595	_	53	3.80	0.1496	_	-	6.75	0.2657		_	11.00	0.4331	7/10	_	28.58	1.1250	1 1/8	71.44	2.8125	213/16
1.55	0.0610	1/16	_	200	0.1520	_	24	- 600	0.2660	_	Н	11.11	0.4375	7/16	_	29.00	1.1417	_	72.00	2.8346	
1.59	0.0625	1/16	_	3.90	0.1535	_	22	6.80	0.2677		_	11.50	0.4528	20/64	_	30.00	1.1811	1 2/16	73.00	2.8740	27/9
1.60	0.0630	_	52	3.97	0.1540	5/32	23	6.90	0.2717	_		11.51 11.91	0.4531	29/64 15/32	_	30.16	1.1875	13/16	73.03 74.00	2.8750 2.9134	27/8
1.65	0.0650		52	3.97	0.1563	5/32	22	7.00	0.2720			12.00	0.4688	15/32		31.00	1.2500	1 1/4	74.00	2.9134	2 15/16
1.70	0.0650		_	4.00	0.1570			7.00	0.2750			12.00	0.4724	31/64		31./5	1.2500	1 1/4	75.00	2.9575	2 13/10
1.70	0.0669		51	4.00	0.1575		21	7.10	0.2770			12.50	0.4921	31/04	_	33.00	1.2598		76.00	2.9528	
1.75	0.0670		31		0.1590		20	7.10	0.2793	_	K	12.70	0.4921	1/2		33.34	1.3125	1 5/16	76.00	3.0000	3
- 1./3	0.0009		50	4.10	0.1614			7.14	0.2813	9/32		13.00	0.5000	- 1/2		34.00	1.3386	1 3/10	70.20	5.0000	3
1.80	0.0700	_		4.10	0.1654	_	_	7.14	0.2835	J/32	_	13.10	0.5116	33/64		34.93	1.3750	1 3/8			
1.00	0.0709			1.20	0.1007			7.20	0.2033			.5.10	0.5150	33/37		31.33	1.5750	. 5,0			

 $M = Millimeters, \, DE = Decimal \; Equivalents, \, F = Fractional, \, DN = Drill \; Number/Letter$



Snap-on Asia Pacific Division, or its assigns, ("Snap-on") warrants to customers who purchase products from authorized Blue-Point distribution channels that Blue-Point® brand products will be free from defects in workmanship and materials for a duration depending upon the nature of the product. Prior to a product purchase, customer can obtain the product warranty duration from a Blue-Point reseller. Customers may also contact the closest sales office as listed below.

During the applicable duration of the warranty, at its option, Snap-on will repair or replace its products which fail to give satisfactory service due to defective workmanship or materials, or provide a refund by repaying or crediting customer with an amount equal to the purchase price of such products. Repair, replacement or refund shall be at the election and expense of Snap-on, and is customer's exclusive remedy in place of all other rights and remedies. Any products or parts replaced or for which Snap-on has provided a refund are the property of Snap-on and will not be returned.

THE FOREGOING WARRANTY IS IN LIEU OF AND EXCLUDES ALL OTHER WARRANTIES NOT EXPRESSLY SET FORTH HEREIN, WHETHER EXPRESS, IMPLIED OR COLLATERAL, BY OPERATION OF LAW OR OTHERWISE, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Descriptions of product contained in this catalog are for the sole purpose of identifying product and shall not be construed as an express warranty.

LIMITATION OF LIABILITY. SNAP-ON AND ITS AFFILIATED COMPANIES AND THIRD PARTY SUPPLIERS SHALL NOT BE LIABLE FOR ANY INCIDENTAL, SPECIAL OR CONSEQUENTIAL LOSSES, COSTS OR DAMAGES INCURRED BY CUSTOMER OR OTHERS, INCLUDING PERSONAL INJURY OR DEATH, DIRECTLY OR INDIRECTLY ARISING FROM THE SALE, HANDLING OR USE OF THE PRODUCTS, OR FROM ANY OTHER CAUSE WITH RESPECT TO THE PRODUCTS OR THE FOREGOING WARRANTY, WHETHER SUCH CLAIM IS BASED UPON BREACH OF CONTRACT, BREACH OF WARRANTY, STRICT LIABILITY IN TORT, NEGLIGENCE OR ANY OTHER LEGAL THEORY (INCLUDING WITHOUT LIMITATION, LOST PROFITS, REVENUES, ANTICIPATED SALES, BUSINESS OPPORTUNITIES, GOODWILL, OR INTERRUPTION OF BUSINESS OR OTHER INJURY OR DAMAGE).

Snap-on® and Blue-Point® are registered trademarks of Snap-on Incorporated



SNAP-ON ASIA PACIFIC OFFICES

Asia / Pacific Division

25 Tagore Lane, #01-02 Singapore 787602 Tel: +(65) 6459-2712 Fax: +(65) 6459-1520

Snap-on Trading (Shanghai) Co., Ltd.

Unit 2001-2005, Cross Tower 318 Fuzhou Road, Shanghai 200001 PR China

Tel: +(86-21) 6391-2388 Fax: +(86-21) 6391-2382

Snap-on Trading (Shanghai) Co., Ltd. Beijing Branch

517B, Grand Pacific Building 8A Guanghua Road Beijing 100026 P.R.China

Tel: +(86-10) 6581-8838 Fax: +(86-10) 6581-6681

Snap-on Tools India Private Ltd.

6/2, Begumpur Khatola, 39 Milestone, NH-8, Gurgaon, Haryana-122004, India Tel: +(91-124) 459-9700

Fax: +(91-124) 405-6866

Snap-on Tools Japan, K.K.

2-1-6 Shinkiba, Koto-ku, Tokyo, 136-0082 Japan Tel: +(81-3) 5534-1285 Fax: +(81-3) 5534-1284

Snap-on Tools Hong Kong Ltd.

Unit 2010, 20/F, Laford Centre, 838 Lai Chi Kok Road, Cheung Sha Wan, Kowloon Hong Kong

Tel: +(852) 2370-3700 Fax: +(852) 2370-3400

Snap-on Tools Korea Ltd.

#201 ~ 205, #236,Sambo Techno Tower, 122 Jomaru-ro 385beon-gil, Bucheon, Gyeonggi-do, Republic of Korea 14556

Tel: +(82) 32-326-7310 Fax: +(82) 32-326-7312

Snap-on Tools Singapore Pte. Ltd.

25 Tagore Lane, #01-01 Singapore 787602 Tel: +(65) 6451-5570 Fax: +(65) 6451-5574

Snap-on Tools Singapore Pte. Ltd.

(Representative Office)
Puri Indah Financial Tower, #17-1705
Jalan Puri Lingkar Dalam Blok T8,
Jakarta Barat 11610, Indonesia
Tel: +(62-21) 2258-2222

Snap-on Tools Singapore Pte. Ltd. Malaysia Branch

B-6-10, Street Mall, One South Jalan OS, Taman Serdang Perdana 43300 Seri Kembangan, Selangor Malaysia

Tel: +(603) 8957-1938 Fax: +(603) 8957-2938

Snap-on Tools Singapore Pte. Ltd. Philippines Branch

Unit 801 Prime Land, Market St. Madrigal Business Park, Ayala Alabang Muntinlupa City, 1781 Philippines

Tel: +(63-2) 8-843-7935 / +(63-2) 8-843-8262

Snap-on Tools Singapore Pte. Ltd. Taiwan Branch

3F-4, #9 Wuquan 1st Road, New Taipei Industrial Park, Xinzhuang District 24892, New Taipei City, Taiwan ROC Tel: +(886-2) 2298-9789 Fax: +(886-2) 2298-2288

Snap-on Tools Singapore Pte. Ltd. Vietnam Branch

Suite U1A, 4th Floor, Broadway A Building No. 100, Nguyen Luong Bang St, Tan Phu Ward Dist. 7, Ho Chi Minh City, Vietnam Tel: +(84-28) 5414-1432

Snap-on (Thailand) Co., Ltd.

4 Kanchanapisek Road, Prawet Bangkok 10250, Thailand

Tel: +(66) 2026-3255



An Extensive Range of Tools & Equipment for the Workplace



Blue-Point