

Specifications

Eaton 170E8883

Fuse-link, high speed, 200 A, DC 4000 V, size 2, 75 x 86 x 414 mm, aR, IEC, with indicator



Photo is representative



General specifications

PRODUCT NAME	Eaton Bussmann series high speed traction fuse
CATALOG NUMBER	170E8883
UPC	051712689854
EAN	5704057005500
PRODUCT LENGTH/DEPTH	416 mm
PRODUCT HEIGHT	55 mm
PRODUCT WIDTH	77 mm
PRODUCT WEIGHT	136.8 g
COMPLIANCES	EAC
CERTIFICATIONS	IEC
GLOBAL CATALOG	170E8883

Product specifications

AMPERAGE RATING	200 A
BREAKING CAPACITY	60 A
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)
FUSE INDICATOR	Top fuse status indicator
FUSE SIZE	2
CLASS	Class aR
WATT LOSSES	228 W
FUSE SHAPE	Square body, offset bolted tags
MOUNTING DIMENSION	M8
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	393 mm
CURRENT TYPE	DC
RATED VOLTAGE DC	4000 V
COLOR	None
INTERRUPT RATING	60 kAIC
CONSTRUCTION SIZE	2
PACKAGING TYPE	Standard
VOLTAGE RATING	4000 V
TYPE	Fuse
APPLICATION	traction
FUSE SYSTEM (ACCORDING TO IEC 60269)	Other

Resources

CATALOGS	Traction fuse-links
MCAD MODEL	eaton-traction-fuses-mcad-3d-models-u1279.stp

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

