## Specifications



Photo is representative

## Eaton 170E8886

Eaton Bussmann series high speed traction fuse, Fuse-link, high speed, 350 A, DC 4000 V, size 2,  $75 \times 155 \times 414$  mm, aR, IEC, with indicator

| General specification   | ns                                             |
|-------------------------|------------------------------------------------|
| PRODUCT NAME            | Eaton Bussmann series high speed traction fuse |
| CATALOG NUMBER          | 170E8886                                       |
| UPC                     | 051712759922                                   |
| EAN                     | 5027590438865                                  |
| PRODUCT<br>LENGTH/DEPTH | 416 mm                                         |
| PRODUCT HEIGHT          | 55 mm                                          |
| PRODUCT WIDTH           | 77 mm                                          |
| PRODUCT WEIGHT          | 3042 g                                         |
| COMPLIANCES             | EAC                                            |
| CERTIFICATIONS          | IEC                                            |
| GLOBAL CATALOG          | 170E8886                                       |



| Product specification                      | IS                                        |
|--------------------------------------------|-------------------------------------------|
| AMPERAGE RATING                            | 350 A                                     |
| BREAKING CAPACITY                          | 60 A                                      |
| UTILIZATION CATEGORY                       | aR (accompanied semiconductor protection) |
| FUSE INDICATOR                             | Other                                     |
| FUSE SIZE                                  | 2                                         |
| CLASS                                      | Class aR                                  |
| WATT LOSSES                                | 400 W                                     |
| MOUNTING DIMENSION                         | M8                                        |
| CENTER-TO-CENTER DISTANCE OF CONNECTIONS   | 394 mm                                    |
| CURRENT TYPE                               | DC                                        |
| RATED VOLTAGE DC                           | 4000 V                                    |
| COLOR                                      | None                                      |
| INTERRUPT RATING                           | 60 kAIC                                   |
| CONSTRUCTION SIZE                          | 2                                         |
| PACKAGING TYPE                             | Standard                                  |
| VOLTAGE RATING                             | 4000 V                                    |
| ТҮРЕ                                       | Fuse                                      |
| FUSE SYSTEM<br>(ACCORDING TO IEC<br>60269) | Other                                     |

| Resources |                            |
|-----------|----------------------------|
| CATALOGS  | <u>Traction fuse-links</u> |

| PROJECT NAME:   |  |
|-----------------|--|
| PROJECT NUMBER: |  |
| PREPARED BY:    |  |
| DATE:           |  |



**Eaton Corporation plc** Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

information.





latest product and support

Follow us on social media to get the



