



MPC300 PCB Connector



MPC300-250



MPC300-350




DIMENSIONS/POSITIONS


DIMENSIONS/POSITIONS		MPC300-250	MPC300-350
間距	Pitch	2.50mm	3.50mm
位數	Poles	2 ~ 16Poles	2 ~ 20Poles
塑膠本體	Housing Material	PA 66	PA 66
夾片	Contact	Copper, Tin Plated	Phosphor Bronze, Tin Plated
彈片	Wire Protector	Stainless Strip Steel	Stainless Strip Steel
電線線徑	Wire Size	20 ~ 28AWG	16 ~ 28AWG
剝線長度	Wire Strip Length	-	9mm
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE			
額定電流 I _n	Nominal Current I _n	4A	8A
額定橫截面	Nominal Cross Section	2.5mm ²	-
最大負載電流	Maximum load current	4A	8A
絕緣材料	Insulating Material	PA	PA
阻燃等級,符合UL94 Inflammability class acc. to UL94		V0	V0
額定電壓,UL/CUL Nominal voltage, UL/CUL		125V	300V
額定電流,UL/CUL Nominal current, UL/CUL		4A	8A



2.50xP+0.60mm



3.50xP+1.00mm

