EPL.0S.302.HLN





Image for illustrative purpose only

Summary

Request a quote

Catalog		
Number of contacts Low Voltage	2	
Socket / Receptacle	Socket / Receptacle - Elbow	
Locking system	Push-pull	
Size	0S	
Suggested matching part	FFA.0S.302.CLAC22	
Series	S - Indoor Stepped Insert	

Technical details

Electrical Configuration

ilocti icai comigaration	
Number of contacts Low Voltage	2
Contact Termination Low voltage	PCB - Straight
R (max)	4.8 mOhm
Insert configuration value	0S.302 - 2 Low Voltage
Insulator	L: PEEK (UL 94 / V-0/1.5)
Test voltage (kV DC)	1.6
Test voltage (kV rms)	1.2
Contact Dia.	0.9 mm (0.0354in)
Form & Material	
Shell style / Model id	EPL - Elbow receptacle for printed circuit (solder or screw fixing)
Socket / Receptacle	Elbow
Housing material	PPS (Polyphenylene) shell, other pieces nickel plated [SAE AMS QQ N 290] brass
Locking system	Push-pull
Keying	Hermaphroditic keying (half moon insert) with femal pin 1
Weight	9.42 g
invironment	
Technical domain	Audio Video, Energy and Industrial, Semiconductor, Test and Measurement
Environmental sealing (IP rating)	IP50
Endurance	5000 mating cycles
Temperature range	-55°C / +220°C
Climatical Category	50/175/21
Humidity (max)	<=95% [at 60 deg C /140 F]
Shielding (min)	75 dB (10 MHz)
Shielding (min)	40 dB (1 GHz)
Shock Resistance	100 g [6 ms]
Vibration	15 g [10 Hz - 2000 Hz]
Salt Spray Corrosion	>144 hr

$\underline{https://www.lemo.com/int_en/solutions/originals/s-indoor-stepped-insert/epl-0s-302-hln.html}$

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Recommended By Lemo

Accessories

Compatible cap

BRE.0S.200.NAS