

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-FST-Coating 362-80
Quality No.: 3628097237000

Revision Date 06.06.2021
Print Date 06.06.2021
Version 1

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Mixture of synthetic resins, water and pigments

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6 01-2120761540-60	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400	>= 0.0025 - < 0.025
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	55965-84-9 613-167-00-5 01-2120764691-48	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 2; H310 Skin Corr. 1C; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	>= 0.0002 - < 0.0015
2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6 613-326-00-9 01-2120764690-50	Acute Tox. 3; H301 Acute Tox. 2; H330 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	>= 0.0002 - < 0.0015
Substances with a workplace exposure limit :			
titanium dioxide	13463-67-7		>= 20 - < 25



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-FST-Coating 362-80
Quality No.: 3628097237000

Revision Date 06.06.2021
Print Date 06.06.2021
Version 1

	236-675-5 01-2119489379-17		
(2-methoxymethylethoxy)propanol	34590-94-8 252-104-2 01-2119450011-60		>= 1 - < 5

These contain:

1,2-dichlorobenzene	95-50-1 202-425-9 602-034-00-7 01-2119451167-40	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1B; H317 STOT SE 3; H335 (Respiratory system) Aquatic Acute 1; H400 Aquatic Chronic 1; H410	> 0.1 - <= 0.25 PPM
---------------------	--	---	------------------------

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : In all cases of doubt, or when sickness symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.
- If inhaled : Remove to fresh air, keep patient warm and at rest.
Irregular breathing/no breathing: artificial respiration.
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash skin thoroughly with soap and water or use recognised skin cleanser.
Do NOT use solvents or thinners !
- In case of eye contact : Remove contact lenses, irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart and seek medical advice.
- If swallowed : Do NOT induce vomiting.
If accidentally swallowed obtain immediate medical attention.
Never give anything by mouth to an unconscious person.
Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

None known.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-FST-Coating 362-80
Quality No.: 3628097237000

Revision Date 06.06.2021
Print Date 06.06.2021
Version 1

4.3 Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Alcohol resistant foam, CO2, powders

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard.

5.3 Advice for firefighters

Special protective equipment for firefighters : Appropriate breathing apparatus may be required.

Further information : Cool endangered containers with water in case of fire.
DO NOT ALLOW RUN-OFF FROM FIRE FIGHTING TO ENTER DRAINS OR WATER COURSES!!

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Exclude sources of ignition and ventilate the area.
Do not inhale vapours.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Do not let product enter drains.
If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see chapter 13).
Clean preferably with a detergent; avoid use of solvents.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Mankiewicz Gebr. & Co. (GmbH & Co. KG) Georg-Wilhelm-Straße 189 21107 Hamburg (Wilhelmsburg) Tel.: +49 (0) 40 / 75 10 30 Fax: +49 (0) 40 / 75 10 33 75 www.mankiewicz.de	Bank Name Deutsche Bank HypoVereinsbank Postbank	Ort Hamburg Hamburg Hamburg	Kto.-Nr. 600227300 59273300 373205	BLZ 200 700 00 200 300 00 200 100 20	BIC DEUTDE33HAN HYVEDE33HAN PBNKDE33HAN	IBAN DE58 2007 0000 0600 2273 00 DE34 2003 0000 0059 2733 00 DE85 2001 0020 0000 3732 05	Sitz/Registriergericht Hamburg: HRA 42442 Persönlich haftende Gesellschafterin: Grau Gebr. Beteiligungs-GmbH Sitz/Registriergericht Hamburg: HRB 17189 Geschäftsführender Gesellschafter: Michael O. Grau	Bureau Veritas Certification: ISO 9001, TS 16949, EN 9100 
--	--	---	--	--	---	--	--	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-FST-Coating 362-80
Quality No.: 3628097237000

Revision Date 06.06.2021
Print Date 06.06.2021
Version 1

Advice on safe handling : Comply with the health and safety at work laws.
In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded.
Smoking, eating and drinking should be prohibited in the application area.
Observe specific national regulations for handling and use of paints.

Advice on protection against fire and explosion : Keep away from ignition sources and provide for good ventilation.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Further information on storage conditions : Always keep in containers of same material as the original one. See also instructions on the label. Avoid heating and direct sunlight. Keep container dry in a cool, well-ventilated place. Avoid cooling to under 0°C.

Advice on common storage : Keep away from oxidizing agents and strongly acid or alkaline materials.

Recommended storage temperature : 5 - 35 °C

7.3 Specific end use(s)

Specific use(s) : This information is not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
titanium dioxide	13463-67-7	TWA (inhalable dust)	10 mg/m ³	GB EH40
		TWA (Respirable dust)	4 mg/m ³	GB EH40
(2-methoxymethylethoxy)propanol	34590-94-8	TWA	50 ppm 308 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 308 mg/m ³	GB EH40
	Further information: Can be absorbed through the skin. The assigned sub-			



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-FST-Coating 362-80
Quality No.: 3628097237000

Revision Date 06.06.2021
Print Date 06.06.2021
Version 1

	stances are those for which there are concerns that dermal absorption will lead to systemic toxicity., Where no specific short-term exposure limit is listed, a figure three times the long-term exposure limit should be used.			
1,2-dichlorobenzene	95-50-1	TWA	20 ppm 122 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 306 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	25 ppm 153 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	50 ppm 306 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
1,2-benzisothiazol-3(2H)-one	Workers	Inhalation	Long-term systemic effects	6.81 mg/m3
	Workers	Dermal	Long-term systemic effects	0.966 mg/kg bw/day
	Consumers	Inhalation	Long-term systemic effects	1.2 mg/m3
	Consumers	Dermal	Long-term systemic effects	0.345 mg/kg bw/day
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Workers	Inhalation	Long-term local effects	0.02 mg/m3
	Consumers	Inhalation	Long-term local effects	0.02 mg/m3
	Consumers	Oral	Long-term systemic effects	0.09 mg/kg bw/day

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
1,2-benzisothiazol-3(2H)-one	Fresh water	4.03 µg/l
	Marine water	0.403 µg/l
	Sewage treatment plant	1.03 mg/l
	Fresh water sediment	0.0499 mg/kg dry weight (d.w.)
	Marine sediment	0.00499 mg/kg dry weight (d.w.)
	Soil	3 mg/kg dry weight (d.w.)



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-FST-Coating 362-80
Quality No.: 3628097237000

Revision Date 06.06.2021
Print Date 06.06.2021
Version 1

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Fresh water	3.39 µg/l
	Sewage treatment plant	0.23 mg/l
	Marine water	3.39 µg/l
	Soil	0.01 mg/kg dry weight (d.w.)
	Marine sediment	0.027 mg/kg dry weight (d.w.)
	Fresh water sediment	0.027 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and below the OEL (= Occupational Exposure Limit), suitable respiratory protection must be worn.

Personal protective equipment

Eye protection : Wear safety goggles to protect against solvent splashes.

Hand protection

Remarks : Adhere to the professional organisation rule "Use of protective gloves". Appropriate chemicals resistant glove tested in compliance with EN 374.
Recommendation for protection against components generally found in the products:

For short-term contact (i.e. splash protection):

Appropriate material:

nitrile rubber, Neoprene

Material thickness: > 0,4 mm

Breakthrough time: > 480 min

Before use, the protective glove should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Preventive hand protection (skin protection cream) recommended. Wash immediately contaminated skin. Design operations thus to avoid permanent use of protective gloves.

Skin and body protection : Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

Respiratory protection : If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-FST-Coating 362-80
Quality No.: 3628097237000

Revision Date 06.06.2021
Print Date 06.06.2021
Version 1

Use half-mask model with cartridge or air-fed.
Dry grinding, torch cutting and/or welding however can produce hazardous dust and/or vapour.
If possible, machine employing a wet medium.
Where practicable, install exhaust hoods to improve capture of vapours and fumes and avoid exposition; otherwise wear respiratory protection equipment.

Protective measures : Do not eat or drink during work - no smoking.
Avoid product contact with skin, eyes and clothing.
When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : according product name

Odour : characteristic

pH : 7 - 9
Concentration: 100 %

Boiling point/boiling range : ca. 100 °C

Flash point : Not applicable

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 100 hPa (50 °C)

Density : 1.39 g/cm³ (20 °C)

Solubility(ies)
Water solubility : completely miscible

Auto-ignition temperature : > 300 °C

Viscosity
Flow time : 61 - 90 s
Cross section: 4 mm
Method: DIN 53211



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-FST-Coating 362-80
Quality No.: 3628097237000

Revision Date 06.06.2021
Print Date 06.06.2021
Version 1

41 s
Cross section: 6 mm
Method: ISO 2431

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.
There are no data available on the preparation itself.

10.4 Conditions to avoid

Conditions to avoid : Stable under recommended storage and handling conditions
(See section 7).

10.5 Incompatible materials

Materials to avoid : Keep away from oxidizing agents, strongly alkaline and
strongly acid materials in order to avoid exothermic reactions.

10.6 Hazardous decomposition products

When exposed to high temperatures may produce hazardous decomposition products such as
carbon monoxide and dioxide, smoke, oxides of nitrogen.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity : LD50 (Rat): 1,193 mg/kg

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

2-methylisothiazol-3(2H)-one:

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-FST-Coating 362-80
Quality No.: 3628097237000

Revision Date 06.06.2021
Print Date 06.06.2021
Version 1

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Exposure of vapour concentration in excess of the stated OEL's may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue muscular weakness, drowsiness and in extrem cases, loss of consciousness.
Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and absorption through the skin. The liquid splashed in the eyes may cause irritation and reversible damage.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : There are no data available on the preparation itself.

Mankiewicz Gebr. & Co. (GmbH & Co. KG) Georg-Wilhelm-Straße 189 21107 Hamburg (Wilhelmsburg) Tel.: +49 (0) 40 / 75 10 30 Fax: +49 (0) 40 / 75 10 33 75 www.mankiewicz.de	Bank Name Deutsche Bank HypoVereinsbank Postbank	Ort Hamburg Hamburg Hamburg	Kto.-Nr. 600227300 59273300 373205	BLZ 200 700 00 200 300 00 200 100 20	BIC DEUTDE33 HYVEDE33 PNKDEFF200	IBAN DE58 2007 0000 0600 2273 00 DE34 2003 0000 0059 2733 00 DE85 2001 0020 0000 3732 05	Sitz/Registergericht Hamburg: HRA 42442 Persönlich haftende Gesellschafterin: Grau Gebr. Beteiligungs-GmbH Sitz/Registergericht Hamburg: HRB 17189 Geschäftsführender Gesellschafter: Michael O. Grau	Bureau Veritas Certification: ISO 9001, TS 16949, EN 9100	
---	---	--------------------------------------	---	---	---	---	--	---	--

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-FST-Coating 362-80
Quality No.: 3628097237000

Revision Date 06.06.2021
Print Date 06.06.2021
Version 1

Components:

1,2-benzisothiazol-3(2H)-one:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2.18 mg/l
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 2.94 mg/l
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : ErC50 (Pseudokirchneriella subcapitata (green algae)): 0.11
plants mg/l
Exposure time: 72 h

reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1):

M-Factor (Acute aquatic tox- : 100
icity)

M-Factor (Chronic aquatic : 100
toxicity)

2-methylisothiazol-3(2H)-one:

M-Factor (Acute aquatic tox- : 10
icity)

M-Factor (Chronic aquatic : 1
toxicity)

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: There are no data available on the preparation it-
self.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: There are no data available on the preparation it-
self.

12.4 Mobility in soil

Product:

Mobility : Remarks: There are no data available on the preparation it-
self.

12.5 Results of PBT and vPvB assessment

Product:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-FST-Coating 362-80
Quality No.: 3628097237000

Revision Date 06.06.2021
Print Date 06.06.2021
Version 1

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : There are no data available on the preparation itself.

The product should not be allowed to enter drains or water courses.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The listed waste code numbers, according to the European Waste Catalogue, are to be understood as a recommendation. A final decision must be made in agreement with the regional waste disposal company.

Contaminated packaging : Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Packaging that cannot be cleaned should be disposed off in agreement with the regional waste disposal company.

Waste key for the unused product : 08 01 11 waste paint and varnish containing organic solvents or other hazardous substances

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good
Remarks : If transported within the user's premises: To be transported always in closed, upright and safe containers. Make sure that persons handling these containers are aware of the rules of conduct in case of incident or spillage.

IMDG : Not regulated as a dangerous good

IATA (Cargo) : Not regulated as a dangerous good

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-FST-Coating 362-80
Quality No.: 3628097237000

Revision Date 06.06.2021
Print Date 06.06.2021
Version 1

IATA (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Not classified as dangerous in the meaning of transport regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: formaldehyde (Number on list 72, 28)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Volatile organic compounds :

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 3.38 %, 65 g/l
Volatile CMR compounds: 0 %
VOC content excluding water

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for the mixture.

SECTION 16: Other information

Full text of H-Statements

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.
H311 : Toxic in contact with skin.

Mankiewicz Gebr. & Co. (GmbH & Co. KG)
Georg-Wilhelm-Straße 189
21107 Hamburg (Wilhelmsburg)
Tel.: +49 (0) 40 / 75 10 30
Fax: +49 (0) 40 / 75 10 33 75
www.mankiewicz.de

Bank Name	Ort	Kto.-Nr.	BLZ	BIC	IBAN
Deutsche Bank	Hamburg	600227300	200 700 00	DEUTDE33HAN	DE58 2007 0000 0600 2273 00
HypoVereinsbank	Hamburg	59273300	200 300 00	HYVEDE33HAN	DE34 2003 0000 0059 2733 00
Postbank	Hamburg	373205	200 100 20	PBNKDE33HAN	DE85 2001 0020 0000 3732 05

Sitz/Registriergericht Hamburg: HRA 42442
Bureau Veritas Certification: ISO 9001, TS 16949, EN 9100
Sitz/Registriergericht Hamburg: HRB 17189
Geschäftsführender Gesellschafter: Michael O. Grau



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-FST-Coating 362-80
Quality No.: 3628097237000

Revision Date 06.06.2021
Print Date 06.06.2021
Version 1

- H314 : Causes severe skin burns and eye damage.
- H315 : Causes skin irritation.
- H317 : May cause an allergic skin reaction.
- H318 : Causes serious eye damage.
- H319 : Causes serious eye irritation.
- H330 : Fatal if inhaled.
- H332 : Harmful if inhaled.
- H335 : May cause respiratory irritation.
- H400 : Very toxic to aquatic life.
- H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

- Acute Tox. : Acute toxicity
- Aquatic Acute : Short-term (acute) aquatic hazard
- Aquatic Chronic : Long-term (chronic) aquatic hazard
- Eye Dam. : Serious eye damage
- Skin Corr. : Skin corrosion
- Skin Irrit. : Skin irritation
- Skin Sens. : Skin sensitisation
- 2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
- GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
- 2000/39/EC / TWA : Limit Value - eight hours
- 2000/39/EC / STEL : Short term exposure limit
- GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
- GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006



Commercial Product Name: CELEROL-FST-Coating 362-80
Quality No.: 3628097237000

Revision Date 06.06.2021
Print Date 06.06.2021
Version 1

Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : The information given in this material safety data sheet does not release the user from its duty of risk assessment and control in the work place defined in other health and safety law. Adhere to the national sanitary and occupational safety regulations when using this product.

This safety datasheet complies with the requirements of regulation (EC) No 1907/2006(2015/830).

Department issuing safety data sheet

UMCO GmbH
Georg-Wilhelm-Str.187, D-21107 Hamburg
Telefon: +49(0)40/555 546 300 Fax: +49(0)40/555 546 357
e-mail:umco@umco.de

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN