FUSES & FUSEHOLDERS

5x20mm Fused Terminal Blocks


- 1 5 pole terminal strip with 5x20mm fuse holder to IEC257
- · Integral spare fuse carrier
- Interlocking fuse holder with CFTBN/1
- · Anti rotation spigot
- · IP20 finger protection
- Cable entry 4mm²
 (2.5mm² with wire protector)
- Wire protector on fuse terminal as standard
- Standard 3 to 5 pole with earth screw, without wire protectors
- Version 2 to 5WP without earth, with wire protector on all poles
- Version 3 to 5EWP with earth, wire protector on all poles except earth
- Version 3 to 5NE without earth, without wire protectors
- Wire protectors on earth pole to order
- Meets creepage and clearance requirements of IEC (8mm)
- · 16mm fixing pitch
- · Easily cut to size
- ANus, ⊕, ♠ (€,S)
 FIMKO, approved, on non earth versions



TYPE NO.	POLES
CFTBN/1	1 interlocking
CFTBN/2	2
CFTBN/3	3 with earth screw
CFTBN/4	4 with earth screw
CFTBN/5	5 with earth screw
CFTBN/3NE	3 no earth facility
CFTBN/4NE	4 no earth facility
CFTBN/5NE	5 no earth facility
CFTBN/2WP	2 with wire protector
	& no earth facility
CFTBN/3WP	3 with wire protector
	& no earth facility
CFTBN/4WP	4 with wire protector
	& no earth facility
CFTBN/5WP	5 with wire protector
	& no earth facility
CFTBN/3EWP	3 with wire protector
	& earth screw (no WP
	on earth connetion)
CFTBN/4EWP	4 with wire protector
	& earth screw (no WP
	on earth connetion) 5
CFTBN/5EWP	with wire protector &
	earth screw (no WP
	on earth connetion)
CFTBN/3EWPG	3 with wire protection
	on all poles &
	earth screw
CFTBN/4EWPG	4 with wire protection
	on all poles &
	earth screw
CFTBN/5EWPG	5 with wire protection
	on all poles &
	earth screw

SPECIFICATION	
Rating	Fuse hol
	Terminal
Current rating	Fuse hol
	Terminal
Moulding	UL94-V0
Terminal	Brass, ni
Fuse clip	Phospho
Wire protector	Stainless
Temperature	-20° to 1
Fuse size	5x20mm
Screws	МЗ

Locating anti-rotation spigot ø3 -Earth screw M3-



On CFTBN/1 spigot to mounting hole = 10mm

