
■ Lead Free ■ HF **■** RoHS Features

- Compact size 3.5x3.55mm.
- Horizontal direction.



DC12V 50mA Rating (max) Contact Resistance 500mΩ max. Insulation Resistance DC500V-100M Ω min. Withstand Voltage AC250V - 1 minute 0.2 ^{+0.2}_{-0.1} mm

Recommended Reflow Soldering Profile



Recommended Manual Soldering Profile


	Temperature	Time
Manual Soldering Temperature	350 ℃ (max.)	3 Sec.(max.)

The solder iron and solder shall be applied at a distance of 1.91 mm to 2.54 mm from the plastic housing.

Operating Force & Durability

$160 \pm \frac{70}{40} \text{ gf}$	100,000 cycles
220 ± 80 gf	100,000 cycles

■ SMT- G Type Horizontal 3.5L x 3.55W x 1.35H ■ Outline Drawing [Without Ground Terminal]



■ Outline Drawing

General Tolerance: ±0.2mm.


■ SMT - T Type Horizontal 3.5L x 3.55W x 1.35H [Without Ground Terminal]

Product No.	Boss	Package
NTC311-EC1T-AT	With	3,500 Pcs/Reel

P.C.B Layout

Schematic


1)-



General Tolerance: ±0.2mm.

3.5L x 3.55W x 1.35H ■ SMT- G Type Horizontal [With Ground Terminal]

Product No.	Boss	Package
NTC311-FC1G-AT	Without	3,500 Pcs/Reel
NTC311-FD1G-AT	With	



■ Outline Drawing

General Tolerance: ±0.2mm.

