

	1	2	3	4	5	6	7																																																																									
A	Recommended P.C.B Layout(Top Side) (PCB BOARD TOLERANCE±0.05) 2,54							A																																																																								
B								B																																																																								
C								C																																																																								
D	⑤ 1.Current Rating: 3AMP/ 2.Voltage Rating: 250V 3.Withstand Voltage: 500V AC/Minute 4.Contact Resistance : 20mΩ max 5.Insulation Resistance: 1000MΩ min ENVIRONMENTAL 1.Operation Temperature: -40°C to +105°C 2.Packing: Tray packing							D																																																																								
E	Order information: xx : 06.08.10.12.14.16.18.20.24 26.30.34.40.50.60.64							E																																																																								
F	<table><thead><tr><th colspan="2">Dimension antitheses list</th></tr><tr><th>NO. Pin</th><th>L</th></tr></thead><tbody><tr><td>6P-8P</td><td>4.00</td></tr><tr><td>10P-64P</td><td>4.40</td></tr></tbody></table>							Dimension antitheses list		NO. Pin	L	6P-8P	4.00	10P-64P	4.40	F																																																																
Dimension antitheses list																																																																																
NO. Pin	L																																																																															
6P-8P	4.00																																																																															
10P-64P	4.40																																																																															
G	Customer-No. ASSMANN WSW-No. AW/HW xxG-0202-T AW/HW xxG-0102-T							G																																																																								
H	Drawing-No. ASS 2314 CO rev05							H																																																																								
RoHS compliant Unit: mm ④ UL File No.: E198287																																																																																
<table><thead><tr><th>Scale</th><th>Free</th><th></th><th></th><th></th><th></th><th></th><th></th></tr></thead><tbody><tr><td>TOLERANCE</td><td>⑤</td><td>Add voltage rating</td><td></td><td></td><td>Date</td><td>Name</td><td></td></tr><tr><td>X.X</td><td>⑤</td><td>Add UL file no.</td><td></td><td>09.07.2019</td><td>Xavier</td><td>Drawn</td><td>25.01.2006</td></tr><tr><td>X.XX</td><td>④</td><td>Add the plating Au 30u"</td><td></td><td>12.12.2013</td><td>Amy</td><td>Approved</td><td>12.12.2013</td></tr><tr><td>X.XXX</td><td>③</td><td>Update</td><td></td><td>23.10.2013</td><td>Winnie</td><td></td><td></td></tr><tr><td>DIM</td><td>②</td><td>Drawn</td><td></td><td>29.06.2009</td><td>Dean</td><td></td><td></td></tr><tr><td>Angle</td><td>①</td><td></td><td></td><td>25.01.2006</td><td>Alex</td><td></td><td></td></tr><tr><td></td><td></td><td>Modification</td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table> ASSMANN components								Scale	Free							TOLERANCE	⑤	Add voltage rating			Date	Name		X.X	⑤	Add UL file no.		09.07.2019	Xavier	Drawn	25.01.2006	X.XX	④	Add the plating Au 30u"		12.12.2013	Amy	Approved	12.12.2013	X.XXX	③	Update		23.10.2013	Winnie			DIM	②	Drawn		29.06.2009	Dean			Angle	①			25.01.2006	Alex					Modification														
Scale	Free																																																																															
TOLERANCE	⑤	Add voltage rating			Date	Name																																																																										
X.X	⑤	Add UL file no.		09.07.2019	Xavier	Drawn	25.01.2006																																																																									
X.XX	④	Add the plating Au 30u"		12.12.2013	Amy	Approved	12.12.2013																																																																									
X.XXX	③	Update		23.10.2013	Winnie																																																																											
DIM	②	Drawn		29.06.2009	Dean																																																																											
Angle	①			25.01.2006	Alex																																																																											
		Modification																																																																														
1 2 3 4 5 6 7																																																																																
SV3409																																																																																

	1	2	3	4	5	6	7	
A	Temperature Time(Sec) A:Preheating B:Soldering C:Gradual Cooling Tip Temperature Time:3-5Sec							A
B								B
C								C
D								D
E								E
F	RoHS compliant Unit: mm File No.: E198287							F
G								G
H								H
1	2	3	4	5	6	7	S/3409	