



02P




03P



12.6

5




11.6

26

8.3

5.8



5.08xN

4


5.08

5.08x(N-1)



1

2




02P: Clasp on the right from this view

3

未注公差/General tolerances (mm)

0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
~3	~6	~10	~18	~30	~50	~80	~120	~180	~250	~315	~400	~500	>500	
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2'



5	Screw	Steel	M3/Zn Plated
4	Cage	Copper alloy	M3/Ni Plated
3	Clamp	Copper alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	300/15	/	300/10
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	/	320/18	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	/	4	/
螺丝扭矩/Torque Tightening(N·m/Lb.in)	M3, 0.66/6		
线径范围(硬线和软线)/Wire Range (rigid and flexible)(AWG/mm ²)	28~12 / 1.0~2.5		
间距/Pitch(mm)/线数范围/Poles	5.08/N=02~24P		
剥线长度/Stripping length(mm)	7		
使用温度范围/Operating temperature(°C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number: PANTONE / RAL	/		

		MATERIAL:	SURFACE/COLOR:	
APPD: 兰春华 2022.11.14		MAT NO./REV:	/ 00 MAT STATUS: 批量	
CHKD: 龚耀志 2022.11.11		NAME		
DRFT: 胡松 2022.11.11		2EDGKA-5.08-XXP-1Y-1000L (H)		
DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
200101574	CUSTOMER DRAWING	已发布	2:1	1/1

00			胡松	2022.11.11
REV	ECN	DESCRIPTION	DRFT	DATE

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless authorized in writing. All rights reserved for patent, utility model or design registrations. 除专利权明确标注外, 其他标注均非本公司所有。未经许可, 不得复制或传播。本公司保留对涉及发明、实用新型及外观设计专利的权利。