

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or design registrations. 除专利、实用新型、外观设计、发明专利、软件著作权、商标、名称权、商号权、域名权、其他知识产权等权利外，本公司保留对涉及发明、实用新型、外观设计、发明专利、软件著作权、商标、名称权、商号权、域名权、其他知识产权等权利的所授权利。

FOR-1755 Rev.1.7

2

3

4

5

6

未注公差/General tolerances (mm)

0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/10
3	6	10	18	30	50	80	120	180	250	315	400	500		±2'
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	

UL 标准/UL Standard:

额定电压/电流/Rated Voltage(V)/Current(A)

B

C

D

IEC 标准/IEC Standard:

过压类别/Overvoltage Category/污染等级/Pollution Degree

III/3

III/2

II/2

额定电压/电流/Rated Voltage(V)/Current(A)

/

320/20

/

额定脉冲电压(KV)/Rate Impulse Voltage(KV)

/

4

/

螺丝扭矩/Torque Tightening(N·m/Lb.in)

M2.5, 0.5/4.43

线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)

28~12 / 0.2~2.5

间距/Pitch(mm)/线数范围/Poles

5.0/N=02~24P

剥线长度/Stripping length(mm)

9~10

使用温度范围/Operating temperature(°C)






-40~+105

符合RoHS环保要求/Conform to RoHS

Yes

6	Screw	Steel	M2.5/Zn Plated
5	Cage	Steel	M2.5/Zn Plated
4	Block	Steel	Zn Plated
3	Clamp	Copper alloy	Sn Plated
2	Cover	PA66	UL94V-0
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES

02P:Clasp on the left from this view



MATERIAL:

SURFACE/COLOR:

MAT NO./REV:

/ 00

MAT STATUS: 批量

APPD: 兰春华

2023.03.31

CHKD: 龚耀志

2023.03.31

DRFT: 朱岳鹏

2023.03.31

DRAWING NO.

TYPE

DRAWING STATUS

SCALE

SHEET

200140180

CUSTOMER DRAWING

已发布

2:1

1/1

01		2x由00版升为01版, 提升UL电流及扭力大小	朱岳鹏	2023.03.31
REV	ECN	DESCRIPTION	DRFT	DATE

1

2

3

4

5

6