



Metal Film Resistors, Military/Established Reliability, MIL-PRF-55182 Qualified, Precision, Type RNC, Characteristics J, H, K



FEATURES

- Meets requirements of MIL-PRF-55182
Very low noise (- 40 dB)
Verified failure rate (contact factory for current level)
100 % stabilization and screening tests. Group A testing, if desired, to customer requirements
Controlled temperature coefficient
Epoxy coating provides superior moisture protection
Standard lead on RNC product is solderable and weldable
Traceability of materials and processing
Monthly acceptance testing
Vishay Dale has complete capability to develop specific reliability programs designed to customer requirements
Extensive stocking program at distributors and factory on RNC50, RNC55, RNC60 and RNC65
For MIL-PRF-55182 characteristics E and C product, see Vishay Angstrom's HDN (Military RNR/RNN) datasheet (www.vishay.com/doc?66001)

Table with 10 columns: GLOBAL MODEL, MIL-PRF-55182 STYLE, MIL SPEC. SHEET, POWER RATING P70 °C W, POWER RATING P125 °C W, TOLERANCE ± %, MAXIMUM WORKING VOLTAGE V, RESISTANCE RANGE Ω, TEMPERATURE COEFFICIENT ± ppm/°C, LIFE FAILURE RATE (1)

Notes


- (1) Consult factory for current QPL failure rates.
(2) Continuous working voltage shall be √P x R or maximum working voltage, whichever is less.
(3) Hot solder dipped leads.
(4) Tolerance of ± 0.1 % is not applicable to characteristics K.

Table with 3 columns: PARAMETER, UNIT, CONDITION

GLOBAL PART NUMBER INFORMATION						
New Global Part Numbering: RNC55H2152FR R36 (preferred part numbering format)						
<div style="display: flex; justify-content: space-around; font-weight: bold; font-size: 1.2em;"> R N C 5 5 H 2 1 5 2 F R R 3 6 </div>						
MIL STYLE	CHARACTERISTICS	RESISTANCE VALUE	TOLERANCE CODE	FAILURE RATE	PACKAGING	SPECIAL
RNC = Solderable/weldable RNR = Solderable only (see Standard Electrical Specifications table)	J = ± 25 ppm H = ± 50 ppm K = ± 100 ppm	3 digit significant figure, followed by a multiplier Use "R" for values < 100 Ω 10R0 = 10 Ω 2152 = 21.5 kΩ 3014 = 3.01 MΩ	B = ± 0.1 % D = ± 0.5 % F = ± 1 %	M = 1.0%/1000 h P = 0.1%/1000 h R = 0.01%/1000 h S = 0.001%/1000 h	B14 = Tin/lead, bulk BSL = Tin/lead, bulk, single lot date code R36 = Tin/lead, T/R (full; 50, 55, 60) R64 = Tin/lead, T/R (full; 65, 70) RE6 = Tin/lead, T/R (1000 pieces) RSL = Tin/lead, T/R, single lot date code	Blank = Standard (Dash number) (Up to 3 digits) From 1 to 999 as applicable 4 = Hot solder dip (70's) 31 = Hot solder dip (50's) 65 = Hot solder dip (55's, 65's) 201 = Hot solder dip (60's)
Historical Part Number example: RNC55H2152FR R36 (will continue to be accepted)						
RNC55	H	2152	F	R	R36	
MIL STYLE	CHARACTERISTIC	RESISTANCE VALUE	TOLERANCE CODE	FAILURE RATE	PACKAGING	

Note

- For additional information on packaging, refer to the Through Hole Resistor Packaging document (www.vishay.com/doc?31544).

DIMENSIONS in inches (millimeters)

Note

- (1) Lead length for product in bulk pack. For product supplied in Tape and Reel, the actual lead length would be based on the body size, tape spacing and lead trim.

VISHAY DALE MODEL	MIL-PRF-55182 STYLE	A	B	C (MAX.)	D	E
ERC50	RNC50, RNR50	0.150 ± 0.020 (3.81 ± 0.51)	0.070 ± 0.010 (1.78 ± 0.25)	0.187 (4.75)	0.016 ± 0.002 (0.41 ± 0.05)	1.25 ± 0.266 (31.75 ± 6.76)
ERC55	RNC55, RNR55	0.250 ± 0.031 - 0.046 (6.35 ± 0.79 - 1.17)	0.094 ± 0.012 (2.39 ± 0.30)	0.300 (7.62)	0.025 ± 0.002 (0.64 ± 0.05)	1.50 ± 0.125 (38.1 ± 3.18)
ERC55..200	RNC60, RNR60	0.280 ± 0.020 (7.11 ± 0.51)	0.097 ± 0.012 (2.46 ± 0.30)	0.350 (8.89)	0.025 ± 0.002 (0.64 ± 0.05)	1.50 ± 0.125 (38.1 ± 3.18)
ERC65	RNC65, RNR65	0.562 ± 0.031 (14.27 ± 0.79)	0.180 ± 0.015 (4.57 ± 0.38)	0.687 (17.45)	0.025 ± 0.002 (0.64 ± 0.05)	1.50 ± 0.125 (38.1 ± 3.18)
ERC70	RNC70, RNR70	0.562 ± 0.031 (14.27 ± 0.79)	0.180 ± 0.015 (4.57 ± 0.38)	0.687 (17.45)	0.032 ± 0.002 (0.81 ± 0.05)	1.50 ± 0.125 (38.1 ± 3.18)

MATERIAL SPECIFICATIONS	
Element	Vacuum-deposited nickel-chrome alloy
Core	Fire-cleaned high purity ceramic
Encapsulation	Specially formulated epoxy compound
Termination	Standard lead material is solder-coated copper solderable and weldable per MIL-STD-1276, type C

POWER RATING

Power ratings are based on the following two conditions:

- ± 2.0 % maximum DR in 10 000 h load life
- + 175 °C maximum operating temperature

APPLICABLE MIL-SPECIFICATIONS
MIL-PRF-55182:

The ERC series meets the electrical, environmental and dimensional requirements of MIL-PRF-55182.

MIL-R-10509:

MIL-PRF-55182 supercedes MIL-R-10509 on new designs. The ERC series meets or exceeds MIL-R-10509 requirements.



DOCUMENTATION:

Qualification and failure rate verification test data is maintained by Vishay Dale and is available upon request. Lot traceability and identification data is maintained by Vishay Dale for five years.

CAGE CODE: 91637



Vishay Dale ERC resistors have an operating temperature range of - 65 °C to + 175 °C. They must be derated according to the following curve:



MARKING (per MIL-PRF-55182)	
Characteristics: K = 100 ppm, H = 50 ppm, J = 25 ppm	
Tolerance: F = 1 %, D = 0.5 %, B = 0.1 %	
Value = Three significant figures and multiplier	
J = JAN (Joint Army - Navy) brand	
RNC/RNR50, 55 (4 lines)	RNC/RNR60, 65, 70 (5 lines)
D Manufacturer's code	91637 CAGE code
210H 3 digit date code and characteristic	1213J 4 digit date code and JAN
1003 Value	RNC60J Style and characteristic
FSCJ Tolerance, failure rate, lead material and JAN	1211FS Value, tolerance, and failure rate
	1209A Production lot code



MILITARY RESISTORS 101

Resistive Products



Overview of Military Resistors from Vishay Dale



MILITARY QUALIFICATIONS

- Film Technology
 - MIL-R-10509 Leaded Metal Film Resistor, type RN
 - MIL-PRF-22684 Leaded Metal Film Resistor, type RL
 - MIL-PRF-32159 Thick Film Chip Jumper, E-Rel type RCZ
 - MIL-PRF-39017 Leaded Metal Film Resistor, E-Rel type RLR
 - MIL-PRF-55182 Leaded Metal Film Resistor, E-Rel type RNC / RNR / RNN
 - MIL-PRF-55342 Thick Film / Thin Film Chip Resistor, E-Rel type RM
- Wirewound Technology
 - MIL-PRF-26 Leaded Wirewound Resistor, type RW
 - MIL-PRF-18546 Housed Wirewound Resistor, type RE
 - MIL-PRF-39007 Leaded Wirewound Resistor, E-Rel type RWR
 - MIL-PRF-39009 Housed Wirewound Resistor, E-Rel type RER
 - MIL-PRF-49465 Leaded Metal Element Resistor, type RLV
- Networks
 - MIL-PRF-83401 Thick Film / Thin Film Resistor Network, type RZ

RESOURCES

- For technical questions on Film and Network products, contact ff2aresistors@vishay.com
- For technical questions on Wirewound products contact ww2bresistors@vishay.com

One of the World's Largest Manufacturers of
Discrete Semiconductors and Passive Components





MILITARY RESISTORS 101

Introduction



Introduction

Vishay's line of high-reliability products reflects a long-term commitment to our military customers. As one of the largest suppliers of military components, we continually strive to meet the changing application requirements of the defense, avionics and aerospace markets by developing new products and manufacturing technologies on an ongoing basis.

Vishay has one of the broadest lines of military-qualified resistors in the industry, and our high-reliability devices can be found in nearly every existing military program, including aircraft, satellites, missiles, weapons, ground vehicles, and ships.

Vishay is equipped to design and produce custom components to meet many design and reliability demands. In addition to standard military-grade resistor products, we also have many resistive products designed to meet various military source-controlled drawings.

Every component Vishay provides to the military, avionics and aerospace markets is backed by the comprehensive testing and failure analysis capabilities of our own technical staff, who are industry experts in understanding and meeting the requirements of the military environment. Our technical expertise, our knowledge of the military industry, our broad product offering, and our ability to work long-term are all part of Vishay's ongoing commitment to meeting the changing requirements of our most reliability-conscious customers, today and in the future.

Target Applications

- Aircraft
- Avionics
- Satellites
- Surveillance
- Communications systems
- Naval vessels
- Sonar
- Missile systems
- Weaponry
- Radar
- Ground vehicles
- Space, ocean, and deep earth exploration
- Medical instrumentation and medical implantables



MILITARY RESISTORS 101

Product Information – Networks



Network Technology

MIL Spec	Product Type		MIL Style	Power Rating (Watts)	Value Range (Ohms)	Tol. Range (± %)	TCR Range (± ppm/°C)	Failure Rate Range
MIL-PRF-83401	Thick Film, Network	Dual-In-Line	RZ010	0.05 to 0.20	10 to 1 M	1 to 5	100 to 300	n/a
			RZ020	0.05 to 0.20	10 to 1 M	1 to 5	100 to 300	n/a
		Flat Pack	RZ030	0.015 to 0.05	10 to 1 M	1 to 5	100 to 300	n/a
			RZ040	0.11 to 0.20	10 to 1 M	1 to 5	100 to 300	n/a
		Single-In-Line	RZ050	0.11 to 0.20	10 to 1 M	1 to 5	100 to 300	n/a
			RZ060	0.11 to 0.20	10 to 1 M	1 to 5	100 to 300	n/a
			RZ070	0.07 to 0.12	10 to 1 M	1 to 5	100 to 300	n/a
			RZ080	0.07 to 0.12	10 to 1 M	1 to 5	100 to 300	n/a
			RZ090	0.07 to 0.12	10 to 1 M	1 to 5	100 to 300	n/a
			RZ180	0.1	n/a	2	100	n/a
	RZ190		0.1	n/a	2	100	n/a	
	RZ240		0.07 to 0.12	10 to 1 M	1 to 5	100 to 300	n/a	
	Thin Film, Network	Single-In-Line	RZ070	0.06 to 0.12	100 to 100k	0.1 to 5	50 to 300	n/a
				0.06 to 0.12	250 to 200k	1 to 5	25 to 50 ¹	n/a
				0.06 to 0.12	250 to 100k	0.1 to 0.5	25 to 50 ¹	n/a
			RZ080	0.06 to 0.12	100 to 100k	0.1 to 5	50 to 300	n/a
				0.06 to 0.12	250 to 200k	1 to 5	25 to 50 ¹	n/a
				0.06 to 0.12	250 to 100k	0.1 to 0.5	25 to 50 ¹	n/a
			RZ090	0.06 to 0.12	100 to 100k	0.1 to 5	50 to 300	n/a
				0.06 to 0.12	250 to 200k	1 to 5	25 to 50 ¹	n/a
				0.06 to 0.12	250 to 100k	0.1 to 0.5	25 to 50 ¹	n/a
			RZ210	0.06 to 0.12	100 to 100k	0.1 to 5	50 to 300	n/a
				0.06 to 0.12	250 to 200k	1 to 5	25 to 50 ¹	n/a
				0.06 to 0.12	250 to 100k	0.1 to 0.5	25 to 50 ¹	n/a
			RZ220	0.06 to 0.12	100 to 100k	0.1 to 5	50 to 300	n/a
				0.06 to 0.12	250 to 200k	1 to 5	25 to 50 ¹	n/a
				0.06 to 0.12	250 to 100k	0.1 to 0.5	25 to 50 ¹	n/a
RZ230			0.06 to 0.12	100 to 100k	0.1 to 5	50 to 300	n/a	
			0.06 to 0.12	250 to 200k	1 to 5	25 to 50 ¹	n/a	
	0.06 to 0.12	250 to 100k	0.1 to 0.5	25 to 50 ¹	n/a			

¹ With ± 5 ppm/°C TC tracking between resistive elements.

Thick Film Military Networks


MIL-PRF-83401, Type RZ

MSM Series, Slash Sheets 04 - 09, 18, 19 and 24

MDM Series, Slash Sheets 01 - 02

DFM Series, Slash Sheets 03

- Thick film element in a rugged molded case construction
- Available in isolated, bussed, and dual terminator schematics
- Hot solder dipped leads



Thin Film Military Networks

MIL-PRF-83401, Type RZ

M83401 Series, Slash Sheets 07 – 09 and 21 – 23

- Thin film element in a rugged molded low profile construction with standoff
- Available in isolated or bussed schematics
- Tolerances to 0.1% and TC's to 25ppm/°C





MILITARY RESISTORS 101

Product Information – Networks



Style Comparison of Vishay Thick Film Networks

Parameter	Military (MDM, MSM, DFM)	Industrial (MDP, MSP, DFP)	Commercial (CSC)
Electrical Specifications	All components conform to military power ratings. Tolerance, resistance and TCR are supplied according to the “Qualified Products List” for MIL-PRF-83401.	Electrical specifications detailed in the Vishay Dale catalog. Industrial power ratings are generally higher than military components. This is possible because industrial components do not have the same reliability requirements.	Electrical specifications detailed in the Vishay Dale catalog. Commercial power ratings are the same as industrial counterparts.
Mechanical Dimensions	Components conform to MIL-PRF-83401.	Dimensions are detailed in the Vishay Dale catalog. Equivalent industrial components are basically the same size as the military components and will fit into the same packages and board spacing.	Dimensions are detailed in the Vishay Dale catalog. Equivalent commercial components are basically the same size as the military components and will fit into the same packages and board spacing.
Material Requirements	All materials for the military components are approved for use within the specific components’ military qualification. All materials are baselined and cannot be modified or substituted without military approval, by request or re-qualification. No materials can be used in their manufacture without labels showing acceptance through incoming inspection.	Most materials are the same for military equivalent components and also require inspection acceptance labels. Materials are not qualified on a military controlled baseline, but are typically internally required to allow the component to meet the MIL-PRF-83401 military specification.	Uses low cost materials that are similar to those used for the Industrial components. Internal qualification of changes does not require a governing agency’s approval.
Process and Test Requirements	Components conform to MIL-PRF-83401 military specifications, and are manufactured using military qualified and documented processes. Requires 1000 hour load life in addition to other rigid environmental testing to conform to the above specifications. 100 % screen tested per MIL-PRF-83401’s Group A.	Do not have additional processing and screening tests that military equivalent components require. Process modifications to conform to special or unique customer requirements is allowed. Only internal qualifications required for major process changes.	Process modifications to conform to special or unique customer requirements are generally not allowed. Product 100 % electrically tested before shipping.
Reliability	Periodic internal testing to specific environmental and electrical parameters derived from the MIL-PRF-83401 military specification are incorporated. Components are pulled from actual production and tested to conformance. Product specific statistics are available upon request.	Periodic internal testing to specific environmental and electrical parameters derived from the MIL-PRF-83401 military specification is incorporated. Components are pulled from actual production and tested to conformance. Product specific statistics are available upon request.	Failure rate is based on field failures, which are the total number of failures versus the total number of products shipped.
Customer Application	Military, space, and medical applications.	Wide range of applications including communications, military, computer, test and control electronics.	Wide range of applications including computer, telecom, and consumer electronics.
Traceability	All component materials are required to be traceable.	Materials are generally not required to be traceable. Traceability can be incorporated on components as a “special” if required by a customer.	Materials are generally not required to be traceable.

Resistors - Military Resistors 101



MILITARY RESISTORS 101

Product Information – Film Axial Leaded



Film Axial Leaded Technology

MIL Spec	Product Type	MIL Style	Power Rating (Watts)	Value Range (Ohms)	Tol. Range (± %)	TCR Range (± ppm/°C)	Failure Rate Range
MIL-R-10509	Metal Film, Axial Leaded	RN50	0.05	10 to 100 k	0.1 to 1	25 to 50	n/a
		RN55	0.10 to 0.125	49.9 to 100 k	0.1 to 1	25 to 50	n/a
				10 to 301 k	1	100	n/a
		RN60	0.125 to 0.25	49.9 to 499 k	0.1 to 1	25 to 50	n/a
				10 to 1 M	1	100	n/a
		RN65	0.25 to 0.50	49.9 to 1 M	0.1 to 1	25 to 50	n/a
				10 to 2 M	1	100	n/a
		RN70	0.5 to 0.75	24.9 to 1 M	0.1 to 1	25 to 50	n/a
10 to 2.49 M	1			100	n/a		
MIL-PRF-22684	Metal Film, Axial Leaded	RL07	0.25	51 to 150 k	2 to 5	200	n/a
		RL20	0.5	4.3 to 470 k	2 to 5	200	n/a
MIL-PRF-39017	Metal Film, Axial Leaded	RLR05	0.125	4.7 to 301 k	1 to 2	100	M, P, R, and S
				302 k to 1 M	1 to 2	100	M, P, and R
		RLR07	0.25	1 to 9.76	1 to 2	100	M
				10 to 3.01 M	1 to 2	100	M, P, R, and S
		RLR20	0.5	3.02 M to 10 M	1 to 2	100	M, P, and R
				4.3 to 3.01 M	1 to 2	100	M, P, and R
RLR32	1	1 to 2.7 M	1 to 2	100	M, P, and R		
MIL-PRF-55182	Metal Film, Axial Leaded	RNC50	0.05 to 0.1	10 to 796 k	0.1 to 1	25 to 100	M, P, R, and S
		RNC55	0.1 to 0.125	10 to 2 M	0.1 to 1	25 to 100	M, P, R, and S
		RNC60	0.125 to 0.25	10 to 2 M	0.1 to 1	25 to 100	M, P, R, and S
				2.01 M to 3.01 M	0.5 to 1	25 to 100	M
		RNC65	0.25 to 0.5	10 to 3.01 M	0.1 to 1	25 to 100	M, P, and R
		RNC70	0.5 to 0.75	10 to 3.01 M	0.1 to 1	25 to 100	M, P, and R
	Metal Film, Axial Leaded, Hermetically-Sealed	RNR55	0.1 to 0.125	10 to 1.21 M	0.1 to 1	25 to 50	M, P, R, and S
		RNR57	0.125 to 0.25	49.9 to 200 k	1	25 to 50	M, P, R, and S
		RNR60	0.125 to 0.25	10 to 2.49 M	0.1 to 1	25 to 50	M, P, R, and S
		RNR65	0.25 to 0.5	24.9 to 4.99 M	0.1 to 1	25 to 50	M, P
		RNR70	0.5 to 0.75	24.9 to 4.99 M	0.1 to 1	25 to 50	M, P
		RNR75	1 to 2	49.9 to 1.21 M	0.1 to 1	25	M

Resistors - Military Resistors 101



MILITARY RESISTORS 101

Product Information – Film Axial Leaded



Resistors - Military Resistors 101

Metal Film Military Resistors

**MIL-R-10509, Type RN,
MIL-PRF-22684, Type RL
CMF Series**



- Available in MIL sheet sizes 50, 55, 60, 65 and 70 for RN style, and sizes 07 and 20 for RL style
- Full material and process traceability
- Values range from 0.1 Ω to 50 MΩ (far beyond military spec value limits)

Established Reliability Metal Film Military Resistors

**MIL-PRF-39017, Type RLR
ERL Series**




- Available in MIL sheet sizes 05, 07, 20 and 32
- Verified failure rates
 - S failure rate standard for most sizes
 - M, P, R failure rate levels also available
- Full material and process traceability
- DSCC drawing (non-QPL) available on multiple sizes to extended resistance ranges

Established Reliability Metal Film Military Resistors

**MIL-PRF-55182, Type RNC/RNR
ERC Series**

- Available in MIL sheet sizes 50, 55, 60, 65 and 70
- Characteristics J, H and K (non hermetically sealed)
- Verified failure rates
 - S failure rate standard for most sizes
 - M, P, R failure rate levels also available
- Full material and process traceability



Established Reliability Metal Film Military Resistors

**MIL-PRF-55182, Type RNR/RNN
HDN Series**

- Available in MIL sheet sizes 55, 57, 60, 65, 70 and 75
- Characteristics C and E (hermetically sealed)
- Verified failure rates
 - S failure rate standard for most sizes
 - M, P, R failure rate levels also available
- Full material and process traceability



Style Comparison of Vishay Metal Film Axial Resistors

Parameter	E-REL MILITARY RLR: (Vishay DALE ERL) RNC: (Vishay DALE ERC)	NON E-REL MILITARY/INDUSTRIAL (Vishay DALE CMF Prefix Designation)	COMMERCIAL CCF
Electrical Specifications	All components conform to military power ratings. Tolerance, resistance and TCR are supplied according to the “Qualified Products List” for MIL-PRF-39017 for RLR series and MIL-PRF-55182 for RNC series.	Non E-Rel power ratings are the same as E-Rel counterparts. Frequently used at the industrial power ratings, which are generally higher than those for E-Rel components.	Electrical specifications detailed in the Vishay Dale catalog. Commercial power ratings are generally higher than E-Rel components. This is possible because commercial components do not have the same reliability requirements.
Mechanical Dimensions	Components conform to MIL-PRF-39017 for the Vishay Dale RLR series. Components conform to MIL-PRF-55182 for the Vishay Dale RNC series.	Components conform to MIL-PRF-22684 for the Vishay Dale RL series. Components conform to MIL-R-10509 for the Vishay Dale RN series.	Dimensions are detailed in the Vishay Dale catalog. Equivalent commercial components are basically the same size as the military components and will fit into the same packages and board spacing.



MILITARY RESISTORS 101

Product Information – Film Axial Leaded



Style Comparison of Vishay Metal Film Axial Resistors, continued

Parameter	E-REL MILITARY RLR: (Vishay DALE ERL) RNC: (Vishay DALE ERC)	NON E-REL MILITARY/ INDUSTRIAL (Vishay DALE CMF Prefix Designation)	COMMERCIAL CCF
Material Requirements	All materials for the E-Rel military components are approved for use within the specific components' military qualification. All materials are baselined and cannot be modified or substituted without military approval, by request or re-qualification. No materials can be used in their manufacture without labels showing acceptance through incoming inspection.	Most materials are the same for E-Rel equivalent components and also require inspection acceptance labels. Materials are not qualified on a military controlled baseline, but are internally required to allow the component to meet the MIL-PRF-22684 or MIL-R-10509 military specifications.	Uses low cost materials that are similar to those used for the Industrial components. Internal qualification of changes does not require a governing agency's approval.
Process and Test Requirements	The RLR series conforms to MIL-PRF-39017 military specifications. The RNC series conforms to MIL-PRF-55182 military specifications. Reliability determination requires 10 000 hour load life in addition to other rigid environmental testing to conform to the above specifications	The RL series conforms to MIL-PRF-22684 military specifications. The RN series conforms to MIL-R-10509 military specifications. Do not have additional processing and screening tests that E-Rel equivalent components require. 1000 hour load life testing performed.	Process modifications to conform to special or unique customer requirements are generally not allowed. Product 100 % electrically tested before shipping.
Reliability	An "Established Reliability" quality level is determined by continuously testing thousands of components in a qualified laboratory. The reliability "Failure Rate Level" is specified in the MIL-PRF-39017 or MIL-PRF-55182 military specifications and is derived from the laboratory data. Product specific statistics are available upon request.	Periodic internal testing to specific environmental and electrical parameters derived from the MIL-PRF-22684 or MIL-R-10509 military specifications are incorporated. Components are pulled from actual production and tested to conformance. Product specific statistics are available upon request.	Failure rate is based on field failures, which are the total number of failures versus the total number of products shipped.
Customer Application	Military, space, medical, and other high-reliability applications.	Wide range of applications including communications, military, computer, test and control electronics.	Wide range of applications including computer, telecom, and consumer electronics.
Traceability	All component materials are required to be traceable.	Materials are generally not required to be traceable. Traceability can be incorporated on components as a "special" if required by a customer.	Materials are generally not required to be traceable.
Packaging	Available in either bulk or reeled.	Available in either bulk or reeled.	Available only as reeled.

Resistors - Military Resistors 101



MILITARY RESISTORS 101

Product Information – Film Surface Mount



Film Surface-Mount Technology

MIL Spec	Product Type	Slash Sheet	MIL Style	Power Rating (Watts)	Value Range (Ohms)	Tol. Range (± %)	TCR Range (± ppm/°C)	Failure Rate Range
MIL-PRF-55342	Thick Film Chip, SMD	/01	RM0502	0.05	1 to 9.1	2 to 10	300	C, M, P, R, U, S, V and T
					10 to 22 M	1 to 10	100 to 300	
		/02	RM0505	0.125	1 to 9.1	2 to 10	300	C, M, P, R, U, S, V and T
					10 to 22 M	1 to 10	100 to 300	
		/03	RM1005	0.2	1 to 5.6	2 to 10	300	C, M, P, R, U, S, V and T
					5.62 to 22 M	1 to 10	100 to 300	
		/04	RM1505	0.15	1 to 5.6	2 to 10	300	C, M, P, R, U, S, V and T
					5.62 to 22 M	1 to 10	100 to 300	
		/05	RM2208	0.225	1 to 5.6	2 to 10	300	C, M, P, R, U, S, V and T
					5.62 to 22 M	1 to 10	100 to 300	
		/06	RM0705	0.15	1 to 5.6	2 to 10	300	C, M, P, R, U, S, V and T
					5.62 to 22 M	1 to 10	100 to 300	
		/07	RM1206	0.25	1 to 5.6	2 to 10	300	C, M, P, R, U, S, V and T
	5.62 to 22 M				1 to 10	100 to 300		
	/08	RM2010	0.8	1 to 5.6	2 to 10	300	C, M, P, R, U, S, V and T	
				5.62 to 22 M	1 to 10	100 to 300		
	/09	RM2512	1	1 to 5.6	2 to 10	300	C, M, P, R, U, S, V and T	
				5.62 to 22 M	1 to 10	100 to 300		
	/10	RM1010	0.5	1 to 5.6	2 to 10	300	C, M, P, R, U, S, V and T	
				5.62 to 22 M	1 to 10	100 to 300		
	/11	RM0402	0.05	1 to 9.1	2 to 10	300	C, M, P, R, U, S, V and T	
				10 to 22 M	1 to 10	100 to 300		
	/12	RM0603	0.1	1 to 5.6	2 to 10	300	C, M, P, R, U, S, V and T	
				5.62 to 22 M	1 to 10	100 to 300		
/13	RM0302	0.04	1 to 9.1	2 to 10	300	C, M, P, R, U, S, V and T		
			10 to 22 M	1 to 10	100 to 300			
Thin Film Chip, SMD	/01	RM0502	0.05	20 to 150 K	0.1 to 5	50 to 300	C, M, P, R and U	
				49.9 to 150 K	0.1 to 5	25		
	/02	RM0505	0.125	20 to 301 K	0.1 to 5	50 to 300	C, M, P, R, U and T	
				49.9 to 301 K	0.1 to 5	25		
	/03	RM1005	0.2	10 to 649 K	0.1 to 5	50 to 300	C, M, P, R, U and T	
				49.9 to 649 K	0.1 to 5	25		
	/04	RM1505	0.15	10 to 1.69 M	0.1 to 5	50 to 300	C, M, P, R, U and T	
				49.9 to 1.69 M	0.1 to 5	25		
	/05	RM2208	0.225	10 to 3.16 M	0.1 to 5	50 to 300	C, M, P, R and U	
				49.9 to 3.16 M	0.1 to 5	25		
	/06	RM0705	0.15	10 to 475 K	0.1 to 5	50 to 300	C, M, P, R, U and T	
				49.9 to 475 K	0.1 to 5	25		
	/07	RM1206	0.25	10 to 1.5 M	0.1 to 5	50 to 300	C, M, P, R, U and T	
				49.9 to 1.5 M	0.1 to 5	25		
	/08	RM2010	0.8	10 to 4.02 M	0.1 to 5	50 to 300	C, M, P, R and U	
				49.9 to 4.02 M	0.1 to 5	25		

Resistors - Military Resistors 101



MILITARY RESISTORS 101

Product Information – Film Surface Mount



Resistors - Military Resistors 101

Film Surface-Mount Technology, continued

MIL Spec	Product Type	Slash Sheet	MIL Style	Power Rating (Watts)	Value Range (Ohms)	Tol. Range (± %)	TCR Range (± ppm/°C)	Failure Rate Range									
MIL-PRF-55342	Thin Film Chip, SMD	/09	RM2512	1	10 to 6.19 M	0.1 to 5	50 to 300	C, M, P, R and U									
					49.9 to 6.19 M	0.1 to 5	25										
		/10	RM1010	0.5	49.9 to 1 M	0.1 to 5	25 to 300	C, M, P, R, U and T									
									/11	RM0402	0.05	20 to 100 K	0.1 to 5	50 to 300	C, M, P, R and U		
		49.9 to 100 K	0.1 to 5	25													
		/12	RM0603	0.1	10 to 261 K	1 to 5	50 to 300	C, M, P, R and U									
									10 to 258 K	0.1	50 to 300						
									49.9 to 261 K	1 to 5	25						
									49.9 to 258 K	0.1	25						
									MIL-PRF-32159	Thick Film Chip, Jumper, SMD	/01	RCZ0502	0.05	0	n/a	n/a	C, M
											/02	RCZ0505	0.1	0	n/a	n/a	C, M
		/03	RCZ1005	0.2	0	n/a	n/a	C, M									
/04	RCZ1505	0.15	0	n/a	n/a	C, M											
/05	RCZ2208	0.225	0	n/a	n/a	C, M											
/06	RCZ0705	0.15	0	n/a	n/a	C, M											
/07	RCZ1206	0.25	0	n/a	n/a	C, M											
/08	RCZ2010	0.8	0	n/a	n/a	C, M											
/09	RCZ2512	1	0	n/a	n/a	C, M											
/10	RCZ1010	0.5	0	n/a	n/a	C, M											
/11	RCZ0402	0.04	0	n/a	n/a	C, M											
/12	RCZ0603	0.07	0	n/a	n/a	C, M											
/13	RCZ0302	0.035	0	n/a	n/a	C, M											

Established Reliability Thick Film Military Chip Jumpers

MIL-PRF-32159, Type RCZ RCWPM Jumper Series



- Available for MIL sheets /01 through /13
- Verified failure rate
 - C, M failure rate levels available
- Termination style
 - Standard pre-tinned nickel barrier wraparound (style B)

Established Reliability Thick Film Military Chip Resistors

MIL-PRF-55342, Type RM RCWPM Series



- Available for MIL sheets /01 through /13
- Verified failure rate
 - C, M, P, R, U, S, V, T failure rate levels available
- Available in K (100 ppm), L (200 ppm) or M (300 ppm) characteristics
- Termination style
 - Standard pre-tinned nickel barrier wraparound (style B)



MILITARY RESISTORS 101

Product Information – Film Surface Mount



Established Reliability Thin Film Military Chip Resistors



MIL-PRF-55342, TYPE RM

E/H Series

- Available for MIL Sheets /01 through /12
- Verified failure rate
 - C, M, P, R, U, T failure rate levels available
- Available in characteristics E (25 ppm), H (50 ppm), K (100 ppm), L (200 ppm) or M (300 ppm)
- Termination style
 - Standard pre-tinned nickel barrier wraparound (style B)

Style Comparison of Vishay Thick Film / Thin Film Chip Resistors

Parameter	Military (RCWPM, 55342)	Industrial (RCWP, P-NS, PTN)	Commercial (CRCW, M)
Construction and Materials	All materials conform to MIL-PRF-55342 and are supplied according to the "Qualified Products List"; Terminations = Precious metal base conductor, Sulfur Impervious, nickel barrier, and 80/20 solder finish. (100 % Sn not allowed). "JAN" branded; Space Level available. No material changes made without DSCC approval.	The same materials as Military chips; 100 % Sn solder is available. RCWP-540 and RCWP-0201 sizes are available. No "JAN" brand. Process change qualifications are not DSCC approved. Qualifications of standard product based on military chip qualification.	Manufactured to EIA-575 with exceptions; RM-1005, RM-1505; RM-2208, RM-1010, RM-0502, and RM-0302 sizes are not available. Silver Base Conductor. 90/10 or 100 % Sn terminations. No "JAN" brand. Internal qualification of changes does not require a governing agency's approval.
Processing and Line Control	Manufactured using military qualified and documented processes. Group-A screening including 100 % pre-cap visual, thermal shock, 100 % visual inspection, and dc resistance. MIL-STD-790 training required. No major process changes made without DSCC approval.	100 % Group-A thermal shock is included with 5 % Percent Defects Allowed (PDA) Process modifications to conform to customer requirements are allowed. Only internal qualifications required for major process changes.	Only internal qualifications required for major process changes. Group-A thermal shock is not done; No 100 % visual inspection required; No PDA requirement; Process modifications to conform to special or unique customer requirements are generally not allowed.
Inspection	Inspection per MIL-PRF-55342; Electrical defects; C = 0 Mechanical defects; C = 0 Visual defects; C = 0 Inspection quality levels: First Submission Electrical = 27 ppm Average Outgoing Visual/mechanical = 30 ppm	Inspection MIL-STD-105 Level II; 1 % AQL major; 4 % AQL minor; C = 0 critical Inspection quality levels: First Submission Electrical = 227 ppm Average Outgoing Visual/mechanical = 24 ppm	Inspection MIL-STD-105 Level I; 1 % AQL major; 4 % AQL minor; C = 0 critical Inspection quality levels: Electrical AOQ = 6 ppm (15 000 pc. Sample/week) Average Outgoing Visual/mechanical = 267 ppm
Reliability	An "Established Reliability" quality level is determined by continuously testing thousands of components in a qualified laboratory. The reliability "Failure Rate Level" is specified in the MIL-PRF-55342 military specification and is derived from the laboratory data. Product specific statistics are available upon request.	Periodic internal testing to specific environmental and electrical parameters is based on MIL-PRF-55342. No failure rate data is available.	Failure rate is based on field failures, which are the total number of failures versus the total number of products shipped.
Traceability	Conforms to MIL-PRF-55342; All Group-A, Group-B, and Group-C test data is recorded and retained for a minimum of 5 years. Only single lots and date codes allowed on a reel.	Final inspection data is retained for a minimum of 1 year; In special cases, multiple date codes and/or production lots may be allowed on a single reel.	Final inspection data is retained for a minimum of 1 year.



MILITARY RESISTORS 101

Product Information – Wirewound/Metal Element Axial Leaded



Resistors - Military Resistors 101

Wirewound / Metal Element Axial Leaded Technology

MIL Spec	Product Type	MIL Style	Power Rating (Watts)	Value Range (Ohms)	Tol. Range (± %)	TCR Range (± ppm/°C)	Failure Rate Range
MIL-PRF-26	Wirewound, Axial Leaded	RW67	6.5	0.1 to 8.2 k	5, 10	20 to 90	n/a
		RW68	11	0.1 to 20 k	5, 10	20 to 90	n/a
		RW69	3	0.1 to 2.0 k	5, 10	20 to 90	n/a
		RW70	1	0.1 to 2.74 k	0.1, 0.5, 1	20 to 90	n/a
		RW74	5	0.1 to 24.3 k	0.1, 0.5, 1	20 to 90	n/a
		RW78	10	0.1 to 71.5 k	0.1, 0.5, 1	20 to 90	n/a
		RW79	3	0.1 to 6.49 k	0.1, 0.5, 1	20 to 90	n/a
		RW80	2	0.1 to 2.74 k	0.1, 0.5, 1	20 to 90	n/a
		RW81	1	0.1 to 1.0 k	0.1, 0.5, 1	20 to 90	n/a
MIL-PRF-39007	Wirewound, Axial Leaded	RWR71	2	0.1 to 12.1 k	0.1, 0.5, 1	20 to 650	M, P, R, and S
		RWR74	5	0.1 to 12.1 k	0.1, 0.5, 1	20 to 650	M, P, R, and S
		RWR78	10	0.1 to 39.2 k	0.1, 0.5, 1	20 to 650	M, P, R, and S
		RWR80	2	0.1 to 3.16 k	0.1, 0.5, 1	20 to 650	M, P, R, and S
		RWR81	1	0.1 to 1.0 k	0.1, 0.5, 1	20 to 650	M, P, R, and S
		RWR82	1.5	0.1 to 1.3 k	0.1, 0.5, 1	20 to 650	M, P, R, and S
		RWR84	7	0.1 to 12.4 k	0.1, 0.5, 1	20 to 650	M, P, R, and S
		RWR89	3	0.1 to 4.12 k	0.1, 0.5, 1	20 to 650	M, P, R, and S
MIL-PRF-49465	Metal Element, Axial Leaded	RLV10	5	0.01 to 0.5	1, 3, 5	50 to 150	n/a
		RLV30	3	0.01 to 0.2	1, 3, 5	50 to 350	n/a
		RLV31	5	0.01 to 0.3	1, 3, 5	50 to 250	n/a

Fixed Wirewound Military Resistors

**MIL-PRF-26, Type RW
RS, NS Series
G, GN Series**



- Available in either standard (RS and G) or non-inductive (NS and GN) winding
- 9 Sizes (1 W to 11 W)

Established Reliability Fixed Wirewound Military Resistors

**MIL-PRF-39007, Type RWR
ESS, ESW, ESN Series
EGS, EGW, EGN Series**



- 100 % power stabilization and screening test
- Available in either standard (RWRxxS) or non-inductive (RWRxxN) winding
- 8 Sizes (1 W to 10 W)
- S failure rate available




MILITARY RESISTORS 101

Product Information – Wirewound/Metal Element Axial Leaded



Fixed Metal Element Military Resistors

**MIL-PRF-49465, Type RLV
LVR Series
SPR-1005 Series**



- Extremely low resistance values
- Ideal for current sensing applications

Style Comparison Of Vishay Wirewound Axial Resistors

Parameter	RWR E-REL MILITARY ESS, EGS (Vishay Dale) ESN, EGN (Vishay Dale)	RW NON E-REL RS (Vishay Dale) NS (Vishay Dale)
Electrical Specifications	All components conform to the electrical requirements of MIL-PRF-39007.	All components conform to the electrical requirements of MIL-PRF-26.
Mechanical Specifications	All components conform to the mechanical requirements of MIL-PRF-39007.	All components conform to the mechanical requirements of MIL-PRF-26.
Material Requirements	All materials for the E-Rel military components are approved for use per MIL-PRF-39007. All materials are baselined and cannot be modified or substituted without military approval by request and/or requalification. No materials can be used in their manufacture without labels showing acceptance through incoming inspection.	Most materials are the same for E-Rel equivalent components and also require inspection acceptance labels. Materials are not qualified on a military controlled baseline, but are internally required to allow the components to meet MIL-PRF-26 specification.
Process and Test Requirements	The RWR series conforms to MIL-PRF-39007, which includes 100 % 100 hour power conditioning. Reliability determination requires 10 000 hour load life in addition to other rigid environmental testing to conform to the above specification.	Do not have additional processing and screening tests that E-Rel equivalent components require.
Reliability	An “Established Reliability” quality level is determined by continuously testing thousands of components in a qualified laboratory. The reliability “Failure Rate Level” is specified in the MIL-PRF-39007 military specification and is derived from the laboratory data. Product specific statistics are available upon request.	Periodic internal testing to specific environmental and electrical parameters derived from the MIL-PRF-26 military specifications are incorporated. Product specific statistics are available upon request.
Customer Application	Military, space, medical, and other high-reliability applications.	Wide range of applications including communications, military, computer, industrial, test and control electronics.
Traceability	All component materials are required to be traceable.	Materials are generally not required to be traceable. Traceability can be incorporated on components as a “special” if required by customer.
Packaging	Available in either bulk or reeled.	Available in either bulk or reeled.

Resistors - Military Resistors 101



MILITARY RESISTORS 101

Product Information – Wirewound Chassis Mount



Resistors - Military Resistors 101

Wirewound Chassis Mount Technology

MIL Spec	Product Type	MIL Style	Power Rating (Watts)	Value Range (Ohms)	Tol. Range (± %)	TCR Range (± ppm/°C)	Failure Rate Range
MIL-PRF-18546	Wirewound, Chassis Mount	RE60	5	0.1 to 3.32 k	1	20 to 100	n/a
		RE65	10	0.1 to 5.62 k	1	20 to 100	n/a
		RE70	20	0.1 to 12.1 k	1	20 to 100	n/a
		RE75	30	0.1 to 39.2 k	1	20 to 100	n/a
		RE77	75	0.05 to 29.4 k	1	20 to 100	n/a
		RE80	120	0.1 to 35.7 k	1	20 to 100	n/a
MIL-PRF-39009	Wirewound, Chassis Mount	RER40	5	1 to 1.65 k	1	20 to 50	M, P, and R
		RER45	10	1 to 2.8 k	1	20 to 50	M, P, and R
		RER50	20	1 to 6.04 k	1	20 to 50	M, P, and R
		RER55	30	1 to 4.99 k	1	20 to 50	M, P, and R
		RER60	5	0.1 to 3.32 k	1	20 to 100	M, P, and R
		RER65	10	0.1 to 5.62 k	1	20 to 100	M, P, and R
		RER70	20	0.1 to 12.1 k	1	20 to 100	M, P, and R
		RER75	30	0.1 to 39.2 k	1	20 to 100	M, P, and R

Wirewound Chassis Mount Military Resistors

MIL-PRF-18546, Type RE RH, NH Series

- Aluminum housed standard (RExxG) or non-inductive (RExxN) winding/molded construction gives complete environmental protection
- Mounts on chassis for high stability at conventional power ratings
- 6 sizes (5 W to 120 W)



Established Reliability Wirewound Chassis Mount Military Resistors

MIL-PRF-39009, Type RER ERH, ENH Series

- Aluminum housed standard (RERxxG) or non-inductive (RERxxN) winding/molded construction gives complete environmental protection
- Mounts on chassis for high stability at conventional power ratings
- Utilize heat sink effect
- 4 Sizes (5 W to 20 W)
- R failure rate





MILITARY RESISTORS 101

Product Information – Wirewound Chassis Mount



Style Comparison of Vishay Wirewound Chassis Mount Resistors

Parameter	RER E-REL MILITARY ERH (Vishay Dale) ENH (Vishay Dale)	RE NON E-REL RH (Vishay Dale) NH (Vishay Dale)
Electrical Specifications	All components conform to the electrical requirements of MIL-PRF-39009.	All components conform to the electrical requirements of MIL-PRF-18546.
Mechanical Specifications	All components conform to the mechanical requirements of MIL-PRF-39009.	All components conform to the mechanical requirements of MIL-PRF-18546.
Material Requirements	All materials for the E-Rel military components are approved for use per MIL-PRF-39009. All materials are baselined and cannot be modified or substituted without military approval by request and/or re-qualification. No materials can be used in their manufacture without labels showing acceptance through incoming inspection.	Most materials are the same for E-Rel equivalent components and also require inspection acceptance labels. Materials are not qualified on a military controlled baseline, but are internally required to allow the components to meet MIL-PRF-18546 specification.
Process and Test Requirements	The RER series conforms to MIL-PRF-39009, which includes 100 % 100 hr power conditioning. Reliability determination requires 10 000 hour load life in addition to other rigid environmental testing to conform to the above specification.	Do not have additional processing and screening tests that E-Rel equivalent components require.
Reliability	An “Established Reliability” quality level is determined by continuously testing thousands of components in a qualified laboratory. The reliability “Failure Rate Level” is specified in the MIL-PRF-39009 military specification and is derived from the laboratory data. Product specific statistics are available upon request.	Periodic internal testing to specific environmental and electrical parameters derived from the MIL-PRF-18546 military specifications are incorporated. Product specific statistics are available upon request.
Customer Application	Military, space, medical, and other high-reliability applications.	Wide range of applications including communications, military, computer, industrial, test and control electronics.
Traceability	All component materials are required to be traceable.	Materials are generally not required to be traceable. Traceability can be incorporated on components as a “special” if required by customer.
Packaging	Available in “Card Pack”	5 W through 30 W available in “Card Pack”, 70 W and 120 W available in “Skin Pack”

Resistors - Military Resistors 101



MILITARY RESISTORS 101

Product Information – DLA L&M / DSCC Drawings



Vishay Qualified Products

DLA L&M/ DSCC Dwg#	Description	Vishay Date	Vishay Techno	Vishay Thin Film
87010	Resistor, Fixed, 0 Ω , 0.125 Watt	X		
87011	Resistor, Chip, Fixed, Film, 0 Ω , Style 1010	X		X
87012	Resistor Network, Fixed, Film, Surface Mount, Gull Wing, 16 Pin	X		X
87013	Resistor Network, Fixed, Film, Surface Mount, Gull Wing, 14 Pin	X		
87014	Resistor Network, 16 Pin, Leadless Chip Carrier			X
87015	Resistor Network, 28 Pin, Leadless Chip Carrier			X
87016	Resistor Network, 20 Pin, Leadless Chip Carrier			X
87017	Resistor Network, Fixed, Film, Surface Mount, 20 Pin, Leadless Chip Carrier			X
87018	Resistor Network, 16 Pin, Leadless Chip Carrier			X
87025	Resistor Network, 8 Pin, Dual-In-Line Package (DIP)			X
87030	Resistor, Network, 6 Pin, Single-In-Line Package (SIP)	X		
87031	Resistor, Network, 8 Pin, Single-In-Line Package (SIP)	X	X	
87032	Resistor Network, 10 Pin, Single-In-Line Package (SIP)	X		X
87033	Resistor Network, 10 Pin, Single-In-Line Package (SIP)	X	X	
87053	Resistor, Network, 14 Pin, Flat Pack	X		
87067	Resistor Network, Fixed, Film, 7 Pin SIP (Low Profile), Multiple Schematics	X	X	
87068	Resistor Network, Fixed, Film, 7 Pin SIP (High Profile), Multiple Schematics	X	X	
87071	Resistor Network, Fixed, Film, 10 Pin SIP, Multiple Resistance Values, Multiple Schematics, (Low Profile)	X	X	
87072	Resistor Network, Fixed, Film, 10 Pin SIP, Multiple Resistance Values, Multiple Schematics and Multiple Tolerances.	X	X	
87073	Resistor Network, Fixed, Film, 8 Pin SIP, Multiple Resistance Values, Multiple Schematics, (Low Profile)	X	X	
87074	Resistor Network, Fixed, Film, 8 Pin SIP, Multiple Resistance Values, Multiple Schematics, (High Profile)	X	X	
87103	Resistor, Network, 9 Pin, SIP Multiple Values, Multiple Tolerances, (Low Profile)	X	X	
87105	Resistor, Network, 9 Pin, SIP Multiple Values, Multiple Tolerances, (High Profile)	X	X	
88014	Resistor, Network, 12 Pin, Single-In-Line Package (SIP)	X		
88015	Resistor, Network, 8 Pin, Single-In-Line Package	X	X	
88018	Resistor, Chip, Fixed, Film, Style 0705	X		
88027	Resistor, Chip, Fixed, Film, Style 0504	X		
88030	Resistor, Chip, Fixed, Film, Style 1005	X		
88031	Resistor, Chip, Fixed, Film, Style 1505	X		
88032	Resistor, Chip, Fixed, Film, 0 Ω , Style 0502	X		
88033	Resistor, Chip, Fixed, Film, Style 1010	X		
89004	Resistor-Capacitor Network, 16 Pin DIP	X		
89023	Resistor/Capacitor Network, 16 Pin Flat Pack	X		
89088	Resistor, Fixed, Film, Precision, 0.1 Watt, Power Curve C	X		
90038	Resistor, Fixed, Film, Precision, 0.25 Watt, Power Curve C	X		
90047	Resistor, Chip, Fixed, Film, 0 Ω , Style 2208	X		X

Resistors - Military Resistors 101

**MILITARY RESISTORS 101**Product Information –
DLA L&M / DSCC Drawings**Vishay Qualified Products, continued**

DLA L&M/ DSCC Dwg#	Description	Vishay Date	Vishay Techno	Vishay Thin Film
90048	Resistor, Chip, Fixed, Film, 0 Ω, Style 0705	X		X
90049	Resistor, Chip, Fixed, Film, 0 Ω, Style 1005	X		X
90092	Resistor, Chip, Fixed, Film, 0 Ω, Style 1505	X		X
92013	Resistor Network, 10 Pin, SIP, Extended Lead Length	X	X	
93075	Resistor, Fixed, Wirewound, Surface Mount, Power Type (0.5 Watt)	X		
93076	Resistor, Fixed, Wirewound, Surface Mount, Power Type (1 Watt)	X		
93077	Resistor, Fixed, Wirewound, Surface Mount, Power Type (2 Watt)	X		
94011	Resistor, Chip, Fixed, Film, 0 Ω, Style 1206	X		X
94012	Resistor, Chip, Fixed, Film, Moisture Resistant, Military and Space Level, Style 0505	X		X
94013	Resistor, Chip, Fixed, Film, Moisture Resistant, Military and Space Level, Style 1005	X		X
94014	Resistor, Chip, Fixed, Film, Moisture Resistant, Military and Space Level, Style 2208	X		X
94015	Resistor, Chip, Fixed, Film, Moisture Resistant, Military and Space Level, Style 0705	X		X
94016	Resistor, Chip, Fixed, Film, Moisture Resistant, Military and Space Level, Style 1206	X		X
94017	Resistor, Chip, Fixed, Film, Moisture Resistant, Military and Space Level, Style 2010	X		X
94018	Resistor, Chip, Fixed, Film, Moisture Resistant, Military and Space Level, Style 2512	X		X
94019	Resistor, Chip, Fixed, Film, Moisture Resistant, Military and Space Level, Style 1010	X		X
94025	Resistor, Chip, Fixed, Film, Moisture Resistant, Military and Space Level, Style 0502	X		X
94026	Resistor, Chip, Fixed, Film, Moisture Resistant, Military and Space Level, Style 1505	X		X
95013	Resistor, Chip, Fixed, Film, Style 0302	X		
95014	Resistor, Chip, Fixed, Film, Style 0402	X		
96002	Resistor, Fixed, Film, Insulated, Low Inductance	X		
97004	Resistor, Fixed, Film (Insulated), 2 Watt	X		
98020	Resistor, Fixed, Film (Insulated), 0.125 Watt	X		
98021	Resistor, Fixed, Film (Insulated), 0.5 Watt	X		
98022	Resistor, Fixed, Film (Insulated), 1 Watt	X		
99011	Resistor, Fixed, Film (Insulated), 0.25 Watt	X		
02001	Resistor, Fixed, Film, Precision, Chip 0.125 Watt, Style 2012	X		
02008	Resistor, Fixed, Film, Chip, Low and High Values, Style 1206	X		X
02010	Resistor, Chip, Fixed, Film, Values Less Than 1 Ohm, Style 1206	X		X
03002	Resistor, Chip, Fixed, Film, 0 Ω, Style 0505	X		X
03011	Resistor, Chip, Fixed, Film, 0 Ω, Style 0201	X		
03012	Resistor, Chip, Fixed, Film, 0 Ω, Style 0302	X		
03013	Resistor, Chip, Fixed, Film, 0 Ω, Style 0603	X		X
03014	Resistor, Chip, Fixed, Film, 0 Ω, Style 0402	X		X
03015	Resistor, Chip, Fixed, Film, 0 Ω, Style 2010	X		X
03016	Resistor, Chip, Fixed, Film, 0 Ω, Style 2512	X		X
03022	Resistor, Chip, Fixed, Film, values less than 1 Ohm, Style 0603	X		X
03025	Resistor, Chip, Fixed, Film, High Voltage, Style 1206		X	
03026	Resistor, Chip, Fixed, Film, High Voltage, Style 2010		X	
03027	Resistor, Chip, Fixed, Film, High Voltage, Style 2512		X	



MILITARY RESISTORS 101

Product Information – DLA L&M / DSCC Drawings



Vishay Qualified Products, continued

DLA L&M/ DSCC Dwg#	Description	Vishay Date	Vishay Techno	Vishay Thin Film
04007	Resistor, Chip, Fixed, Film, Moisture Resistant, Military and Space Level, Style 0302	X		
04008	Resistor, Chip, Fixed, Film, Moisture Resistant, Military and Space Level, Style 0402	X		X
04009	Resistor, Chip, Fixed, Film, Moisture Resistant, Military and Space Level, Style 0603	X		X
06003	Resistor, Chip, Fixed, Power Metal Strip®, Surface Mount, Low Value (2 Watt)	X		
06006	Resistor, Chip, Fixed, Power Metal Strip, Surface Mount, Low Value (3 Watt), Style 4527	X		
06007	Resistor, Chip, Fixed, Power Metal Strip, Surface Mount, Low Value (0.1 Watt), Style 0603	X		
06008	Resistor, Chip, Fixed, Power Metal Strip, Surface Mount, Low Value (0.125 Watt), Style 0805	X		
06009	Resistor, Chip, Fixed, Power Metal Strip, Surface Mount, Low Value (0.25 Watt), Style 1206	X		
06010	Resistor, Chip, Fixed, Power Metal Strip, Surface Mount, Low Value (0.5 Watt), Style 2010	X		
06011	Resistor, Chip, Fixed, Power Metal Strip, Surface Mount, Low Value (1.0 Watt), Style 2512	X		
06012	Resistor, Chip, Fixed, Power Metal Strip, Surface Mount, Low Value (2.0 Watt), Style 2816	X		
06018	Resistor Network, Fixed, Film, Surface Mount, Voltage Divider, 3 Pin			X
07002	Resistor, Fixed, Wirewound, Surface Mount, Power Type (3 Watt)	X		
07009	Resistor, Chip, Fixed, Film, Style 0201	X		
07010	Resistor, Chip, Fixed, Film, Moisture Resistant, Military and Space Level, Style 0201	X		
12003	Resistor, Chip, Fixed, Film, Values Less Than 1 Ohm, Style 0502	X		
12004	Resistor, Chip, Fixed, Film, Values Less Than 1 Ohm, Style 0505	X		X
12005	Resistor, Chip, Fixed, Film, Values Less Than 1 Ohm, Style 1005	X		X
12006	Resistor, Chip, Fixed, Film, Values Less Than 1 Ohm, Style 1505	X		X
12007	Resistor, Chip, Fixed, Film, Values Less Than 1 Ohm, Style 2208	X		
12008	Resistor, Chip, Fixed, Film, Values Less Than 1 Ohm, Style 0705	X		X
12009	Resistor, Chip, Fixed, Film, Values Less Than 1 Ohm, Style 2010	X		X
12010	Resistor, Chip, Fixed, Film, Values Less Than 1 Ohm, Style 2512	X		X
12011	Resistor, Chip, Fixed, Film, Values Less Than 1 Ohm, Style 1010	X		
12012	Resistor, Chip, Fixed, Film, Values Less Than 1 Ohm, Style 0402	X		
A-A-55502	Resistor, Fixed, 0 Ω, 1/8 Watt	X		
A-A-55534/01	Resistor, Fixed, Wirewound or Metal Element, (Power Type), Style VLV1	X		
A-A-55534/02	Resistor, Fixed, Wirewound or Metal Element, Chip, (Power Type), Style VLV1206	X		
A-A-55534/03	Resistor, Fixed, Wirewound or Metal Element, (Power Type), Style VLV3	X		
A-A-55534/04	Resistor, Fixed, Wirewound or Metal Element, (Power Type), Style VLV5	X		
A-A-55534/07	Resistor, Fixed, Wirewound or Metal Element, Chip, (Power Type), Style VLV2010	X		
A-A-55534/08	Resistor, Fixed, Wirewound or Metal Element, Chip, (Power Type), Style VLV2512	X		
A-A-55534/09	Resistor, Fixed, Wirewound or Metal Element, Chip, (Power Type), Style VLV2	X		

Resistors - Military Resistors 101



MILITARY RESISTORS 101

Terminology



Common Terminology

C of C (Certificate of Conformance)

- Material supplied to MIL Specs shall be accompanied by a C of C, which may include:
 1. Original manufacturer's name, address, telephone number and CAGE number
 2. Purchase order number
 3. Part number
 4. Drawing or specification number and revision
 5. Serial numbers or date code or lot number (as applicable)
 6. QA signature and date
 7. Statement of conformance to all requirements

Note: The supplier shall also retain the C of C and all relevant supporting data on file for a period of time after completion of the purchase order.

CAGE Code (Commercial and Government Entity code)

- A five-digit number assigned to a company to represent the company's physical address. Formerly referred to as FSCM (Federal Supply Code for Manufacturers).
It is used for mailing, payments and administrative records. A vendor cannot do business with the government without a CAGE code.

COTS (Commercial Off The Shelf)

- Any item of supply that is (i) a commercial item; (ii) sold in substantial quantities in the commercial marketplace; and (iii) offered to the government, without modification, in the same form in which it is sold in the commercial marketplace.

Date Code Restriction

- Product must be manufactured within a specified period of time prior to shipment.

DFAR (Defense Federal Acquisition Regulations)

- Procurement regulations used by organizations in the Department of Defense. Also called Defense Acquisition Regulations (DAR).

DFARS (Defense Federal Acquisition Regulations Supplement)

- Interpretation and regulations specifically for Department of Defense Procurement. Supplements the Federal Acquisition Regulations (FAR).

DFARS 252.225-7014, Preference for Domestic Specialty Metals, Alt I

- Specifies that specialty metals must be melted in the United States or a qualifying country, or they can be melted anywhere but must be incorporated in an article manufactured in a qualifying country.
- Vishay DALE Resistors are DFARS Compliant.

DLA (Defense Logistics Agency)

- The Department of Defense (DoD) Agency responsible for supplying military needs. The Agency is headquartered at Ft. Belvoir, VA and maintains several Inventory Control Points (ICPs) including DLA Land and Maritime, DLA Troop Support, and DLA Aviation.

DLA Aviation (former DSCR)

- Serves as the Aviation supply chain manager for the Defense Logistics Agency. They support major weapon systems and are one of the U.S. military's integrated materiel managers for repair parts and operating supply items. They manage aviation parts, including spares for engines on fighters, bombers, cargo aircraft and helicopters; airframe and landing gear parts; flight safety equipment; and propeller systems.



MILITARY RESISTORS 101

Terminology



DLA Land and Maritime (former DSCC)

- Serves as the Maritime and Land weapons systems supply chain manager for the Defense Logistics Agency. DLA L&M is one of the U.S. Military's largest suppliers of weapon systems spare parts, and they also manage the MIL Specs and Drawings for the DLA.

DLA Troop Support (former DSCP)

- Provides United States armed services members with food, clothing, textiles, medicines, medical equipment, and construction supplies and equipment. They also support United States humanitarian and disaster relief efforts.

DPA (Defense Production Act)

- Under authority of the Defense Production Act of 1950 and related executive Order 12656, the Commerce Department is charged with identifying critical defense-related industries, assessing their capability to meet peacetime and national security needs, identifying current and potential production constraints, and proposing remedial actions as appropriate. Title I of the DPA requires that: (i) contracts or orders relating to certain approved defense and energy programs be accepted and performed on a preferential basis over all other contracts and orders and (ii) materials, facilities, and services be allocated in such a manner as to promote approved programs, facilities, and services be allocated in such a manner as to promote approved programs.

DPAS (Defense Priorities and Allocation System)

- The goals of the DPAS are to (i) assure the timely availability of industrial resources to meet current national defense requirements and (ii) provide a framework for rapid industrial expansion in case of a national emergency.
 - There are two levels of priority established by this regulation, identified by the rating symbols "DO" and "DX". All DO rated orders have equal priority with each other and take preference over unrated orders. All DX orders have equal priority with each other and take preference over DO rated orders and unrated orders.

DSC, DSCC, DSCP, DSCR

- Former abbreviations for the Supply Centers, which procure supplies for the Military. Each Supply Center manages different types of items.
- DSC = Defense Supply Center
 - DSCC = Defense Supply Center Columbus (Columbus, OH) – now DLA Land and Maritime
 - Maritime and land weapon systems support
 - DSCP = Defense Supply Center Philadelphia (Philadelphia, PA) – now DLA Troop Support
 - Food, clothing, medical, construction, and equipment support
 - DSCR = Defense Supply Center Richmond (Richmond, VA) – now DLA Aviation
 - Aviation weapon systems and environmental logistics support

EDI (Electronic Data Interchange)

- The electronic communications of business transactions; specifically the exchange of trade-related documents such as purchase orders, invoices, and corporate Electronic Funds Transfer (EFTs) in a standard format.

ESD (Electrostatic Sensitive Devices)

- The devices supplied under contract shall be packaged in accordance with the latest revision of the MIL-STD- 1686 (Electrostatic Discharge Control Program for Protection of Electronic Devices) and MIL-HDBK-263 (ESD Handbook for Protection Parts, Assemblies and Equipments). Packaging shall be marked with an ESD cautionary note or symbol.

E-REL (Established Reliability)

- A quantitative maximum failure rate demonstrated under controlled conditions specified in a Department of Defense specification and usually expressed as percent failures per thousand hours of test.



MILITARY RESISTORS 101

Terminology



Failure Rate

- The probability of failure per unit of time of items in operation. Sometimes estimated as a ratio of the number of failures to the accumulated operating time for the items.

Failure Rate Level Designation / Symbol	Failure Rate (Percent/1000 Hours)
C	Non-Established Reliability
M	1
P	0.1
R, U ¹	0.01
S, V ¹	0.001
T	Space Level

¹ Failure rates U and V require Group A and B inspection run on each production lot.

Failure Rate	Failure Rate Substitution
T (Space)	–
V (0.001) ¹	–
U (0.01) ¹	V
S (0.001)	V
R (0.01)	V, U, S
P (0.1)	V, U, S, R
M (1.0)	V, U, S, R, P
C (Non-ER)	V, U, S, R, P, M

¹ Failure rates U and V require Group A and B inspection run on each production lot.

FAR (Federal Acquisition Regulations)

- The main guidance for procurement supplies and services in the Federal Government. Procurement regulations used by both civilian and defense organizations.

FAT (First Article Testing)

- A performance test required on certain items prior to manufacture. A specified sample of the product is tested and must be approved prior to manufacture of a full production run. Testing is generally extensive and expensive.

FIT (Failures In Time)

- The number of component failures that can be expected in one billion hours of operation.

FSC (Federal Stock Class)

- A term for the first four digits of an NSN. It identifies government procured commodities into broad categories. Defense Supply Center management responsibilities are divided based on assignment of FSCs.

FSG (Federal Supply Group)

- The first two digits of a four digit federal stock class (FSC) and therefore, the first two digits of an NSN. It is the broadest categorization of an item.

ITAR Compliance

- Information contained on documentation may be subject to International Traffic Arms Regulations (ITAR) or Export Administration Regulations (EAR) Controls and may not be disclosed to any foreign person(s) or firms, including persons employed by or associated with your company, without first complying with all requirements of the ITAR, 22 CFR 120-130 and the EAR, 15 CFR 730-774.

Military Drawings

- Some items at the DSCs are required to be manufactured in accordance with a drawing. The drawing may have been designed by either a government agency or a commercial vendor. If a drawing is cited in the Acquisition Item Description (AID), the vendor is responsible for assuring the product offered meets the standards and requirements of the drawing.

Military Handbooks

- MIL-HDBKs are generally how to do documents intended to standardize and educate.

Military Specs

- Some items at the DSCs are required to be manufactured in accordance with a specification. The specification may be designated as a Federal Specification (Fed-Spec - applicable to all military services), a Military Specification (MIL-



MILITARY RESISTORS 101

Terminology



Spec - used by a specific service) or a commercial specification such as North American Specification (NAS) or American National Standards Institute (ANSI). If a specification is cited in the Acquisition Item Description (AID), the vendor is responsible for assuring the product offered meets the requirements of the specification.

Military Standards

- MIL-STDs are generally documents that imposed requirements and give details on what to do.

MIL-STD-202G Test Methods Standard Electronic and Electrical Component Parts

- This military standard establishes uniform methods for testing electronic and electrical component parts, including basic environmental tests to determine resistance to deleterious effects of natural elements and conditions surrounding military operations, and physical and electrical tests.

MIL-STD-883F Test Method Standard Microcircuits

- This military standard establishes uniform methods, controls, and procedures for testing microelectronic devices suitable for use within Military and Aerospace electronic systems including basic environmental tests and other controls and constraints as have been deemed necessary to ensure a uniform level of quality and reliability suitable to the intended applications of those devices.

MTBF (Mean Time Between Failures)

- The average time a component works without failure. It is the number of failures divided by the hours under observation.

NIIN (National Item Identification Number)

- The second of two main parts of the National Stock Number. The NIIN is a unique number with no two items having the same NIIN. An item can be tracked in technical files using just the NIIN. Contract files require the full NSN to track information.

NSN (National Stock Number)

- A unique government tracking number assigned by the General Services Administration consisting of a Federal Stock Class (FSC) and a National Item Identification Number (NIIN). The number is used by requisitioners to identify the item needed and is associated with all buys related to that item. More than one part number may be associated with an NSN; however, all parts associated will have to be the same in form, fit and function.

Prohibited Materials (Tin Whiskers)

- Unless otherwise specified in the product specification, material supplied meet the requirements of ANSI/J-STD-002, Category 3 Test Method A, B, or C as applicable. In addition, constructions and finishes containing pure tin are prohibited unless they contain a minimum of 3 percent by weight alloying element(s) (i.e. lead, silver, etc.).

QPL (Qualified Products List)

- A list of pre-tested qualified manufacturers and products as they related to a specific military specification. A solicitation specifying a QPL restriction requires contractors to supply only the source and part number specified on the QPL list.
- Failure Rated QPL
 - Established Reliability product with a verified Failure Rate that has been qualified to a military specification.
- Non-Failure Rated QPL
 - Product without a verified Failure Rate that has been qualified to a military specification or drawing.

Single Lot Traceability

- Items provided in accordance with this purchase order clause requires each shipment (i) be from only one OEM; (ii) be from one Manufacturing Lot; (iii) components that are too small to have the Lot Code marked on them are to have their packaging identified with the appropriate Lot Code marking / serial number. Also known as Single Lot Date Code (SLDC) and Date Code (DC).



MILITARY RESISTORS 101

Resistive Products



WORLDWIDE SALES CONTACTS

THE AMERICAS

UNITED STATES

VISHAY AMERICAS
ONE GREENWICH PLACE
SHELTON, CT 06484
UNITED STATES
PH: +1-402-563-6866
FAX: +1-402-563-6296

ASIA

SINGAPORE

VISHAY INTERTECHNOLOGY ASIA PTE LTD.
37A TAMPINES STREET 92 #07-00
SINGAPORE 528886
PH: +65-6788-6668
FAX: +65-6788-0988

P.R. CHINA

VISHAY CHINA CO., LTD.
15D, SUN TONG INFOPORT PLAZA
55 HUAI HAI WEST ROAD
SHANGHAI 200030
P.R. CHINA
PH: +86-21-5258 5000
FAX: +86-21-5258 7979

JAPAN

VISHAY JAPAN CO., LTD.
SHIBUYA PRESTIGE BLDG. 4F
3-12-22, SHIBUYA
SHIBUYA-KU
TOKYO 150-0002
JAPAN
PH: +81-3-5466-7150
FAX: +81-3-5466-7160

EUROPE

GERMANY

VISHAY ELECTRONIC GMBH
DR.-FELIX-ZANDMAN-PLATZ 1
95100 SELB
GERMANY
PH: +49-9287-71-0
FAX: +49-9287-70435

FRANCE

VISHAY S.A.
199, BD DE LA MADELEINE
06003 NICE, CEDEX 1
FRANCE
PH: +33-4-9337-2727
FAX: +33-4-9337-2726

UNITED KINGDOM

VISHAY LTD.
SUITE 6C, TOWER HOUSE
ST. CATHERINE'S COURT
SUNDERLAND ENTERPRISE PARK
SUNDERLAND SR5 3XJ
UNITED KINGDOM
PH: +44-191-516-8584
FAX: +44-191-549-9556



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Material Category Policy

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as RoHS-Compliant fulfill the definitions and restrictions defined under Directive 2011/65/EU of The European Parliament and of the Council of June 8, 2011 on the restriction of the use of certain hazardous substances in electrical and electronic equipment (EEE) - recast, unless otherwise specified as non-compliant.

Please note that some Vishay documentation may still make reference to RoHS Directive 2002/95/EC. We confirm that all the products identified as being compliant to Directive 2002/95/EC conform to Directive 2011/65/EU.

Vishay Intertechnology, Inc. hereby certifies that all its products that are identified as Halogen-Free follow Halogen-Free requirements as per JEDEC JS709A standards. Please note that some Vishay documentation may still make reference to the IEC 61249-2-21 definition. We confirm that all the products identified as being compliant to IEC 61249-2-21 conform to JEDEC JS709A standards.