



### Main

Product or component type	Circuit breaker
Range of product	PowerPact R
Current sensor rating range	1200 A
Trip unit technology	Electronic, standard, Micrologic 5.0, LSI

### Complementary

[Ie] rated operational current	1200 A
[Ue] rated operational voltage	600 V AC
Mounting mode	I-Line
Poles description	3P
Breaking capacity	65 KA 240 V AC 65 KA 480 V AC 65 KA 600 V AC
Breaking capacity code	K
Continuous current rating	100 %
Electrical connection	I-Line connection line Lugs load
AWG gauge	AWG 3/0...600 kcmil aluminium/copper
Maximum Height	13.38 in (339.85 mm)
Maximum Width	14.96 in (379.98 mm)
Maximum Depth	13.78 in (350.01 mm)
Tightening torque	247.82 lbf.in (28 N.m) 0.15...0.37 in <sup>2</sup> (95...240 mm <sup>2</sup> ) AWG 4/0...500 kcmil)

### Environment

Product certifications	CSA IEC UL Listed
------------------------	-------------------------

### Ordering and shipping details

Category	01240-RG,H,J,K,L,N I-LINE BREAKERS
Discount Schedule	DE2
Package weight(Lbs)	52.00 lb(US) (23.587 kg)
Returnability	Yes
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DIDP and DINP which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to <a href="http://www.p65warnings.ca.gov">www.p65warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

## Contractual warranty

Warranty	18 months
----------	-----------